MILITARY SPECIFICATION

PACKAGING OF FOOD PACKET, ASSAULT COMPONENTS (IN POUCHES)

This specification is approved for use by Natick Research and Development Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers packaging of the Food Packet, Assault component items.

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

L-P-378	-	Plastic Sheet and Strip, Thin Gauge, Polyolefin
QQ-A-1876	-	Aluminum Foil

MILITARY

MIL-L-1497	-	Labeling of Metal Cans for Subsistence Items

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 89GP

Source: https://assist.dla.mil -- Downloaded: 202640-22T00:11Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-595 - Colors

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

OTHER GOVERNMENT DOCUMENTS

Laws and Regulations

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder (21 CFR Parts 1-199)

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

Meat and Poultry Inspection Regulations

(Applications for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 882 - Tensile Strength of Thin Plastic Sheeting
D 1238 - Flow Rates of Thermoplastics by Extrusion Plastometer
D 1505 - Density of Plastics by Density Gradient Technique

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 Components and materials.

3.1.1 Food product. The food product to be unit packed shall be as specified in the applicable component document (see 6.2).

3.1.2 Mixing bag. Mixing bags shall be fabricated from clear, high density (0.941 to 0.965 g/cm^3) food grade, flat polyethylene tubing. The bottom seal shall be of adequate strength to withstand the crumbling of the food bars, the addition of boiling water (as applicable) and the agitation of the mixture without leaking, when tested in accordance with 4.3.1.3. Size of the mixing bags shall be as follows:

a. Entree bars (see 6.2): 6 inches wide by 8-1/2 inches long (inside dimensions) by 0.004 inch thick.

b. Pudding bars: 5 inches wide by 6 inches long (inside dimensions) by 0.003 inch thick.

3.1.3 Individual bag (for oatmeal cookie and granola bars). Individual bags shall be fabricated from clear, high density (0.941 to 0.965 g/cm^3) food grade, flat polyethylene tubing. One end shall be sealed to form a bag. The bags shall be 2-1/4 inches wide by 6 inches long by 0.002 inch thick.

3.1.4 Mixing bag closure device. The mixing bag closure device shall be the Dennison "Flip-Clip" (see 6.3) or equivalent and shall be fabricated from molded white nylon. It shall be capable of keeping the mixing bag closed, after the bag has been filled with the required amount of water, after the top of the bag has been twisted shut, and during the time required for rehydration of the product.

3.1.5 Pouch.

3.1.5.1 Pouch material. The pouch shall be constructed from a three ply flexible laminate barrier material consisting of an outer ply of 0.0009 inch thick oriented polypropylene bonded to an intermediate ply of 0.0007 inch thick aluminum foil with 10 pounds per ream pigmented polyethylene or adhesive, and bonding the opposite side of the aluminum foil to 0.003 inch thick ionomer (inner ply) or a blend of not less than 50 percent linear low density polyethylene and polyethylene. The linear low density polyethylene portion of

Source: https://assist.dla.mil -- Downloaded: 202640-22T00:11Z
Check the source to verify that this is the currentversion before use.

the blend shall be the copolymer of ethylene and octene-1, having a melt index range of 0.8 to 1.2 g/10 minutes in accordance with ASTM D 1238 and a density range of 0.918 to 0.922 g/cm^3 in accordance with ASTM D 1505. The pigmented polyethylene or adhesive shall be colored overall with a color in the range of 34079 through 34087, or 24052 through 24087, 10045 or 30045 through 30118 (except that 30109 may not be used) of FED-STD-595. The material shall be suitably formulated for food packaging and shall not impart an odor or flavor to the product being packaged. The material shall show no evidence of delamination, degradation, or foreign odor when heat sealed or fabricated into pouches.

3.1.5.2 Pouch construction. The pouch shall be a flat style preformed pouch having inside dimensions as specified in table I. The first dimension specified in table I shall be the opening of the pouch between the heat sealed sides. The empty pouch shall be made by heat sealing three edges with 3/8 inch (± 1/8 inch) wide seals. The heat seals shall be made in a manner that will assure hermetic seals. The pouch shall maintain its integrity and air tightness of the side and bottom seals when tested as specified in 4.3.1.6. The side and bottom seals shall have an average seal strength of not less than 6 pounds per inch and no individual specimen shall have a seal strength of less than 5 pounds per inch when tested as specified in 4.3.1.5. A V-shaped or C-shaped (half round) tear notch at least 1/32 inch deep, located 1 to 1-1/4 inches from the top edge of the pouch shall be made in one or both side seals. The distance between the inside edge of the tear notch and the inside edge of the seal shall be at least 3/16 inch. One side of the open end of the pouch shall be provided with an extended or foldover lip, extended not more than 1/8 inch (± 1/16 inch) to facilitate opening and filling. Tear notch location shall be measured from the top of the pouch, excluding the extended or foldover lip.

TABLE I. Pouch dimensions

Item	Pouch inside dimensions (± 1/16 inch)
Entree (compressed bars)	4-3/4 by 6-5/8
Entree (preconcentrated and formed slices)	5 by 8
Oatmeal cookie and granola bars	3-1/2 by 5-3/4
Beverage base: orange compressed	2 by 5
Pudding bars (vanilla or chocolate)	2 by 5
Beef jerky	3-3/8 by 5-3/8
Pepperoni	3 by 5-3/8
Chocolate bar with toffee	2-3/8 by 5-7/8
Caramels	2-1/2 by 6-1/2
Fudge bar	2-3/8 by 5-7/8

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

TABLE I. Pouch dimensions (cont'd)

Item	Pouch inside dimensions (± 1/16 inch)
Fig bars	3-1/4 by 6

3.2 Pouch filling and sealing. The ration components shall be inserted in pouches, as specified in the applicable component specification or the assembly specification in such a manner as to avoid puncturing pouch material or contaminating seal area. The filled pouches shall be sealed under a vacuum as specified in table II with a 3/8 inch (± 1/8 inch) heat seal. The sealed pouch shall show no loss of vacuum when examined as specified in 4.3.2. If thermal impulse closure seals are used, a seal width of 1/8 inch will be acceptable. The closure seal shall not extend below the tear notch on either side of the pouch. The closure seal shall have an average seal strength of not less than 6 pounds per inch and no individual specimen shall have a seal strength of less than 5 pounds per inch when tested as specified in 4.3.4.

TABLE II. Vacuum requirements

Item	Vacuum requirement (Hg)
Entree (compressed bars)	28
Entree (preconcentrated and formed slices)	28
Oatmeal cookie and granola bars	28
Beverage base: orange compressed	28
Pudding bars (vanilla or chocolate)	28
Beef jerky	28
Pepperoni	28
Chocolate bars with toffee	10 to 15
Caramels	10 to 15
Fudge bar	10 to 15
Fig bars	8 to 12

3.3 Labeling and marking.

3.3.1 Mixing bag. Each mixing bag shall be clearly printed in a manner that does not damage the mixing bag material, with a permanent, grease/oil resistant, food compatible, black ink which is free of carcinogenic elements or ingredients. Size of the lettering shall be 5/32 inch block letters. The following information, as applicable, shall be located on the body of the mixing bag:

Source: https://assist.dla.mil -- Downloaded: 202640-22T00:11Z
Check the source to verify that this is the currentversion before use.

a. Entree bars:

CRUMBLE BARS INTO SMALL PIECES. ADD 1/3 CANTEEN CUP OF HOT WATER. SEAL BAG WITH PLASTIC FASTENER. WAIT 10 MINUTES. MORE WATER MAY BE ADDED.

b. Pudding bars:

MIXING BAG PUDDING

EAT AS IS OR CRUMBLE INTO SMALL PIECES. ADD WATER TO FILL LINE. KNEAD GENTLY. WAIT 5 MINUTES.

NOTE: In addition, mixing bags for the pudding bars shall have a 4 inch long fill line printed on the bag, 1-3/4 inches (± 1/16 inch) from the bottom seal, as follows:

Fill Line

3.3.2 Individual bag (for oatmeal cookie and granola bars). Each individual bag shall be clearly printed or stamped with the name of the product in a manner that does not damage the individual bag material, with a permanent, grease/oil resistant food compatible, black ink which is free of carcinogenic elements or ingredients. Size of lettering shall be 5/32 inch block letters.

3.3.3 Pouches. Each pouch shall be clearly printed or stamped, in a manner that does not damage the pouch, with permanent black ink which is free of carcinogenic elements or ingredients. The following information shall be located on the body of the pouch not closer than 1/16 inch to any seal. All pouches shall be coded. If a non-contact type printer is used, the following information, as applicable, may be located anywhere on the pouch, except the closure seal area:

a. Entree bars or slices:

Product name (letters not less than 7/32 inch high)
MIXING BAG WITH INSTRUCTIONS INSIDE (letters not less than 5/32 inch high)
Ingredients (letters not less than 3/32 inch high)
Date markings (in accordance with MIL-L-1497) (letters not less than 1/4 inch high)
Net weight (letters not less than 1/8 inch high)
Official establishment number (e.g. EST-38) (letters not less than 1/8 inch high)
Name and address of producer (letters not less than 1/8 inch high)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

b. Pepperoni or beef jerky:

Product name (letters not less than 7/32 inch high)
Ingredients (letters not less than 3/32 inch high)
Date markings (in accordance with MIL-L-1497) (letters not less than 1/4 inch high)
Net weight (letters not less than 1/8 inch high)
Official establishment number (e.g. EST-38) (letters not less than 1/8 inch high)
Name and address of producer (letters not less than 1/8 inch high)

c. Oatmeal cookie and granola bars:

Product name (letters not less than 7/32 inch high)
Name and address of producer (letters not less than 1/8 inch high)

d. Fig bars:

FIG BARS (letters not less than 7/32 inch high)
Name and address of producer (letters not less than 1/8 inch high)

e. Fudge bar:

FUDGE BAR (letters not less than 7/32 inch high)
EAT AS IS OR BREAK INTO SMALL PIECES IN CANTEEN CUP. ADD 1/3 CANTEEN CUP HOT WATER. STIR UNTIL DISSOLVED (letters not less than 5/32 inch high)
Name and address of producer (letters not less than 1/8 inch high)

f. Orange beverage bar:

ORANGE BEVERAGE BAR (letters not less than 7/32 inch high)
EAT AS IS OR BREAK INTO SMALL PIECES IN CANTEEN CUP. ADD 1/3 CANTEEN CUP OF WATER. STIR UNTIL DISSOLVED. (letters not less than 5/32 inch high)
Name and address of producer (letters not less than 1/8 inch high)

g. Chocolate or vanilla pudding bar:

Product name (letters not less than 7/32 inch high)
MIXING BAG WITH DIRECTIONS INSIDE (letters not less than 5/32 inch high)
Name and address of producer (letters not less than 1/8 inch high)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

h. Chocolate bars with toffee:

CANDY, CHOCOLATE BARS WITH TOFFEE, ENRICHED SWEET (letters not less than 7/32 inch high)
Name and address of producer (letters not less than 1/8 inch high)

i. Caramels:

CARAMELS (letters not less than 7/32 inch high)
Name and address of producer (letters not less than 1/8 inch high)

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all the requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and acceptance service. Product acceptability shall be determined by the USDA. The USDA will determine the degree of acceptance service nesessary to assure compliance with the requirements of this document. The cost of grading and acceptance services performed by the USDA involving inspection, official documentation, and related services shall be borne by the contractor.

4.3 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.3.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.3.1.1 Material certification. Material listed below shall be accepted on the basis of a contractor's certificate of conformance to the indicated requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

Requirement	Requirement paragraph	Test procedure
Mixing bag and individual bag material identification:	3.1.2 and 3.1.3	Laboratory evaluation
Mixing bag closure device	3.1.4	Visual examination
Thickness of films for laminated material	3.1.5.1	As specified in L-P-378, except that a machinists' micrometer may be used provided that its graduations and accuracy conform to the requirements of L-P-378
Aluminum foil thickness	3.1.5.1	As specified in QQ-A-1876
Laminated material identification and construction	3.1.5.1	Laboratory evaluation
Color of laminated material	3.1.5.1	Visual evaluation

4.3.1.2 Unfilled mixing bag or individual bag examination as applicable. The unfilled mixing bags or individual bags shall be examined for the defects listed in table III. The lot size shall be expressed in bags. The sample unit shall be one unfilled mixing bag or individual bag. The inspection level shall be S-4 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 0.65 for major defects.

TABLE III. Unfilled mixing bag or individual bag defects

Category	Defect
Major	
151	Not formed as specified
152	Inside dimensions not as specified
153	Tear, hole, or open seal
154	Required marking missing, incorrect,or illegible
155	Not material specified
156	Bags stick together
157	Not clean
158	Foreign odor

Source: https://assist.dla.mil -- Downloaded: 202640-22T00:11Z
Check the source to verify that this is the current version before use.

4.3.1.3 Unfilled mixing bag leakage testing. The unfilled mixing bags shall be tested for leakage as follows: Each sample bag shall be filled with 8 ounces of boiling water (being careful not to spill any water on the outside) and suspended 8 to 12 inches above a sheet of clean paper for 10 minutes. Any moisture on the paper attributable to bag leakage shall be considered a major defect. The lot size shall be expressed in bags. The sample unit shall be one bag. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

4.3.1.4 Unfilled pouch examination. The unfilled pouches shall be examined for the defects listed in table IV. The lot size shall be expressed in pouches. The sample unit shall be one unfilled pouch. The inspection level shall be S-4 and the AQL, expressed in terms of defects per hundred units, shall be 0.65 for major defects and 4.0 for minor defects.

TABLE IV. Unfilled pouch defects

Category		Defect
Major	Minor	
151		Not size specified
152		Heat seal dimensions on three edges not as specified
153		Tear, hole, or open seal
154		Not clean
155		Color not as specified
156		Not material specified
157		Individual pouches stick together or tear when separated
158		Pouch has foreign odor
	201	Tear notch missing
	202	Tear notch not located as specified
	203	Depth of tear notch not as specified

4.3.1.5 Unfilled pouch seal strength testing. The unfilled pouches shall be tested for seal strength in accordance with Method A or B of ASTM D 882 except that testing speed may be 10 or 12 inches per minute. The lot size shall be expressed in pouches. The sample size shall be the number of pouches indicated by inspection level S-1. Three adjacent specimens shall be cut from each of the three sealed sides of each pouch in the sample. The results shall be reported to the nearest 0.1 pound. The average seal strength of each seal shall be calculated by averaging the strengths of the three test specimens cut from that seal. Any test specimen failing to meet the individual test specimen seal strength requirement specified in 3.1.5.2 or any seal failing to meet the average seal strength requirement specified in 3.1.5.2 shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 202640-22T00:11Z
Check the source to verify that this is the current version before use.

4.3.1.6 Unfilled pouch integrity and air tightness of seals testing. The unfilled pouches shall be tested for conformance to the pouch integrity and air tightness of seals requirement in 3.1.5.2 by placing a rigid material similar in size and shape to the product, in the appropriate size pouch (see table I) and sealing under the applicable vacuum requirement specified in table II. The pouch shall be examined for vacuum loss in accordance with the procedure specified in 4.3.2 not less than 96 hours after sealing. Any evidence of loss of vacuum shall be considered a major defect. The lot size shall be expressed in pouches. The sample unit shall be one unfilled pouch. The inspection level shall be I and the AQL, expressed in terms of defects per hundred units, shall be 0.65.

4.3.2 Pouch vacuum examination. The filled and sealed pouches shall be visually examined for conformance to the vacuum requirement in 3.2 not less than 96 hours after filling and sealing. The sealed pouch shall continue to exhibit tight adherence to the surface contours of the contents when a pulling force is applied at the center of each side seal. This force shall be applied by holding each side seal between thumb and forefinger of each hand, while simultaneously exerting a slight pull with both hands. Any evidence of loss of vacuum shall be considered a major defect. The lot size shall be expressed in pouches. The sample unit shall be one filled and sealed pouch. The inspection level shall be I and the AQL, expressed in terms of defects per hundred units, shall be 0.65.

4.3.3 Filled and sealed pouch examination. The filled and sealed pouches shall be examined for the defects listed in table V. The lot size shall be expressed in pouches. The sample unit shall be one filled and sealed pouch. The inspection level shall be I and the AQL, expressed in terms of defects per hundred units, shall be 0.65.

TABLE V. Filled and sealed pouch defects 1/

Category	Defect
Major	
151	Not clean
152	Tear, hole, or open seal
153	Closure seal not produced by specified method
154	Evidence of delamination 2/
155	Closure seal width not as specified
156	Closure seal extends into or below tear notch
157	Pouch has foreign odor
158	Required marking missing, incorrect, or illegible
159	Contents caught in closure seal

1/ Any evidence of rodent or insect infestation shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:11Z
Check the source to verify that this is the current version before use.

2/ Delamination shall be scored as a defect except delamination of outer ply when located in the seal area 1/16 inch or further from food product edge of seal. Pouches exhibiting this type of delamination shall be tested by manually flexing the delaminated area ten times. The area of delamination shall be held between the thumb and forefinger of each hand with both thumbs and forefingers touching each other. The delaminated area shall be rapidly flexed by rotating both hands in alternating clockwise-counterclockwise directions. Care shall be exercised when flexing delaminated area near the tear notches to avoid tearing the pouch material. After flexing, the separated outer ply shall be grasped between the thumb and forefinger and gently lifted toward the food product edge of the seal. If the separated area is too small to be held between thumb and forefinger, a number two stylus shall be inserted into the delaminated area and a gentle lifting force applied against the outer ply. If separation of the outer ply can be made to extend to less than 1/16 inch from the product edge of the seal with no discernible resistance to the gentle lifting, the pouch shall be rejected.

4.3.4 Pouch closure seal testing. The filled and sealed pouches shall be tested for closure seal strength in accordance with method A or B of ASTM D 882 except that the testing speed may be 10 or 12 inches per minute. Three adjacent specimens, 1/2 or 1 inch wide, shall be cut from the top closure seal of each pouch in the sample. The results shall be reported to the nearest 0.1 pound per linear inch. The average seal strength of the closure seal shall be calculated by averaging the test results of the three test specimens cut from the seal. Any test specimen failing to meet the individual test specimen seal strength requirement of 3.2 or any closure seal failing to meet the average seal strength requirement specified in 3.2 shall be scored a defect. The lot size shall be expressed in pouches. The sample unit shall be one filled and sealed pouch. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 1.5.

5. PACKAGING

5.1 Packaging. This section is not applicable to this document.

6. NOTES

6.1 Ordering data. Acquisition documents should specify the title, number, and date of this document.

6.2 Use information. This document covers the packaging requirements for the following component items of the food packet, assault.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

Document No.	Product
	Entree component
MIL-C-44148(GL)	Chicken Stew, Cooked, Dehdyrated-(Operational Ration Component)
MIL-B-44140(GL)	Beef Stew, Cooked, Dehydrated-(Operational Ration Component)
MIL-E-44141(GL)	Escalloped Potatoes and Pork, Cooked, Dehydrated-(Operational Ration Component)
MIL-C-44137(GL)	Chicken a la King, Cooked, Dehydrated-(Operational Ration Component)
MIL-C-44138(GL)	Chicken and Rice, Cooked, Dehydrated-(Operational Ration Component)
MIL-V-44139(GL)	Vermicelli with Meat and Sauce, Cooked, Dehydrated-(Operational Ration Component)
	Other components
MIL-O-44136(GL)	Oatmeal Cookie and Granola Bars-(Operational Ration Component)
MIL-B-44135(GL)	Beverage Base: Orange Compressed-(Operational Ration Component)
MIL-P-44147(GL)	Pudding, Bar-(Operational Ration Component)
Z-C-2104	Candy and Chocolate Confections, Types III, VII, and VIII
Nabisco Fig Newton Cakes	Fig Bar
Smokecraft, Inc., Product Code 1350	Beef Jerkey
Smokecraft, Inc., Product Code 2500	Pepperoni

6.3 Closure device. The Flip-Clip Fastener is manufactured by the Dennison Manufacturing Company, Framingham, MA 01701.

Custodian:

Army - GL

Review activities:

Army - MD, TS
DP - SS

Preparing activity:

Army - GL

Project No. 89GP-A118

Source: https://assist.dla.mil -- Downloaded: 202640-22T00:11Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-P-44146(GL)	Packaging of Food Packet, Assault Components (In Pouches)

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 1 Apr 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.