MIL-V-44145
24 September 1984
SUPERSEDING
(see 6.4)

MILITARY SPECIFICATION

VEGETABLES, MIXED, DEHYDRATED, COMPRESSED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers dehydrated, compressed, mixed vegetables in disc form, for use by the Department of Defense as an item of general issue.

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

TT-C-495	-	Coatings, Exterior, For Tinned Food Cans
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-C-29	-	Canned Subsistence Items, Packaging and Packing of

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8915

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-1497 - Labeling of Metal Cans for Subsistence Items
MIL-L-35078 - Loads, Unit, Preparation of Nonperishable Subsistence Items, General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting officer or as directed by the contracting officer.)

OTHER GOVERNMENT DOCUMENTS

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder (21 CFR Parts 1-199)

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Interim Primary Drinking Water Regulations

(Application for copies should be addressed to the Office of Drinking Water, WH550, Environmental Protection Agency, Washington, DC 20406.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

U.S. Standards for Grades of Frozen Green Beans and Frozen Wax Beans

U.S. Standards for Grades of Frozen Lima Beans

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

U.S. Standards for Grades of Frozen Carrots

U.S. Standards for Grades of Frozen Whole Kernel (or Whole Grain) Corn

U.S. Standards for Grades of Frozen Peas

(Application for copies should be addressed to the Chief, Processed Products Branch, Fruit and Vegetable Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

U.S. Standards for Condition of Food Containers

(Application for copies should be addressed to the Director, Market Research and Development Division, Agricultural Marketing Service, Washington, DC 20250.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

AMERICAN DRY MILK INSTITUTE, INC.

Standards for Grades of Dry Milk, Including Methods of Analysis, Bulletin 916

(Application for copies should be addressed to the American Dry Milk Institute, Inc. 130 North Franklin Street, Chicago, IL 60606.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Suite 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 Bid sample. Unless otherwise specified (see 6.1), six cans with a net weight of at least 8 ounces each, representative of the product which the bidder proposed to furnish and which have been nitrogen gas packaged and comply with the document requirements, shall be submitted to the contracting officer prior to the bid opening. One of the samples shall be evaluated by a technical group at the U.S. Army Natick Research and Development Center to determine compliance with 3.4.2 for the subjective characteristics (flavor, odor, color, texture, and appearances). In addition, technical groups shall rate the samples as to overall quality, taking into consideration all the subjective characteristics. The remaining samples shall be held at 40°F or lower until used as a standard for the subjective characteristics in determining acceptance of intended delivery products. The approval of any bid sample for the aforementioned characteristics shall not constitute approval of the product as meeting the other requirements of this document

3.2 Ingredients. All ingredients shall be clean, sound, wholesome and shall be as specified herein or in referenced documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

3.2.1 Green beans. The green beans shall be Tender Green or other suitable round type variety, from the latest harvest and shall meet the U.S. Grade A requirements of the U.S. Standards for Grades of Frozen Green Beans and Frozen Wax Beans. The green beans shall be size graded so that not more than 3 percent are less than 18/64 inch and not more than 5 percent are more than 27/64 inch in thickness when the shorter diameter of the bean, transverse to the longitudinal axis at the thickest portion of the pod, is measured. The green beans shall be cut into approximately 1-inch segments.

3.2.2 Carrots. The carrots shall be Imperator, Red Chateney or a similar variety suitable for dehydration, shall be from the latest harvest, and shall meet the U.S. Grade A requirements of the U.S. Standards for Grades of Frozen Carrots. The carrots shall be diced into nominal 3/8 by 3/8 by 3/8 inch dice.

3.2.3 Corn. The corn shall be golden (or yellow) kernels of varieties such as Style Pack, Jubilee, Dividend, or Mellogold. The corn shall be from the latest harvest and shall meet the U.S. Grade A requirements of U.S. Standards for Grades of Frozen Whole Kernel (or Whole Grain) Corn.

3.2.4 Peas. The peas shall be of a freezer variety such as Thomas Laxton or Freezer Perfection and shall meet the U.S. Grade A requirements of the U.S. Standards for Grades of Frozen Peas. The peas shall be size graded so that not more than 5 percent are less than 10/32 inch and not more than 5 percent are more than 14/32 inch in diameter. The peas shall be perforated, slit or otherwise mechanically treated to aid dehydration and rehydration.

3.2.5 Lima beans. Lima beans shall be of a single variety such as Fordhook, of the latest harvest and shall meet the U.S. Grade A requirements of the U.S. Standard for Grades of Frozen Lima Beans.

3.2.6 Sodium sulfite or sodium acid sulfite. The sulfite(s) shall meet the requirements of the Food Chemicals Codex.

3.2.7 Water. Water used for ice making formulation, and washing shall conform to the National Interim Primary Drinking Water Regulations.

3.3 Preparation and processing.

3.3.1 Blanching. The vegetables shall be adequately blanched to the point of peroxidase enzyme inactivation. If the vegetables have been blanched only to catalase inactivation, additional blanching will be necessary.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

3.3.2 Sulfiting. The blanched vegetables, either prior to or after dehydration, shall receive a sulfite treatment by such a method as will insure a reasonably uniform distribution of the sulfite throughout the product and a residual sulfur dioxide content in the dehydrated product within the limitation specified in 3.4.1. Contact of the wet vegetables with iron, or other metals, subsequent to the sulfiting operation, shall be strictly avoided.

3.3.3 Dehydration. The vegetables shall be dehydrated by any method that produces a product that is unscorched or otherwise heat damaged and complies with the requirements of 3.4.1.

3.3.4 Mixing. The dehydrated vegetable components shall be mixed in such proportions as to meet the requirements of 3.4.2.

3.3.5 Conditioning. The dehydrated mixed vegetables shall be conditioned by spraying with moisture to increase the weight by 10 to 15 percent. The mixture shall be tumbled while spraying to insure thorough wetting and then heated in a closed container at 150°F for 5 minutes to equilibrate the moisture. Alternatively, any other method which provides equivalent results may be used.

3.3.6 Mechanical pressing. The moistened and sulfited vegetables shall be placed into a 3-3/4 ± 1/8 inch diameter mold and compressed into discs by applying adequate pressure and dwell time (see 6.3) to yield a cohesive disc which resists breakage during handling and packaging.

3.3.7 Redrying. The compressed vegetables shall be redried within a minimum of time so that the finished product complies with 3.4.1.

3.4 Finished product.

3.4.1 Compressed dehydrated product. The compressed dehydrated product shall be free from hay-like, scorched, musty, or other objectionable odors; shall not exceed 3.0 percent by weight of moisture; and shall contain a sulfite level (calculated as sulfur dioxide) of 570 ± 250 ppm, by weight.

3.4.2 Rehydrated product. The compressed vegetables shall rehydrate to approximately their original form when the disc of dehydrated compressed product is added to boiling water in the proportion of 12 ounces of water for every 1 ounce of product. The water shall be brought back to boiling, stirred

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

gently to break the disc apart and simmered for 2 minutes. After simmering the vegetables shall be allowed to stand for 5 minutes. The rehydrated product shall consist of the following:

Ingredient	Percent by weight
Green beans	32 ± 8
Carrots	20 ± 5
Corn	20 ± 6
Peas	20 ± 7
Lima beans	8 ± 4

The rehydrated product shall have a color, odor, flavor, texture and appearance typical of the vegetable component and shall contain not more than 2 percent by weight of defective pieces. A piece shall be considered defective if it has been damaged by insect or pathological injury, decay, scorch, bruise, dirt, discoloration or any other abnormality.

3.4.3 Palatability. The product shall be comparable to the approved bid sample in color, odor, flavor, texture and appearance.

3.5 Plant qualification. The product shall be prepared, processed, and packaged under sanitary conditions in accordance with good manufacturing practice. The product shall be processed in establishments meeting the sanitary requirements of the applicable Government inspection agency.

3.6 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and acceptance service. Product acceptability shall be determined by the USDA. The USDA will determine the degree of acceptance service necessary to assure compliance with the requirements of this docu-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

ment. The cost of grading and acceptance services performed by the USDA involving inspection, official documentation, and related services shall be borne by the contractor.

4.3 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.3.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.3.1.1 Ingredient examination. Conformance of ingredients to identity and condition requirements shall be determined by examination of pertinent labels, markings, U.S. Grade certificates, invoices, certificates of analysis, or other valid documents. In addition, each ingredient shall be examined organoleptically as necessary to determine conformance to the condition requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient lot or of any involved product.

4.3.1.2 Unfilled can inspection. Conformance of unfilled cans to the requirements specified in 5.1.1 shall be determined by examination of certificates of conformance or other valid documents. Any nonconformance shall be cause for rejection of the can lot or of any involved product.

4.3.2 In-process inspection.

4.3.2.1 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.3.2.2 In-process testing. As each production run is initiated, a sample of the blanched vegetables prior to dehydration, shall be tested in accordance with 4.4.4. A test result indicating active peroxidase enzymes shall be cause for reblanching of the affected lot of vegetables until the peroxidase enzymes have been inactivated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

4.3.3 Net weight examination. The cans of product shall be examined for net weight. Any individual sample having a net weight of less than 15.25 ounces shall be scored as a minor defect. The lot size shall be expressed in units of cans. The sample unit shall be one can of product. The inspection level shall be S-3 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5. In addition, the lot shall be rejected if the sample average net weight is less than 16.0 ounces.

4.3.4 Can condition examination. Examination of the filled and sealed cans shall be in accordance with the U.S. Standards for Condition of Food Containers, except that inspection for labeling shall be in accordance with MIL-L-1497 (see 5.4).

4.3.5 Product examination. The finished product shall be examined for the defects listed in table I. The lot size shall be expressed in cans. The sample unit shall be the contents of one filled and sealed can. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 1.5.

TABLE I. Product defects 1/

Category	Defect
Major	Dehydrated product
151	Presence of hay-like, scorched, musty, or other objectionable odors.
	Rehydrated product 2/ 3/
152	Vegetables do not rehydrate to their original form.
153	Vegetable proportions not as specified.
154	More than 2 percent by weight of defective pieces.
155	Color, odor, flavor, texture, and appearance not typical of mixed vegetables. 3/

1/ The presence of any foreign material (e.g. glass, dirt, insect parts, hair, wood, metal, etc.), foreign odor or flavor (e.g. burnt, scorched,

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

moldy, rancid, sour, stale, etc.), or foreign color shall be cause for rejection of the lot.

2/ The dehydrated compressed vegetables shall be rehydrated by adding 12 ounces of water to 1 ounce of vegetables in accordance with 3.4.2. The rehydrated vegetables shall be drained on a U.S. No. 8 sieve for 5 minutes, sorted, and each component weighed individually. The percent by weight of the components of each disc shall comply with 3.4.2.

3/ Product not equal to or better than the approved bid sample (see 6.1) in color, odor, flavor, texture, and appearance shall be cause for rejection of the lot. (This comparison shall only be performed when deemed necessary by the AMS agent.)

4.3.6 Moisture and sulfur dioxide content testing. The finished product shall be tested as specified in 4.4.1 and 4.4.2 for conformance to the moisture and sulfur dioxide requirements in 3.4.1. The sample for testing shall be a 4-ounce composite, derived from the number of cans indicated by inspection level S-2. The lot size shall be expressed in units of cans. Results shall be reported to the nearest 0.1 percent for moisture and to the nearest 10 ppm for sulfur dioxide. A test failure for either moisture or sulfur dioxide content shall be cause for rejection of the lot.

4.3.7 Oxygen in headspace testing. The filled and sealed cans shall be tested as specified in 4.4.3 for conformance to oxygen in headspace requirement in 5 1.1. Any test result not conforming to the requirement in 5.1.1 shall be scored a major defect. The lot size shall be expressed in cans. The sample unit shall be one filled and sealed can. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

4.3.8 Can labeling examination. Examination of can labeling shall be in accordance with MIL-L-1497 (see 5 4).

4.3.9 Leakage inspection. Inspection for leakage shall be in accordance with PPP-C-29 (see 5.1 1)

4.3.10 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure and reinforcement in accordance with the appendix of PPP-B-636. In addition, the following defects shall be classified as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

Major: National stock number, item description, contract number or date of pack markings missing, incorrect, or illegible.

Minor: Other required markings missing, incorrect, or illegible.
Arrangement or number of cans not as specified.
Contents not snug-fitting.
Reinforcement with nonmetallic strapping or tape is not used.
Tier pad separator missing or not as specified.

4.3.11 Unit load inspection. Inspection of unit loads shall be in accordance with quality assurance provisions of MIL-L-35078.

4.4 Methods of inspection.

4.4.1 Moisture content test. Prepare a clean, dry Waring blender or similar mill by grinding a sample and discarding it. Grind approximately 100 grams of a well mixed sample in the prepared blender. Pass the ground material through a U.S. Standard No. 20 sieve and collect that portion which passes through in a clean, dry, tightly closed container. Weigh two samples, approximately 3 grams each of the sieved material, into tared, dry, aluminum weighing dishes (approximately 2 or 1-1/2 inches in diameter and 3/4 inch in depth) with tight-fitting covers. Place the dishes with cocked lids in a vacuum oven and dry for 16 hours at 60°C under a pressure of not more than 100 mm mercury. During drying, admit to the oven a slow current of air (approximately two bubbles per second) dried by passing through concentrated sulfuric acid. Remove the dishes and allow them to cool in a desiccator before weighing. Calculate the percent of moisture in the original samples.

4.4.2 Sulfur dioxide content test. Sulfur dioxide content of the ground sample shall be determined in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, Chapter: Food Additives: Direct, section: Chemical Preservatives, method: Total Sulfurous Acid, Modified Monier-Williams.

4.4.3 Oxygen content test. Oxygen content of the headspace gas shall be determined in accordance with the American Dry Milk Institute, Inc., publication, bulletin 916, Standards for Grades of Dry Milks, Including Methods of Analysis: Determination of Oxygen. Alternatively, the headspace oxygen content may be determined by an Instrumentation Laboratories Oxygen Analyzer or equivalent instrument. Test results shall be reported to the nearest 0.1 percent. When referee testing is necessary, The American Dry Milk Institute Method shall be followed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

4.4.4 Peroxidase activity test. The test to show adequate blanching shall be made in accordance with one of the following procedures:

a. Reagents. (Reagents shall be reagent grade, Analytical Reagent or Chemically pure as defined by the American Chemical Society in the A.C.S. Analytical Reagents or meet the requirements of the Food Chemicals Codex.)

Distilled water.
0.5 percent guaiacol in 50 percent ethyl alcohol solution.
0.08 percent hydrogen peroxide (2.8 mL of 30 percent hydrogen peroxide per liter). Keep in refrigerator in dark bottle and renew solution each week or two.
Clean sand.

b. Apparatus:

Test tubes, 3/4 or 7/8 inch in diameter.
3 or 4 inch diameter funnels.
6 or 7 inch cotton milk filters.
Waring blender or similar mixer or porcelain mortar (4 to 6-inch diameter) and pestle.
50 mL graduated cylinder.
1 and 2 mL pipettes.
Timer or watch with second hand.
Test tube rack.
Balance which will weigh 200 gram samples to $\pm$ 0.1 gram (A triple-beam type balance is recommended).
If blender is used, a larger sample will permit use of less sensitive balance.

c. Procedure, using blender:

1. Weigh out representative 100 to 200 gram sample.
2. Place in blender with 3 mL of water to each gram of vegetable.
3. Grind for 1 minute at moderate or high speed.
4. Filter through cotton milk filter.
5. Add 2 mL of filtrate to 20 mL of distilled water in test tube.
6. Prepare a blank by adding 2 mL of filtrate to 22 mL of distilled water in a second test tube, mix and use as a color comparison tube. (Do not add any guaiacol or peroxide to this tube.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

7. Add 1 mL of 0.5 percent guaiacol solution to first test tube without mixing.
8. Add 1 mL of 0.08 percent hydrogen peroxide to the same tube without mixing.
9. Mix contents thoroughly by inverting and watch for development of any color differing from the blank, regardless of hue, but of sufficient intensity to show an obvious contrast. Development of color is a positive test and indicates inadequate blanching. If no color contrast develops in 3-1/2 minutes, consider the test negative and the product adequately blanched. If color develops after 3-1/2 minutes, it is to be disregarded and the test still considered negative.

d. Procedure, using mortar:

1. Slice product to be tested into small pieces and weigh out representative 10 gram sample.
2. Place 30 mL of distilled water in graduated cylinder.
3. Place sample in mortar with a little clean sand, add minimum amount of water from graduated cylinder to give best consistency for thorough maceration, and grind for 3 minutes. Add remainder of water from cylinder and mix.
4. Proceed as under c. above, 4 through 9 inclusive.

NOTE: Because of the limits of mortar grinding when using mortar with 10-gram samples, special attention should be given to assuring representative samples. Sample size can be increased to 20 to 30 grams with additional time given to grinding, or the number of units represented can be increased by halving or quartering, if the sample is uniform.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A or C, as specified (see 6.1).

5.1.1 Level A. A net weight of 16.0 ounces of compressed discs shall be unit packed in a size 401 by 411 can. A minus tolerance of 0.75 ounce will be permitted in any individual can provided that the average net weight of cans examined in accordance with 4.3.3 is not less than 16.0 ounces. The can shall be an open top style, round, metal can with soldered or welded side seam and compound-lined, double-seamed ends. The can shall be made throughout from

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

not less than commercial 0.25-pound per base box electrolytic tin plate (see 4.3.1.2) and shall be coated overall on the outside with a coating conforming to type I or when specified (see 6.1) type III of TT-C-495. The can shall have a sufficient base plate weight and temper to protect the product during shipment and storage. The can shall be hermetically sealed under an atmosphere of nitrogen so that the oxygen content of the headspace gases in the filled and sealed container shall not exceed 2.0 percent when tested in accordance with 4.3.7. The can shall not leak when examined in accordance with 4.3.9.

5.1.2 Level C. The product shall be preserved as specified in 5.1.1 except that cans with or without commercial exterior coating will be acceptable. Alternatively, cans may be made from 0.20 pound per base box electrolytic tinplate, provided the cans have an exterior commercial coating.

5.2 Packing. Twenty-four cans of product, preserved as specified in 5.1, shall be packed on end 4 in length, 3 in width, and 2 in depth, within a snug-fitting shipping container in accordance with level A, B or C as specified (see 6.1).

5.2.1 Level A packing. The shipping container shall be a fiberboard box, constructed and closed in accordance with style RSC, V2s of PPP-B-636. The tiered cans shall be separated with a full length and width fiberboard pad made of the same material as the box. Each fiberboard box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. The shipping container shall be a fiberboard box, constructed and closed in accordance with style RSC, V3c, V3s, or V4s of PPP-B-636 The tiered cans shall be separated with a full length and width fiberboard pad made of the same material as the box Each fiberboard box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament reinforced tape in accordance with the appendix of PPP-B-636.

5.2.3 Level C packing. The shipping container shall comply with the National Motor Freight Classification or Uniform Freight Classification, as applicable, except the closure of the fiberboard box shall be in accordance with method II as specified in the appendix of PPP-B-636. The tiered cans shall be separated with a full length and width pad.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping.

5.4 Labeling and marking.

5.4.1 Cans. Can shall be labeled in accordance with MIL-L-1497 and shall include the following information:

VEGETABLES, MIXED, DEHYDRATED, COMPRESSED

Net weight 16 oz.
Name and address of supplier
Date packaged
Preserved with Sulfur Dioxide
GAS-PACKED

DIRECTIONS FOR USE

Vegetables, Mixed, Dehydrated, Compressed	16 oz. (401 x 411 can)
Water, hot	6 quarts
Salt	2 tbsp.
Butter or margarine	6 ounces
Pepper, Black	1/2 tsp.

Add mixed vegetable discs to boiling salted water. Return water to boiling, stirring discs gently to break apart. Simmer 2 minutes, turn off heat and let vegetables remain in liquid 5 to 7 minutes. Reserve 1-1/3 cups of cooking liquid, drain balance and place vegetables in serving pan. Combine melted butter and pepper with the reserved liquid. Pour over mixed vegetables.

YIELD: 34 servings of 1/2 cup each.

5.4.2 Shipping containers. Shipping containers shall be marked in accordance with MIL-STD-129.

5.4.3 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this document
b. When a bid sample is not required (see 3.1).
c. Levels of preservation and packing required (see 5.1 and 5.2).
d. When type III exterior coating of the cans is required (see 5.1.1).
e. Type and class of unit load when required (see 5.2.1 and 5.3).

6.2 Appropriate level of pack. Based on conditions known or expected to be encountered during shipment, handling, and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.3 Mechanical pressuring procedure. Satisfactory compressed discs have been obtained by using a pressure of 1000 to 1500 pounds per square inch and a dwell time of 10 to 30 seconds.

6.4 Supersession data. This document includes the requirements of LP/P DES 3-77 - Vegetables, Mixed, Dehydrated, Compressed, dated 1 March 1977.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Preparing activity:

Army - GL

Project No. 8915-0777

Review activities:

Army - MD, TS
Navy - MC, MS
DP - SS

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
US Army Natick Research and Development Center
Natick, Massachusetts 01760-5014

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1 DOCUMENT NUMBER	2 DOCUMENT TITLE
MIL-V-44145	Vegetables, Mixed, Dehydrated, Compressed

3a. NAME OF SUBMITTING ORGANIZATION	4 TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)* _____

5 PROBLEM AREAS

a. Paragraph Number and Wording

b Recommended Wording

c Reason/Rationale for Recommendation

6 REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8 DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

NATICK OP: 1 Apr 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.