MIL-A-37571A
3 August 1978
SUPERSEDING
MIL-A-37571
3 June 1976

MILITARY SPECIFICATION

ALUMINUM HYDROXIDE GEL, DRIED, MAGNESIUM HYDROXIDE AND SIMETHICONE TABLETS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers Aluminum Hydroxide Gel, Dried, Magnesium Hydroxide and Simethicone Tablets.

1.2 Classification. The tablets covered by this specification shall be of the following sizes and strengths (see 6.2):

Strength 1 - Regular Strength
Strength 2 - Double Strength

Size 1 - Individually sealed, 60s
Size 2 - Individually sealed, 100s

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Personnel Support Center, Directorate of Medical Materiel, DPSC-ATT, 2800 South 20th Street, Philadelphia, PA 19101, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 6505

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:01Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-C-186 - Containers, Packaging and Packing for Drugs, Chemicals and Pharmaceuticals.

STANDARDS

FEDERAL

FED-STD-140 - Tablets (for Medicinal Purposes).

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposals shall apply.

U. S. DEPARTMENT OF HEALTH, EDUCATION, AND WELFARE,
FOOD AND DRUG ADMINISTRATION (FDA)

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder.

(Application for copies should be addressed to the Food and Drug Administration, Washington, D.C. 20204.)

U.S. PHARMACOPEIAL CONVENTION, INC.

The United States Pharmacopeia (USP).

(Application for copies should be addressed to the Mack Publishing Company, Easton, PA 18042.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:01Z
Check the source to verify that this is the current version before use.

The National Formulary (NF).

(Application for copies should be addressed to the Mack Publishing Company, Easton, PA 18042.)

3. REQUIREMENTS

3.1 Material. Shall be Aluminum Hydroxide Gel, Dried, Magnesium Hydroxide and Simethicone Tablets and shall be in accordance with all applicable requirements of FED-STD-140, and as specified herein.

S2. Classification. Shall be type I, class 1.

S5.3 The following is added to this paragraph:

* For strength 1, shall be flavored, chewable tablets containing in each tablet, dried aluminum hydroxide gel equivalent to 200 mg of aluminum hydroxide, 200 mg of magnesium hydroxide and 20-25 mg of simethicone within the designated assay limits for the tablets.

For strength 2, shall be flavored, chewable tablets containing in each tablet, dried aluminum hydroxide gel equivalent to 400 mg of aluminum hydroxide, 400 mg of magnesium hydroxide and 30 mg of simethicone within the designated assay limits for the tablets.

S6.4.10.1 Uncoated tablets. The tablets shall meet the requirements of the weight variation test as set forth in the USP, including any supplements or revisions thereto.

3.2 Tests.

3.2.1 Assay for aluminum oxide.

3.2.1.1 Strength 1. For strength 1, the aluminum oxide content of each tablet shall be not less than 90.0 mg and not more than 115.0 mg, when assayed as specified in 4.5.1.

3.2.1.2 Strength 2. For strength 2, the aluminum oxide content of each tablet shall be not less than 180.0 mg and not more than 230.0 mg, when assayed as specified in 4.5.1.

3.2.2 Assay for magnesium.

3.2.2.1 Strength 1. For strength 1, the magnesium content of each tablet shall be not less than 76.6 mg and not more than 88.7 mg, when assayed as specified in 4.5.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:01Z
Check the source to verify that this is the current version before use.

3.2.2.2 Strength 2. For strength 2, the magnesium content of each tablet shall be not less than 153.3 mg and not more than 177.6 mg, when assayed as specified in 4.5.2.

3.2.3 Assay for simethicone.

* 3.2.3.1 Strength 1. For strength 1, the simethicone content of each tablet shall be not less than 18.0 mg and not more than 27.5 mg when assayed as specified in 4.5.3.

3.2.3.2 Strength 2. For strength 2, the simethicone content of each tablet shall be not less than 27.0 mg and not more than 33.0 mg, when assayed as specified in 4.5.3.

* 3.2.4 Acid neutralizing capacity. The acid neutralizing capacity shall be in accordance with the requirement and test for acid neutralizing capacity as specified in the over-the-counter drugs monograph for antacid and anti-flatulent products.

3.2.5 Defoaming activity. The defoaming activity of the tablets shall be not more than 45 seconds for strengths 1 and 2, when determined as specified in 4.5.4.

3.3 Flavor and palatability. The tablets shall be flavored, and shall be palatable and pleasant to the taste with no unpleasant aftertaste, when chewed. Not later than the time specified for opening of bids or receipt of proposals, the offeror shall submit to the contracting officer six (6) individually packaged samples (each containing 60 tablets for size 1, or 100 tablets for size 2) of Aluminum Hydroxide Gel, Dried, Magnesium Hydroxide and Simethicone Tablets, representative of the product which the offeror proposes to furnish. Two (2) samples will be subjected to panel testing for a determination of palatability (see 4.5.5 - Palatability test). A portion will be used by the cognizant Government inspection and quality assurance activities for determining compliance of supplies furnished hereunder with the palatability requirement. Approval as to palatability of any sample submitted by the offeror will not constitute approval of the sample as to any other requirement of this specification. The requirement for submission of samples for use in determining compliance with the palatability requirement may be waived, provided the offeror states, in his bid or proposal, that the product he proposes to furnish is the same product he has offered to the purchasing activity on a previous procurement and the contracting officer determines that such product was previously procured and/or tested by the purchasing activity and found to comply with the specification requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:01Z
Check the source to verify that this is the current version before use.

3.4 Ingredients.

3.4.1 Dried aluminum hydroxide gel. The dried aluminum hydroxide gel used in the manufacture of the tablets shall comply with the tests, standards, and requirements of the USP, including any supplements or revision thereto.

3.4.2 Magnesium hydroxide and simethicone. The magnesium hydroxide and simethicone used in the manufacture of the tablets shall comply with the tests, standards, and requirements of the NF, including any supplements or revisions thereto.

3.5 Other ingredients. All other ingredients used in the manufacture of the tablets shall comply with S5.1 of FED-STD-140.

3.6 Delivery. Not more than 6 months shall have elapsed from the date of manufacture of the tablets to the date of delivery to the Government.

4. QUALITY ASSURANCE PROVISIONS

4.1 Supplier responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and, (i) as to any expiration dated item, for the expiration dating period specified by the contractor for such item, or such longer period as may be required by by regulation of any federal agency; or (ii) as to non-dated items, for not less than 3 years after delivery of the item to the Government.

4.1.2 No company supplying any ingredient(s) to the contractor will be considered an acceptable facilitiy for the performance of any inspection requirements specified herein.

4.2 Sampling. Sampling shall be conducted in accordance with FED-STD-140.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:01Z
Check the source to verify that this is the current version before use.

4.3 Packaging inspection. The inspection of the intermediate packge, packing and marking for shipment and storage shall be in accordance with quality assurance provisions of the applicable container specification and the marking requirements of MIL-STD-129.

4.4 Labeling inspection. Sampling shall be in accordance with MIL-STD-105 and the unit of product shall be the unit issue. The inspection lot shall be the number of units of issue of each batch, lot, control number, etc., offered for inspection at one time. The inspection level for labeling shall be S-2 and the accceptance number shall be zero.

4.5 Tests.

4.5.1 Aluminum oxide.

Reagents:

1. Concentrated hydrochloric acid (HCl).
2. 0.05 M disodium ethylenediaminetetraacetate (EDTA) - Prepare and standardize as described in the USP.
3. Ammonium acetate buffer - Dissolve 77.1 grams of ammonium acetate in purified water, add 57 ml of glacial acetic acid, and dilute with purified water to 1000 ml.
4. SDA-3A alcohol.
5. Dithizone - Dissolve 25.6 mg of dithizone in 100 ml of SDA-3A alcohol.
6. 0.05 M zinc sulfate - Dissolve 14.4 grams of zinc sulfate, heptahydrate $ZnSO_4.7H_2O$) or 9.0 grams of zinc sulfate, dried ($ZnSO_4.H_2O$) in sufficient purified water to make 1 liter. Standardize as follows:

Pipet 10 ml of standardized EDTA solution into a 125 ml Erlenmeyer flask and add in the order given: 10 ml ammonium acetate buffer, 25 ml of SDA-3A alcohol and 1 ml dithizone. Titrate with the zinc sulfate solution to a clear rose-pink color. Calculate the molarity of the zinc sulfate solution.

Procedure:

Weigh and finely powder not less than 20 tablets. Weigh accurately a portion of the powdered tablets, equivalent to one tablet for strength 2 and two tablets for strength 1 into a 150 ml beaker. Add 50 ml of purified water and 5 ml of concentrated HCl to the beaker and boil for 15 minutes.

Source: https://assist.dla.mil -- Downloaded: 202610-21T11:01Z
Check the source to verify that this is the currentversion before use.

Filter (if necessary) into a 100 ml volumetric flask, cool to room temperature, dilute to the mark with purified water and shake. Pipet 10 ml of this solution into 150 ml beaker, add a Teflon stirring bar and place the beaker on a magnetic stirrer. Add in the order named with constant stirring, 15.0 ml of EDTA, 10 ml of ammonium acetate buffer, 25 ml of SDA-3A alcohol and 1 ml of dithizone solution. Titrate with 0.05M zinc sulfate solution to a color change from blue-green to rose-pink. Perform a blank titration substituting 10 ml of purified water for the sample.

Calculate the amount of aluminum oxide present in the sample as follows:

* Calculation:

$$\frac{(V_B - V_S) \times M \times 50.98 \times 100 \times W_T}{10 \times W_S} = \text{mg aluminum oxide/tablet}$$

Where:

V_B = mls of 0.05M zinc sulfate required by the blank
V_S = mls of 0.05M zinc sulfate required by the sample
M = actual molarity of the zinc sulfate solution
50.9 = equivalent weigth of aluminum oxide (mg)/ml
$\frac{100}{10}$ = dilution factor
W_T = average weight of one tablet, in grams
W_S = weigth of sample used, in grams

4.5.2 Magnesium.

Reagents:

1. Concentrated hydrochloric acid.
2. 0.05M Disodium ethylenediaminetetraacetate (EDTA) (Standardized).
3. Triethanolamine, reagent grade.
4. Triethanolamine solution - Dilute triethanolamine, reagent grade 1:1 with purified water.
5. Ammonium chloride, reagent grade.
6. Ammonium hydroxide, ACS.
7. Ammonia Buffer solution - Dissolve 6.75 grams of ammonium chloride, reagent grade in 30 ml of purifed water. Add 57 ml of ammonium hdyroxide, 58 percent analytical reagent and dilute to 100 ml with purified water.

Source: https://assist.dla.mil -- Downloaded: 202640-21T11:01Z
Check the source to verify that this is the currentversion before use.

8. Eriochrome Black-T.
9. Hydroxylamine hydrochloride, reagent grade.
10. Methanol.
11. Eriochrome Black-T indicator - Dissolve 500 mg of Eriochrome Black-T and 4.5 gram of hydroxylamine hydrochloride in methanol to make 100 ml of solution.

Procedure:

Weigh and finely powder not less than 20 tablets. Weigh accurately a portion of the powdered tablets equivalent to one tablet for strength 2 and two tablets for strength 1.

Transfer the sample into a clean 150 ml beaker. Add 5 ml of concentrated hydrochloric acid and 50 ml of purified water, and place on a hot plate for 15 minutes. Remove the beaker and filter the solution into a 100 ml volumetric flask through type D (or equivalent) fast filter paper. Wash the filter paper with small portions of hot purified water and add these washings to the filtrate. Cool to room temperature, dilute to mark with purified water and mix thoroughly. Pipet 10 ml of this solution into a 250 ml flask of triethanolamine solution, 5 ml of 0.05M EDTA solution, 4 drops of Eriochrome Black-T indicator and 5 ml of ammonia buffer.

NOTE: This order of the addition of the reagents is important to prevent the precipitation of the Magnesium from the solution. Titrate with 0.05M EDTA solution to a blue endpoint. The color change is red to blue. Titrate slowly near the endpoint as the color change occurs slowly at the endpoint. Record the total volume of EDTA used (including the original 5 ml added previous to titration) and calculate the amount of magnesium present in the sample as follows:

Calculation:

$$\frac{M \times V \times 1.216 \times 100 \times W_T}{0.05 \times 10 \times W_S} = \text{mg magnesium/tablet}$$

Where:

M = actual molarity of EDTA solution
V = total volume of EDTA solution, in ml
1.216 = equivalent weight of magnesium, in mg/ml
$\frac{100}{10}$ = dilution factor
W_T = average weight of one tablet, in grams
W_S = weight of sample used, in grams

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:01Z
Check the source to verify that this is the current version before use.

4.5.3 Simethicone.

* Reagents:

1. Carbon tetrachloride, analytical reagent grade.
2. Hydrochloric acid, 6N.
3. Polydimethylsiloxane NF Reference Standard.

* Polydimethylsiloxane Standard

Accurately weigh approximately 1.000 gram of Polydimethylsiloxane NF Reference Standard into a 250 ml volumetric flask with carbon tetrachloride and mix. This standard may be stored at room temperature for approximately one month.

Procedure:

Weigh and finely powder not less than 20 tablets. Weigh accurately to the nearest mg a portion equivalent to approximately 40 mg of simethicone into a 50 ml centrifuge tube. Add 10.0 ml of carbon tetrachloride and 10 ml of 6N HCl, stopper tightly, and shake on a reciprocal shaker for 30 minutes. Remove from the shaker and centrifuge for 5 minutes. Filter through phase separating paper and collect the carbon tetrachloride filtrate in a beaker. Using a glass syringe, fill a sodium chloride sample cell (0.2 mm) with the filtrate. Fill the 0.2 mm reference cell with carbon tetrachloride. Place the cells in a IR spectrophotometer and scan from 1350 to 1150 cm^{-1} at medium speed. Obtain the net absorbance of the C-Si stretching band occurring at approximately 1268 cm^{-1}. (The net absorbance is obtained by subtracting the baseline absorbance at the same wavelength from the maximum absorption of the band.) The baseline for sample & standard is obtained by extrapolating the absorption line from 1340 cm^{-1} and 1200 cm^{-1}. Pipet 10.0 ml of the stock polydimethylsiloxane standard solution into a 50 ml centrifuge tube containing 10 ml of 6N HCl and treat the same as the sample starting with "shake on a reciprocal shaker for 30 minutes . . ." Calculate the simethicone content of the sample.

Calculation:

$$\frac{Au \times Wstd \times W_T}{As \times 0.9575 \times W_S} = \text{simethicone/tablet}$$

Where:

Au = net absorbance of sample at 1268 cm^{-1}
As = net absorbance of standard at 1268 cm^{-1}
Wstd = weight of standard, mg/10ml
* 0.9575 = conversion factor (from polydimethylsiloxane to simethicone)
W_T = average weight of one tablet, in grams
W_S = weight of sample used, in grams

Source: https://assist.dla.mil -- Downloaded: 20260-21T11:01Z
Check the source to verify that this is the current version before use.

4.5.4 Defoaming activity.

Reagents:

1. Triton X-100.
2. F. D. & C. Blue #1.
3. Hydrochloric acid, concentrated, reagent grade.

Procedure:

Preparation of Foaming Solution

Prepare a 1 percent (W/v) solution of Triton X-100 in purified water.
Add 8.3 ml of concentrated hydrochloric acid and 5 mg of F.D. & C. Blue #1 of each liter of solution.

Preparation of Samples

For strength 1, grind one tablet into a fine powder with a mortar and pestle. For strength 2, grind one tablet into a fine powder with a mortar and pestle and accurately weigh a sample portion equivalent to 2/3 tablet weight. Pour 100 ml of the foaming solution into a jar, cap, and place in a 37°C water bath for approximately 20 minutes. Remove the jar from the water bath & clamp into position on a shaker (see Note 1). Add the prepared sample directly to the jar; cap and shake for 10 seconds using the number 10 setting on a Burrell wrist action shaker, model BB, or other equivalent shaker. Determine the foam collapse time in seconds. The collapse time is taken when the first position of the foam free liquid surface can be observed.

Note:

1. The shaker clamp should be adjusted so that the distance between the center of the shaft and the center of the jar is 5-1/4 inches.

4.5.5 Palatability test. A taste panel consisting of 10 members will be used to determine acceptability of samples. Samples will be prepared for testing (samples will be tested undiluted), coded, served to panel members under controlled serving conditions, e.g., all samples will be of the same amount, and served at the same temperature; each panel member will receive an equal number of samples; the order of serving will be varied among panel members; an interval of at least five (5) minutes will elapse between successive samples and panel members will rinse their mouths with water (room temperature) after each sample; panel members will test without interference either from each other or from outsiders. The product offered

Source: https://assist.dla.mil -- Downloaded: 202610-21T11:01Z
Check the source to verify that this is the currentversion before use.

shall be rated equal to or better than the Palatability Standard, 1/ when determined by the taste panel, using the following 9-point hedonic rating scale. The average rating of the samples shall be equal to or greater than the average rating of the standard, similarly prepared and tested.

1	2	3	4	5	6	7	8	9
Dislike extremely	Dislike very much	Dislike moderately	Dislike slightly	Neither like nor dislike	Like slightly	Like moderately	Like very much	Like extremely

1/ The Palatability Standard is available upon separate request to the contracting officer, Defense Personnel Support Center, Directorate of Medical Materiel.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with all applicable requirements of PPP-C-186, and as specified herein.

5.2 Packaging. Packaging shall be level A or C, as specified (see 6.1).

5.2.1 Unit of issue. One box containing 60 tablets of size 1 or one box containing 100 tablets of size 2, as specified, constitutes one unit of issue.

5.2.2 Level A.

5.2.2.1 Immediate container: size 1 and size 2. The immediate container for size 1 and size 2 shall be a commercially available blister or strip packaging considered acceptable by the Food and Drug Administration (FDA) for the product contained therein and shall be of such compatability that neither the contents nor the container are altered in any way by each other.

5.2.2.2 Unit packaging. Each unit shall be packaged as specified in 5.2.5 of PPP-C-186.

5.2.3 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose.

5.3 Packing. Packing shall be level A, B or C, as specified (see 6.1).

Source: https://assist.dla.mil -- Downloaded: 202640-21T11:01Z
Check the source to verify that this is the currentversion before use.

5.3.1 Level A. Seventy-two (72) units of issue of size 1 or one hundred forty-four (144) units of issue of size 2 shall be packed as specified in 5.4.4 of PPP-C-186.

5.3.2 Level B. Seventy-two (72) units of issue of size 1 or one hundred forty-four (144) units of issue of size 2 shall be packed as specified in 5.4.3.1.1 of PPP-C-186.

* 5.3.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, to point of delivery called for in the contract or purchase order.

5.4 Marking.

* 5.4.1 Labeling. Labeling shall be in accordance with the requirements of the Federal Food, Drug and Cosmetic Act, and regulation promulgated thereunder, and shall iinclude the information required below:

5.4.1.1 Immediate container. Each immediate container label shall bear the following information:

(a) label information in accordance with commercial practice.

5.4.1.2 Unit package. Each unit package label shall bear the following information:

(a) label information in accordance with commercial practice.
(b) the National Stock Number.
(c) the date of manufacture prefixed by "MFD".

* NOTES: (1) The National Stock Number need not be preceded by any prefix.
(2) Strip labeling may be used.
(3) Label adhesion test shall not apply.

5.4.2 Intermediate package. Each intermediate package shall be marked as specified in 5.5.3 of PPP-C-186. Date of manufacture shall be shown in lieu of date packed.

5.4.3 Exterior container. Exterior containers shall be marked as specified in 5.5.4 of PPP-C-186. Date of manufacture shall be shown in lieu of date packed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:01Z
Check the source to verify that this is the current version before use.

* 6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) National Stock Number.
(c) Selection of applicable levels of packaging and packing (see 5.2 and 5.3).

6.2 This specification covers the following items:

National Stock Number	Item Identification	Specification Designation
6505-00-149-0121	ALUMINUM HYDROXIDE GEL, DRIED MAGNESIUM HYDROXIDE, AND SIMETHICONE TABLETS, Individually Sealed, Double Strength, 60s	Strength 2, Size 1
6505-00-735-1742	ALUMINUM HYDROXIDE GEL, DRIED, MAGNESIUM HYDROXIDE, AND SIMETHICONE TABLETS, Individually Sealed, 100s	Strength 1, Size 2

6.3 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenieence only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Reviewing activity:
DoD-MB

Preparing activity:
DLA-DM

Project No. 6505-2037

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:01Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:01Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-A-37571A ALUMINUM HYDROXIDE GEL, DRIED, MAGNESIUM HYDROXIDE AND SIMETHICONE TABLETS

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202640-21T11:01Z
Check the source to verify that this is the current version before use.

FOLD

DEFENSE PERSONNEL SUPPORT CENTER
2800 SOUTH 20TH STREET
PHILADELPHIA, PA 19101

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

DEFENSE PERSONNEL SUPPORT CENTER
DIRECTORATE OF MEDICAL MATERIEL, CODE ATT
2800 SOUTH 20TH STREET
PHILADELPHIA, PA 19101

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:01Z
Check the source to verify that this is the current version before use.