INCH-POUND

**TT-A-511E**
May 20, 1992

SUPERSEDING
TT-A-511D
August 24, 1984

# FEDERAL SPECIFICATION

# AMYL ACETATE, TECHNICAL

*This specification is approved by the Commissioner of Federal Supply Service, General Services Administration, for use by all Federal agencies.*

## 1. SCOPE

**1.1 Scope.** This specification covers technical grade amyl acetate, $CH_3COOC_5H_{11}$.

## 2. APPLICABLE DOCUMENTS

**2.1** The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

Federal Specifications:

| | | |
|---|---|---|
| PPP-B-585 | - | Boxes, Wood, Wirebound |
| PPP-B-636 | - | Boxes, Shipping, Fiberboard |
| PPP-C-96 | - | Cans, Metal, 28 Gauge and Lighter |
| PPP-D-729 | - | Drums, Shipping and Storage, Steel, 55-Gallon (208 Liters) |
| PPP-F-320 | - | Fiberboard: Corrugated and Solid, Sheet Stock (Container Grade) and Cut Shapes |
| PPP-P-704 | - | Pails, Metal: (Shipping, Steel, 1 Through 12 Gallons) |

Comments or suggestions pertaining to this specification should be addressed to: Commander, U.S. Army Chemical Research, Development and Engineering Center, ATTN: SMCCR-PET-S, Aberdeen Proving Ground, MD 21010-5423.

AMSC N/A FSC 6810

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:16Z
Check the source to verify that this is the current version before use.

**Federal Standards:**

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies)
FED-STD-313 - Material Safety Data, Transportation Data and Disposal Data for Hazardous Materials Furnished to Government Activities

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification, other Federal specifications, and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston, MA; New York, NY; Washington, DC; Philadelphia, PA, Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Auburn, WA.

(Federal Government activities may obtain copies of Federal standardization documents and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Military Standards:

MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

(Copies of military specifications and standards required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

**Code of Federal Regulations (CFR):**

29 CFR 1900.1200 - Hazard Communication
49 CFR 171 to 199 - Hazardous Materials Regulations

(The Code of Federal Regulations and Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:16Z
Check the source to verify that this is the current version before use.

**2.2 Other publications.** The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

**ASTM Standards:**

| | | |
|---|---|---|
| D 891 | - | Specific Gravity, Apparent, of Liquid Industrial Chemicals |
| D 1078 | - | Distillation Range of Volatile Organic Liquids |
| D 1193 | - | Reagent Water |
| D 1209 | - | Color of Clear Liquids (Platinum-Cobalt Scale) |
| D 1353 | - | Nonvolatile Matter in Volatile Solvents for Use in Paint, Varnish, Lacquer, and Related Products |
| D 1364 | - | Water in Volatile Solvents (Fischer Reagent Titration Method) |
| D 1613 | - | Acidity in Volatile Solvents and Chemicals Intermediates Used in Paint, Varnish, Lacquer, and Related Products |
| D 1617 | - | Ester Value of Solvents and Thinners |

(Application for copies should be addressed to ASTM, 1916 Race Street, Philadelphia, PA 19103.)

**International Civil Aviation Organization**

"Technical Instructions for the Safe Transport of Dangerous Goods by Air"

(Application for copies should be addressed to the International Civil Aviation Organization, 1000 Sherbrooke Street West, Suite 400, Montreal, Quebec, Canada H3A 2R2.)

**International Maritime Organization**

"International Maritime Dangerous Goods Code"

(Application for copies should be addressed to the International Maritime Organization, 101-104 Piccadilly, London, WIV OAE, England.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

**2.3 Order of precedence.** In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:16Z
Check the source to verify that this is the current version before use.

## 3. REQUIREMENTS

**3.1 Appearance.** Amyl acetate shall be a clear liquid, free of sediment and suspended matter when examined as specified in 4.2.4.1.

**3.2 Chemical and physical characteristics.** Amyl acetate shall conform to the chemical and physical characteristics of table I when tested as specified therein.

TABLE I. **Chemical and physical characteristics**

| Characteristic | Requirements | | Test paragraph |
|---|---|---|---|
| | Minimum | Maximum | |
| Color, Pt-Co scale | ---- | Number 15 | 4.2.4.2 |
| Odor | ---- | To pass test | 4.2.4.3 |
| Water content, percent by weight | ---- | 0.2 | 4.2.4.4 |
| Specific gravity at 20 °/20 °C | 0.871 | 0.879 | 4.2.4.5 |
| Nonvolatile matter (g/100 mL) | ---- | 0.005 | 4.2.4.6 |
| Acidity (mg of KOH/g) | ---- | 0.28 | 4.2.4.7 |
| Distillation: | | | 4.2.4.8 |
| Initial boiling point at 760 mm pressure (°C) | 124 | ---- | |
| Distillate below 130° C, percent by volume | ---- | 10 | |
| Distillate below 140° C, percent by volume | ---- | 75 | |
| Dry point at 760 mm pressure (°C) | ---- | 155 | |
| Ester content, percent by weight | 95 | ---- | 4.2.4.9 |

**3.3 Material Safety Data Sheets.** Material Safety Data Sheets for amyl acetate shall be prepared and submitted by the contractor in accordance with FED-STD-313 (see 6.3).

## 4. QUALITY ASSURANCE PROVISIONS

**4.1 Responsibility for inspection.** Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

**4.1.1 Responsibility for compliance.** All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:16Z
Check the source to verify that this is the current version before use.

the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

**4.1.2 Contractor assurance of compliance.** The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable specification requirements using, as a minimum, the conformance criteria specified herein.

**4.1.3 Alternative inspection provisions.** Alternative inspection procedures, methods, or equipment, such as statistical process control, tool control, and other types of sampling procedures may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the inspection provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation and approval. (See 6.4.) When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the quality assurance provisions specified herein. In cases of dispute as to whether the contractor's proposed alternative provides equal quality assurance, the provisions of this specification shall apply. All approved alternative inspection provisions shall be specifically incorporated into the contractor's quality program or detailed inspection system, as applicable.

**4.2 Quality conformance inspection.**

**4.2.1 Lotting.** A lot shall consist of the amyl acetate produced by one manufacturer, at one plant, from the same materials, and under essentially the same manufacturing conditions provided the operation is continuous. In the event the process is a batch operation, each batch shall constitute a lot (see 6.5).

**4.2.2 Sampling.**

**4.2.2.1 For examination of packaging.** Sampling shall be conducted in accordance with table II. The sample unit shall be one filled unit pack or packing container, as applicable, ready for shipment.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:16Z
Check the source to verify that this is the current version before use.

TABLE II. **Sampling for packaging examination and test**

| Number of containers in batch or lot | Number of sample containers |
|---|---|
| 1 or 2 | all |
| 3 to 25 | 3 |
| 26 to 50 | 5 |
| 51 to 90 | 6 |
| 91 to 150 | 7 |
| 151 to 280 | 10 |
| 281 to 500 | 11 |
| 501 to 1,200 | 15 |
| 1,201 to 3,200 | 18 |
| 3,201 to 10,000 | 22 |
| over 10,000 | 29 |

**4.2.2.2 For amyl acetate test.** See 6.6 for sampling and testing precautions. Sampling shall be conducted in accordance with table III. A representative specimen of approximately 450 milliliters (mL) shall be removed from each sample container and placed in a suitable clean, dry container labeled to identify the lot and container from which it was taken.

TABLE III. Sampling for amyl acetate test

| Number of containers in batch or lot | Number of sample containers |
|---|---|
| 2 to 25 | 2 |
| 26 to 150 | 3 |
| 151 to 1,200 | 5 |
| 1,201 to 7,000 | 8 |
| 7,001 to 20,000 | 10 |
| Over 20,000 | 20 |

**4.2.2.3 For container leakage test.** Sampling shall be conducted in accordance with table II. The sample unit shall be one container.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:16Z
Check the source to verify that this is the current version before use.

**4.2.3 Inspection procedure.**

**4.2.3.1 For examination of packaging.** Sample unit packs and packing containers shall be examined for the characteristics listed below. Failure of any sample unit pack or packing container to conform to all characteristics shall be cause for rejection of the lot represented.

(a) Contents per container
(b) Container
(c) Container closure
(d) Container free of damage and leaks
(e) Fiberboard pads or partitions evident, correct, and properly placed, or as specified (when required)
(f) Marking evident, correct, and legible
(g) Unitization

**4.2.3.2 For amyl acetate test.** See 6.6 for sampling and testing precautions. Each sample specimen taken in 4.2.2.2 shall be tested as specified in 4.2.4. Failure of any test by any specimen shall be cause for rejection of the lot represented.

**4.2.3.3 For container leakage test.** The sample containers selected in 4.2.2.3 shall be tested as specified in 4.2.5. Failure of any test by any container shall be cause for rejection of the lot represented.

**4.2.4 Amyl acetate tests.** Water in accordance with ASTM D 1193 and reagent grade chemicals shall be used throughout the tests. Where applicable, blank determinations shall be run and corrections applied where significant. Tests shall be conducted as follows:

**4.2.4.1 Appearance.** Pour approximately 25 mL of the specimen into a clean, dry test tube. Allow to stand for no less than 10 minutes. Examine by transmitted light for clarity, sediment, and suspended matter.

**4.2.4.2 Color.** Determine the color in accordance with ASTM D 1209.

**4.2.4.3 Odor.** Dip a strip of heavy filter paper (Whatman No. 2 or equal) into the amyl acetate. Hang the test strip on a suitable support and allow to dry at room temperature for 2 hours. There shall be no residual odor on the dry filter paper.

**4.2.4.4 Water content.** Determine the presence of moisture in accordance with ASTM D 1364.

**4.2.4.5 Specific gravity.** Determine the specific gravity in accordance with ASTM D 891.

**4.2.4.6 Nonvolatile matter.** Determine the nonvolatile matter in accordance with ASTM D 1353.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:16Z
Check the source to verify that this is the current version before use.

**4.2.4.7 Acidity.** Determine the acidity in accordance with ASTM D 1613, substituting potassium hydroxide for the sodium hydroxide.

**4.2.4.8 Distillation.** Determine the distillation in accordance with ASTM D 1078.

**4.2.4.9 Ester content.** Determine the percent by weight of ester in accordance with ASTM D 1617.

**4.2.5 Container leakage test.** Place the container in each of the following positions, and leave it in each for a period of 15 minutes.

(a) Upright
(b) Upside down
(c) On one side (or one quadrant)
(d) On one end (or second quadrant)
(e) On other side (or fourth quadrant)

Examine the container after each period for any evidence of leakage.

## 5. PACKAGING

Note: The metric equivalents given for inch-pound quantities are nominal values provided for informational purposes and should not be considered as quantity requirements.

**5.1 Packaging.** Packaging shall be in accordance with the applicable requirements of 49 CFR 171 to 199 and the International Civil Aviation Organization - Technical Instructions for the Safe Transport of Dangerous Goods by Air (ICAO-TDGA) or the International Maritime Organization - International Maritime Dangerous Goods Code (IMO-IMDGC), as applicable to the mode of transportation. The packaging shall meet the applicable packaging performance tests specified in ICAO-TDGA or IMO-IMDGC, as applicable.

**5.2 Unit packing.**

**5.2.1 One-pint (0.5-liter) quantity.** A quantity of 1 pint (+1/8 or -0 fluid ounces) (0.5 liters) of amyl acetate shall be unit packed in a nominal 1-pint (0.5-liter) oblong tin-plate metal can conforming to an IP.3 container of ICAO-TDGA or IMO-IMDGC, as applicable. The IP.3 container shall conform to type V, class 4 of PPP-C-96. The can shall be formed from minimum grade number 100 electrolytic tin-plate, coated plan B, side seam striped, and furnished with temper evident inner or outer seal. The cap shall be tightened to a torque within the range specified by the can manufacturer, and it shall be provided with a feature which prevents it from backing off during transit and storage.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:16Z
Check the source to verify that this is the current version before use.

**5.2.2 One-quart (1.0-liter) quantity.** A quantity of 1 quart (+1/4 or -0 fluid ounces) (1.0 liter) of amyl acetate shall be unit packed in a nominal 1-quart (1.0-liter) oblong tin-plate metal can in the same manner as specified in 5.2.1.

**5.2.3 One-gallon (4.0-liter) quantity.** A quantity of 1 gallon (+1 or -0 fluid ounces) (4.0 liters) of amyl acetate shall be unit packed in a nominal 1-gallon (4.0-liter) metal can in the same manner as specified in 5.2.1, except that the can shall be furnished with a bridge type tin-plate handle on the top.

**5.3 Packing.** Packing shall be level A or B as specified (see 6.2).

**5.3.1 Level A.**

**5.3.1.1 One-gallon (4.0-liter) quantity.** Six 1-gallon (4.0-liter) cans, unit packed as specified in 5.2.3, shall be packed in two rows of three, with closure ends uppermost in a close-fitting wirebound wood box. The wood box shall conform to the requirements of a 4C1 container of ICAO-TDGA or IMO-IMDGC, as applicable. The 4C1 container shall conform to class 3, style optional of PPP-B-585. Each can shall be placed in close-fitting, full-can-height cell formed from half-slotted fiberboard partitions. The fiberboard pads shall be used to line all inside faces of the box. The fiberboard pads shall conform to class weather-resistant, grade V3c of PPP-F-320. Each box shall be closed and reinforced as specified in accordance with the general packing requirements of ICAO-TDGA or IMO-IMDGC, as applicable.

**5.3.1.2 Five-gallon (20.0-liter) quantity.** A quantity of 5 gallons (+5 or -0 fluid ounces) (20.0 liters) of amyl acetate shall be packed in a nominal 5-gallon (20.0-liter) steel pail conforming to the requirements of a 1A1 container of ICAO-TDGA or IMO-IMDGC, as applicable. The 1A1 container shall conform to type I, class 4 of PPP-P-704, furnished with a push-pull out spout. The can shall also be furnished with a tamper evident inner or outer seal. The cap shall be tightened to a torque within the range specified by the can manufacturer, and it shall be provided with a feature which prevents it from backing off during transit and storage.

**5.3.1.3 Fifty-five-gallon (210.0-liter) quantity.** A quantity of 55 gallons (+1/2 or -0 gallons) (210.0 liters) of amyl acetate shall be packed in a nominal 55-gallon (210.0-liter) steel drum conforming to the requirements of a 1A1 container of ICAO-TDGA or IMO-IMDGC, as applicable. The 1A1 container shall conform to type I, class A of PPP-D-729 furnished with cap seals and with exterior paint forest green. The drum shall be furnished with a 3/4-inch and 2-inch diameter threaded gaskets flange-plug closure in the head of the drum. The plug shall be tightened to a torque within the range specified by the drum manufacturer.

**5.3.2 Level B.**

**5.3.2.1 One-pint (0.5-liter) quantity.** Twelve 1-pint (0.5-liter) cans of amyl acetate, unit packed as specified in 5.2.1, shall be packed in three rows of four cans in a close-fitting,



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:16Z
Check the source to verify that this is the current version before use.

weather-resistant fiberboard box conforming to the requirements of a 4G container of ICAO-TDGA or IMO-IMDGC, as applicable. Each can shall be placed in a close-fitting, full-can-height cell formed from half-slotted fiberboard partitions. Fiberboard pads shall be placed on top of and beneath the cans. Partitions and pads shall be formed from fiberboard conforming to class weather-resistant, grade V3c of PPP-F-320. Each box shall be closed and reinforced as specified in accordance with the general packing requirements of ICAO-TDGA or IMO-IMDGC, as applicable.

**5.3.2.2 One-quart (1.0-liter) quantity.** Twelve 1-quart (1.0-liter) cans, unit packed as specified in 5.2.2, shall be packed in the same manner as specified for the 1-pint (0.5-liter) quantity in 5.3.2.1.

**5.4 Overpacking.** Overpacking shall be level A or B as specified (see 6.2).

**5.4.1 Level A.**

**5.4.1.1 One-pint (0.5-liter) quantity.** Four packs of 1-pint (0.5-liter) cans shall be overpacked with closure ends uppermost in a close-fitting wirebound wood box. The wood box shall conform to class 3, style optional of PPP-B-585. All inside faces of the box shall be lined with fiberboard pads and additional pads shall be inserted where needed to prevent motion of contents. The pads shall be formed from fiberboard conforming to class weather-resistant, grade V3c of PPP-F-320. The box shall be closed as specified in the appendix to PPP-B-585.

**5.4.1.2 One-quart (1.0-liter) quantity.** Two packs of 1-quart (1.0-liter) cans shall be overpacked as specified for the 1-pint (0.5-liter) quantity in 5.4.1.1.

**5.4.2 Level B.**

**5.4.2.1 One-pint (0.5-liter) quantity.** Four packs of 1-pint (0.5-liter) cans shall be overpacked in a close-fitting, weather-resistant fiberboard box conforming to grade V3c of PPP-B-636. The fiberboard box shall be closed as specified in the appendix to PPP-B-636.

**5.4.2.2 One-quart (1.0-liter) quantity.** Two packs of 1-quart (1.0-liter) cans shall be overpacked in a close-fitting, weather-resistant fiberboard box conforming to grade V3c of PPP-B-636. The fiberboard box shall be closed as specified in the appendix to PPP-B-636.

**5.5 Marking.** Shipments for civil agencies shall be marked in accordance with Fed. Std. No. 123. Shipments for military activities shall be marked in accordance with MIL-STD-129.

**5.5.1 Container compliance markings.** Each shipping container shall be marked in accordance with 49 CFR 171 to 179 and either ICAO-TDGA or IMO-IMDGC, as applicable.

**5.5.2 Hazard class label.** Each shipping container and pallet load shall be labeled in accordance with 49 CFR 171 to 179 and either ICAO-TDGA or IMO-IMDGC, as applicable.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:16Z
Check the source to verify that this is the current version before use.

**5.5.3 Proper shipping name.** Each shipping container and pallet load shall be marked with the proper shipping name in accordance with 49 CFR 171 to 179 and either ICAO-TDGA or IMO-IMDGC, as applicable.

**5.5.4 Precautionary markings.** Each unit pack, pack, and shipping container shall be marked or labeled, as applicable, in accordance with 29 CFR, Hazards Communication, 1900.1200(f) to show the required precautionary information. Each outer container shall be marked to show the top of the container by use of an arrow and the word "UP".

**5.5.5 Overpack markings.** Each overpack shall be marked "Inner packages comply with prescribed specification 4G."

**5.6 Palletization.** Uniform quantities of like packs and overpacks of 1-pint, 1-quart, and 1-gallon quantities of amyl acetate shall be palletized in accordance with load type I of MIL-STD-147. The 5-gallon packs shall be palletized in accordance with load type III of MIL-STD-147. The bonding means for both types of load shall be strapping.

## 6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

**6.1 Intended use.** Technical grade amyl acetate is intended for use as a solvent for organic compounds, including nitrocellulose and waterproofing compounds; as a solvent for organic protective coatings; and for general uses.

**6.2 Acquisition requirements.** Acquisition documents must specify the following:

(a) Title, number, and date of this specification
(b) Level of unit packing and packing required (see 5.2 and 5.3)
(c) Level of overpacking required (see 5.4)
(d) If palletization is required for shipment (see 5.6).

**6.3 Material Safety Data Sheets.** Contracting officers will identify those activities requiring copies of completed Material Safety Data Sheets prepared in accordance with FED-STD-313. The pertinent mailing addresses for submissions of data are listed in FED-STD-313.

**6.4 Submission of alternative inspection provisions.** Proposed alternative inspection provisions should be submitted by the contractor to the procuring contracting officer for evaluation and approval by the technical activity responsible for preparation of this specification.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:16Z
Check the source to verify that this is the current version before use.

**6.5 Batch.** A batch is defined as that quantity of material which has been manufactured by some unit chemical process or subjected to some physical mixing operation intended to make the final product substantially uniform.

**6.6 Sampling and testing precautions.** This specification requires inspection of chemical material which is potentially hazardous to personnel. This specification does not purport to address all of the safety problems associated with its use. It is the responsibility of the user of this specification to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

**6.7 Significant places.** For the purpose of determining conformance with this specification, an observed or calculated value shall be rounded off "to the nearest unit" in the last right-hand place of figures used in expressing the limiting value, in accordance with the rounding-off method of ASTM E 29.

**6.8 Changes from previous issues.** Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

**6.9 Subject term (key word) listing.**

nitrocellulose
organic compounds
protective coatings
solvent
waterproofing



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:16Z
Check the source to verify that this is the current version before use.

ution test chart patterns are visually examined. A pattern is whereby resolu

MILITARY INTERESTS:

**Custodians:**

Army - EA
Air Force - 68

**Review activities:**

Army - MD
DLA - GS

**User activities:**

Navy - AS, OS, SH

CIVIL AGENCY COORDINATING ACTIVITIES:

COM-NIST
GSA-FSS (9FTE-10)

**Preparing activity:**

Army - EA

Project No. 6810-1274



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:16Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

## INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

| I RECOMMEND A CHANGE: | 1. DOCUMENT NUMBER | 2. DOCUMENT DATE (YYMMDD) |
|---|---|---|
| | TT-A-511E | 920520 |

3. DOCUMENT TITLE
AMYL ACETATE, TECHNICAL

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

| a. NAME (Last, First, Middle Initial) | b. ORGANIZATION | |
|---|---|---|
| c. ADDRESS (Include Zip Code) | d. TELEPHONE (Include Area Code)<br>(1) Commercial<br>(2) AUTOVON<br>(If applicable) | 7. DATE SUBMITTED (YYMMDD) |

8. PREPARING ACTIVITY

| a. NAME<br>Army Chemical Research, Development and Engineering Center | b. TELEPHONE (Include Area Code)<br>(1) Commercial: (410) 671-3259<br>(2) AUTOVON: DSN 584-3259 |
|---|---|
| c. ADDRESS (Include Zip Code)<br>Cdr, U.S. Army CRDEC<br>ATTN: SMCCR-PET-S<br>Aberdeen Proving Ground, MD 21010-5423 | IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:<br>Defense Quality and Standardization Office<br>5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466<br>Telephone (703) 756-2340 AUTOVON 289-2340 |

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T12:16Z
Check the source to verify that this is the current version before use.