TT-I-526a
INTERIM AMENDMENT-4
October 28, 1971
SUPERSEDING
Int. Amendment-3
December 20, 1967

INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

INK, DRAWING, BLACK AND COLORS: (FOR GLAZED PLASTIC SURFACES)

This interim amendment was developed by the General Services Administration, Federal Supply Service, Standardization Division, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal Specification TT-I-526a, dated July 2, 1964.

PAGE 1

Section 2: Delete and substitute, APPLICABLE DOCUMENTS.

Paragraph 2.1: In the third line after the word bids, insert "or request for proposal". Under Federal Specifications, after PPP-B-636 delete the word "boxes" and substitute "box". Under Federal Specifications delete PPP-B-676 - Boxes, Set-Up Paperboard; PPP-T-45 - Tape, Gummed, Paper Reinforced; PPP-T-97 Tape; Pressure-Sensitive Adhesive, Filament Reinforced. Under Federal Standards, delete Fed. Std. No. 102. In second parenthetical paragraph, line 7, delete "Dallas" and substitute "Fort Worth".

PAGE 2

Paragraph 2.1 Delete "Military Specification" and "MIL-L-10547".

Add paragraph 2.2:

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, D. C. 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 202 Union Station, 516 W. Jackson Blvd., Chicago, Illinois 60606.)

Paragraph 3.8 Line 2. Delete "3/4" substitute"1". Line 3. Delete "three-fourth" and substitute "One". delete "a quill, or equivalent" and substitute "an applicator".

Section 4: Delete and substitute, QUALITY ASSURANCE PROVISIONS.

PAGE 4

Paragraph 4.4.5 Line 2. Delete "3/4" substitute "1". Line 3. Delete "3/4" substitute "1".
Line 3. Delete "3/4" substitute "1".

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:17Z
Check the source to verify that this is the current version before use.

Paragraph 4.4.5 Line 2. Delete "3/4" and substitute "1".

Section 5 Delete entire section and substitute:

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Unit package. One, two, eight and sixteen ounces of ink shall be packaged in 1-, 2-, 8-, and 16-ounce bottles, respectively, and shall be furnished as specified (see 6.2). The bottles shall be fabricated from commercial grade glass or from polyethylene material conforming to L-P-390, type I, grade 1. If a polyethylene material is used, the average weight loss due to permeation of the ink through the container shall not exceed 0.4 gram per 1-ounce container when tested as specified in 4.4.5. The shape of the 1-ounce bottles shall be such that each can be inserted in the ink bottle holders commercially available. Each 1-ounce bottle shall be provided with a plastic continuous-thread screw-cap closure with ink applicator. The cap and applicator shall not be affected by the ink, nor shall the ink be affected by the cap and applicator. The applicator shall extend down to within one-eighth inch of the bottom of the bottle when the cap is tightly in place. Each 2-, 8-, and 16-ounce bottle shall be provided with a metal or plastic continuous-thread screw-cap closure (see 5.1.1.1.1).

Caps shall be of adequate weight sidewall so that an average of not more than 10 out of 30 caps will be broken in application by capping machines at 30 inch-pounds torque and no individual cap will break at less than 15 inch-pounds. All screw caps shall have a nonabsorbent resilient lining or a lining backed by resilient material which will remain in the cap. An inner seal shall be used to cover and adhere to the mouth of the 2-, 8-, and 16-ounce bottles which will prevent loss of the contents should the cap become loosened. Caps shall be tightened to prevent leakage. Each glass bottle and each 1-ounce plastic bottle shall be packaged in a snug-fitting box conforming to PPP-B-566, style II, type D, class a. Boxes shall have tuck ends of a lock type specified in PPP-B-566 for the style of box specified. In addition, each box containing 16-ounce glass bottles shall be fitted with a single-faced corrugated liner. Each individual box containing 8- or 16-ounce bottles shall be sealed with tape as specified in the appendix to the box specification.

5.1.1.1.1 Alternate closure. Alternate non-metal continuous-thread screw-cap closure for the 2-, 8-, and 16-ounce bottles of pourout-type or other design in accordance with standard commercial practice, will be acceptable provided the alternate closure meets the quality established by this specification and is at least equally effective to the described above for the purpose intended.

5.1.1.2 Intermediate package. Ink, unit packaged as specified in 5.1.1.1, except for 16-ounce bottles, shall be intermediate-packaged in quantities specified in table III in boxes conforming to PPP-B-566, style II, type D, class a or alternately intermediate-packaged as specified in note 1 to table III. Sixteen-ounce bottles shall be intermediate packaged in boxes conforming to PPP-B-636 or PPP-B-665, in quantities as indicated in table III.

TABLE III

Size (ounces)	Quantity of unit packages per intermediate package	Quantity of unit package per shipping container
1	1/ 12	144
2	1/ 12	144
8	6	96
16	6	48

1/ Alternate intermediate packaging; Two boxes, each tightly wrapped with kraft paper and each container containing 6 unit packages as specified in 5.1.1.1, may be inserted in a snug-fitting box (intermediate package) as specified in 5.1.1.2 to comply with the requirement for 12 unit packages per intermediate package.

5.1.1.2.1 Sets (type II only). Each individual set (see 3.8.1) shall be intermediate packaged in a close-fitting box conforming to PPP-B-636. Interior slotted partitions shall be used to form cells for each bottle. The partitions shall be made of the same type material as used in the box construction. Each box shall be closed in accordance with the appendix to the box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:17Z
Check the source to verify that this is the current version before use.

5.1.2 Level B. Packaging for level B shall be as specified in 5.1.1 for level A.

5.1.3 Level C. The ink shall be packaged in accordance with the manufacturer's standard practice, providing that this insures protection for the ink during shipment and provides for safe delivery at its destination.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Ink, packaged as specified in 5.1, shall be packed in quantities as specified in table III in a snug-fitting fiberboard box conforming to PPP-B-636, class weather resistant. Closure shall be in accordance with the appendix to the box specification.

5.2.2 Level B. Ink, packaged as specified in 5.1, shall be packed in quantities as specified in table III in a snug-fitting fiberboard box conforming to PPP-B-636, class domestic. Closure shall be in accordance with the appendix to the box specification.

5.2.3 Level C. The ink, packaged as specified in 5.1.3, shall be packed in containers that will assure carrier acceptance and safe arrival at destination in compliance with the Uniform Freight Classification rules and the National Motor Freight Classification rules.

5.3 Marking. Marking shall be in accordance with paragraph 5.3.1 or 5.3.2 as specified (see 6.2).

5.3.1 Civil agencies. In addition to any special markings required by the contract or order, all interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123, including specification classification (such as type, class, color, etc.).

5.3.2 Military agencies. In addition to any special markings required by the contract or order, all interior packages and shipping container shall be marked in accordance with MIL-STD-129.

5.3.3 Special marking. Each shipping container shall be marked "KEEP FROM FREEZING" on each end in 1-inch letters. Shipping containers containing glass bottles shall bear "FRAGILE" markings. All shipping containers shall bear arrows and the word "UP" on at least one side and one end and the word "TOP" and "THIS SIDE UP" on the top surface.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:17Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:17Z
Check the source to verify that this is the current version before use.