MIL-C-63325(AR)
1 March 1979

MILITARY SPECIFICATION

COUPLING, FLUSH-LATCH
ASSEMBLY AND METAL PARTS FOR

This specification is approved for use by US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the parts and assembly for one type of coupling designated as Flush-Latch Coupling for Demolition Kit, Cratering: M180.

2 APPLICABLE DOCUMENTS

2.1 Issues of Documents. - The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Porovisions, General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1188 - Commerial Packaging of Supplies and Equipment.

FSC: 1375

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:39Z
Check the source to verify that this is the current version before use.

DRAWINGS (See 6.5)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

PRODUCT DRAWINGS

9329461 - Coupling, Flush-Latch

INSPECTION EQUIPMENT DRAWINGS

C9329655 - Check Block V-Clamp

(Copies of specifications, standards, drawings, required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. - Materials shall be in accordance with the applicable drawings and specifications.

3.4 First Article Inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.5 Workmanship. - All parts and assemblies shall be fabricated and finished in a thorough workmanlike manner and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly nor shall they be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings and stamping shall be neat and sharply defined. (Required packing shall be dry).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:39Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. - The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First Article inspection

4.3.1 Sumbission. - The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2 and 4.3.3. The first article sample shall consist of the following items in sample quantities as indicated in Table 1.

4.3.2 Inspection to be performed. - See MIL-A-48078 and Table 1 specified herein.

4.3.3 Rejection. - (See MIL-A-48078)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:39Z
Check the source to verify that this is the current version before use.

TABLE 1 - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63325(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Coupling, Flush-Latch				See below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Coupling, Flush-Latch (Dwg. 9329461) Examination for defects	10	-	3.1	4.4.2.1

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:39Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. - (See MIL-A-48078). Unless otherwise specified in the classification of defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:39Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63325(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 9329461
4.4.2.1	Coupling, Flush-Latch				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Coupling fails to fit over check block when force of 10-30 lbs. is applied to end of handle		100%	3.1	Check Block V-Clamp (C9329655)
102	Spotwelds or seamwelds in restricted area (4 places)		0.40%	3.1	Visual
103	Latch and Connectors fail to rotate freely		0.40%	3.1	Manual
104	Thickness of V-Band (a)		0.40%	3.1	Gage
105	Width of V-Band trough (a)		0.40%	3.1	Gage
106	Angle of V-Band trough walls (a)		0.40%	3.1	Gage
107	Welds between V-Band (Left and Right) and Adapters missing or improper (4 places)		0.40%	3.1	Visual
108	Welds between Flat Head Pins and Latch missing or improper (2 places)		0.40%	3.1	Visual
109	Spotwelds between Adapters (2) and V-Bands (Left and Right) missing or improper (2 places)		0.40%	3.1	Visual
110	Spotwelds between Outer Jacket and V-Bands (Left, Right & center) missing or improper		0.40%	3.1	Visual
111	Any components missing or improperly assembled		0.40%	3.1	Visual

NOTES:

(a) These three inspections should be done on each V-Band (Left, Right, and Center).

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:39Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63325(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.1	Coupling, Flush-Latch Continuation Sheet				9329461
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Width of slots on Outer Jacket (4 places)		0.65%	3.1	Gage
202	Lacquer missing or improper		0.65%	3.1	Visual
203	Evidence of poor workmanship		1.00%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:39Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. - Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.4 Inspection Equipment. - The inspection equipment (gage) required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1, and the test method paragraph (See 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and 6.3 herein.

4.5 Test Methods and Procedures. - N/A

5. PACKAGING

5.1 Preservation-packaging. - Packaging shall be in accordance with MIL-STD-1188.

5.2 Packing. - Packing shall be in accordance with MIL-STD-1188.

5.3 Marking. - Marking shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended Use. - The Coupling covered by this specification is intended for use on the Warhead assembly for the M180 Cratering Demolition Kit.

6.2 Ordering Data. - Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Provisions for submission of first article samples.
c. Provisions of MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. - (See MIL-A-48078). Submit equipment designs as required to Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAA-I, Dover, New Jersey 07801.

6.4 Distribution of ammunition data cards. - Distribution of data cards shall include the following: Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAA-Q, Dover, New Jersey 07801.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:39Z
Check the source to verify that this is the current version before use.

6.5 Drawings. - Drawings listed in Section 2 fo this specification under the heading U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal Drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
ARMY-AR

Preparing Activity:
ARMY-AR

Project Number: 1375-A233

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:39Z
Check the source to verify that this is the current version before use.