INCH-POUND

MIL-C-55302/61F
8 April 1993
SUPERSEDING
MIL-C-55302/61E
26 August 1988

MILITARY SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES, PLUG, PIN CONTACTS, DECADE INCREMENTS 10 THRU 70 CONTACT POSITIONS AND INTERMEDIATE POSITIONS OF 14, 24, 44, 54, AND 26, 36, 56, AND 66 FOR PRINTED WIRING BOARDS (100 INCH SPACING)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation MIL-C-55302





FIGURE 1 Connector, plug, 100 (2.54 mm) spacing

(F) denotes changes

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:47Z
Check the source to verify that this is the current version before use.

Number of contacts	Dimensions				
	A ± 010	BSC B	REF C	BSC D	E ± 010
10	850 (21 59)	650 (16 51)	400 (10 16)	1 100 (27 94)	1 350 (34 29)
14	1 050 (26 67)	850 (21.59)	600 (15 24)	1.300 (33 02)	1.550 (39.37)
20	1 350 (34 29)	1 150 (29 21)	.900 (22.86)	1 600 (40 64)	1 850 (46 99)
24	1 550 (39.37)	1 350 (34 29)	1 100 (27 94)	1 800 (45 72)	2 050 (52 07)
26	1 650 (41 91)	1 450 (36 83)	1 200 (30 48)	1 900 (48 26)	2 150 (54 61)
30	1 850 (46 99)	1 650 (41 91)	1 400 (35 56)	2 100 (53 34)	2 350 (59 69)
36	2 150 (54 61)	1 950 (49 53)	1 700 (43 18)	2 400 (60 96)	2 650 (67 31)
40	2 350 (56.69)	2 150 (54 61)	1 900 (48 26)	2 600 (66 04)	2 850 (72 39)
44	2 550 (64 77)	2 350 (59 69)	2 100 (53 34)	2 800 (71 12)	3 050 (77 47)
50	2 850 (72 39)	2 650 (67 31)	2 400 (60 96)	3 100 (78 74)	3 350 (85 09)
54	3 050 (77 47)	2 850 (72 39)	2 600 (66 04)	3 300 (83 82)	3 550 (90 17)
56	3 150 (80 01)	2 950 (74 93)	2 700 (68 58)	3 400 (86 36)	3 650 (92 71
60	3 350 (85.09)	3 150 (80 01)	2 900 (73 66)	3 600 (91 44)	3 850 (97 79)
66	3.650 (92 71)	3 450 (87 63)	3 200 (81 28)	3 900 (99 06)	4 150 (105.41)
70	3 850 (97 79)	3 650 (92 71)	3 400 (86 36)	4 100 (104 14)	4 350 (110 49)



Inches	mm
001	0 03
005	0 13
006	0 15
008	0 20
010	0 25
015	0 38
017	0 43
025	0 64
030	0 76
051	1 30
058	1 47
075	1 91
078	1 98
086	2 18
094	2 39
100	2 54
107	2 72
109	2 77
120	3 05
125	3 18
130	3 30
140	3 56
150	3 81
186	4 72
190	4 83
225	5 72
250	6 35
325	8 26
350	8 89
400	10 16

NOTES

1. Dimensions are in inches
2. Metric equivalents are given for general information only
3. Unless otherwise specified, tolerance is ± 005 (0 13 mm)
4. These connectors mate with connectors specified in MIL-C-55302/62, MIL-C-55302/65, MIL-C-55302/66 and MIL-C-55302/58 using appropriate hardware
5. Numbers indicating the first and last position in each row and every fourth contact position in between shall be marked on the side(s) of the connector. As an option to the above, numbers indicating every fourth cavity may be stamped on the side of the connector, with the exception that the number 1 contact shall be marked
6. Termination layout on .020 (0 51 mm) modular grid
7. Metric equivalents are in parentheses
8. Optional undercut .020 maximum PCB side for cleaning purposes
9. (F) Position of the Hex orientation is optional. Hex shall not break through the side of the insulator
10. (F) Hole depth to female guide hardware .282 min (7 16 mm). Max thread depth to female threaded hardware .240 min (6 1 mm)

FIGURE 1. Connector, plug, .100 (2 54 mm) spacing. (Continued)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:47Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Dimensions and configuration See figure 1

Material Jackscrews and jacksockets shall be made of corrosion-resisting stainless steel in accordance with ASTM-A581 or ASTM-A582 passivated in accordance with QQ-P-35 or shall be corrosion-resistant copper nickel alloy (61 ±2% copper, 25 ±2% nickel, 2 5% max other, and the balance zinc) and shall have a brinell hardness of 145 to 175.

Plating The contact plating shall be in accordance with MIL-C-55302 or gold in accordance with MIL-G-45204, type II, grade C, class 1, over nickel plating in accordance with QQ-N-290, class 2, 50 to 150 microinches in the engaging area and gold in accordance with MIL-G-45204, type II, grade C, class 00, or type III, grade A, class 00, over nickel plating in accordance with QQ-N-290, class 02, 50 to 150 microinches in the termination area

Contact identification. See figure 1

Contact resistance The average contact resistance of all contacts measured shall not exceed 0 010 ohm, and no individual contact pair shall have a resistance exceeding 0 020 ohm

Dielectric withstanding voltage

Sea level 1,000 volts rms

High altitude 300 volts rms

Current rating 5 0 amperes maximum per contact

Example of part number

M55302/61 — Basic number of specification sheet

A — Type of terminal (see figure 1)

- A = dip terminal 109 long
- B = dip terminal 140 long
- C = dip terminal 172 long

10 — Number of contacts (see figure 1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:47Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians
Army - CR
Navy - EC
Air Force - 17
NASA - NA

Review activities
Army - AR, MI
Navy - AS
Air Force - 85, 99
DLA - ES

User activities
Army - AT, AV, ME
Navy - MC, OS
Air Force - 11, 19, 80

Preparing activity
Army - CR

Agent
DLA - ES

(Project 5935-3860-7)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:47Z
Check the source to verify that this is the current version before use.