INCH-POUND

MIL-C-70478 (AR)
AMENDMENT 2
22 October 1990
SUPERSEDING
AMENDMENT 1
23 May 1988

MILITARY SPECIFICATION

CONTAINER, AMMUNITION, METAL FOR CARTRIDGE, 120MM, TANK AMMUNITION

This amendment forms a part of Military Specification MIL-C-70478(AR), dated 8 September 1986 and is approved for use within the U. S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* 2.2: Under American Society for Testing and Materials (ASTM), delete: "ASTM - D412 - Tension Testing of Vulcanized Rubber, Standard Method of".

PAGE 7

First article inspection: Under Examination or Test column:

* First line, delete: "9386818" and substitute "9344042".

* Sixth line, delete: "9386829" and substitute "12910349".

* Ninth line, delete: "c. Tensile stress (see note) 3 3.2 4.5.5".

* Under Notes, delete: "body tensile strength, spring tests and gasket tensile stress test" and substitute: "body tensile strength and spring tests".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.

PAGE 9

* 4.4.2.1: Under drawing number, delete: "9386817" and substitute "9344043".

* Under next high assembly, delete: "9386820" and substitute "9344044".

PAGE 10

* 4.4.2.2: Under drawing number, delete: "9386818" and substitute "9344042".

* Under next high assembly, delete: "9386820" and substitute "9344044".

PAGE 11

* 4.4.2.3: Under drawing number, delete: "9386819" and substitute "9344035".

* Under next high assembly, delete: "9386820" and substitute "9344044".

PAGE 12

* 4.4.2.4: Under drawing number, delete: "9386820" and substitute "9344044".

PAGE 13

* 4.4.2.5: Under drawing number, delete: "9386823" and substitute "9344036".

PAGE 14

* 4.4.2.6: Under drawing number, delete: "9386816" and substitute "9344037".

PAGE 15

* 4.4.2.7: Under drawing number, delete: "9386814" and substitute "9344038".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.

PAGE 16

* 4.4.2.8: Under drawing number, delete: "9386813" and substitute "9344041".

PAGE 18

* 4.4.2.10: Under drawing number, delete: "9386829" and substitute "12910349".

Delete:

Major				
"102	Tensile stress	5	3.2	4.5.5"
"108	Misalignment of joint	0.40%	3.2	Gage"
"109	Diameter of hole in cross section	5	3.2	Gage".

PAGE 22

* 4.4.2.14:

Major
103: Delete in its entirety.
105: Delete "Inside dimension" and substitute "Dimension".
106: Delete "Inside dimension" and substitute "Dimension".

Minor
202: Delete in its entirety.
203: Delete in its entirety.

PAGE 23

* 4.4.2.15:

Major
103: Delete in its entirety.
104: Delete "Inside dimension" and substitute "Dimension".

Minor
202: Delete in its entirety.
203: Delete in its entirety.
206: Delete "Depth of Interlocking Cutouts" and substitute "Depth from interlocking cutout to inside flat".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.

PAGE 25

4.4.2.17:

Major
103: Delete in its entirety.
* 104: Delete in its entirety.
* 105: Delete in its entirety.

PAGE 26

* 4.4.2.18

Minor
201: Delete in its entirety.
202: Delete in its entirety.

PAGE 27

* 4.4.2.19: Add:

Major				
"109	Flatness of body	0.40%	3.2	Gage
110	Body end irregularities	0.40%	3.2	4.5.10
111	Depth of body weldment	0.40%	3.2	Gage".

PAGE 28

4.4.2.20: Add:

Major				
"104	Inside diameter, minimum	0.40%	3.2	Gage".

PAGE 30

* 4.4.2.22:

Major 101: Delete "weldnut" and substitute "self clinching nut".

Minor 202: Delete in its entirety and substitute:

"202	Pushout force improper	0.65%	3.2	Gage".

Minor 203: Delete "weldment" and substitute "self clinching nut".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.

PAGE 31

* 4.4.3.4 Spring embrittlement: delete "9386818" and substitute "9344042".

* 4.4.3.5 Hardness of spring: delete "9386818" and substitute "9344042".

* 4.4.3.6 Tensile stress of gasket: delete in its entirety.

* 4.4.3.7 Hardness of gasket: delete "9386829" and substitute "12910349".

PAGE 32

* 4.5.5 Delete paragraph 4.5.5 in its entirety.

PAGE 33

* 4.5.10 Add:

"Body end irregularities. Visually inspect the body end for any nicks, dents, gouges, or mismatch. If a defect is evident, place a .01 inch diameter wire on the defect and a one inch long block over the wire with the wire nested in the irregularity, gently press down on the block and remove the wire. If there is no evidence of resistance caused by the block, the part shall be classed defective."

PAGE 34

6.1 Intended use. Delete: "Tactical".

NOTE: The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 8140-A825)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.