MIL-F-63519 (AR)
AMENDMENT 3
20 March 1986
SUPERSEDING
AMENDMENT 2
01 August 1985

MILITARY SPECIFICATION

FUZE, POINT DETONATING, M739A1
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-F-63519 (AR), dated 18 March 1982, and is approved for use within the US Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Under "Beneficial Comments" block at bottom of page: Delete address and substitute "Commander, US Army Armament Research and Development Center, ATTN: AMSMC-QA (D), Dover, NJ 07801-5001."

PAGE 2

2.1.2: Delete "ARRADCOM" and substitute "ARDC".

PAGE 3

4.3.2.1: Delete "Inspection Level II" and substitute "CSP-2".

PAGE 5

4.3.2.2: Delete in its entirety.

PAGE 7

4.3.2.4: Add Major Defect 103 as follows: "103. External Fuze Body Threads Damaged 0.40% 3.2 Visual".

PAGE 8

* 4.3.2.5:

Critical 3: Delete "35(a)" and substitute "20(a)".

Critical 4: Delete "10" and substitute "5".

AMSC N/A
FSC 1390
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

* 4.3.3.1.1: third line, delete "fifteen (15)" and substitute "ten (10)".

* 4.3.3.2.1: Delete "seventy (70)" and substitute "thirty (30)".

PAGE 18

* Delete 4.4.4.1 in its entirety and substitute the following:

"4.4.4.1 The fuzes shall be assembled to the appropriate HE loaded projectiles, except for the non-functioning test where inert loaded projectiles with T2 supplementary charges shall be used, and fired from the weapons specified below. Target distances for all phases except for the one (1) inch plywood screen shall be any convenient distance. The quadrant elevations shall be as specified below. For all ground impact functioning, appropriate geophonic sensing devices shall be employed to verify high order functioning of the projectile upon impact. The acceptance criteria is as follows:

DEFECT	ACCEPT	REJECT
Premature Burst	0	1
Non-Functioning	0	1
Duds (see 6.6)	1	2
Reverse Functioning	1	2

WEAPON	ZONE	QUADRANT ELEVATION	TARGET	FUZE SETTING	SAMPLE SIZE
Non-Functioning:					
105MM, M102	7		1" Plywood @ 115 Feet	SQ	7
Functioning:					
105MM, M102	7	Low	Ground	SQ	9*
105MM, M102	7		1" Plywood @ 500 Feet	SQ	5
155MM, M109A1	2	Low	Ground	SQ	9*

* 5 Transportation Vibration Conditioned Fuzes"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

* Delete 4.4.4.2 in its entirety and substitute the following:

"4.4.4.2 The testing shall be conducted as specified in 4.4.4.1 except that the acceptance criteria and weapon firings shall be as specified below.

DEFECT	ACCEPT	REJECT
Premature Burst	0	1
Non-Functioning	0	1
Duds (see 6.6)	0	2**
Reverse Functioning	1	2

WEAPON	ZONE	QUADRANT ELEVATION	TARGET	FUZE SETTING	SAMPLE SIZE
Non-Functioning:					
105MM, M102	7		1" Plywood @ 115 Feet	SQ	5
Functioning:					
105MM, M102	7	Low	Ground	SQ	5*
105MM, M102	7		1" Plywood @ 500 Feet	SQ	5
155MM, M109A1	2	Low	Ground	SQ	5

* 5 Transportation Vibration Conditioned Fuzes"
** If only one dud occurs during the Functioning tests repeat the Functioning tests with a second sample of 15 fuzes. If no additional duds occur, accept the lot.

If any production lot fails to meet the above criteria, testing shall revert to 4.4.4.1 until three (3) consecutive lots have been accepted."

Source: https://assist.dla.mil Downloaded: 202640-23T03:03Z
Check the source to verify that this is the current version before use.

6.3: Delete address and substitute "Commander, US Army ARDC, ATTN: AMSMC-QAR-I(D), Dover, NJ 07801-5001."

* 6.5: Delete in its entirety and substitute the following:

"6.5 Proving ground test summary.

QUALITY CONFORMANCE TEST

FIRST 3 CONSECUTIVE ACCEPTABLE LOTS

ACCEPTABLE CRITERIA

DEFECT	ACCEPT	REJECT
Premature Burst	0	1
Non-Functioning	0	1
Duds (see 6.6)	1	2
Reverse Functioning	1	2

TESTING

WEAPON	ZONE	QUADRANT ELEVATION	TARGET	FUZE SETTING	SAMPLE SIZE
Non-Functioning:					
105MM, M102	7		1" Plywood @ 115 Feet	SQ	7
Functioning:					
105MM, M102	7	Low	Ground	SQ	9*
105MM, M102	7		1" Plywood @ 500 Feet	SQ	5
155MM, M109A1	2	Low	Ground	SQ	9*

* 5 Transportation Vibration Conditioned Fuzes"

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:03Z
Check the source to verify that this is the current version before use.

* 6.5: Delete in its entirety and substitute the following:

SUBSEQUENT LOTS

ACCEPTABLE CRITERIA

DEFECT	ACCEPT	REJECT
Premature Burst	0	1
Non-Functioning	0	1
Duds (see 6.6)	0	2**
Reverse Functioning	1	2

TESTING

WEAPON	ZONE	QUADRANT ELEVATION	TARGET	FUZE SETTING	SAMPLE SIZE
Non-Functioning:					
105MM, M102	7		1" Plywood @ 115 Feet	SQ	5
Functioning:					
105MM, M102	7	Low	Ground	SQ	5*
105MM, M102	7		1" Plywood @ 500 Feet	SQ	5
155MM, M109A1	2	Low	Ground	SQ	5

* 5 Transportation Vibration Conditioned Fuzes"
** If only one dud occurs during the Functioning tests repeat the Functioning tests with a second sample of 15 fuzes. If no additional duds occur, accept the lot."

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-A492)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.