MILITARY SPECIFICATION SHEET

GENERATOR SETS, DIESEL ENGINE DRIVEN,

10 KW, 60 HERTZ; TACTICAL, UTILITY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

REQUIREMENTS

1. Drawings. The set shall be in accordance with Top Assembly 30554-71-003 and as specified herein.

2. Short circuit. The generator, exciter and voltage regulator, operating as a unit, shall withstand 10 consecutive and instantaneous 10-second single phase line-to-line, single phase line-to-neutral, and symmetrical 3 phase short circuits at the generator output terminals when operating at rated load and frequency without reduction of dielectric strength to a point where it will not meet the requirements of 3.9.5. The sustained 3 phase short circuit current shall not be less than 250 percent of rated output current. This requirement applies to each of the following conditions:

(a) 120V, 1 phase L1-L3.
(b) 120/240V, 1 phase. L1-L0, L3-L0, L1-L3.
(c) 120/208V, 3 phase. L1-L0, L2-L0, L3-L0, L1-L2-L3, L1-L2, L2-L3, L1-L3.

3. Transient reactance, rated voltage. With the generator connected for 120/208 volts, 3 phase, 4 wire, the direct axis transient reactance shall not exceed 18 percent. With the generator connected for 120 volts, single phase, 2 wire, the direct axis transient reactance shall not exceed 25 percent.

4. Negative sequence impedance. The generator negative sequence impedance, with the set connected for 120/208 volts, 3 phase, 4 wire, shall be not more than 18 percent.

5. Voltage modulation. The voltage modulation shall not exceed 1.0 percent.

6. Field current. With the generator temperature stabilized at normal ambient conditions, the exciter field current shall not exceed 0.55 ampere for no load and 1.10 amperes for rated load.

FSC 6115

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:39Z
Check the source to verify that this is the current version before use.

7. Generator efficiency. The generator (including the excitation system) efficiency shall not be less than 88 percent at 0.8 pf in the 3 phase 120/208 voltage connection.

8. Alternating current circuit interrupter. The alternating current circuit interrupter shall operate as follows for all voltage connections. At 110 percent of rated set current, the circuit interrupter shall not open. At 135 percent of rated set current, the circuit interrupter shall open between 1.5 and 20 minutes at ambient temperatures above 60° F (15.6° C) and within 40 minutes below 60° F (15.6° C). The circuit interrupter shall open within 0.05 second under the conditions of a short circuit in any one phase or in all phases simultaneously. In all cases, all phases shall open simultaneously.

Custodians:
Army - ME
Navy - YD
Air Force - 99

Preparing activity:
Army - ME

Project 6115-0229

Review activities:
Navy - MC
DLA - GS

User activity:
Navy - CG

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:39Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS This form is provided to solicit beneficial comments which may improve this document and enhance its use DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government Fold on lines on reverse side, staple in corner, and send to preparing activity Attach any pertinent data which may be of use in improving this document If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed

NOTE This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-G-52889/2C Generator Sets, Diesel Engine Driven, 10 KW, 60 Hertz, Tactical, Utility

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID RESTRICTIVE LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDED WORDING CHANGE

C REASON FOR RECOMMENDED CHANGE(S)

2 REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:39Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Mobility Equipment Research and
Development Command
ATTN: DRDME-DS
Fort Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:39Z
Check the source to verify that this is the current version before use.