MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, METALLIZED PLASTIC DIELECTRIC,
DC-AC, IN NONMETAL CASES, ESTABLISHED RELIABILITY,
STYLE CFR09

This amendment forms a part of Military Specification Sheet MIL-C-55514/7A(USAF), dated 29 February 1980, and is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

FIGURE 1, NOTES: After note 4, add the following:

"5. Lead length may be a minimum of 1-inch long for use in tape and reel packaging when specified in the ordering data."

PAGE 7

Insulation resistance:

Delete "Terminal to terminal (dc rated voltage): See figure 2." and substitute "Terminal to terminal (dc rated voltage or derated voltage, if applicable): See figure 2."

* Life (at +125°C), delete and substitute:

"Life (at 85°C): In accordance with 2000 hour (qualification inspection) of MIL-C-55514 except:

Accelerated conditions: 125 percent of the 85°C rated voltage.

Rated conditions: 100 percent of the 85°C rated voltage.

IR (terminal to terminal) (at 25°C): Not less than 33.3 percent of initial requirement.

ΔCap.: Maximum of ±5.0 percent.

DF (at 25°C) after life: 0.6 percent, maximum."

PAGE 8

FIGURE 2, delete "IR (in megohms x 104)" and substitute "IR (in megohms x 10^4)".

PAGE 9

AC conditioning, delete and substitute:

"AC conditioning: Capacitors shall be exposed to 120 percent of the 400 Hz voltage specified in table I at +105 +0°, -5°C.

Test samples shall be in accordance with table III.

Post test requirements:

DF (at +105°C): 0.5 percent, maximum.

IR (terminal to terminal) (at +25°C): Not less than 33.3 percent of initial requirement.

ΔCap.: Maximum of ±5.0 percent.

DF (at +25°C) after life: 0.6 percent, maximum.

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:29Z
Check the source to verify that this is the current version before use.

TABLE III. AC conditioning test samples.

DC rated voltage (volts)	Total cap. value of sample (µF)	Cap. range for selection of sample 1/
50	40	.056 to 18.0 µF
75	40	.033 to 15.0 µF
100	20	.027 to 10.0 µF
150	40	.015 to 5.0 µF
200	20	.010 to 3.9 µF

1/ Each test sample shall contain at least one capacitor of the highest and lowest capacitance value of each voltage group manufactured during the three month period."

NOTE: The margin of this amendment is marked with an asterisk to indicate where a change from the previous amendment was made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Air Force - 11

Review activities:
Air Force - 17, 99
DLA - ES

Agent:
DLA - ES

Preparing activity:
Air Force - 11

(Project 5910-F377)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:29Z
Check the source to verify that this is the current version before use.