MILITARY SPECIFICATION

SUPPORT, COVER

This specification is approved for use by the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the requirements, quality assurance provisions, and packaging for the metal parts cover support.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

TT-C-490	-	Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings

MILITARY

MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1167	-	Ammunition Data Card
MIL-STD-1169	-	Packaging, Packing and Marking for Shipment of Inert Ammunition Components

FSC 1320

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn. DRSMC-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter. Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER (ARDC)

9369960 - Support, Cover

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 General. Materials, parts and assemblies, shall comply with the requirements specified on the applicable drawings and specifications.

3.2 First article inspection. This specification contains technical provisions for first article inspection. Requirements for submission of first article samples by the contractor shall be as specified in the contract.

3.6 Workmanship. All parts shall be fabricated and finished in a thorough, workmanlike manner. They shall be clean and free of burrs, sharp edges, unblended radii, cracks, surface defects, chips, dirt, grease, dust and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawings	Quantity
Support, Cover (uncoated)	9369960	50
Support, Cover (phosphated)	9369960	10
Support, Cover (painted)	9369960	10

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Support, Cover				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Washer, Support (without coating) (Dwg. 9369960)				
	Examination for defects	50	-	3.1	4.4.2.1
	Support, Cover (with phosphate coating) (Dwg. 9369960)				
	Examination for defects	10	-	3.1	4.4.2.2
	Support, Cover (after painting) (Dwg.9369960)				
	Examination for defects	10	-	3.1	4.4.2.3

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9369960
4.4.2.1	Support, Cover (uncoated)				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major					
101	Thickness		.40	3.1	Gage
102	Outside diameter		.40	3.1	Gage
103	Inside diameter		.40	3.1	Gage
104	Length of slot		.40	3.1	Gage
105	Width of slot (2 places)		.40	3.1	Gage
106	True position of slot length		.40	3.1	Gage
107	True position of slot width (2 places)		.40	3.1	Gage
108	True position of inside diameter		.40	3.1	Gage
Minor					
201	Evidence of poor workmanship		.65	3.1	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-70440 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Support, Cover (after phosphate coating)	1 OF 1	9369960
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major					
101	Phosphate coating weight	See 4.5.1		3.1	4.5.1
Minor					
201	Coating incomplete or damaged		.65	3.1	Visual
202	Evidence of poor workmanship		.65	3.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-70440 (AR)

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
4.4.2.3	Support, Cover		1 OF 1	9369960
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major					
101	Salt spray test	See 4.5.2		3.1	4.5.2
Minor					
201	Bare spots in paint in excess of .250 inches in length		.65	3.1	Visual
202	Evidence of poor workmanship		.65	3.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. The tests (First Article and Quality Conformance) listed in the Item Detail Specification shall be performed on inspection lots as defined in 4.4.1 of this specification.

4.4.4 Inspection equipment. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and paragraph 6.3 herein.

4.5 Test methods and procedures.

4.5.1 Phosphate coating weight. Two samples per shift shall be selected for this test. Testing and rejection shall be in accordance with TT-C-490.

4.5.2 Salt spray test. Two samples per shift shall be selected for this test. The test shall be performed on the washers as specified in TT-C-490. The test shall be for 48 hours with a 5% sodium chloride solution. Examination shall be made for any evidence of corrosion of the painted areas. If any support, cover fails to comply with the specified requirements, it shall be classified defective and corrective actions taken as specified in TT-C-490.

5. PACKAGING

5.1 Packing.

5.1.1 Overseas shipments. Cover supports shall be semi-bulk packaged, moisture-proof packaged (barrier bag only), packed, marked and palletized in accordance with MIL-STD-1169, Level A. Supports shall be separated in the unit pack to protect the paint surfaces.

5.1.2 Domestic shipments. Cover supports shall be semi-bulk packaged, packed and marked in accordance with MIL-STD-1169, Level B. Palletization is optional. Supports shall be separated in the unit package to protect the paint surfaces.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use in handling artillery projectiles.

6.2 Ordering data. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

6.3 Submission of inspection equipment for design approvals. See MIL-A-48078. Submit designs as required to Commander, US Army Armament Research and Development Center, ATTN: DRSMC-QAR-I (D), Dover, NJ 07801.

6.4 Data requirements. Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Center (ARDC) may also include drawings prepared by and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal, or ARRADCOM drawings. Technical data originally prepared by these activities is now under the cognizance of ARDC.

6.6 Inspection lot size. It is noted that the size of inspection lots of components, assemblies or items of delivery may differ from the actual quantities contractually scheduled for delivery. However, in order to facilitate scheduling of tests or deliveries, inspection lots of items of delivery may be equivalent to such contract quantities provided all of the lot formation criteria and sampling provisions of this specification are maintained.

6.7 Visual examination qualification. When compliance with applicable requirement is in doubt as a result of visual examination, the characteristics may be measured or gaged to determine acceptability.

6.8 Alternative testing procedures. Alternative testing procedures may be used by the contractor when such testing and procedures provide as a minimum the qualify assurance provisions specified herein. Prior to applying alternative procedures, the contractor shall describe them in a written proposal and shall demonstrate for the approval of the responsible Government technical agency that their effectiveness is equal to, or better than the quality assurance provisions specified herein.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project: 1320-A744)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.