MIL-C-11015/20C
AMENDMENT 2
14 July 1983
SUPERSEDING
AMENDMENT 1
16 August 1976

MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, CERAMIC DIELECTRIC (GENERAL PURPOSE),
STYLES CK12, CK13, CK14, CK15, AND CK16

Inactive for new design after 28 September 1970.
For new design use MIL-C-39014/5.

This amendment forms a part of Military Specification MIL-C-11015/20C, dated 28 September 1970, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Dimension table, lines 1 and 2, "C" dimension, delete and substitute:

.016 +.006, -.001	.41 +.15, -.03
.016 +.006, -.001	.41 +.15, -.03

PAGE 3

* Design and construction: Delete case type in its entirety and substitute "Case type - Tubular, molded or preformed plastic encapsulated with axial leads."

PAGE 4

* Temperature cycling and immersion: First sentence: Delete "Temperature cycling and immersion: Temperature cycling: Method 102 of MIL-STD-202, condition D, except step 3 shall be at high test temperature." and substitute "Thermal shock and immersion: Thermal shock: Method 107 of MIL-STD-202, condition A, except step 3 shall be at high test temperature."

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy - AS, OS, SH
Air Force - 17, 99
DLA - ES

User activities:
Navy - MC
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5910-1466)

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:56Z
Check the source to verify that this is the current version before use.