MIL-T-13795A
28 JUNE 1961
SUPERSEDING
MIL-T-13795 (Ord)
22 NOVEMBER 1954

MILITARY SPECIFICATION

TABLE, FOLDING LEGS, PORTABLE

This specification has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force.

1. SCOPE

1.1 Scope. This specification covers one type of portable worktable with folding legs.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-N-290 —Nickel Plating (Electrodeposited).
QQ-P-416 —Plating, Cadmium (Electrodeposited).
TT-E-529 —Enamel, Alkyd, Semi-gloss.
TT-P-636 —Primer Coating, Synthetic, Wood and Ferrous Metal.
TT-W-572 —Wood Preservative; Water-Repellent.
PPP-B-585 —Boxes, Wood, Wirebound.
PPP-B-591 —Boxes, Fiberboard, Wood-Cleated.
PPP-B-601 —Boxes, Wood, Cleated Plywood.
PPP-B-621 —Boxes, Wood, Nailed and Lock-corner.
PPP-B-636 —Box, Fiberboard.
PPP-B-00640 —Boxes, Corrugated, Triple Wall, 350-Pound Maximum Weight.
PPP-T-60 —Tape; Pressure-Sensitive Adhesive, Waterproof — For Packaging and Sealing.

MILITARY

MIL-C-490 —Cleaning and Preparation of Ferrous and Zinc Coated Surfaces for Organic Protective Coating.
MIL-B-10377 —Box, Wood, Cleated, Veneer, Paper-Overlaid.
MIL-P-16232 —Phosphate Coatings, Heavy, Manganese or Zinc Base, for Ferrous Metals.

STANDARDS

FEDERAL

Fed. Std. No. 595—Colors.

MILITARY

MIL-STD-105 —Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-109 —Inspection Terms and Definitions.
MIL-STD-129 —Marking for Shipment and Storage.
MIL-STD-130 —Identification Marking for U.S. Military Property.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless other-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:24Z
Check the source to verify that this is the current version before use.

wise indicated, the issue in effect on date of invitation for bids shall apply.

UNIFORM CLASSIFICATION COMMITTEE
Uniform Freight Classification Rules.
(Application for copies of these freight classification rules should be addressed to the Uniform Classification Committee, 202 Chicago Union Station, Chicago 6, Ill.).

NATIONAL BUREAU OF STANDARDS
Handbook H28—Screw-Thread Standards for Federal Services.
(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, D. C.).

UNITED STATES DEPARTMENT OF COMMERCE
Commercial Standard CS 45–60 Douglas Fir Plywood.
(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, D. C.).

3. REQUIREMENTS

3.1 Preproduction sample. Unless otherwise specified (see 6.2), before production is commenced, a sample of the end item shall be submitted or made ready for approval by the contracting officer or his authorized representative. The purpose of testing the preproduction sample is to determine whether the item manufactured by the contractor has the performance characteristics required by the specifications. It is not the purpose of preproduction sample testing to determine compliance with the detailed requirements of the specification and approval of the preproduction sample does not constitute approval of the item as complying with the detailed requirements of the specifications inasmuch as each production item must comply with the detailed requirements of the specifications. The preproduction sample shall be manufactured by the contractor in the same facilities to be utilized for manufacture of the production items.

3.2 Materials. The material specified shall conform to the referenced specifications and requirements specified hereinafter. Unless otherwise specified, materials will conform to commercial tolerances.

3.2.1 *Plywood.* The plywood used in fabrication of the table top shall be 5/8-inch thick, 5-ply, Douglas-fir, exterior type, grade AC, sanded two sides, conforming to Commercial Standard CS 45–60.

3.2.2 *Hardware, miscellaneous.* All screws, nuts, pins, bolts, washers, lock-washers, and rivets shall be steel. All threaded hardware shall be in accordance with the applicable requirements of Handbook H–28.

3.2.3 *Primer.* The primer shall conform to Specification TT–P–636.

3.2.4 *Enamel.* The enamel shall conform to Specification TT–E–529. The color shall be olive drab, No. X24087 of Fed. Std. No. 595.

3.2.5 *Preservative.* The preservative shall conform to composition A or B of Specification TT–W–572.

3.3 *Design.*

3.3.1 *Load.* The steel components of the table shall be without permanent set and the deflection of the table top shall not exceed 0.8 inch when tested as specified in 4.4.1. The table shall not collapse or exhibit instability and the leg locking devices shall not release when tested as specified in 4.4.2.

3.3.2 *Vibration.* The table components shall show no permanent deformation, cracks, or loosening and the legs and braces shall function manually after testing as specified in 4.4.3.

3.4 Construction. The construction of the table covered herein shall conform to the requirements of this specification. The dimensions of the table with the legs in the unfolded position shall be 72 inches minimum length, 30 inches minimum width, and not less than 29 inches or more than 31 inches in height. The table shall be 2 5/8 inches maximum depth in the folded position and shall weigh not more than 65 pounds. The table top shall be flat within 1/4 inch when tested as specified in 4.4.4. The table shall not rock more than 1/8 inch when placed on a level surface.

3.4.1 *Table top.* The table top shall be fabricated of plywood specified in 3.2.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:24Z
Check the source to verify that this is the current version before use.

Edges of the table top shall be protected with a suitable molding of plastic, steel or aluminum of a color which harmonizes with the table top. The underside of the table top shall be provided with an apron to house the folded table legs.

3.4.2 *Apron.* At the option of the manufacturer either a formed steel apron or angle iron apron as specified herein shall be used.

3.4.2.1 *Formed steel apron.* The formed steel apron shall be made of not less than 0.0598-inch thick (16-gage) steel, reinforced on the long sides and set back from the bottom edges of table top. The apron shall be welded at the corners and securely attached to the underside of top.

3.4.2.2 *Angle iron apron.* The angle iron apron shall consist of a frame of angle irons not less than 1⅝ inches by 1⅛ inches by ⅛ inch thick running lengthwise on the bottom of the table top and across each end between the longitudinal angles. The angles shall be set back from the bottom edge of the table top and securely attached to the underside of the top.

3.4.3 *Legs and braces.* The legs shall be fabricated of steel tubing with a wall thickness of not less than 0.049-inch thick (18-gage). One set of legs shall be located at each end of the table and the bottom of the legs shall have smooth caps, plugs, or glides, made of steel. Each set of legs shall have two steel braces of the manual folding type with positive acting locking devices in the open and closed positions. The braces and locking devices shall be constructed to prevent loss of tightness required for proper operation and permit accessibility for adjustment and repair.

3.5 Maintainability. All replaceable parts shall be manufactured to definite standards, tolerances and clearances in order that any such part of a particular type or model may be replaced or adjusted without requiring modification.

3.6 Finish.

3.6.1 *Pretreatment.*

3.6.1.1 *Plywood.* All plywood surfaces shall be treated with a preservative specified in 3.2.5.

3.6.1.2 *Hardware, miscellaneous.* All screws, nuts, pins, bolts, washers, lock-washers, and rivets shall be phosphate coated in accordance with type Z, class 4 of Specification MIL-P-16232; cadmium plated in accordance with class 3, type II of Specification QQ-P-416; or nickel plated in accordance with class 1, type IV of Specification QQ-N-290.

3.6.1.3 *Ferrous metal.* All ferrous metal surfaces shall be treated for painting in accordance with any method of Specification MIL-C-490.

3.6.2 *Priming.* All wood and treated ferrous metal surfaces shall be coated with enamel specified in 3.2.3.

3.6.3 *Enameling.* All primed surfaces of the table shall be coated with enamel specified in 3.2.4. The final finish shall be uniform in appearance and shall be free of runs, wrinkles, and sags.

3.7 Marking for identification. Each table shall be marked for identification in accordance with Standard MIL-STD-130.

3.8 Workmanship. The finished table shall be clean, well-made, and free of any defects which may affect appearance or serviceability. Rough and sharp edges injurious to the hands shall be removed from all metal components of the table. Welds shall be smooth and sound and free from pits, slag inclusion and porosity.

4. QUALITY ASSURANCE PROVISIONS

4.1 Inspection responsibility. The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order (see 6.2). The Government reserves the right to perform any of

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:24Z
Check the source to verify that this is the current version before use.

the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Preproduction sample testing. When required, testing of the preproduction sample shall be made of a completely fabricated table for all provisions of this specification applicable to end product performance tests.

4.3 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in Standard MIL–STD–105, except where otherwise indicated. The inspection terms and definitions shall be interpreted in accordance with Standard MIL–STD–109.

4.3.1 *Component and material inspection.* In accordance with 4.1 herein, the supplier is responsible for insuring that components and materials used are manufactured, tested, and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified herein, or if none, in accordance with this specification.

4.3.2 *Process examination.* Examination shall be made of the following operations to establish that no deviation is made from indicated requirements. Whenever a deviation

Classification of defects

Examine	Defect	Classification	
		Major	Minor
Finish	Not type or color specified	X	
	Poor adhesion— i.e., blistered, checking, or peeling	X	
	Tacky, soft runs or sags		X
	Not smooth or uniform, or foreign matter embedded in finish		X
	Scratched affecting appearance		X
	Bare spots, or area of visibly thin coating		X
Construction and workmanship	Component missing, affecting serviceability	X	
	Component malformed, dented, buckled, or bent, affecting serviceability	X	
	Component malformed, dented, buckled, or bent, not affecting serviceability		X
	Sharp edge or projection that may cause injury	X	
Apron, formed steel	Not reinforced or reinforcement not as specified	X	
	Omitted or not attached as specified	X	
	Not welded at corners as specified	X	
Apron, angle iron	Omitted or not attached as specified	X	
Welds	Omitted where specified	X	
	Not fused, is burnt through, cracked or fractured	X	
	Not smooth, or flash or splatter not removed		X
	Pitted or not complete		X
Table top	Not smooth	X	
	Gouges, chipped veneer or any delamination	X	
	Torn grain, splintered, or small checks		X
	Molding omitted, not type specified, or color does not harmonize with table top	X	
	Edge surfaces of table top not completely covered by molding		X
Legs	Table legs do not fold properly or not located as specified	X	
	Table rocks more than 1/8 inch	X	
	Screws, nut, pins, and washers not nickel or cadmium plated (if applicable)		X
	Any glide, cap or plug missing	X	
	Leg braces do not have positive acting locking device, or locking device not constructed to prevent loss of tightness	X	
	Locking device not accessible for adjustment or repair	X	
Identification marking	Missing, illegible, incomplete or wrong location		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:24Z
Check the source to verify that this is the current version before use.

is noted, correction shall be made. Failure to make immediate correction may cause rejection of the affected end item lot:

(a) Plywood has been treated with wood preservative as specified in 3.6.1.1.

(b) Hardware items have been phosphate coated, cadmium plated or nickel plated (as applicable) as specified in 3.6.1.2.

(c) Ferrous metal surfaces have been prepared for painting as specified in 3.6.1.3.

(d) Wood and treated metal surfaces have been coated with primer as specified in 3.6.2.

4.3.3 *End item inspection.*

4.3.3.1 *Visual examination.* Examination of the end item shall be in accordance with the classification of defects and Acceptable Quality Levels (AQL's) set forth below. The lot size shall be expressed in units of tables for the purpose of determining the sample size in accordance with Standard MIL–STD–105. The sample unit for this examination shall be one completely fabricated table.

4.3.3.2 *Dimensional examination.* Inspection will be made of the table for defects in dimensions. Any dimension not within specified tolerances shall be classified as a defect.

4.3.3.3 *Examination of preparation for delivery.* An examination will be made to determine that packaging, packing and marking as required by section 5 of this specification are complied with. Defects will be scored as specified herein. The sample unit shall be one shipping container fully prepared for delivery. The lot size shall be the number of containers in the inspection lot.

Examine	Defect
Markings (exterior and interior container)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Component missing, damaged, or otherwise defective affecting serviceability.
Workmanship	Inadequate application of components such as incomplete closure of case liners, containers flaps, loose strapping, inadequate stapling; bulging, or distortion of containers.
Contents	Number per container is more or less than required.

4.3.3.4 *Inspection levels and AQL's.* The Acceptable Quality Levels (AQL's), expressed in defects per one hundred units, and inspection levels shall be as follows:

	Inspection level	AQL's Major	AQL's Total
For examination in 4.3.3.1	II	4.0	6.5
For examination in 4.3.3.2	L–4 (one class)		4.0
For examination in 4.3.3.3	L–4 (one class)		4.0

4.3.3.5 *Testing of the end item.* Tests shall be performed on two sample tables from each lot in accordance with table I for the characteristics specified therein with no indication of failure. These characteristics are applicable to individual unit requirements.

TABLE I. *Testing of end item*

Characteristic	Requirement paragraph	Test method
Static load test	3.3.1	4.4.1
Horizontal force test	3.3.1	4.4.2
Vibration test	3.3.2	4.4.3
Level test	3.4	4.4.4

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:24Z
Check the source to verify that this is the current version before use.

4.4 Tests.

4.4.1 *Static load test.* With the table erected and with legs locked in the unfolded position, a dead weight of 800 pounds shall be applied at the center of the table top over an area not to exceed 1 square foot. The table shall remain loaded for a period of not less than 8 hours.

4.4.2 *Horizontal force test.* With the table loaded as specified in 4.4.1 an additional 50-pound horizontal force shall be applied to a corner at a direction of 90° to the long edge of the table.

4.4.3 *Vibration test.* The table with legs locked in the unfolded position shall be rigidly fastened through mounting holes on a vibrating machine and subjected to vibrations with an amplitude of 1/16 inch (1/8 in. total excursion) at a frequency of not less than 600 cycles per minute, for a period of 1 hour in the direction of the vertical axis.

4.4.4 *Level test.* Place the table on a level surface with the legs locked in the unfolded position. Place a straight edge diagonally between two corners of the table top and measure the maximum gap between the straight edge and the table top. Repeat this measurement for the remaining two corners of the table top.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 *Level A.* Each table with legs folded and locked in closed position shall be packaged in a snug-fitting fiberboard folder or box conforming to class 2, V3c, style FPF or FTC of Specification PPP–B–636, except that the dimensional limitations shall be waived. The inside dimensions of each folder shall approximate 31 inches in length, 2⅝ inches in width, and 73 inches in depth. Inside box dimensions shall approximate 73 inches in length, 31 inches in width, and 2⅝ inches in depth. Approximate dimensions are furnished as a guide only. Closure of the folder shall be affected by securing the end flaps and the tuck flap by application throughout the entire area of contact between the flaps with adhesive commercially used for the specific product being packaged, or by metal stitching, or by a combination of metal stitching and adhesive. Each box shall be closed in accordance with the appendix of the box specification. Each folder or box shall be waterproofed by sealing all seams and corners with minimum 3-inch width tape conforming to type III, class 1 of Specification PPP–T–60.

5.1.2 *Level B (see 6.3).* Each table with legs folded and locked in closed position shall be packaged in a snug-fitting fiberboard folder or box conforming to type I, class 1, style FPF or FTC of Specification PPP–B–636, except that the minimum bursting strength of fiberboard shall be 275 psi, and that the dimensional limitations shall be waived. The inside dimensions of each folder shall approximate 31 inches in length, 2⅝ inches in width, and 73 inches in depth. Inside box dimensions shall approximate 73 inches in length, 31 inches in width, and 2⅝ inches in depth. Approximate dimensions are furnished as a guide only. Closure of the folder shall be effected by securing the end flaps and the tuck flap by application throughout the entire area of contact between the flaps with adhesive commercially used for the specific product being packaged, or by metal stitching, or by a combination of metal stitching and adhesive. Each box shall be closed in accordance with the appendix of the box specification.

5.1.3 *Level C.* Each table shall be packaged in a box in accordance with the industry's practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 *Level A.* Two tables, packaged as specified in 5.1, shall be packed flat in a snug-fitting shipping container conforming to overseas type of Specification PPP–B–591, PPP–B–601, or MIL–B–10377; class 2, style F of Specification PPP–B–00640; style 1, 2, or 2A, class 3 use, type 2 load of Specification PPP–B–585; or class 2, style 2 or 4 of Speci-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:24Z
Check the source to verify that this is the current version before use.

fication PPP–B–621. Each shipping container shall be closed and reinforced with flat steel strapping or tape banding in accordance with the appendix of the applicable container specification.

5.2.2 *Level B.* Each table, packaged as specified in 5.1, shall be reinforced with flat steel strapping or tape banding in accordance with the appendix of Specification PPP–B–636. No further packing required.

5.2.3 *Level C.* Tables, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination. Containers shall be in accordance with Uniform Freight Classification Rules or regulations of other carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Standard MIL–STD–129.

6. NOTES

6.1 Intended use. The portable folding table covered by this specification is intended for use in vehicle maintenance shops to provide a working surface for vehicle equipment.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) When preproduction sample is waived (see 3.1).
(c) Inspection record details (see 4.1).
(d) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.3 Level B packaging is intended to provide economical but limited protection, and should be specified only when it is determined the tables will be held in covered storage approximately one year from date of packaging (see 5.1.2).

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodians:
Army—QMC
Navy—Docks

Preparing activity:
Army—QMC

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:24Z
Check the source to verify that this is the current version before use.