INCH-POUND

MIL-T-13795B
2 November 1992
SUPERSEDING
MIL-T-13795A
28 June 1961

MILITARY SPECIFICATION

TABLE, FOLDING LEGS, PORTABLE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of portable worktable with folding legs (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government Documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

TT-W-572	-	Wood Preservative: Water-Repellent
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5017 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7195

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:24Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-H28 - Screw-Thread Standards for Federal Services
FED-STD-123 - Marking for Shipment (Civil Agencies)
FED-STD-595 - Colors Used in Government Procurement

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-130 - Identification Marking of U.S. Military Property
MIL-STD-171 - Finishing of Metal and Wood Surfaces

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094).

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

U.S. PRODUCT STANDARD (PS)

PS 1 - For Construction & Industrial Plywood, with Typical APA Trademarks

(Application for copies should be addressed to the Office of Standards Code and Information Program at the National Institute of Standards and Technology, Admin. Building 411, Room A163, Gaithersburg, MD 20879).

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:24Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (6.3) in accordance with 4.3.

3.2 Material. The material shall be as specified herein. However, when a definite material is not specified, a material shall be used which will enable the table to meet the performance requirements of this specification. Unless otherwise specified, material shall conform to commercial tolerances. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.2.1 Plywood. The plywood used in the fabrication of the table top shall be Group 1, exterior type, Grade A-C of U.S. Product Standard PS 1.

3.2.2 Hardware, miscellaneous. All screws, nuts, pins, bolts, washers, lock-washers, and rivets shall be steel and have a commercial rust retarding coating. All threaded hardware shall be in accordance with the applicable requirements of FED-STD-H28.

3.2.3 Preservative. The preservative shall conform to composition A, B or D of TT-W-572.

3.3 Design and construction. The design and construction of the table shall be specified herein. The dimensions of the table with the legs in the unfolded position shall be 72 to 73 inches in length, 30 to 31 inches in width, and 29 to 31 inches in height. The table shall be 2-5/8 inches maximum depth with legs in the folded position and shall weigh not more than 65 pounds.

3.3.1 Table top. The table top shall be fabricated of plywood specified in 3.2.1. Edges of the table top shall be protected with a suitable molding of plastic, steel, or aluminum. The plastic molding shall be black in color. The metal molding shall be painted the color of the table (see 3.4.1). The underside of the table top shall be provided with an apron to house the folded table legs.

3.3.2 Apron. At the option of the manufacturer either a formed steel apron or angle iron apron as specified herein shall be used.

3.3.2.1 Formed steel apron. The formed steel apron shall be reinforced on the long sides and set back from the bottom perimeter of the table top. The apron shall be welded (see 3.6.1) at the corners and securely attached to the underside of the top.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:24Z
Check the source to verify that this is the current version before use.

3.3.2.2 Angle iron apron. The angle iron apron shall consist of a frame of angle irons. The angles shall be set back from the bottom perimeter of the table top and securely attached to the underside of the top.

3.3.3 Legs and braces. The legs shall be fabricated of steel tubing. One set of legs shall be located at each end of the table and the bottom of the legs shall have smooth caps, plugs, or glides, made of steel. The legs shall fold under the table in the lengthwise direction. Each set of legs shall have two steel braces of the manual folding type with positive acting locking devices in the open and closed positions. The braces and locking devices shall be constructed to prevent loss of tightness required for proper operation and permit accessibility for adjustment and repair.

3.3.4 Static load. When tested as specified in 4.4.4 with the static load applied, the table shall not collapse or show any of the following conditions: Crack, instability, permanent deformation, failure or loosening of any part, deflection of the top in excess of 3/4 inch, or failure of the locking device to release after the load is removed.

3.3.5 Vibration. The table components shall show no permanent deformation, cracks, or loosening. The legs and braces shall function normally after testing as specified in 4.4.4.

3.3.6 Flatness, table top. The erected table shall be placed upright on a level surface and a straight edge placed diagonally between two corners of the table top. The gap between the table top and the straight edge shall be no more than 1/4 inch at the center of the table. This measurement shall be repeated for the remaining two corners and shall be tested as specified in 4.4.4.

3.3.7 Levelness. The erected table shall be placed upright on a flat, level surface and rocked using two diagonal corners of the table top. The table shall rock no more than 1/8 inch. This measurement shall be repeated for the remaining two corners and shall be tested as specified in 4.4.4.

3.4 Finish.

3.4.1 Plywood. Prior to assembly, all plywood surfaces shall be treated with a preservative as specified in 3.2.3 and allowed to dry per the manufacturers instructions. The plywood shall then be painted in accordance with finish number 27.1 of MIL-STD-171, color number 24084 of FED-STD-595.

3.4.2 Legs, braces, and steel apron. Prior to assembly, all steel components shall be treated and painted in accordance with finish number 21.3 of MIL-STD-171, color number 24084 of FED-STD-595.

3.5 Marking for identification. The table shall be marked for identification in accordance with MIL-STD-130.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:24Z
Check the source to verify that this is the current version before use.

3.6 Workmanship. The end item shall conform to the quality of product established by this document and the occurrence of defects shall not exceed the applicable acceptable quality levels.

3.6.1 Welds. The surfaces of parts to be welded shall be free from oxide, scale, paint, grease, and other foreign matter. Spot welds shall be adherent and not burned through. Welds shall be continuous, sound, smooth, and free from porosity, cracks, incomplete fusion, and deformation of material. All scale and flux deposits (when flux is used) shall be removed from the finished welds, and rough edges and projections shall be dressed smooth.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless otherwise disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility of dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.1.3 Certificates of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:24Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.2 and 4.4.3 and tested for the characteristics specified in 4.4.4. Any nonconformance shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.1 Component and material certification. A certificate of compliance shall be acceptable as evidence that the finish conforms to the requirement specified in 3.4.

4.4.2 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of tables. The sample unit shall be one table. The inspection level shall be II. An acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0 for major defects and 10 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Finish	Not type specified	101	
	Color not as specified		201
	Area of no film		202
	Contains streaks, runs, drops, or wrinkles		203
	Dirt, grit, or foreign material		204
	Not smooth or uniform		205
	Poor adhesion, i.e., blistering or peeling	102	
Construction	Component loose or missing	103	
	Component broken, cracked, split, or malformed	104	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:24Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction (cont'd)	Component not located as specified	105	
	Component has rough edges, burrs not removed	106	
Welds	Missing	107	
	Not as specified	108	
	Not fused, is burnt through, cracked or fractured	109	
	Not smooth, flush, or splatter not removed		206
	Pitted or not complete	110	
Legs	Do not fold properly	111	
	Pin or rivet missing	112	
Identification markings	Missing, illegible, incomplete, or wrong location		207

4.4.3 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified in 3.3. Only those dimensions that can be evaluated without damaging or disassembling the end item shall be examined. Any dimension not as specified shall be classified as a defect. The lot size shall be expressed in units of tables. The sample unit shall be one table. The inspection level shall be II, and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.4 End item testing. The end items shall be tested for the characteristics listed in Table II. The lot size shall be expressed in units of tables. The sample unit shall be one table. The inspection level shall be S-1. Any test failure shall be cause for rejection of the lot.

TABLE II. End item tests

Characteristic	Requirement paragraph	Test paragraph
Static load	3.3.4	4.5.1
Vibration	3.3.5	4.5.2
Flatness, table top	3.3.6	4.5.3
Levelness	3.3.7	4.5.4

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:24Z
Check the source to verify that this is the current version before use.

units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2, and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required
Skidding	Skidding not as specified

4.5 Methods of inspection.

4.5.1 Static load test. With the table upright and with the legs locked in the upright position, a dead weight of 500 pounds shall be applied at the center of the table top over an area not to exceed 1 square foot. The table shall remain loaded for a period of not less than 8 hours. Noncompliance with any of the requirements in 3.3.4 shall constitute a test failure.

4.5.2 Vibration test. The table with legs locked in the upright position shall be rigidly fastened on a vibrating machine and subject to vibrations with an amplitude 1/16 inch (1/8 total excursion) at a frequency of not less than 600 cycles per minute, for a period of one hour in the direction of the vertical axis. Noncompliance with any of the requirements in 3.3.5 shall constitute a test failure.

4.5.3 Flatness test, table top. Place the table on a level surface with the legs locked in the upright position. Place a straight edge diagonally between two corners of the table top and measure the maximum gap at the table's centerpoint, between the straight edge and the table top. Repeat this measurement for the remaining two corners of the table top. Any measurement over 1/4 inch shall constitute failure of this test.

4.5.4 Level test. Place the table on a flat, level surface with the legs locked in the upright position. Alternately rock the table diagonally (opposite corners). Rocking more than 1/8 inch on either of the diagonally opposite corners shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:24Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A preservation. Each table, with legs folded and locked in the closed position, shall be preserved in a 4 mil polyethylene plastic bag. One table shall be packaged in a box conforming to style FTC, grade V3c of PPP-B-636. Inside box dimensions shall approximate 73 inches in length, 31 inches in width, and 2-3/4 inches in depth. Each box shall be closed, waterproofed, and reinforced in accordance with the appendix of PPP-B-636.

5.1.2 Commercial preservation. Each table shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial (see 6.2).

5.2.1 Level A packing. Ten tables, preserved as specified in 5.1, shall be packed in a shipping container conforming to domestic type, any style of PPP-B-601. Each shipping container shall be skidded, closed, and strapped in accordance with PPP-B-601.

5.2.2 Level B packing. Ten tables, preserved as specified in 5.1, shall be closed, fitted with edge protectors, strapped and skidded in accordance with PPP-B-601.

5.2.3 Commercial packing. Tables, packaged as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking. Marking shall be in accordance with 5.3.1 or 5.3.2 as specified (see 6.2).

5.3.1 Civil agencies. In addition to any special marking required by the contract or purchase order, all marking shall be in accordance with FED-STD-123.

5.3.2 Military activities. In addition to any special marking required by the contract or purchase order, all marking shall be in accordance with MIL-STD-129.

5.3.3 Special marking. In addition to the marking required by 5.3.1 or 5.3.2, the following shall be marked on the top in characters a minimum of 2 inches high:

FURNITURE
FRAGILE - HANDLE WITH CARE
TOP - THIS SIDE UP

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:24Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The portable folding table is intended for use in vehicle maintenance shops to provide a working surface for vehicle equipment.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Levels of preservation and packing (see 5.1 and 5.2).
e. Type of marking required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Federal Acquisition Regulation (FAR) 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Subject term (key word) listing.

Bench
Equipment
Steel table
Work Bench

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Air Force - 99

Review activity:

Air Force - 84

Civil agency coordinating activity:

GSA - FSS

Preparing activity:

Army - GL

(Project 7195-0090)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-T-13795B	1992 November 2

3. DOCUMENT TITLE

TABLE, FOLDING LEGS, PORTABLE

4. NATURE OF CHANGE (*Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.*)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (*Last, First, Middle Initial*)	b. ORGANIZATION	
c. ADDRESS (*Include Zip Code*)	d. TELEPHONE (*Include Area Code*) (1) Commercial (2) AUTOVON (*If applicable*)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (*Include Area Code*) (1) Commercial	(2) AUTOVON/DSN
U.S. Army Natick RD&E Center	508-651-4531	256-4531
c. ADDRESS (*Include Zip Code*) Commander, U.S. Army Natick RD&E Center ATTN: SATNC-UXT Natick, MA 01760-5017	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026/01/16 02:42
Check the source to verify that this is the current version before use.