MILITARY SPECIFICATION

BEACON SET, RADIO AN/URT-33

1. SCOPE

* 1.1 This specification covers the requirements for one type of electronic rescue beacon, designated Beacon Set, Radio, AN/URT-33, henceforth known as the beacon set.

2. APPLICABLE DOCUMENTS

* 2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of the specification to the extent specified herein.

SPECIFICATIONS

Federal

| | |
|---|---|
| ZZ-R-765 | Rubber, Silicone: Low And High-Temperature and Tear Resistant |
| PPP-B-576 | Box, Wood, Cleated, Veneer, Paper Overlaid |
| PPP-B-636 | Box, Fiberboard |
| PPP-B-676 | Box, Set-Up, Paperboard |

Military

| | |
|---|---|
| MIL-P-116 | Preservation, Methods Of |
| MIL-C-3098 | Crystal Units, Quarts, General Specification For |
| MIL-E-5272 | Environmental Testing, Aeronautical And Associated Equipment, General Specification For |
| MIL-E-5400 | Electronic Equipment, Aircraft, General Specification For |
| MIL-B-5423 | Boots, Dust And Water Seal (For Toggle And Push-Button Switches And Rotary-Actuated Parts), General Specification |
| MIL-C-5541 | Chemical Film Materials For Aluminum And Aluminum Alloys |
| MIL-I-6869 | Impregnants For Aluminum Alloy And Magnesium Alloy Castings |



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:34Z
Check the source to verify that this is the current version before use.

| | |
|---|---|
| MIL-A-8625 | Anodic Coatings, For Aluminum And Aluminum Alloys |
| MIL-L-10547 | Liners, Case, And Sheet, Overwrap; Water-Vaporproof Or Waterproof Flexible |
| MIL-I-46058 | Insulating Compound, Electrical |

STANDARDS

Federal

| | |
|---|---|
| FED-STD-595 | Colors |

Military

| | |
|---|---|
| MIL-STD-129 | Marking For Shipment And Storage |
| MIL-STD-192 | Alloy And Temper Designation System For Wrought Aluminum |
| MIL-STD-276 | Impregnation Of Porous Nonferrous Metal Castings |
| MIL-STD-781 | Reliability Tests; Exponential Distribution |
| MIL-STD-785 | Requirements For Reliability Program |
| MIL-STD-831 | Test Reports, Preparation Of |

DRAWINGS

National Cash Register

300008 Crystal Unit
81000018 Bulkhead Receptacle
81000025 Antenna, 8 Section

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

## 3. REQUIREMENTS

3.1 Preproduction. This specification makes provisions for preproduction testing.

3.2 General specification. The requirements of MIL-E-5400 shall apply as requirements of this specification, with additions or exceptions to the paragraphs of MIL-E-5400, as identified by similarity of paragraph headings, called out herein. When the two documents conflict, this specification shall govern.

* 3.2.1 Classification. The beacon set, shall be Class 1 equipment as defined in MIL-E-5400, with exceptions specified herien.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:34Z
Check the source to verify that this is the current version before use.

3.2.2 Materials, parts and processes.

* 3.2.2.1 Approval of nonstandard parts and materials. Contracts requirements for approval of nonstandard parts and materials are Category III as defined in MIL-E-5400.

3.2.2.2 Castings. Porous metal castings shall be impregnated in accordance with MIL-STD-276, as deemed necessary, to insure compliance with all requirements of this specification. Material used shall conform to MIL-I-6869.

3.2.2.3 Finishes.

3.2.2.3.1 Aluminum case and other aluminum components. The aluminum outer case of the beacon set shall be treated in accordance with MIL-C-5541 prior to painting. Other aluminum components may be anodized in accordance with MIL-A-8625.

* 3.2.2.3.2 Cases and front panels. The outside case and panels of the beacon set shall be finished in a smooth olive drab enamel, color 34087 of FED-STD-595.

3.2.2.4 Tubes (electron) and solid state devices. Vacuum tubes shall not be used. All semiconductors shall be silicon. However, germanium diodes may be used.

3.2.3 Design and construction.

3.2.3.1 Interference. Interference requirements shall not apply.

3.2.3.2 Reliability, longevity, and maintainability.

* 3.2.3.2.1 Reliability program. The contractor shall establish a reliability assurance program and submit reports thereon in accordance with MIL-STD-785.

3.2.3.2.1.1 Mean-time-between-failure (MTBF). The beacon set shall provide a minimum acceptable MTBF of 500 hours (specified MTBF of 750 hours).

3.2.3.2.2 Longevity. The beacon set shall have a service life of not less than 2000 hours before wearout failures occur or the equipment consistently fails to meet the specified MTBF index.

3.2.3.2.3 Maintainability. Operational maintenance shall not be required other than a periodic functional check and battery replacement.

3.2.3.3 Service conditions (electrical). The beacon set shall be powered by battery, dry, BA-1516/U (see 3.3.8).

3.2.3.4 Service conditions (environmental). Class 1 equipment requirements of MIL-E-5400 shall apply, except as specified herein.

3.2.3.4.1 Temperature. The beacon set shall be capable of operating throughout the temperature range of -40° Centigrade (C) to +55°C. The beacon set shall not be damaged by storage at any temperature in the range of -54°C to +55°C.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:34Z
Check the source to verify that this is the current version before use.

3.2.3.4.2 Salt water immersion. The beacon set shall not suffer any mechanical or electrical damage and shall be capable of operating within specification requirements immediately after immerison in salt water at a depth of 29 inches for a period of 15 hours.

3.3 Design and construction. The beacon set shall be completely transistorized, reliable and compact. Its construction shall be rugged and the equipment shall be completely waterproof, weatherproof, and dustproof.

3.3.1 Case. The beacon set case shall be aluminum, temper T6 in accordance with MIL-STD-192. Provision shall be made to prevent buckling or denting of the case by proper location of stiffening ribs.

* 3.3.2 Electronic components. All electronic components shall be protected against moisture, fungus, vibration, and shock by coating with polyurethane resin in accordance with MIL-I-46058.

* 3.3.3 Seals. The rubber material used for static O ring seals shall conform to ZZ-R-765 Class 3b (silicone).

3.3.4 Leakage. The case and seals shall withstand at least 5 pounds per square inch (psi) differential air pressure without leaking.

* 3.3.5 Quartz crystal units. Crystal units shall meet the requirements of MIL-C-3098 as modified by National Cash Register Drawing 300008.

3.3.6 Switch. A single switch shall be provided to turn the beacon set on by automatic activation and on and off by manual operation. The beacon set shall be designed to be housed in a reinforced opened fabric pocket that shall be provided for this purpose in each parachute.

* 3.3.6.1 Manual operation. Manual activation shall be possible and shall be achieved by a simple single-motion manipulation of a switch which shall require a force of 4 ±1.0 pounds. A detent shall be provided at the two extreme switch positions, and switch position shall be discernable by feel.

* 3.3.6.2 Automatic activation. The automatic activation shall consist of the complete removal of a snap plug by means of a lanyard attached to the parachute riser that will replace the beacon set in full operation, when the switch is manually set in the ON position. The beacon set shall not radiate if the switch has been previously set in the OFF position. The means for accomplishing automatic activation shall be so designed that a force of 20 ±5 pounds, acting from the switch through any point on or above the largest case side, shall cause complete extraction of the automatic activation device.

* 3.3.6.3 Switch boots. Switch boots shall conform to MIL-B-5423. Rubber used for switch boots shall conform to ZZ-R-765 Class 3b (silicone).

* 3.3.7 Antenna. A telescopic, one half wavelength antenna shall be incorporated in the beacon set. A connector also shall be provided for connection to a one half wavelength flexible antenna.

* 3.3.7.1 Telescopic antenna. The antenna shall be an end-fed vertical antenna whose height is one half wavelength and it shall be constructed in accordance with National Cash Register drawing 81000025.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:34Z
Check the source to verify that this is the current version before use.

* 3.3.7.1.1 Extension. The telescopic antenna shall provide maximum effective line of sight transmission when fully extended, when the beacon set is held in the hand of the user. When completely collapsed and secured, this antenna shall be entirely contained within the beacon set case and shall not be electrically connected to the transmitter output.

* 3.3.7.1.2 Wet operation. There shall be no change in performance due to prior immersion, rain, snow, fog, et cetera, with the antenna extended, on the performance of the transmitter.

* 3.3.7.2 Antenna connector. The beacon shall be fitted with a waterproof coaxial output connector for connection to a flexible antenna. The antenna connection shall conform to National Cash Register drawing 81000018.

* 3.3.7.3 Antenna matching. The output impedance of the transmitter shall be such as to provide maximum power output and optimum matching at 243.0 Megahertz (MHz) when connected to a one half wavelength end-fed vertical monopole antenna such as that of the model.

* 3.3.7.4 Overload protection. The transmitter circuit shall be so designed and its components so selected that operation of the beacon set shall not be affected, circuitry shall not be damaged, and input electrical current shall not be increased to more than 300 milliamperes by varying antenna (output) loads of any value from a shorted output to no load.

3.3.8 Battery. The beacon set shall include a self-contained replaceable low-temperature 8.1 volt (nominal) mercury battery, type BA-1516/U. The battery shall be replaceable without the use of special tools.

* 3.3.9 Lanyard. The beacon set shall include a 3-foot nylon lanyard, one end of which is securely attached to the case and the other end provided with a means of secure attachment to the life raft or survivor's clothing. The lanyard shall prevent irretrievable loss of the radio beacon.

* 3.3.10 Operating instructions. Operating instructions shall be stencilled as a permanent decal on the back panel of the beacon set. Equipment and switch function identification shall be similarly affixed on the front of the equipment. A label containing space for writing one battery installation date and six beacon test dates shall be affixed to the bottom of the beacon set.

* 3.4 Performance.

* 3.4.1 Input power. The input power requirement of the beacon set shall be such that a BA-1516/U battery will provide power to operate the beacon for a period of fifteen hours of continuous transmission at a temperature of 0°C. The average RF power output of the beacon set shall be a minimum of 200 milliwatts during the first twelve hours of this period and a minimum of 150 milliwatts during the last three hours.

* 3.4.2 Frequency. The radio beacon set shall operate at 243 MHz unless otherwise specified by the procuring activity.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:34Z
Check the source to verify that this is the current version before use.

* 3.4.2.1 Frequency stability. Under any natural combination of battery operating voltage range and environmental conditions specified herein, the frequency of the transmitter shall not deviate more than ±0.003 percent from the selected frequency. Crystal control shall be provided. At rated voltage and 25°C, the frequency shall not be more than 2.4 kilocycles from 243 MHz.

* 3.4.3 Type of transmission. The beacon set shall be pulsed carrier tone modulated. The modulation duty cycle shall be 30 percent minimum and shall have characteristics such that a continuous signal is available for automatic direction finder (adf) lock-on. The frequency of the tone modulation shall be swept from 1000 cycles per second, +30 percent or -0 percent, to 300 cycles per second, +30 percent or -0 percent, at a rate of not less than 2, and not more than 3, times per second.

* 3.4.4 Power output. The radio frequency (rf) power output of the beacon set, as measured into an approved load that simulates the antenna and is located at the antenna feed point, shall not be less than 200 milliwatts average.

* 3.4.5 Durability. During and after successive exposure of the radio beacon set to the environmental conditions specified herein, such as vibration, acceleration, shock, temperature, fungus, decompression, humidity, and water immersion, at normal operating voltage, there shall be no degradation in mechanical or electrical performance and the radio beacon power output shall not be less than 200 milliwatts.

* 3.4.6 Operation at reduced voltages. With a decrease in supply voltage of 30 percent from nominal, the rf power output of the beacon set shall not be less than 150 milliwatts average.

3.5 Size and weight.

3.5.1 Size. The overall dimension of the radio beacon set with antenna collapsed and including the self-contained battery shall not exceed 1-1/4 by 2-5/8 by 4-7/8 inches.

3.5.2 Weight. The radio beacon set including the self-contained battery and self-contained antenna shall not weigh more than 18 ounces.

3.6 Government loaned property. When the contract or purchase order so provides the Government will loan the following to the contractor upon his request.

| Item No. | Description | Quantity |
|---|---|---|
| 1 | AN/URT-33, Beacon Set | 1 |
| 2 | AN/URM-95A, Test Set | 1 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:34Z
Check the source to verify that this is the current version before use.

## 4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 The quality assurance provisions of MIL-E-5400 and the requirements specified herein shall be applicable to this specification. When the two documents conflict, this specification shall govern.

4.2.1 Classification of tests. The inspection and testing of the beacon set shall be classified as follows:

a. Preproduction tests.

b. Acceptance tests.

4.3 Test conditions. Unless otherwise specified, the equipment shall be subjected to the tests under the following test conditions:

a. Temperature: Room ambient (23°C ±10°C).

b. Atmosphere pressure: Prevailing room ambient.

c. Vibration: None.

d. Humidity: Room ambient.

e. Primary power supply: A new battery or adjustable power supply.

4.4 Preproduction testing.

4.4.1 Preproduction test samples. The preproduction test samples shall consist of models representative of the production equipment. They shall be tested under the test conditions specified herein and at the point designated by the contract.

4.4.1.1 Sampling instructions. The contractor shall conduct tests on at least 8 preproduction sample equipments to determine that the design of the equipments meets the requirements specified herein. The contractor's test shall be conducted in accordance with the test procedures specified herein.

4.4.1.1.1 One or more preproduction sample beacon sets, as specified in the contract or purchase order, shall be subjected to all the tests specified in 4.6.1 and 4.6.3.4.

4.4.1.1.2 Seven preproduction samples shall be subjected to the tests specified in 4.6.1, 4.6.2 and 4.6.3.4

4.4.2 Preproduction tests. Preproduction tests shall consist of the tests specified under 4.6, subject to the test conditions specified herein.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:34Z
Check the source to verify that this is the current version before use.

* 4.5 Acceptance tests. Acceptance tests shall consist of individual tests and sampling plans and tests.

4.5.1 Individual tests. Each beacon set shall be subjected to the following tests:

| Test | Applicable Paragraph |
|---|---|
| Examination of Product | 4.6.1 |
| Performance | 4.6.2 |

4.5.2 Sampling plans and tests.

* 4.5.2.1 Sampling plan A - reliability acceptance test. The contractor shall test beacon sets for reliability in accordance with Test Plan XXVII of MIL-STD-781 using test level E except that -54°C should be changed to -40°C. The following parameters shall be measured at least every twelve hours during the reliability acceptance test.

a. Modulation characteristics

b. RF power output

c. Frequency

d. Switch function

In case of a failure, all operating time shall be referred to the time of the last data measurement.

4.5.2.2 Sampling plan B. Beacon sets having passed the individual tests shall be selected at random in accordance with the following:

| Quantity of Items on Contract | Quantity of Items to be Tested |
|---|---|
| 1 to 50 | 1 |
| 51 to 125 | 2 |
| 301 to 500 | 4 |
| over 500 | 1 for each additional 300 on order |

* 4.5.2.2.1 Sampling tests. Selected samples shall be tested as follows:

| Tests | Applicable Paragraph |
|---|---|
| High temperature | 4.6.3.1a |
| Low temperature | 4.6.3.1b |
| Altitude | 4.6.3.1d |
| Immersion (leakage) | 4.6.3.1i |
| Shock and acceleration | 4.6.3.1j |
| Breathing | 4.6.3.2 |
| Decompression | 4.6.3.3 |
| Switch Function | Performance test to insure compliance with 3.3.6 |
| Frequency Stability | Performance test to insure compliance with 3.4.2.1 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:34Z
Check the source to verify that this is the current version before use.

4.5.2.2.2 Rejection and retest. When one equipment from a production run fails to meet the specification, no equipments still on hand or produced later shall be accepted until the extent and cause of failure are determined and corrected.

4.5.2.2.3 Continuation of tests. For operational reasons, individual tests may be continued pending the investigation of a sampling test failure. Final acceptance of equipments on hand or produced later shall not be made until it is determined that equipments meet all the requirements of the specification.

4.5.3 Defects in equipments already accepted. The investigation of a test failure could indicate that defects may exist in equipments already accepted. If so, the contractor shall fully advise the procuring activity of all defects likely to be found and methods of correcting them.

4.6 Test methods.

4.6.1 Examination of product. The beacon set shall be visually inspected to verify that the materials, design and construction, necessary mechanical measurements, marking, and workmanship comply with the requirements of this specification.

* 4.6.2 Performance tests. The procedures and application of performance tests to determine proper performance and compliance with the requirements of this specification shall be prepared by the contractor and subject to approval by the procuring activity. The performance test procedures shall insure compliance with the following requirements:

a. Leakage test (4.6.3.1i)

b. Modulation characteristics (3.4.3)

c. RF power output (or reference field intensity) (3.4.4)

d. Frequency (3.4.2)

e. Power input (3.4.1)

f. Operation at reduced voltage (3.4.6)

4.6.3 Environmental tests. After each environmental test specified herein, the following parameters shall be measured:

a. Modulation (3.4.3)

b. RF power output (3.4.4)

c. Frequency (3.4.2)

d. Switch function (3.3.6)



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:34Z
Check the source to verify that this is the current version before use.

* 4.6.3.1 The following environmental tests shall be in accordance with the indicated procedures of MIL-E-5272, except as modified herein:

a. High temperature test, procedure II. The high temperature shall be +55°C.

b. Low temperature test, procedure II. The temperature of the chamber shall be raised to -40°C.

c. Humidity test, procedure I. After 4 hours under normal room conditions following removal from the humidity chamber, performance shall be equal to that obtained before exposure.

d. Altitude test, procedure VI. The altitude shall be 40,000 feet. With the chamber at these conditions, the power output of the radio transmitter shall be measured. The equipment shall be subjected to a nonoperating altitude test to an altitude of 70,000 feet (1.32 inches of mercury) for a period of 1 hour with no subsequent degradation in performance.

e. Salt water test. The beacon set shall be completely immersed to a depth of 10 feet for 15 minutes and subsequently to a depth of 29 inches for 15 hours in an 8 percent salt (sodium chloride) water solution at normal room temperature and shall meet the performance requirements specified herein after the salt water immersion.

f. Vibration test, procedure XII.

g. Fungus test, procedure I. Immediately after the test model has been subjected to the humidity test, the chassis shall be removed from its case (unless hermetically sealed therein) and subjected to the fungus resistance test. The beacon set shall be tested to, and meet all requirements of 4.6.3.

h. Sand and dust tests, procedure I. The beacon set shall be tested to and meet all requirements of 4.6.3.

i. Immersion (leakage) test, procedure I.

j. Shock and acceleration test. The beacon set shall be firmly mounted on the shock testing machine and subjected to 6 repeated shocks of 100g each for a duration of 11 milliseconds consisting of 1 shock in each directional edgewise plane and 1 shock in each directional longitudinal plane. There shall be no evidence of electrical or mechanical failure.

* 4.6.3.2 Breathing test. The beacon set shall be immersed for 30 minutes in water at a temperature of 60°C. Immediately after removal from the hot water, the beacon set shall be immersed in water at 10°C for not less than 10 minutes. There shall be no indication of water absorption or leakage and the beacon set shall be tested to, and meet all requirements of 4.6.3.

4.6.3.3 Decompression test. The unit shall operate satisfactorily after nonoperating exposure to a change in pressure within 0.1 second, equivalent to a change in altitude from 8,000 to 60,000 feet. The unit shall operate within specified performance limits during return to sea level at the rate of 10,000 feet per minute. Performance in all operational modes shall be equal to that measured prior to exposure.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:34Z
Check the source to verify that this is the current version before use.

* 4.6.3.4 Preproduction reliability and longevity test. The beacon sets shall be subjected to a reliability test in accordance with test plan XXVI of MIL-STD-781 using Test Level E except that -54°C should be changed to -40°C. Two beacon sets shall be tested for longevity in accordance with Test Plan XXVIII of MIL-STD-781. The following parameters shall be measured at least every twelve hours during these tests:

a. Modulation characteristics (3.4.3)

b. RF power output (3.4.4)

c. Frequency (3.4.2)

d. Switch function (3.3.6)

In case of a failure, all operating time shall be referred to the time of the last data measurement.

4.7 Design data and material.

4.7.1 Preproduction test report. The contractor shall submit a preproduction test report in accordance with MIL-STD-831. (See 6.3).

* 4.8 Inspection of the preservation, packaging, packing and marking for shipment and storage. Sample items or packs and the inspection of the preservation, packaging, packing and marking for shipment and storage shall be in accordance with the requirements of Section 5, or the documents specified therein.

5. PREPARATION FOR DELIVERY

* 5.1 Preservation and packaging. Preservation and packaging shall be level A or C, as specified (see 6.2).

* 5.1.1 Level A. Each beacon set shall be packaged Method IC, in accordance with MIL-P-116 (preservative compound not required) and overboxed in a snug-fitting unit container conforming to PPP-B-676.

* 5.1.2 Level C. Beacon sets shall be packaged to afford adequate protection against deterioration and physical damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets these requirements.

* 5.2 Packing. Packing shall be level A, B or C, as specified (see 6.2).

* 5.2.1 Level A. Beacon sets packaged as specified in 5.1 shall be packed in exterior overseas type shipping containers conforming to PPP-B-636 or PPP-B-576. As far as practicable, exterior shipping containers shall be of uniform shape and size, be of minimum cube and tare consistent with the protection required, and contain identical quantities. The gross weight of each shipping container shall not exceed the limitation of the container specification. Containers shall be closed and strapped in accordance with the applicable container specification or appendix thereto. Containers conforming to PPP-B-576 shall be provided with a case liner conforming to MIL-L-10547 and sealed in accordance with appendix thereto.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:34Z
Check the source to verify that this is the current version before use.

* 5.2.2 Level B . Beacon sets packaged as specified in 5.1 shall be packed in domestic type shipping containers conforming to PPP-B-636 or PPP-B-576. Shipping containers shall be of minimum cube and tare consistent with the protection required. As far as practical, shipping containers shall be of uniform shape and size and contain identical quantities. The gross weight of each shipping container shall not exceed the limitation of the container specification. Containers shall be closed and strapped in accordance with the applicable contianer specification or appendix thereto. When fiberboard containers are used, such containers shall meet the special requirements table of PPP-B-636, as applicable.

* 5.2.3 Level C. Beacon sets packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules as applicable.

* 5.3 Marking of shipments. Interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

## 6. NOTES

6.1 Intended use. The beacon set is a subminiature electronic rescue radio beacon intended to be carried in the parachute pack, included in a life vest, or carried by other means by each member of an aircrew. The equipment provides one-way tone transmission to any standard ultra high frequency (UHF) airborne communication equipment and provides tone-modulated signals by which any aircraft equipped with Direction Finder Group AN/ARA-50 and Radio Set AN/ARC-34 can home to the location of the radio beacon.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.

b. Number of preproduction samples, point of testing, and delivery of preproduction test report (see 4.7.1 and 6.3).

c. Submission of test programs for approval (preproduction, acceptance, and reliability) (see 6.3).

d. Selection of applicable levels of preservation and packaging, and packing (see 5.1 and 5.2)

e. The operating frequency of the preproduction samples shall be 242.5 MHz unless otherwise specified by the procuring activity.

f. The operating frequency of the production units if other than 243.0 MHz.

g. Provisions for Government-loaned equipment (see 3.6).

6.3 The delivery and quantity of the preproduction test reports and programs shall be reflected on the DD Form 1423 at the time of award of contract.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:34Z
Check the source to verify that this is the current version before use.

* 6.4 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requriements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Air Force - 82

Preparing Activity:
Air Force - 82

Project No. 5821-F094



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:34Z
Check the source to verify that this is the current version before use.

# SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD, FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:34Z
Check the source to verify that this is the current version before use.