Page 12, table I: Delete and substitute:

"TABLE I

Maximum Noise Level Limits

Octave Band Center Frequencies (Hz)	Sound Pressure Level (Decibels Ref. 0.0002 Dynes/CM^2)	
	Near-Field Positions	Operator's Position
63	115	110
125	110	109
250	116	121
500	107	110
1,000	105	106
2,000	102	105
4,000	97	104
8,000	93	101

Page 13: Add:

"3.14.6 Caution notice. The following marking shall be provided on the long sides of the base (see 3.7.2) in 1-inch high letters and numerals. The letters and numerals shall be color No. 33538 of FED-STD-595.

WARNING - EAR PROTECTION REQUIRED WITHIN
50 FEET WHEN EQUIPMENT IS
OPERATING"

Page 18, paragraph 4.6.8.2, lines 3 and 4: Delete "USA" and substitute "ANSI".

Page 23, last line: Delete "85".

Custodian:
Air Force - 11

Reviewer:
Air Force - 84

Preparing activity:
Air Force - 11

Project No. 4320-F091

☆ U.S. GOVERNMENT PRINTING OFFICE: 1979 -633-690/1422

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:38Z
Check the source to verify that this is the current version before use.

MILITARY SPECIFICATION

PUMPING ASSEMBLY, FLAMMABLE LIQUID, BULK TRANSFER, TRAILER MOUNTED A/M32R-22 DIESEL ENGINE, 600 GPM

This amendment forms a part of Military Specification MIL-P-38447B(USAF) dated 4 January 1968.

Page 2, paragraph 2.1: Delete reference to Military standard "MS33586" and Air Force-Navy Aeronautical standard "AN2552". Under Military, add:

"MIL-STD-889 Dissimilar Metals".

Page 3, paragraph 2.2: Delete reference to the American Standards Association standards and substitute:

"American National Standards Institute, Inc

S1.4	General Purpose Sound Level Meters
S1.6	Preferred Frequencies for Acoustical Measurements
Z24.10	Octave Band Filter Sets for the Analysis of Noise and Other Sounds

(Application for copies should be addressed to the American National Standards Institute, Incorporated; 10 East 40th Street; New York, New York 10016.)"

Page 4, paragraph 3.4.3: Delete and substitute:

"3.4.3 Metals. Unless otherwise specified herein, all components that come into contact with the fuel shall be fabricated of nonferrous metals or 300 series stainless steel."

Page 4, paragraph 3.4.3.1, line 3: Delete "MS33586" and substitute "MIL-STD-889".

Page 8, paragraph 3.7.3.6: Delete.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:38Z
Check the source to verify that this is the current version before use.