MILITARY SPECIFICATION

SLEEPING BAG-CONTAINER, PARACHUTE BAILOUT SRU-15/P

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the requirements for one type of sleeping bag and container of single unit design, designated SRU-15/P.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

UU-P-268	Paper, Kraft, Untreated, Wrapping
CCC-T-191	Textile Test Methods
DDD-L-20	Label; for Clothing, Equipage, and Tentage, (General Use)
PPP-B-636	Box, Fiberboard
PPP-T-60	Tape: Pressure-Sensitive Adhesive, Waterproof, for Packaging

Military

MIL-C-508	Cloth, Oxford, Nylon, 3 Ounce

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage

DRAWINGS

Air Force

56J3637	Patterns - Sleeping Bag, Aircrew Survival

FSC 8465

Source: https://assist.dla.mil -- Downloaded: 202610-21T12:36Z
Check the source to verify that this is the current version before use.

57A3630	Pin - Threaded, Sleeping Bag, Parachute Bailout
58K3727	Sleeping Bag - Aircrew Survival, Type MC-1, Assembly of
59D3988	Sleeping Bag - Container, Parachute Bailout, SRU-15/P, Assembly of
59D3989	Container, Sleeping Bag, Parachute Bailout, Upper Section
59D3990	Container, Sleeping Bag, Parachute Bailout, Lower Section
59A3991	Nut - Retention, Sleeping Bag, Parachute Bailout
59A3992	Wing - Collapsible Sleeping Bag, Parachute Bailout

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Preproduction samples. When specified (see 6.2), before production is commenced, a sample of one completely fabricated and filled sleeping bag and one assembled container, with sleeping bag sealed inside, shall be submitted to or made ready for the contracting officer or his authorized representative for inspection as specified in 4.2. The approval of the preproduction samples authorizes the commencement of production but does not relieve the supplier of responsibility for compliance with all applicable provisions of this specification. The preproduction samples shall be manufactured by the supplier in the same facilities to be used for the manufacture of the production item.

3.2 Materials. Materials for the sleeping bag and container and all components thereof shall be as specified on the applicable drawings (see 3.3). The colors of the outside casing material, thread, and nylon tape for the sleeping bag, as specified on Drawing 58K3727, shall match the standard samples (see 6.3).

3.3 Design and construction. The SRU-15/P sleeping bag and container shall be designed and constructed in accordance with the Drawing 59D3988. The pattern for the sleeping bag shall be in accordance with Drawing 56J3637. The sleeping bag, filled with down and sealed in a vinyl envelope, shall conform to Drawing 58K3727. After sealing the bag in the envelope, air shall be extracted from the envelope by an extraction valve (see Drawing 58K3727) to any degree necessary to pressure-pack the bag in the container. The bag shall be packed in a plastic container consisting of two sections. The upper section shall conform to Drawing 59D3989, and the lower section shall conform to Drawing 59D3990. Polyester tape and pressure-sensitive tape shall be wrapped around the container as specified on Drawing 59D3988. The threaded pin (Drawing 57A3630), the retention nut (Drawing 59A3991), the collapsible wing (Drawing 59A3992), and flat washers shall be installed as shown on Drawing 59D3988. The container shall be compressed so that the thickness of the assembly shall not exceed 2-3/8 inches.

Source: https://assist.dla.mil -- Downloaded: 202610-21T12:36Z
Check the source to verify that this is the current version before use.

3.4 Marking

3.4.1 Sleeping bag

3.4.1.1 Part No. The part number shall be in accordance with Drawing 58K3727.

3.4.1.2 Identification. Identification marking conforming to type IV, class 11 of DDD-L-20 shall be located on the lower inner casing approximately 18 inches from the head end, measured along the centerline, and shall be as follows:

Nomenclature
Stock number
Name of manufacturer
Contract number
Letters "US"

The height of the characters shall be not less than 1/4 inch. The fastness requirement of class 11 labels shall be as specified for class 5.

3.4.1.3 Content label. A content label shall be attached at the foot end of the bag. The back side of the label shall be utilized for recording the weight before and after filling. Format for printing or stenciling the back of the label shall be as follows:

Lot No. _____
Down Lot No. _____
Weight of Empty Casing _____ lbs _____ oz
Net Weight of Down _____ lbs _____ oz
Total Weight _____ lbs _____ oz

3.4.2 Container. All marking on the container shall be in accordance with Drawing 59D3988.

3.5 Workmanship. The sleeping bags and containers shall conform to the quality and grade of product established by this specification, and the occurrence of defects shall not exceed the applicable acceptable quality level.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:36Z
Check the source to verify that this is the current version before use.

4.2 Preproduction sample inspection. When required, the preproduction samples submitted in accordance with 3.1 shall be inspected as specified in 4.3.3.1 and 4.3.3.2 to determine compliance with design, construction, workmanship, and dimensional requirements.

4.3 Inspection. Except where otherwise indicated, inspection shall be in accordance with MIL-STD-105.

4.3.1 Inspection of components. The quality assurance provisions for components, except as otherwise required by this specification, shall be in accordance with subsidiary specifications and standards referenced on the drawings specified herein to the extent applicable.

4.3.1.1 Testing of components. In addition to the quality assurance provisions of the subsidiary specifications and standards, testing shall be performed on the nylon cloth component for the sleeping bag casings as specified in table I. The lot size shall be expressed in units of 1 yard. The sample unit shall be 1 yard, full width of the finished cloth. The sample size (number of sample units) shall be as specified in table II. The lot shall be unacceptable if one or more sample units fail to meet the specified requirement. Tests shall be conducted in accordance with the specified test methods of CCC-T-191.

TABLE I. Component tests

Component	Characteristic	Test method of CCC-T-191
Nylon cloth for sleeping bag casings, MIL-C-508, type II	Spray rating (before and after 3 dry cleanings in accordance with method 5508 of CCC-T-191.	5526

TABLE II. Sample size

Lot size in yards	Sample size
800 or less	2
801 up to and including 22,000	3
22,001 and over	5

4.3.1.2 Certificate of compliance. When specified in the contract or order (see 6.2d), the supplier shall furnish a certificate of compliance for the following listed components and materials. The certificate of compliance shall be accompanied by actual test or inspection reports, or other verifiable data.

Source: https://assist.dla.mil -- Downloaded: 202610-21T12:36Z
Check the source to verify that this is the current version before use.

Component	Drawing reference
Tape, polyester	59D3988-1
Cement	59D3988
Air evacuation valve	58K3727
Premix	59D3989

4.3.2 In-process inspection. Inspection will be made at any point or during any phase of the manufacturing process to determine whether operations or assemblies are carried out as specified. The Government reserves the right to exclude from consideration for acceptance any material or service for which in-process inspection had indicated nonconformance.

4.3.2.1 Intermediate inspection

4.3.2.1.1 Inspection of sleeping bag. Inspection of the unfilled sleeping bags shall be made to verify the weight of individual casings recorded on the content label attached to each bag. The drawstring retainer, leather drawstring keeper, reinforcements or extension, drawstring, and a pair of grommets and washers shall be included in the weight of the casing. This inspection shall be performed prior to filling bags with down. (NOTE: A vinyl envelope containing one drawstring retainer cut to specified length and including either the reinforcement patches or extension, a pair of grommets and washers, leather drawstring keeper, and a complete drawstring shall be included in the unfilled weight of the casing. As an option, the equivalent weight of the referenced components may be added to the unfilled weight of the casing.) The sample unit for this examination shall be one unfilled casing. The inspection level shall be I, and the acceptable quality level (AQL) shall be 1.5 major and 6.5 total expressed in defects per 100 units.

Examine	Defect	Classification	
		Major	Minor
Weight	In excess of weight indicated on content label:		
	- by 1 ounce or less		X
	- by more than 1 ounce	X	

4.3.2.1.2 Unassembled container. The two parts of the container shall be examined unassembled. The sample unit for these examinations shall be one lower and one upper section.

Source: https://assist.dla.mil -- Downloaded: 202610-21T12:36Z
Check the source to verify that this is the current version before use.

4.3.2.1.2.1 Visual examination. The inspection level shall be I, and the AQL shall be 4.0 defects per 100 units, one class.

Examine	Defect
Container halves	Any hole, cut, or crack (except center drill hole).
	Thin spots (areas of sparse distribution of fiber).
	Any globs of cured resin clearly noticeable on surfaces.
	Any foreign matter such as oil or grease spots, carbonized binder, or particles of dirt.
	Any required detail of construction omitted or not as specified.
	Any burrs on inside or outside surface.
Nylon loop	Ends of loop not securely molded or cemented to inside of container.
	Loop not extending to outside through slot in upper half.

4.3.2.1.2.2 Dimensional examination. The inspection level shall be S-3, and the AQL shall be 0.65 defects per 100 units, one class.

Examine	Defect
Dimensions of container halves	Any dimension not as specified on drawings.

NOTE: Determination of compliance with dimensional requirements shall be made for all dimensions indicated on drawings.

4.3.3 End item examination. The defects found during examination shall be classified in accordance with 4.3.3.1, 4.3.3.2, 4.3.3.3, and 4.3.3.4. The lot shall be inspected in accordance with 4.3.4. The sample unit for these examinations shall be one completely fabricated and filled sleeping bag and one assembled container with bag sealed inside.

Source: https://assist.dla.mil -- Downloaded: 202610-21T12:36Z
Check the source to verify that this is the current version before use.

4.3.3.1 Visual examination of sleeping bags

Examine	Defect	Classification: Major	Minor: A	Minor: B
Fabric	Holes, cuts, or tears.	X		
	Any smash, large slubs, broken or missing yarns, multiple floats, or open place, clearly visible at normal inspection distance.	X		
	Shade bar, fine or coarse filling, abrasion mark, or kinks.		X	
Seams and stitching: Open seams (except channel stitching)	On all seams except those which permit escape of down:			
	- 1/2 inch or less.			X
	-More than 1/2 inch but not more than 1 inch.		X	
	-More than 1 inch.	X		
	On seams which permit escape of down:			
	-Any open seam.	X		
On channel stitching	-1/2 inch or more but not more than 1 inch.			X
	-More than 1 inch.		X	
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more continuous skipped stitches or runoffs occur. On doublestitched seams, a seam shall be considered open when either one or both sides of the seam are open.			
Runoffs (see open seams)				
Raw edges (when securely caught in stitching)	-1/2 inch or less.			X
	-More than 1/2 inch.		X	
	NOTE: Raw edges not securely caught in stitching shall be classified as open seams.			

Source: https://assist.dla.mil -- Downloaded: 202610-21T12:36Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification		
		Major	Minor A	Minor B
Seam and stitch type	Wrong seam or stitch type.	X		
Stitch tension	Loose, resulting in loose top or bottom thread.			X
	Tight, resulting in tightness of fabric on seams.	X		
Stitches per inch	One stitch less than minimum specified.			X
	Two or more stitches less than minimum specified.		X	
	One stitch in excess of maximum specified.			X
	Two or more stitches in excess of maximum specified.		X	
	NOTE: Variation in the number of stitches per inch caused by operator's speeding up the machine and pulling the fabric over heavy places, or in turning corners shall be classified as follows: (a) Within the Minor B defect classification - No defect. (b) Within the Minor A defect classification - Minor B defect.			
Stitching margins	Not as specified.			X
Stitching ends	Not backstitched or backstitched less than 1/2 inch (except where held down by other stitching or turned under in a hem)			X
Thread breaks	Overstitched less than 1/2 inch past end of break.		X	

Source: https://assist.dla.mil -- Downloaded: 202610-21T12:36Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification		
		Major	Minor A	Minor B
Thread breaks (continued)	NOTE: Thread breaks not overstitched shall be classified as open seams.			
Stitching	Any required row of stitching omitted.	X		
	Any mends, darns, or patches.	X		
Components and assembly	Any required component part or operation omitted (unless otherwise classified herein).	X		
	Seams badly twisted, pleated, or excessively puckered.	X		
	Needle chews which permit escape of down.	X		
	Needle chews which do not permit escape of down.			X
	Any part of bag spliced: i.e., made from more than one piece of material.	X		
Drawstring	Inserted in drawstring retainer single strand instead of double.	X		
	Cut, chafed, abraded, or otherwise damaged: any part of drawstring caught in stitching.	X		
	Free ends of drawstring not seared or not securely knotted.			X
	Free ends of drawstring not threaded through leather keeper.			X
Drawstring retainer	Twisted, pleated or tight, causing excessive puckering or pleats on bag at face opening.		X	

Source: https://assist.dla.mil -- Downloaded: 202610-21T12:36Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification		
		Major	Minor A	Minor B
Drawstring retainer (continued)	Ends of retainer not finished as specified.		X	
Grommets (Two required)	Not specified type or size.			X
	One or more omitted; broken or malformed, failing to serve intended purpose; burrs or sharp edges.	X		
	Finish not as specified.		X	
	Not securely clinched, or excessively clinched, cutting surrounding fabric.	X		
	Misplaced: - Set on outside of retainer instead of inside.		X	
	- Set with rim of grommet extending beyond edges of retainer.		X	
	- Not set through reinforcement pieces or extended turn under of drawstring retainer.	X		
Quilting	One or more sections of quilted area empty; i.e., no down between outer and inner plies of bag.	X		
	One or more sections of quilted area partially filled.		X	
	Stitching formation irregular or not as specified.			X
Binding	Ends of binding not finished as specified.			X
Channels	Number of channels less than specified.	X		
	Any channel trapped, causing part of channel to remain unfilled.	X		

Source: https://assist.dla.mil -- Downloaded: 202610-21T12:36Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification: Major	Minor: A	Minor: B
Channels (continued)	Channels vary from specified width by more than 1/2 inch.		X	
Filling of channels and edges of bag	Any unfilled channel.	X		
	Any partially filled channel.		X	
	Unevenly filled channels.			X
Cleanness	Spots or stains clearly noticeable; thread ends or clinging down not removed throughout bag.			X
Marking: Identification labels; Content label (when required)	Any required marking omitted, misplaced, incorrect, or illegible.		X	

4.3.3.2 Dimensional examination of sleeping bag

Examine	Defect	Classification: Major	Minor
Dimensions, overall	Smaller than nominal dimensions less applicable minus tolerance, but not smaller than nominal dimensions less twice the applicable minus tolerance indicated on drawing.		X
	Smaller than nominal dimensions less twice the applicable minus tolerance.	X	
	Larger than nominal dimensions and applicable plus tolerance indicated on drawing.		X
Components and location dimensions	Not within specified tolerance.		X

Source: https://assist.dla.mil -- Downloaded: 202610-21T12:36Z
Check the source to verify that this is the current version before use.

4.3.3.3 Examination for weight of down in filled bag

Examine	Defect	Classification One Class
Filled bag for weight of down	Weight not within specified range.	
NOTE: To determine weight of down blown into sleeping bag, deduct the weight of unfilled casing indicated on content label from the total weight of bag.		

4.3.3.4 Examination of assembled container after sealing. The sample unit for this examination shall be one completely assembled container with sleeping bag sealed inside.

4.3.3.4.1 Visual examination

Examine	Defect
Tape, polyester	Any unsealed areas more than 1/4 inch in length or depth.
	Wrapped around sides of container with less than three complete turns.
	Free end of tape not securely sealed: extending over upper half in lieu of lower half of container; sealed portion extending less than 1 inch beyond center of pinhole.
	Loop at free end of tape not formed as specified.
	Length of loop not within specified tolerance.
Pin, threaded	Loosely or insecurely applied.
	End of pin protruding noticeably beyond surface of the wing nut.
Washers	Any required washer omitted.
Marking	Identification or instruction labels for opening omitted, incorrect, illegible, or improperly applied.
Tape reinforcements (Four required)	Any section omitted.

Source: https://assist.dla.mil -- Downloaded: 202610-21T12:36Z
Check the source to verify that this is the current version before use.

Examine	Defect
Tape reinforcements (Four required) (continued)	Any section wrapped less than 2-1/2 turns, or free end not formed into a tab.
	Reinforcement placed over identification or instruction label.
	Set beyond specified location by more than 1/4 inch.
	Length of tab less than specified by more than 1/2 inch.

4.3.3.4.2 Examination for thickness of assembled container. An examination shall be made to determine compliance with the requirement for maximum thickness of the assembled container. Determination of compliance with thickness requirements of assembled containers shall be made in accordance with the following method. The assembled container shall be placed upon a flat surface inclined at an angle of 45°; the container shall slide (due to its own weight) underneath a plate mounted 2-3/8 inches above and parallel to the inclined flat surface. A cutout shall be provided in the plate to enable the carrying tape loop to pass under. The distance the assembly slides on the surface before passing under the plate shall not exceed 6 feet. Any failure shall be the basis for rejection of the lot.

Examine	Defect
Thickness of assembled container	Any container failing to slide freely under its own weight between the flat surface and mounted weight of testing equipment.

4.3.4 Inspection level and AQL. The inspection levels and AQL's (expressed in defects per 100 units unless otherwise specified) shall be as follows:

Examination	Inspection Level	AQL
For defects applicable to 4.3.3.1, visual examination of bag.	II	2.5 Major 10.0 Major and Minor A 25.0 Total Major Minor A and B
For defects applicable to 4.3.3.2, dimensional examination of bag.	S-3	6.5 Major 15.0 Minor 40.0 Total

Source: https://assist.dla.mil -- Downloaded: 202610-21T12:36Z
Check the source to verify that this is the current version before use.

Examination	Inspection Level	AQL
For defects applicable to 4.3.3.3, examination for weight of down in filled bag.	II	2.5 defective
For defects applicable to 4.3.3.4.1, visual examination of assembled and sealed container.	I	2.5 one class
For defects applicable to 4.3.3.4.2, examination for thickness of assembled and sealed container.	III	See 4.3.3.4.2

4.3.5 Examination of preparation for delivery requirements. An examination shall be made to determine that packing and marking requirements of section 5 of this specification are met. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. The inspection level shall be S-2 and the AQL shall 2.5 defects per 100 units. Shipping containers fully prepared for delivery shall be examined for defects of closure; defects shall be scored as follows:

Examine	Defect
Marking (exterior and interior)	Omitted, incorrect, illegible, of improper size, location, sequence, or method of application.
Materials	Any component missing.
	Any component damaged.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, loose or improper taping, inadequate stapling.
	Bulging or distortion of containers.
Content	Number per container is more or less than required.

Source: https://assist.dla.mil -- Downloaded: 202610-21T12:36Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A. Ten containers with sleeping bags sealed inside shall be packed on end 10 in length, 1 in width, and 1 in depth within a fiberboard shipping container conforming to PPP-B-636, class weather resistant, V3s, style RSC-L. The inside of each fiberboard shipping container shall be fitted with a taped, one-piece, double-faced corrugated liner having a minimum bursting strength of 275 pounds per square inch (psi) and conforming to PPP-B-636. Inside dimensions of each shipping container shall be approximately 25-3/4 inches in length, 14-1/2 inches in width, and 13-1/2 inches in depth. Approximate dimensions are furnished as a guide only. Each fiberboard container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to grade B of UU-P-268. Each fiberboard shipping container shall have all seams, corners, and manufacturer's joint sealed by the application of a 3-inch minimum width, olive drab color cloth tape conforming to PPP-T-60, class 1. Each shipping container shall be closed and reinforced with flat steel strapping or tape banding in accordance with the appendix of the container specification.

5.1.2 Level B. Ten bags shall be packed on end 10 in length, 1 in width, and 1 in depth within a fiberboard shipping container conforming to PPP-B-636, type CF or SF, class domestic, style RSC-L. The minimum bursting strength of the fiberboard shall be 275 psi. The inside of each fiberboard shipping container shall be fitted with a taped, one-piece, double-faced corrugated liner having a minimum bursting strength of 275 psia and conforming to PPP-B-636. Inside dimensions of each shipping container shall be approximately 25-3/4 inches in length, 14-1/2 inches in width, and 13-1/2 inches in depth. Approximate dimensions are furnished as a guide only. Each fiberboard container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to grade B of UU-P-268. All flaps of the fiberboard shipping container shall be securely sealed with an adhesive used commercially for the specific product being packed by application throughout the entire area of contact between the flaps, or by a combination of metal stitching the bottom flaps and sealing the top flaps with adhesive.

5.1.3 Level C. Bags shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with rules or regulations of carriers applicable to the mode of transportation.

5.2 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 202610-21T12:36Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The sleeping bag-container assembly covered by this specification is intended for use in survival kits.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification

b. Stock number

c. Whether preproduction sample is required (see 3.1)

d. When certificate of compliance and test or inspection reports are required. Data for the Air Force should be submitted in accordance with AFSCM/AFLCM 310-1 procedures. (See 4.3.1.2.)

e. Selection of applicable levels of packing (see 5.1).

6.3 Standard shade samples. For access to standard shade samples of nylon oxford cloth, tape, and thread, requests should be addressed to the procuring activity issuing the invitation for bids.

Custodians:
Army - GL
Navy - SA
Air Force - 11

Review activities:
Army - GL, MD
Navy - SA, MC
Air Force - 11, 67

User activity:
Navy - WP

Preparing activity:
Air Force - 11

Project No. 8465-0139

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:36Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)*

CITY AND STATE

CONTRACT NO.

QUANTITY OF ITEMS PROCURED

DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*

DATE

DD, FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE C-8279

Source: https://assist.dla.mil -- Downloaded: 202610-21T12:36Z
Check the source to verify that this is the current version before use.

FOLD

SEG (SEPS)
WRIGHT-PATTERSON AFB, OHIO

POSTAGE AND FEES PAID

UNITED STATES AIR FORCE
OFFICIAL BUSINESS

Commander
Systems Engineering Group
ATTN: SEPS
Wright-Patterson AFB, Ohio

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:36Z
Check the source to verify that this is the current version before use.