NOT MEASUREMENT SENSITIVE

MIL-DTL-20633D
14 January 2000
SUPERSEDING
MIL-S-20633C
16 February 1989

DETAIL SPECIFICATION

SIGNS AND MARKER, ALUMINUM; MINED AREA MARKING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This detail specification covers safe-lane and mined-area marking signs and a mine marker.

1.2 Classification. The signs and markers should be of the following classes as specified (see 6.2(b)).

Class D - Safe-lane sign
Class E - Mine marker
Class F - Mined area sign

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents in other sections of the specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: Defense Supply Center Richmond (DSCR), ATTN: DSCR-VBD, 8000 Jefferson Davis Highway, Richmond, VA 23297-5610 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 9905

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:08Z
Check the source to verify that this is the current version before use.

2.2 Government documents.

2.2.1 Government documents, drawings, and publications. The following other Government documents, drawing, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation (see 6.2(c)).

DRAWINGS

U.S. ARMY TANK AUTOMOTIVE COMMAND

13211E7810 - Sign, Mined Area Marking
13211E7811 - Sign Safe Lane Marking
13211E7812 - Marker, Land Mine

(Copies of drawings are available from the U.S. Army Tank Automotive Command, ATTN: AMSTA-TR-E/EDS, Engineering Business Group MS#270, Warren, MI 48397-5000.)

2.3 Non-Government Publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DoDISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS are the issues of the documents cited in the solicitation.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI/ASQC Z1.4-1994 Sampling Procedures and Tables for Inspection by Attributes (DoD adopted)

(Applications for copies should be sent to: American National Standards Institute, 11 West 42nd Street, New York, NY 10036.)

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated specifications or specification sheets), the text of the document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2(d)), a sample shall be subjected to first article inspection in accordance with 4.2.

3.2 Quality Conformance. Items shall meet the requirements of section 4.3.

3.3 Packaging. Items shall meet the requirements of section 4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:08Z
Check the source to verify that this is the current version before use.

3.4 Materials and components. Materials and components shall be as specified on the drawings referenced herein. When substitute components are proposed, the contractor shall submit to the responsible agency a listing of all substitute components, samples of the components, and supporting data which proves the functional equivalence and design compatibility of the items. Approval of the submitted listing authorizes construction of the first article.

3.5 Construction. Construction shall conform in all respects to the drawings listed in section 2 and as specified herein.

4 VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2)
b. Quality Conformance inspection (see 4.3)
c. Inspection of packaging (see 4.4)

4.2 First article inspection. When specified (see 6.2(e)), a random sample shall be subject to first article inspection. The contractor shall furnish to the Government one or more safe-lane and mined-area marking signs and mine markers, as specified by the contract. Unless otherwise specified (see 6.2(e)), all examination and test shall be conducted by the contractor and subjected to surveillance and approval by the Government. The signs and markers shall be examined for the characteristics in table I. Failure of first article signs and markers to meet examination criteria of table I shall be cause for rejection of the first article signs and markers. Any failure shall be cause for the Government to reject any production signs and markers until the contractor has provided acceptable evidence that the defects have been eliminated.

Table I. Examination characteristics.

Defects
Components missing or not assembled as specified.
Dimensions not as specified.
Materials not as specified.
Workmanship not as specified.

4.3 Quality conformance inspection. Samples shall be examined for the defects listed in table I. Sampling for examination shall be in accordance with ANSI/ASQC Z1.4. Lot size shall be as specified (see 6.2(f)). The unit of product is one safe-lane sign, one mined-area sign, and one mine marker.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:08Z
Check the source to verify that this is the current version before use.

4.4 Inspection of packaging. The fully packaged end items shall be examined for compliance in accordance with section 5.1. Sampling shall be in accordance with ANSI/ASQC Z1.4. The unit of product shall be a completed pack prepared for shipment. The lot size will be specified by the contracting officer.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2(g)). When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

6.1 Intended use. The class D sign is intended for marking a safe lane through a mined area. The class E mine marker is intended for marking the location of a detected mine until removal is accomplished. The class F sign is intended for marking mined areas.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this document
b. Class of sign or marker required (see 1.2)
c. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.2.1)
d. First article, if required (see 3.1)
e. First article examination responsibility, if different (see 4.2)
f. Quality conformance lot size, specify requirements (see 4.3)
g. Packaging requirements (see 5.1)

6.3 Part identification number (PIN). The PIN to be used for signs and markers acquired to this specification are created as follows:

M	20633-	X
Prefix for military specification	Specification number	Class

6.4 Subject term (key word) listing.

Safe-lane

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:08Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR4
Air Force - 99

Preparing activity:
DLA - GS

(Project 9905-0349)

Reviewers:
Army - GL, MI
Air Force - 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:08Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** MIL-DTL-20633D	**2. DOCUMENT DATE (YYYYMMDD)** 20001401

DOCUMENT TITLE **SIGNS AND MARKER, ALUMINUM; MINED AREA MARKING**

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE (Include Area Code) (1) Commercial (2) DSN *(if applicable)*	**7.DATE SUBMITTED** (YYYYMMDD)

8. PREPARING ACTIVITY

a. NAME DEFENSE SUPPLY CENTER	b. TELEPHONE *Include Area Code)* (1) Commercial 804-279-5019 (2) DSN 695-6011
c. ADDRESS *(Include Zip Code)* Attn: DSCR-VBD, 8000 Jefferson Davis Hwy Richmond, VA 23297-5610	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** DEFENSE STANDARDIZATION PROGRAM OFFICE (DLSC-LM) 8725 John J. Kingman Road, Suite 2533 Fort Belvoir, Virginia 22060-6221 Telephone (703) 767-6888 DSN 427-6888

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:08Z
Check the source to verify that this is the current version before use.