INCH-POUND

MIL-P-20689D
AMENDMENT 3
1 June 1990
SUPERSEDING
AMENDMENT 2
6 April 1990

MILITARY SPECIFICATION

PLASTIC PLASTISOL (FOR COATING METALLIC OBJECTS)

This amendment forms a part of Military Specification MIL-P-20689D, dated 12 February 1988, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

2.2: Delete "ASTM D618 - Conditioning Plastics and Electrical Insulating Materials for Testing."

PAGE 7

4.4.2: Delete and substitute:

"4.4.2 Conditioning and testing. Unless otherwise specified in the applicable test method, all specimens and other test samples (dispersed plastisol) shall be conditioned for 40 hours at 23° ± 2°C (73° ± 4°F) and 50 ± 5 percent relative humidity for specimens less than or equal 7 mm (0.25 in.) in thickness and 88 hours at the same conditions for specimens greater than 7 mm (0.25 in) in thickness."

PAGE 14

Table I - Delete "Viscosity, Castor-Severs, 1/8 inch orifice, poise at sec^{-1}"

Substitute - "Viscosity, Castor-Severs, 1/8 inch orifice, poise at sec^{-1}, maximum"

Custodians:
Army - MR
Navy - SH
Air Force-84

Preparing activity:
Army - MR

Project 8030-0628

Review activities:
Army - MI, AR, EA
Navy - SH
Air Force - 84

User activities:
Army - AT, ME
Navy - YD, AS, EC

DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:12Z
Check the source to verify that this is the current version before use.