NOTICE OF
CHANGE

DOD-STD-35-71A(MI)
NOTICE 2
18 SEPTEMBER 1992

MILITARY STANDARD

AUT0MATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

SWITCHES (THERMAL)

TO ALL HOLDERS OF DOD-STD-35-71A(MI):

1. THE FOLLOWING PAGES OF DOD-STD-35-71A(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
v	18 SEPTEMBER 1992	v	14 JANUARY 1983
1	14 JANUARY 1983 (Reprinted without change)		
2	18 SEPTEMBER 1992	2	14 JANUARY 1983
3	18 SEPTEMBER 1992	3	14 JANUARY 1983
4	18 SEPTEMBER 1992	4	14 JANUARY 1983
9	18 SEPTEMBER 1992	9	14 JANUARY 1983
10	14 JANUARY 1983 (Reprinted without change)		
43	14 JANUARY 1983 (Reprinted without change)		
44	18 SEPTEMBER 1992	44	14 JANUARY 1983
45	18 SEPTEMBER 1992	45	14 JANUARY 1983
46	18 SEPTEMBER 1992	46	14 JANUARY 1983

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of DOD-STD35-71A(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army-MI

Review activities:
Army–KI, AV, CR, ER
ME, MR, SC

User activity
Army-AR

Preparing activity:
Army - MI

(Project EGDS-A428)

AMSC N/A

AREA EGDS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

CONTENTS

			Page
Paragraph	1.	SCOPE	1
	1.1	General	1
	1.2	Purpose	1
	1.3	Utilization	1
	1.4	Military Specification Exception Title Index	1
	2.	APPLICABLE DOCUMENTS	3
	2.1	Government documents	3
	2.2	Non-Government publications	4
	3.	DEFINITIONS	5
	4.	GENERAL REQUIREMENTS	7
	4.1	Introduction	7
	4.2	Specification Requirement Sheet (SRS)	7
	4.3	Configuration	7
	4.3.1	Dimensions	7
	4.3.2	Illustrations	7
	4.4	Units of measure	7
	5	DETAILED REQUIREMENTS	8
	5.1	Introduction	8
	5.2	MSE Formats	8
	5.3	Referenced documents	8
	5.4	Deleted	8
	5.5	Tabulation	9
	5.6	Keyword Code Index (KCI) and Standard paragraphs	13
	5.6.1	Interrelationship of Codes	13
	5.6.2	Automatic MSE Data	13
	5.6.3	DOD-STD-35 Tables	13

TABLES

Table	I.	Title Index	2
	II.	Deleted	9
	III.	Tabulation Candidates	10

APPENDICES

Appendix	A.	Illustrations	
	B.	Characteristic Code Index	195
		Index	203

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 General. This dash-numbered part of the Automated Engineering Document Preparation System (ADEPS) provides detailed requirements for the preparation of Military Specification Exception (MSE) documentation for themral switches.

1.2 Purpose. This military standard provides the necessary information to prepare a Specification Requirement Sheet (SRS) which will be used to generate an MSE by automated data processing.

1.3 Utilization. General instructions, quality assurance provisions, packaging, and notes, applicable to all AEDPS dash-numbered parts have been included in the basic document (DOD-STD-35) to avoid redundancy. Unless otherwise specified in this dash–numbered part, the following list contains additional subjects that are applicable to all AEDPS dash-numbered parts and are included in DOD-STD-35:

a. Writing Methodology
b. Document and Part Numbering
c. Applicable Documents
d. Single and Multi-item Specifications (Tabulation)
e. Keyword Code Index (KCI)
f. General Requirements of AEDPS

1.4 Military Specification Exception Title Index. It is recommended that MIL-STD-1132, Selection and Use of Switches and Associated Hardware, be reviewed prior to using this dash–numbered part book.

The title code for an MSE shall be selected from one of the MSE titles listed in the Title Index (see table I). Data bases have been established for the generation of MSEs for the MSE titles indicated. If a suitable title code is not contained in the Title Index. leave the title code spaces on the SRS blank, and attach a request for the assignment of a title code. Include in the request the desired title and the base document identifier. A code will be assigned and the code, title, and base document will be made a part of the Title Index.

One of the six-digit codes listed in the Title Index entered on a SRS, specifies that the title of the MSE will be the title shown in the Title Index.

Each MSE title listed in the Title Index, is compatible with the document(s) listed with that title under base document. The list of base documents may or may not be a conplete listing. The information shown under coverage is intended for the user’s reference; when more than one document is listed for an MSE title, this information will be found useful in determining which of the documents is most suitable for use as the base document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

The MSE title may or may not be the same as the title used in DODISS, FIIG, or the base document. In general, the MSE title uses the basic federal item name listed in Cataloging Handbook H6. However, titles with additional modifying and identifying words are provided to assist in defining the sccpe of the MSE. Also, less restrictive titles are provided to prevent exclusion of items.

TABLE I. TITLE INDDX

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
SWITCH, THERMOSTATIC	017001	MIL-S-12285	ENGINE FLUID
		MIL-T-21944	MINES
		MIL-S–24236	ELECT. EQUIP.
		MIL-S–82529	FUZE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-F-13927	Fungus Resistance Test, Automotive Components
MIL-S-24236	Switches, Thermostatic, (Metalic and Bimetallic), General Specification for
MIL-S-82529	Switch, Thermal Mark 56 Mod 1

STANDARDS

MILITARY

DOD-STD-35	Automated Engineering Document Preparation, System
MIL–STD-130	Identification Marking of U.S. Military Property
MIL-STD-202	Test Methds for Electronic and Electrical Component Parts
MIL-STD-810	Environmental Test Methods
MIL-STD-1184	Electrical Components for Automotive Vehicles; Waterproofness Tests
MIL-STD-1276	Leads for Electronic Component Parts
MIL-STD-1285	Marking 0[Electrical and Electronic Parts

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

2.2 Non-Goverment publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are these listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the docurmnts cited in the solicitation.

ASTM E 380 Metric Practice Guide

(Application for copies should be addressed to the American Society for Testing and Materials, , 1916 Rae St., Philadelphia, Pa. 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

5.5 Tabulation. Instructions for tabulation are provided in DOD- STD-35. Table III provides codes for column headings which may be used for thermal switch characteristi. When different units of measure within one system (U.S. or SI) are available for specifying a characteristic, only one of the units may be tabulated; e.g. either ounces or pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

TABLE III. TABULATION CANDIDATES

CODE	COLUMN HEADING	CODE	COLUMN HEADING	CODE	COLUMN HEADING
1590	EASE DOC TYPE	1591	BASE DOC CLASS	1592	BASE DOC KIND
1593	BASE DOC CLASSIFI-CATION	1594	BASE DOC CONFIGUR-ATION	1595	LIFE CYCLE RATNG
4000	RES RATING VOLIS DC	4004	RES RATING AMPS DC	4008	RES RATING VOLTS AC
4016	RES RATING AMPS AC	4020	IND RATING VOLTS DC	4024	IND RATING AMPS DC
4028	IND RATING VOLTS AC	4036	IND RATING AMPS AC	4064	LAMP RTG VOLTS DC
4068	LAMP RTG AMPS DC	4072	LAMP RTG VOLTS AC	4080	LAMP RTG AMPS AC
4100	OPEN ON INCREASING TEMP DEG C	4101	OPEN ON INCREASING TEMP + TOL DEG C.	4102	OPEN ON INCREASING TEMP - TOL DEG C
4103	OPEN ON DECEASING TEMP DEG C	4104	OPEN ON DECREASING TEMP + TOL DEG C	4105	OPEN ON DECREASING TEMP - TOL DEG C
4106	CLOSE ON INCREASING TEMP DEG C	4107	CLOSE ON INCREASING TEMP + TOL DEG C	4108	CLOSE ON INCREASING TEMP - TOL DEG C
4109	CLOSE ON DECREASING TEMP DEG C	4110	CLOSE ON DECREASING TEMP + TOL DEG C	4111	CLOSE ON DECREASING TEMP - TOL DEG C
4112	OPENING TEMP DEG C	4113	OPENING TEMP + TOL DEG C	4114	OPENING TEMP - TOL DEG C

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1652	CALIBRATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1652.
1654	CALIBRATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1654.
2100	TEST FIXTURE SHALL BE 2100.
2102	INITIAL FIXTURE TEMPERATuRE SHALL BE 2102 DEGREES CELSIUS.
2104	INITIAL FIXTURE TEMPERATURE SHALL BE 2104 DB3N3ES FAHRENHEIT.
1656	TEMPERATURE CHANGE RATE SHALL BE NOT GREATER THAN 1656 DEGREE(S) CELSIUS PER MINUTE.
2106	TEMPERATURE CHANGE RATE SHALL BE NOT GREATER THAN 2106 DEGREE(S) FAHRENHEIT PER MINUTE.
2108	SECOND OR FINAL FIXTURE TEMPERATURE SHALL BE 2108 DEGREES CELSIUS.
2110	SECOND OR FINAL FIXTURE TEMPERATURE SHALL BE 2110 DEGREES FAHRENHEIT.
1660	THE NUMBER OF CYCLES USED TO COMPUTE THE AVERAGE SHALL BE 1660.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
CALIBRATION (CONT)	
PER (DOC DES) (CONT)	
MAXIMUM TIME BETWEEN TEMPERATURE EXPOSURES (SELECT ONE)	
(SECDNDS)	2112
(MINUTES)	2114
CONNECTOR TORQUE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2120
NO PHYSICAL DAMAGE.	2122
SWITCHING POINT (SELECT ONE)	
CONFORM TO CALIBRATION REQUIREMENTS.	2124
MAXIMUM CHANGE (DEGREES CELSIUS)	2126
MAXIMUM CHANGE (DEGREES FAHRENHEIT)	2128
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2140
PER (DOC DES)	2142

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2112	THE TIME BETWEEN TEMPERATURE EXPOSURES SHALL BE NOT GREATER THAN 2112 SECOND(S).
2114	THE TIME BETWEEN TEMPERATURE EXPOSURES SHALL BE NOT GREATER THAN 2114 MINUTE(S).
2120	CONNECTOR TORQUE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2120.
2122	CONNECTOR TORQUE. THERE SHALL BE NO LOOSENING, ROTATION, DISTORTION, SHORT CIRCUIT OR OTHER DAMAGE.
2124	UNITS SHALL CONF0RM TO CALIBRATION REQUIREMENTS AFTER TEST.
2126	THE CHANGE IN SWITCHING POINT SHALL BE NOT GREATER THAN 2126 DEGREE(S) CELSIUS.
2128	THE CHANGE IN SWITCHING POINT SHALL BE NOT GREATER THAN 2128 DEGREE(S) FAHRENHEIT.
2140	CONNECTOR TORQUE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, FXCEPT 2140.
2142	CONNECTOR TORQUE. TESTING SHALL BE PEFORMED IN ACCORDANCE WITH 2142.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
CONNECTOR TORQUE (CONT)	
PER (DOC DES) (CONT)	
APPLIED TORQUE (SELECT ONE)	
(POUND FEET)	2144
(NEWTON METERS)	2146
TORQUE DURATION (MINUTES)	2148
CONTACT RESISTANCE	
REQUIREMENTS (SELET ONE)	
PER BASE DOCUMENT EXCEPT _____	1688
MAXIMUM CONTACT RESISTANCE (MILLIOHMS)	1690
MAXIMUM CONTACT RESISTIYICE (OHMS)	2150
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT _____	1672
PER MIL-STD-202, METHOD 307.	1673
CURRENT (AMPERES)	1674
OPEN CIRCUIT VOLTAGE (VOLTS DC)	1676

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.