MIL-STD-35-35(MI)
NOTICE 2
6 September 1976

MILITARY STANDARD

AUTOMATED ENGINEERING

DOCUMENT PREPARATION SYSTEM

NETWORKS, PULSE FORMING

TO ALL HOLDERS OF MIL-STD-35-35(MI):

1. THE FOLLOWING PAGES OF MIL-STD-35-35(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED:

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
Cover	19 November 1973	Cover	19 November 1973
ii	6 September 1976	ii	19 November 1973
iii	6 September 1976	iii and iv	19 November 1973
ix	14 February 1975	(REPRINTED WITHOUT CHANGE)	
x	6 September 1976	x - xii	14 February 1975
5	6 September 1976	5	14 February 1975
6	14 February 1975	(REPRINTED WITHOUT CHANGE)	
33	19 November 1973	(REPRINTED WITHOUT CHANGE)	
34	6 September 1976	34	19 November 1973
35	6 September 1976	35	19 November 1973
36	6 September 1976	36	19 November 1973
43	19 November 1973	(REPRINTED WITHOUT CHANGE)	
44	6 September 1976	44 - 48	14 February 1975
57	19 November 1973	(REPRINTED WITHOUT CHANGE)	
58	6 September 1976	58	19 November 1973
71	6 September 1976	71	19 November 1973
72	6 September 1976	72	19 November 1973
73	6 September 1976	73	19 November 1973
74	6 September 1976	74	19 November 1973
123	6 September 1976	123 and 124	14 February 1975
131	6 September 1976	131	19 November 1973
132	6 September 1976	132	19 November 1973
157	6 September 1976	157- 158	14 February 1975

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of MIL-STD-35-35(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army - MI

Review activities:
Army - AT
Army - AV
Army - EL
Army - ME
Army - MR
Army - SG
Army - WC

User activity:
Army - MU

Preparing activity:
Army - MI

(Project EDS-A157)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

MIL-STD-35-35(MI)

19 NOVEMBER 1973

MILITARY STANDARD

AUTOMATED ENGINEERING DOCUMENT PREPARATION SYSTEM

NETWORKS, PULSE FORMING

Supersedes title page of 19 November 1973.

FSC-EDS

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF THE ARMY
U.S. ARMY MATERIEL
DEVELOPMENT AND READINESS COMMAND
ALEXANDRIA, VA 22333

Automated Engineering
Document Preparation System,
Networks, Pulse Forming

MIL-STD-35-35(MI)

1. This Military Standard is approved by the U.S. Army Materiel Development and Readiness Comnand, Department of the Army, and is approved for use by all its activities. All other military activities are required to employ this Standard where suitable.

2. Recommended corrections, additions, or deletions should be addressed to Commander, U.S. Army Missile Command, ATTN: DRSMI-RCS, Redstone Arsenal, Alabama 35809.

Supersedes page ii of 19 November 1973.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

FOREWORD

1. The purpose of MIL-STD-35-35(MI) is to facilitate the preparation of Military Specification, Exceptions for Networks, Pulse Forming.

2. In order to properly utilize this document, it is necessary to have a complete and thorough understanding of the basic MIL-STD-35.

3. It is important that the procedure described in the basic document (MIL-STD-35C) and subsequent revisions be followed explicitly in order for the computer to produce a document suitable for competitive procurement. Information which is standard for all dash-numbered parts has been included in the basic document at the issuance of MIL-STD-35C. This information is. not repeated in each dash-numbered part.

Supersedes pages iii and iv of 19 November 1973.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS (CONT)

SECTION	TITLE	PAGE
1.2.55	Seal	36
1.2.55.1	Test Methods	36
1.2.55.2	Requirements	38
1.2.56	Fungus	38
1.2.56.1	Test Methods	38
1.2.56.2	Requirements	39
1.2.57	Resistance to Solvents	39
1.2.57.1	Test Methods	39
1.2.57.2	Requirements	40
1.2.58	Radiographic	40
1.2.59	Environmental Test Methods and Requirements	41
1.2.59.1	Test Methods	42
1.2.59.2	Requirements	42
1.2.59.3	Electrical and Mechanical Limits	42
1.2.60	Humidity	43
1.2.60.1	Test Methods	43
1 .2.60.2	Requirements	43
	Specification Requirements	49

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS (CONT)

SECTION	TITLE	PAGE
Table 1.	Deleted	
Table II.	Deleted	
Table III.	Deleted	
Table IV.	Wiring Table	125
Table V.	Terminal Table	126
Table VI.	Terminal Hardware Table	127
Table VII.	Deleted	
Table VIII.	Deleted	
Table IX.	Deleted	
Table X.	Waveshape Characteristics Table	130
Table XI.	Dielectric Withstanding Voltage Table	131
Table XII.	Insulation Resistance Table.	132
1.3	Configuration and Drawings	147
1.3.1	Figure Titles vs Figure Numbers	149
1.3.2	Legend Index	151
	Figures	153

Supersedes pages x - xii of 14 February 1975.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SECTION 1.2

SPECIFICATION REQUIREMENTS INSTRUCTIONS

1.2.1 General

The purpose of these instructions is to establish the procedures to be followed, and the format to be used, for submission of requirements to obtain a computer generated procurement document.

The requester will find it impossible to complete an SRS using only this dash-numbered part of MIL-STD-35. Information which is standard for all generic families has been included in the master document at the issuance of MIL-STD-35C. This information is not repeated for each dash-numbered part. The following list contains the subjects which are pertinent to every family unless otherwise excepted.

General Description of AEDPS
Part Numbering
Specification Requirements Sheet
Writing Methodology
Mandatory Specification Requirements
General Specification Requirements
Dimensions-and Drawings
Applicable Documents
Materials
Finishes
Inspections
Single and Multi-item Specification (Tabulation)
Sources
Search
General Instructions for SRL
Tables

Supersedes page 5 of 14 February 1975.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

1.2.2 Approved Item Name Code

The item name code for a network, to be entered on the SRS with Code 1007, is selected from the Item Name Code column of the following list.

Approved Item Name	Item Name Code
Network, Pulse Forming	60769
Unapproved Names	77777

1.2.3 Figure Number

Code 1009 must show the figure number selected from Section 1.3.

1.2.4 Dimensions

MIL-STD-35 must be used in conjunction with this dash-numbered part to completely delineate the dimensions for a network.

The figures and corresponding legends, representing different configurations of networks, are located at the end of Section 1.3. The figure number (representing the selected figure) is mandatory and shall be entered on the SRS with Code 1009. The figure legends in this document (AA, AB, AC, etc.) representing dimensions shall be employed with corresponding legends in Table A of MIL-STD-35.

The remaining instructions for dimension networks are located in MIL-STD-35.

1.2.5 Tabulation

The explanation of, and the instructions for using tabulation are found in MIL-STD-35. Candidates for tabulation for this part are the dimensional codes shown in Table A of MIL-STD-35 and the following.

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

b. For exceptions to the requirements of the specification referenced with Code 1006, complete the sentence with Code 2774. The exceptions stated must be limited to 189 characters, including punctuation and spaces.

c* For detailed requirements, it is mandatory to write in the waveshape characteristic name with Code 2778, and to specify the deviation value (percent) with Code 2777.

If desired, enter an "X" with Code 2776 to specify that the network shall have electrical continuity.

1.2.52 Strength of Mounting Means

1 .2.52.1 Test Methods

The test method for strength of mounting means may be specified on the SRS by using one of the following:

a. For testing in accordance with the specification referenced with Code 1006, enter an "X" with Code 2800.

b. For exceptions to the test method of the specification referenced with Code 1006, complete the sentence with Code 2802. The exceptions stated must be limited to 189 characters, including punctuation and spaces.

c. For detailed testing, it is mandatory to write in the value (pounds) nominal with Code 2804 and the value (minutes) nominal with Code 2806, to specify that an axial load of the specified pounds shall be applied to each segment of the mounting means for the specified minutes using the appropriate mating hardware.

The following may also be used. Write in the value (pounds-inches) nominal with Code 2808, to specify that a torque of the specified pounds-inches shall be applied to the mounting means using appropriate mating hardware to apply the torque.

If a Test Method Code is used, a Requirement Code must also be used. Do not use a combination of Codes 2800 and 2810 (see 1.2.59).

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

1.2.52.2 Requirements

Requirements for strength of mounting means may be specified on the SRS by using one of the following:

a. For requirements in accordance with the requirements of the specification referenced with Code 1006, enter an "X" with Code 2810.

b. For exceptions to the requirements of the specification referenced with Code 1006, complete the sentence with Code 2812. The exceptions stated must be limited to 189 characters, including punctuation and spaces.

c. For detailed requirements, it is mandatory to enter an "X" with Code 2814, to specify that there shall be no breakage, malfunction, or evidence of any damage which would impair normal operation.

1.2.53 Dielectric Withstanding Volts

1 .2.53.1 Sea Level

Dielectric withstanding volts can be specified by placing an "X" with "Code 4860 or by completing the sentence with Code 4861 or completion of Table XI and specifying the nature of potential with Code 4864. Table XI must be completed for each line used although all lines need not be used. If a value is not necessary the code shall be entered on the SRS with three dashes (---). Codes 4866 through 4872 are optional and can be used to enter the applicable item. Requirements shall be specified when either Code 4860, 4861, or 4864 is used. The requirement shall be specified by placing an "X" with Code 4873 or by completing the sentence with Code 4874 or by entering an "X" with Code 4856 to specify there shall be no evidence of breakdown or flashover. Codes 4875 and 4876 are optional if Code 4856 is used.

1 .2.53.2 Reduced Barometric Pressure

Dielectric withstanding volts can be specified by placing an "X" with Code 4883 or by completing the sentence with Code 4884 or by entering the test condition letter with Code 4886, the nature of potential with Code 4888 and the completion of Table XI. Table XI must be completed for each line used, although all lines need not be used. If a value is not necessary, the code shall be entered on the SRS with three dashes (---).

Supersedes page 34 of 19 November 1973.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

The use of Codes 4890 through 4893 and 4900 through 4904 is optional and can be used to enter the applicable item. Requirements shall be specified by placing an "X" with Code 4907 or by completing the sentence with Code 4908, or by entering an "X" with Code 4906 to specify there shall be no evidence of breakdown or flashover. Codes 4894 and 4895 are optional if Code 4906 is used.

1.2.54 Insulation Resistance

1.2.54.1 Test Methods

The test method for insulation resistance may be specified on the SRS by using one of the following:

a. For testing in accordance with the specification referenced with Code 1006, enter an "X" with Code 1370.

b. For exceptions to the test method of the specification referenced with Code 1006, complete the sentence with Code 1371. The exceptions stated must be limited to 189 characters, including punctuation and spaces.

c. For testing in accordance with Method 302 of MIL-STD-202, it is mandatory to enter an "X" with Code 1372. If Code 1372 is used, it is mandatory to use both of the following:

(1) Enter an "X" with Code 1374 to specify points of measurement shall be in accordance with the Insulation Resistance Table.

(2) Generate the Insulation Resistance Table (Table XII, which is located before the drawings). To generate this table, write in the "from" terminal number with Code 3201; write in the "to" terminal number with Code 3202 (if only one terminal number is required, enter three dashes (---) with Code 3202); write in minimum insulation resistance (megohms) with Code 3203; write in the test temperature (deg C) at which insulation resistance is to remeasured with Code 3204; and write in the test potential (volts) with Code 3206. For additional measurements, follow the same procedure. Use as many codes from the From Terminal No. column as are required (Codes 3207, 3212, 3217, 3222, and 3227) and complete each horizontal line started.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

In addition to (1) and (2) above, one or more of the following may also be used. Complete the sentence with Code 1375, to specify special preparations or conditions (write-in limited to 189 characters, including punctuation and spaces); write in electrification time (minutes) with Code 1376; and/or write in the measurement error (percent) with Code 1377, to specify that measurement error at the insulation resistance value required shall not exceed the selected percent.

If a Test Method Code is used, a Requirement Code must also be used. Do not use 3 combination of Codes 1370 and 1379 (see 1.2.59).

1 .2.54.2 Requirements

Requirements for insulation resistance may be specified on the SRS by using one of the following:

a. For requirements in accordance with the requirements of the specification referenced with Code 1006, enter an "X" with Code 1379.

b. For exceptions to the requirements of the specification referenced with Code 1005, complete the sentence with Code 1380. The exceptions stated must be limited to 189 characters, including punctuation and spaces.

c. For detailed requirement;, it is mandatory to specify minimum insulation resistance on the Insulation Resistance Table. If Test Method 1.2.54.1.c was not selected, this table must be generated at this time. Follow the instructions in 1.2.54.1.c (2).

1.2.55 Seal

1 .2.55.1 Test Methods

The test method for seal may be specified on the SRS by using one of the following:

a. If the first test method is desired, use Code 4733 with an "X" on the SRS to specify testing per the specification referenced with Code 1006.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

1.2.60 Humidity

1 .2.60.1 Test Methods

The test method for humidity may be specified on the SRS by using one of the following:

a. For testing in accordance with the specification referenced with Code 1006, enter an "X" with Code 4787.

b. For exceptions to the test method of the specification referenced with Code 1006, complete the sentence with Code 4788. The exceptions stated must be limited to 189 characters, including punctuation and spaces.

c. For testinq in accordance with MIL-STD-202, Method 103, it is mandatory to write in the test condition letter with Code 4790 and complete the sentence (write-in limited to 189 characters, including punctuation and spaces) with Code 4793, to specify points of application of polarizing voltage.

One or more of the following may also be used. Complete the sentence with Code 4791, to specify measurements after conditioning; with Code 4794, to specify final measurements at high humidity; with Code 4795, to specify final measurements after drying period (each write-in limited to 189 characters, including punctuation and spaces). Write in the minimum time period with Code 4792, to specify the duration of application of polarizing voltage (i.e., 2 hours, 15 minutes, etc). Write in the value (volts DC) nominal with Code 4804 to specify the polarizing voltage.

If a Test Method Code is used, a Requirement Code must also be used. Do not use a combination of Codes 4784 and 4796 (see 1.2.59).

1 .2.60.2 Requirements

Requirements for humidity may be specified on the SRS by using one of the following:

a. For requirements in accordance with the requirements of the specification referenced with Code 1006, enter an "X" with Code 4796.

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

b. For exceptions to the requirements of the specification referenced with Code 1006, complete the sentence with Code 4797. The except ons stated must be limited to 189 characters , including punctuation and spaces.

co For detailed requirements, it is mandatory to enter an "X" with Code 4798, to specify that there shall be no evidence of physical damage, or degradation of performance.

If Code 4791 is used, it is mandatory to complete the sentence with Code 4806, to specify requirements after conditioning; if Code 4794 is used, it is mandatory to complete the sentence with Code 4800, to specify requirements after test and at high humidity; if Code 4795 is used, it is mandatory to complete the sentence with Code 48C , to specify requirements after test and drying period (eat write-in limited to 189 characters, including punctuation and spaces).

When the insulation resistance requirement is applicable, enter an "X" with Code 4799. Review Table XII to ensure that the value (megohms) minimum requirement has been specified. (See 1.2.54.2)

Supersedes pages 44 - 48 of 14 February 1975.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
1.2.45.1 Cont.	Temperature	
	*Min (deg C)	1696
	*Max (deg C)	1698
	Angle of inclination (deg max)	3300
	Altitude (feet max)	3302
1.2.45.2	Requirement (Select one) (Mandatory if 'either Code 1690, 1692, or 1694 is selected)	
	Requirements per Specification shown with Code 1006	3304
	or	
	Requirements per Specification shown with Code 1006 except .	3306
	or	

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
1.2.45.2 (Cont)	Requirements as follows:	
	No indication of corona	3308
	or	
	No indication of corona in excess of microamps) ,	3309
1.2.46	Dissipation Factor	
1.2.46.	Test Procedure (Select one if required)	
	Test per Specification shown with Code 1006	3370
	or	
	Test per Specification shown with Code 1006 except .	3312
	or	
	Test as follows:	
	*Voltage (Select one)	
	Voltage (volts RMS)	3318
	*Test reference frequency (hertz)	3316
	Voltage (volts DC)	3320

Supersedes page 58 of 19 November 1973.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
1.2.53.1 (Cont.)	Requirements per Specification shown with Code 1006 except .	4874
	or	
	Requirements as follows:	
	*No evidence of breakdown or flashover	4856
	Maximum leakage current (milliamps)	4875
	Requirements after test shall be ___.	4876
1.2.53	Dielectric Withstanding Volts at Reduced Barometric Pressure	
1 .2.53.2	Test Procedure (Select one if required)	
	Test per Specification shown with Code 1006	4883
	or	
	Test per Specification shown with Code 1006 except .	4884
	or	
	Test per Method 301 of MIL-STD-202 .	
	*Altitude per (Test Condition Letter) of Method 105 of MIL-STD-202	4886

‘ Supersedes page 71 of 19 November 1973.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
1.2.53.2 (Cont.)	*Magnitude of test voltage (Enter applicable codes and values on SRS from Table XI)	Table XI
	*Nature of potential (AC or DC)	4888
	*Points of application of test voltage shall be as shown in Table XI)	4889
	Special preparation or conditions shall be .	4890
	Time of application of test voltage (seconds)	4891
	Special method of connection of test voltage to specimen shall be .	4892
	Regulation of test voltage (percent)	4893
	Minimum kilovolt-ampere rating of high voltage source (KVA)	4900
	Limiting value of surge current (amps)	4902
	Tests during subjection to reduced pressure shall be .	4903
	"Measurements after test shall be .	4904

Supersedes page 72 of 19 November 1973.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC	
	NAME	CODE
1.2.53.2	Requirement (Select one) (Mandatory if either Code 4883, 4884, or 4886 is selected)	
	Requirements per Specification shown with Code 1006	4907
	or	
	Requirements per Specification shown with Code 1006 except .	4908
	or	
	Requirements as follows:	
	*No evidence of flashover or breakdown.	4906
	Maximum leakage current (milliamps)	4894
	Requirements after test shall be ___.	4895
1.2.54	Insulation Resistance	
1 .2.54.1	Test Procedure (Select one if required)	
	Test per Specification shown with Code 1006	1370
	or	
	Test per Specification shown with Code 1006 except .	1371
	or	

Supersedes page 73 of 19 November 1973.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
1.2.54.1 (Cont.)	Test per Method 302 of MIL-STD-202	1372
	*Test potential (Enter applicable codes and values on SRS from Table XII)	Table XII
	*Points of measurement shall be shown in Table XII.	1374
	Special preparation or conditions shall be .	1375
	Electrification time (minutes)	1376
	Measurement error at the insulation resistance value required (percent)	1377
1.2.54.2	Requirement (Select one) (Mandatorv if either Code 1370, 1371, or Table XII is selected)	
	Requirements per Specification shown with Code 1006	1379
	or	

Supersedes page 74 of 19 November 1973.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE I. DELETED

TABLE II. DELETED

TABLE III. DELETED

Supersedes pages 123 and 124 of 14 Febuary 1975.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE XI, DIELECTRIC WITHSTANDING VOLTAGE AT SEA LEVEL
(See 1.2.53)

DIELECTRIC WITHSTANDING VOLTAGE AT SEA LEVEL TABLE

FROM TERMINAL NUMBER	TO TERMINAL NUMBER	TEST VOLTAGE (VOLTS)
4351	4352	4353
4355	4356	4357
4359	4360	4361
4363	4364	4365
4367	4368	4369
4371	4372	4373
4375	4376	4377
4379	4380	4381
4383	4384	4385
4387	4388	4389
*8	*8	*7

*Number of print characters per column (column width). Heading spans are shown by underlining. Number of print characters will not appear on the generated document.

Codes selected from the table and entered on the SRS along with the desired data will cause the computer to generate the table and enter the data in the respective cells. Only those lines from which codes are used will print. The table will appear in Section 4 of the MSE.

Supersedes page 131 of 19 November 1973.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE XIa. DIELECTRIC WITHSTANDING VOLTAGE AT REDUCED BAROMETRIC PRESSURE

(See 1.2.53)

DIELECTRIC WITHSTANDING VOLTAGE AT REDUCED BAROMETRIC PRESSURE TABLE

FROM TERMINAL NUMBER	TO TERMINAL NUMBER	TEST VOLTAGE (VOLTS)
3000	3001	3002
3003	3004	3005
3006	3007	3008
3009	3010	3011
3012	3013	3014
3015	3016	3017
3018	3019	3020
3021	3022	3023
3024	3025	3026
3027	3028	3029
*8	*8	*7

*Number of print characters per column (column width). Heading spans are shown by underlining. Number of print characters will not appear on the generated document.

Codes selected from the table and entered on the SRS along with the desired data will cause the computer to generate the table and enter the data in the respective cells. Only those lines from which codes are used will print. The table will appear in Section 4 of the MSE.

persedes page 132 of 19 November 1973.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

Custodians:
Army - MI

Review Activities
Army - AT
Army - AV
Army - EL
Army - ME
Army - MR
Army - SG
Army - WC

User Activity:
Army - MU

Preparing Activity:
Army - MI

(Project EDS-A024-8)

Supersedes pages 157 - 158 of 14 February 1975.

*U.S. GOVERNMENT PRINTING OFFICE: 1976-603-766/6715

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.