INCH-POUND

MS87006A
11 July 2018
SUPERSEDING
MS87006
16 October 1962


DETAIL SPECIFICATION SHEET

HOOK, CHAIN-S

This specification is approved for use by all Departments and Agencies of the Department of Defense.

Reactivated after 11 July 2018 and may be used for new and existing designs and acquisitions.

The requirements for acquiring the product described herein shall consist of this specification sheet.



See notes at end of figure.

FIGURE 1. S-Hook.

AMSC N/A

FSC 4030

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:30Z
Check the source to verify that this is the current version before use.

Wire gage G	14	12	12	11	11	10	8
Diameter (decimal)	.080	.105	.105	.120	.120	.134	.162
L Reach	27/32	15/16	1-3/32	1-7/16	1-7/16	1-1/16	1-1/16
A dia.	9/32	9/32	25/64	9/32	13/32	11/32	3/8
B dia.	5/16	5/16	13/32	11/16	11/16	11/32	3/8
C	1/8	11/64	3/32	9/32	5/16	3/16	1/4
D	3/16	3/16	1/8	13/32	9/16	1/4	9/32
E	13/32	15/32	1/2	9/16	5/8	17/32	9/16
F	3/8	13/32	15/32	13/16	7/8	1/2	9/16

Decimal and metric equivalents. 2/

Diameter Inch (mm)	.080 (2.03)	.105 (2.67)	.105 (2.67)	.120 (3.05)	.120 (3.05)	.134 (3.40)	.162
L Reach Inch (mm)	.844 (21.44)	.938 (23.83)	1.094 (27.79)	1.438 (36.53)	1.438 (36.53)	1.063 (27.00)	1.063 (27.00)
A dia. Inch (mm)	.281 (7.14)	.281 (7.14)	.391 (9.93)	.281 (7.14)	.406 (10.31)	.406 (10.31)	.375 (9.53)
B dia. Inch (mm)	.313 (7.95)	.313 (7.95)	.406 (10.31)	.688 (17.48)	.688 (17.48)	.406 (10.31)	.375 (9.53)
C Inch (mm)	.125 (3.18)	.172 (4.38)	.094 (2.39)	.281 (7.14)	.313 (7.95)	.188 (4.78)	.250 (6.35)
D Inch (mm)	.188 (4.78)	.188 (4.78)	.125 (3.18)	.406 (10.31)	.563 (14.30)	.250 (6.35)	.281 (7.14)
E Inch (mm)	.406 (10.31)	.468 (11.89)	.500 (12.70)	.563 (14.30)	.625 (15.88)	.531 (13.49)	.563 (14.30)
F Inch (mm)	.375 (9.53)	.406 (10.31)	.469 (11.91)	.813 (20.65)	.875 (22.23)	.500 (12.70)	.563 (14.30)

NOTES:
1. Dimensions are in inches.
2. Decimal and metric equivalents are for reference only.
3. Tolerance for decimals ±.005 inch (0.13 mm) and fractions ± 1/16 inch (.0625 inch decimal (1.59 mm).

FIGURE 1. S-Hook - Continued.

REQUIREMENTS:

S-Hooks shall be as specified on figure 1, table I, and table II.

Materials: See table I.

Brass alloy C26000, half-hard temper.

Low carbon steel alloy UNS G10100 or UNS G10200.

Corrosion resistant steel (CRES) alloy UNS S30400.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:30Z
Check the source to verify that this is the current version before use.

Finish: See table I.

Cadmium plating in accordance with SAE-AMS-C-81562, type II, class 3 or SAE-AMS-QQ-P-416, type II, class 3.

Mechanically deposited zinc coating in accordance with ASTM-B695, class 50, type II (chromate) or zinc coating (electrodeposited) in accordance with ASTM-B633, Fe/Zn 12, type VI.

Electrodeposited zinc-nickel in accordance with ASTM F1941, Fe/Zn-Ni 5C 5CNS, 5DNS, or 5ENS

CRES shall be passivated in accordance with SAE-AMS2700, method 1, type 6 or 7.

TABLE I. Material and finish designators.

Material/finish	Dash numbers						
Steel							
Uncoated	-1	-11	-21	-31	-41	-51	-61
Cadmium 1/	-3	-13	-23	-33	-43	-53	-63
Zinc 2/	-4	-14	-24	-34	-44	-54	-64
Zinc-nickel	-6	-16	-26	-36	-45	-56	-66
Brass							
Uncoated	-2	-12	-22	-32	-42	-52	-62
Corrosion resistant steel	-5	-15	-25	-35	-45	-55	-65

NOTE:
1. See table II for color designators.
2. This finish has a chromate conversion coating, which includes hexavalent chromium, which is toxic, carcinogenic, highly regulated, and typically prohibited in Army contracts.


TABLE II. Cadmium color designators.

Color designator	Color
Blank	No or any color
C	Yellow iridescent
D	Olive green shading to brown or bronze
E	Black

S-Hook shall be capable of being bent with hand tools, in the closed position, and shall not crack or break.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:30Z
Check the source to verify that this is the current version before use.

PIN: The PIN consists of the letters “MS”, the specification number, a dash and number for S-hook wire gage, material/finish designator, and color for cadmium plated S hooks only.



PIN example: MS87006-11 indicates an S-Hook, steel alloy 12 AWG with a 15/16 inch reach, steel uncoated.

Cadmium is not recommended. To the users of this document, it is recommended that the use of carbon steel material with cadmium plating be used only when other materials and finishes specified in this document cannot meet performance requirements.

Cadmium is prohibited from use in NAVSEA owned shipboard systems in accordance with the requirements of T9070-AL-DPC-020/077-2.

Class I and II ozone depleting substances (ODS) shall not be used in MS87006 or any referenced procedures.

Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Referenced documents shall be of the issue in effect on date of invitations for bid.
Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. This document references the following:

ASTM B633	SAE-AMS-C-81562
ASTM-B695	SAE-AMS-QQ-P-416
ASTM F1941	T9070-AL-DPC-020/077-2
SAE-AMS2700	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:30Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - AT
Navy - SH
Air Force - 99
DLA - CC

Preparing activity:
DLA - CC

(Project 4030-2018-004)

Review activities:
Army - AR, MI
Navy - AS, CG, SA
Air Force - 71

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:30Z
Check the source to verify that this is the current version before use.