J-C-001686
March 13, 1972

INTERIM FEDERAL SPECIFICATION

CABLE ASSEMLY, POWER, ELECTRICAL

(FOR 125/250-VOLT RANGES AND DRYERS)

This Interim Federal Specification was developed by General Services Administration, Federal Supply Service, Standardization Division, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers electrical cable assemblies for use with 125/250-volt ranges and dryers.

1.2 Classification. The cable assemblies shall be of the following types, sizes, and styles, as specified (see 6.2):

Type I. 25A-125/250V, 2 No. 10, unidentified conductors, and 1 No. 10 grounded conductor

size 1	3 feet long
size 2	4 feet long
size 3	5 feet long
size 4	6 feet long

Type II, 25A-125/250-V, 2 No. 10, unidentified conductors, and 1 No. 10 grounded conductor, and 1 No. 10 grounding conductor.

size 1	3 feet long
size 2	4 feet long
size 3	5 feet long
size 4	6 feet long

Type III, 35A-125/250-V, 2 No. 8 unidentified conductors, 1 No. 10 grounded conductor.

size 1	3 feet long
size 2	4 feet long
size 3	5 feet long
size 4	6 feet long

Type IV, 35A-125-250-V, 2 No. 8 unidentified conductors, 1 No. 10 grounded conductor and 1 No. 10 grounding conductor.

size 1	3 feet long
size 2	4 feet long
size 3	5 feet long
size 4	6 feet long

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:08Z
Check the source to verify that this is the current version before use.

Type V, 35A-125/250-V, 2 No. 8, unidentified conductors, and 1 No. 8 grounded conductor.

size 1	3 feet long
size 2	4 feet long
size 3	5 feet long
size 4	6 feet long

Type VI, 45A-125/250-V, 2 No. 6 unidentified conductors and 1 No. 8 grounded conductor.

size 1	3 feet long
size 2	4 feet long
size 3	5 feet long
size 4	6 feet long

Type VII, 45A-125/250V, 2 No. 6 unidentified conductors, 1 No. 8 grounded conductor and 1 No. 8 grounding conductor.

size 1	3 feet long
size 2	4 feet long
size 3	5 feet long
size 4	6 feet long

Type VIII, 45A-125/250-V, 2 No. 6, unidentified conductors, and 1 No. 6 grounded conductor.

size 1	3 feet long
size 2	4 feet long
size 3	5 feet long
size 4	6 feet long

Style 1 - separately attached plug connector.
Style 2 - Molded to the cable jacket plug connector.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issues in effect on the date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein:

Federal Specification:

PPP-B-566 - Boxes, Folding Paperboard.
PPP-B-665 - Boxes; Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676 - Boxes, Setup.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specification and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:08Z
Check the source to verify that this is the current version before use.

Military Specifications:

MIL-E-17555 - Electronic and Electrical Equipment, Accessories, and Repair Parts, Packaging and Packing of.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids, or request for proposal shall apply:

Underwriters' Laboratories, Inc. (UL), Inc. Standards:

No. 817 - Cord Sets and Power Supply Cords.
No. 62 - Flexible Cord and Fixture Wire.

(Application for copies should be addressed to the Underwriters' Laboratories, Inc., 207 East Ohio Street, Chicago, Illinois 60611; 1285 Walt Whitman Road, Melville, Long Island, New York 11746; or 1655 Scott Blvd., Santa Clara, California 95050.)

National Electrical Manufacturers Association (NEMA) Publications:

WD-1-General Purpose Wiring Devices

(Technical Society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Fire and casualty hazards.

3.1.1 Each bidder shall submit to the contracting agency proof that the equipment he proposes to supply under this specification conforms to the requirements of UL-817 for Cord Sets and Power-Supply Cords. The label or listing mark, of the Underwriters' Laboratories, Inc., may be accepted as evidence that the equipment conforms to this requirement.

3.1.2 In lieu of the label, or listing mark, the contractor may submit independent proof, satisfactory to the contracting agency, that his equipment conforms to the published standards, including methods of tests of UL-817.

3.1.3 Compliance with the above preliminary requirements in regard to fire and casualty hazards, does not absolve the contractor from complete compliance with the requirements of this specification, in order to secure acceptance of his equipment.

3.2 Cable assemblies. Cable assemblies shall be furnished with a connector molded or clamped to the range or dryer cable.

3.2.2 Cable.

3.2.2.1 Types I, III, V, VI, and VIII, cable assemblies. The cable shall be three-conductors flexible cable SRD or SRDT in accordance with J-C-580.

3.2.2.2 Types II, IV, and VII, cable assemblies. The cable shall be three conductor, with one grounding conductor, flexible cable SRD or SRDT in accordance with UL-62.

3.2.2.3 Conductor identification. The separate conductors shall be identified in accordance with UL-62.

3.2.3 Cable assemblies.

3.2.3.1 Type I, cable assemblies. The plug connectors that are separately attached shall be in accordance with W-C-596, Table XIV, Series S, Style S21 or S22. For plug connectors that are molded to the cable jacket, the blade configuration shall be in accordance with NEMA WD-1, Figure 10-30P.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:08Z
Check the source to verify that this is the current version before use.

3.2.3.1 Type II, cable assemblies. Plug connectors that are separately attached or molded to the cable jacket, shall be in accordance with NEMA WD-1, configuration 14-30P.

3.2.3.2 Type III, V. VI, and VIII, cable assemblies. The plug connectors that are separately attached shall be in accordance with W-C-596. Table XV, Series T, Style T21, T22 or T23. For plug connectors that are molded to the cable jacket, the blade configuration shall be in accordance with NEMA WD-1, Figure 10-50P.

3.2.3.3 Type IV, and VII, Cable assemblies. Plug connectors that are separately attached or molded to the cable jacket, the blade configuration shall be in accordance with NEMA WD-1, Figure 14-50P.

3.2.4 The cable assemblies shall have terminal lugs permanently secured to the conductor ends opposite the plug connector at the ampere rating of the cable assembly.

3.2.5 A strain relief clamp shall be provided on the terminal end of the cable assembly so that a pull exerted on the cord will not be transmitted directly to binding-screw terminals of a fitting.

3.3 Workmanship. Workmanship shall be first class in every respect

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspections requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling for quality conformance inspection.

4.2.1 Inspection lot. All cable assemblies of the same type manufactured under essentially the same conditions, and offered for delivery at one time, shall be considered a lot.

4.2.2 Sampling for examination and tests. A random of cable assemblies shall be selected from each lot in accordance with MIL-STD-105, at inspection level II.

4.3 Visual and mechanical examination. The sample cable assemblies selected in accordance with 4.2.2 shall be visually and mechanically examined to verify conformance with this specification. Defects are classified as shown in Table I. The acceptable quality level (AQL) is 1.0 percent defective major.

TABLE I. Classification of Defects in Accordance With MIL-STD-105

Defects
Critical:
Grounding wire identification not as specified.
Major:
Cable size and number of conductors not as specified.
Plug connector broken, craked, contracts loose, or plug connector not as specified.
Jacket (outside cover) cracked, split, bruised, or size not as specified.
Length of cable less than specified.
Packaging, packing, and marking not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:08Z
Check the source to verify that this is the current version before use.

4.4 Inspection of preparation for delivery. The packaging, packing, and marking shall be inspected for compliance with section 5.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A. Each cable assembly shall be preserved and packaged in accordance with the level A packaging requirements of MIL-E-17555.

5.1.2 Level B. Each cable assembly shall be coiled and the coil shall be secured with tape or twine. Each coil shall be packaged in a close-fitting paperboard box conforming to PPP-B-566, PPP-B-665 or PPP-B-676.

5.1.3 Level C. Each cable assembly shall be packaged in accordance with the level C packaging requirements of MIL-E-17555.

5.2 Packing. Cable assemblies, furnished in quantities as specified in the contract or order, shall be packed in accordance with the packing requirements of MIL-E-1755. Packing shall be level A, B, or C, as specified (see 6.2).

5.3 Marking. Marking shall be in accordance with 5.3.1 or 5.3.2, as specified (see 6.2).

5.3.1 Civil agencies. In addition to any special markings required by the contract or order, all interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military Agencies. In addition to any special markings required by the contract or order, all interior packages and shipping containers shall be marked in accordance with the marking requirements of MIL-E-17555.

6. NOTES

6.1 Intended use. The cable assemblies covered by this specification are intended for use with 125/250-volt, 60-Hertz, A.C. ranges and dryers with a rating of 25, 35 and 45 amperes.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type, style, and size of cable required (see 1.2).
(c) Selection of the applicable level of packaging and packing required (see 5.1 and 5.2).
(d) Marking required (see 5.3).

Preparing activity:

GSA-FSS

GSA DC 72-11296

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:08Z
Check the source to verify that this is the current version before use.