L-W-25D
June 29, 1973
SUPERSEDING
Fed. Spec. L-W-25C
March 7, 1968

FEDERAL SPECIFICATION

WASTE RECEPTACLE, PLASTIC

This specification was approved by the Commissioner Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1 SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers polyethylene (PE) plastic waste receptacles with or without covers.

1.2 Classification Plastic waste receptacles shall be one type with the following sizes as specified (see C.2)

Size	Capacity, gallons
0	6
1	10
2	12
3	20
Class A (with cover)	
Class B (without cover)	
4	24
5	32
6	44

2 APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein

Federal Specifications

PPP-B-636 - Box, Shipping Fiberboard

Federal Standards

Fed Std No 123 - Marking for Domestic Shipment (Civil Agencies).
Fed Std No 224 - Closing, Sealing and Reinforcing of Fiberboard, General Methods for

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

FSC 7240

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:08Z
Check the source to verify that this is the current version before use.

Military Standards·

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply

Uniform Classification Committee, Agent

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Association, Inc , Tariff Order Section, 1616 P Street, N. W. , Washington, DC 20036)

3. REQUIREMENTS

3 1 Material.

3 1 1 Plastic Polyethlene shall be virgin material or virgin material blended with clear rework material, generated from the manufacturer's own production When reworked material is used it shall be blended back into the same type and kind of virgin compound to produce a container equal in quality to the one molded from virgin material.

3.1.2 Wire Wire shall be carbon steel or corrosion resisting metal Carbon steel shall be coated with either zinc, cadmium, or other corrosion resisting metal

3.2 Dimensions The covers and receptacles shall conform to the dimensions in table I, except for size 3, class B receptacles (see 3.9).

TABLE I. Dimensions

Size	Capacity tolerance +10 - 5%	Max height including cover 1/	Minimum outside diameter	Minimum wall and bottom thickness, average 2/
	Gallons	Inches	Inches	Inches
0	6	17-1/2	11-3/4	0.065
1	10	24-1/2	10	.070
2	12	21	12	.070
3 class A	20	27-1/2	14-1/4	.075
4	24	29	14-1/4	.080
5	32	32-1/4	16	.090
6	44	32-1/4	23-3/4	0 118

1/ Exclusive of bail when furnished as part of container.
2/ When inspected in accordance with 4.4.7.

3.3 Receptacle. The waste receptacle shall be molded in one piece and shall be water tight. The interior and exterior shall be either smooth, corrugated, ribbed, or of other design at the option of the manufacture. The receptacle, except size 3, class B (see 3.9), shall have either two or more lugs or metal carrying handles designed to lock on the cover. The receptacle except size 3, class B (3.9) shall be provided with covers specified in 3.4. Receptacle shall be equipped with handles as specified in 3 5. The receptacles shall show no cracks or permanent set when tested in accordance with 4.4.3.1, 4.4.3.2, and 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:08Z
Check the source to verify that this is the current version before use.

3.4 Cover. The cover, except size 3, class B (see 3.9) shall be molded in one piece and shall have a handle for removing it from the receptacle. The cover shall be designed to lock securely to the receptacle either by lugs or by the use of metal handles assembled to the receptacle. The cover shall be capable of passing the tests in 4.4.5.

3.5 Carrying handles.

3.5.1 Sizes 3, 4, 5 and 6. Receptacles furnished in handles in sizes 3, 4, 5, and 6 shall have two carrying handles, diametrically opposite each other, either of metal conforming to 3.1.2 or molded into the body of the receptacle. Handles shall be capable of passing test described in 4.4.6

3.5.2 Sizes 0, 1, and 2. Receptacles furnished in sizes 0, 1, and 2 shall have handles conforming to the requirements of 3.5.1 or have an edge formed so as to provide a suitable means for carrying the receptacle. When the formed-edge type handle is supplied, its interior configuration shall be such that the distance from the formed edge to the side of the can is a minimum of 3/4 inch and the distance from the uppermost point of the formed edge to the bottom lip shall be a minimum of 3/4 inch. Handles shall be capable of passing the test described in 4.4.6.

3.6 Finish. The receptacle and cover shall be smooth and free from seams, welds, cracks, or chipped edges.

3.7 Color. Unless otherwise specified (see 6.2) the receptacle shall be gray and the cover shall be either gray or black

3.8 Labeling. Containers shall be labled on the outside in two places on the opposite sides, in positions that will be noticable to the user. Labels shall be placed on a continuous surface and shall be so applied as to smoothly conform to the configuration of the receptacle and to leave no airspaces between the label and the receptacle.

The label shall be half moon or rectangular in shape and shall be not less than 2 inches high and 3-1/2 inches wide. The label shall read "CAUTION" in yellow letters 13/32 to 21/32 inches high or a black or dark blue background 13/16 to 15/16 inch wide. The remainder of the label shall have a yellow background with black or dark blue letters reading "COMBUSTIBLE CONTAINER" in letter 7/16 to 9/16 inch high. The last line to read "DO NOT USE FOR BURNABLE MATERIAL" in black or dark blue letters 1/4 inch high.

3.9 Size 3, class B receptacle without covers. Size 3, class B receptacle shall be furnished without covers. The dimensions of the receptacle shall be as follows

	Inches
Wall and bottom, thickness, minimum	0.075
Height, maximum	.24
Outside top diameter, maximum	.20
Outside bottom diameter, maximum	17

Capacity of the receptacle shall be 20 ± 5 percent gallons. Lugs or metal handles designed to lock on covers shall be supplied at the manufacturer's option. Size 3, class B receptacle shall conform to all requirements of this specification except those noted in 3.2, 3.3 and 3.4

3.10 Workmanship. The receptacles and covers shall be free of fins, sharp edges and defects that may affect their durability or serviceability.

4 QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:08Z
Check the source to verify that this is the current version before use.

4.2 Sampling.

4.2.1 Lot. Unless otherwise specified (see 6.2), a lot shall consist of all receptacles and covers of the same size, submitted for inspection at the same time.

4.2.2 Visual examination of end item. Sampling for this examination shall be according to level S-2 in MIL-STD-105. The Acceptable Quality Levels (AQL's) for defects listed in table II shall be 2.5 percent defective for major defects and 6.5 percent defective for total defects The sample unit shall consist of one receptacle with cover, except size 3, class B, where the sample unit shall consist of one receptacle without cover.

4.2.3 Sampling for tests. Sampling for tests shall be in accordance with level S-2 in MIL-STD-105. The AQL for tests shall be 2.5 on the basis of percent defective per test. The sample unit for tests shall consist of the number of receptacles and covers needed to perform all the specified tests one time, i.e. three containers and two covers.

4.3 Examination.

4.3.1 End item Receptacles and covers selected in accordance with 4.2.2 shall be examined for defects listed in table II

TABLE II Classification of defects, end item

Defects	Major	Minor
Size not as specified	X	
Dimensions not as specified	X	
Color not as specified		X
Scratches in receptacle or cover		X
Dirt, grit or other foreign matter imbedded in finish		X
Component not of specified design.	X	
Handle missing	X	
Component malformed or damaged	X	
Sharp or burred edges which might cause injury.	X	
Ball does not have clearance or function as specified		X
Label missing or in wrong location, incorrect size, or not applied as required	X	
Damage or defects not affecting function or serviceability		X

4.3.2 Inspection of preparation for delivery. An inspection shall be made to determine that the packaging, packing and marking comply with the requirements in section 5 of this specification Defects shall be scored in accordance with table III For examination of interior packaging the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105 Defects of closure listed in table III shall be examined on shipping containers fully prepared for delivery The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an acceptable quality level (AQL) of 4.0 defects per hundred units

TABLE III Classification of preparation for delivery defects

Examine	Defects
Markings (exterior)	Omitted, incorrect, illegible, improper size, location, sequence, or method of application.
Materials	Any component missing or damaged
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Distortion of container.

4.4 Tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:08Z
Check the source to verify that this is the current version before use.

4.4.1 General. Receptacles and covers selected in accordance with 4.2.3 shall be tested to verify compliance with this specification.

4.4.2 Conditioning for tests. One container with cover filled with crushed ice in accordance with table IV and two containers, one without cover, shall be placed in an environmental chamber at a temperature of minus 10° ± 2°F. After conditioning the containers for a minimum of 12 hours they shall be tested in accordance with 4.4.3 and 4.4.4. Covers not required for size 3, class B containers.

TABLE IV Crushed ice for tests

Container size, gallons	Crushed ice, pounds
44	120
32	100
20 and 24	80
10 and 12	40
6	20

4.4.3 Drop test.

4.4.3.1 Weighted containers. Remove one container with the prescribed amount of ice, and cover locked in position from the environmental chamber. Raise the container to 3 feet above a concrete floor and tilt at an angle of approximately 45° Release and allow to fall freely striking the bottom edge This test shall commence within 5 seconds after removal Cover not required for size 3, class B container The 10 gallon container with cover if furnished without side handles shall be lifted by the rim for this test.

4.4.3.2 Empty containers. Remove empty container with cover from the environmental chamber and within 30 seconds drop the container 3 times from a height of 6 feet on a concrete floor Tilt container at an angle of approximately 45° causing the container to strike the floor or the bottom edge in two opposite positions and once on the top edge. Cover not required for size 3 class B container

4.4.4 Deformation Remove the empty container without cover from the environmental chamber and within 5 seconds place it on the side of a concrete floor. Step on the container at a point 4 to 6 inches below the top rim with enough weight to make one side touch the opposite side This completed test shall be conducted within 15 seconds from removal from the environmental chamber

4.4.5 Covers One empty container after reaching room temperature shall be used to test the covers Covers shall fit the receptacles snuggly, and when locked in place shall not become loosened when knocked or rolled over under normal conditions

4.4.6 Carrying handles The receptacles, filled with ice in accordance with table IV shall be lifted and carried for a distance of approximately 100 feet Any failure or permanent deformation of the handle shall constitute failure of the test

4.4.7 Wall thickness. Measure the wall thickness of the receptacles a minimum of 4 places at 90° intervals around the periphery, not less than 1 inch from the top edge The average of the 4 measurements shall not be less than the thickness requirements for the various sizes nor shall any one of the measurements be more than 0.005 inch less than the thickness requirements as indicated in table I

5 PREPARATION FOR DELIVERY

5.1 Packaging Packaging shall be level A, B, or C as specified (see 6.2)

5.1.1 Level A.

5.1.1.1 Six, 10, 12, 20, and 24-gallon sizes Six, 10, 12, 20, and 24-gallon receptacles of like description, nested together with applicable covers shall be packaged in quantities of 6 in a close-fitting box conforming with PPP-B-636, class weather-resistant. Closure shall be in accordnace with the appendix to the box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:08Z
Check the source to verify that this is the current version before use.

5.1.1.2 32 and 44 gallon sizes. The 32 and 44 gallon receptacles, nested together with covers shall be packaged in quantities of 4 in a close-fitting box conforming to PPP-B-636, class weather-resistant. Closure shall be in accordance with the appendix to the box specification.

5.1.2 Level B. No packaging required.

5.1.3 Level C. The receptacles shall be packaged in accordance with the suppliers commercial practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Unit packages of receptacles of like description shall be packed in close-fitting boxes conforming with PPP-B-585, class 3, PPP-B-591, class II, PPP-B-601, overseas type, PPP-B-621, class 2, or PPP-B-640, class 2. The boxes shall be closed and strapped in accordance with the applicable specification or appendix thereto. The gross weight shall not exceed approximately 200 pounds.

5.2.2 Level B.

5.2.2.1 Six, 10, 12, 20, and 24-gallon size. Six, 10, 12, 20, 24-gallon receptacles of like description, nested together with applicable covers, shall be packed in quantities of 6 in a close-fitting box conforming with PPP-B-363, class domestic. Closure shall be in accordance with the appendix to the box specification.

5.2.2.2 32 and 44 gallon sizes. The 32 and 44 gallon receptacles nested together with covers shall be packed in quantities of 4 in a close-fitting box conforming with PPP-B-636, class domestic. Closure shall be in accordance with the appendix to the box specification.

5.2.3 Level C. Receptacles, packages as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers and packing shall comply with Uniform Freight Classification Rules or National Motor Freight Classification Rules.

5.3 Marking.

5.3.1 Civil agencies. In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with Fed Std No 123.

5.3.2 Military agencies. In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Plastic trash cans covered by this specification are intended for refuse, waste or garbage prior to bulk disposal. These containers are not to be used for hot ashes or near an open flame.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Size (see 1.2).
(c) Color (see 3.7).
(d) Size of lot, if different from 4.2.1.
(e) Selection of applicable levels of packing (see 5.1)
(f) Selection of civil or military marking (see 5.2).
(g) When weather resistant grade fiberboard shipping containers are required for level B packing (see 5.1.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:08Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Army - GL
Air Force - 84

User interest:

Navy - CG, MC

Preparing activity:

GSA-FSS

Civil Agency Coordinating Activity:

HEW-FDA

Orders for this publication are to be placed with the General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:08Z
Check the source to verify that this is the current version before use.