[INCH-POUND]
A-A-59715/3
10 June 2002

COMMERICAL ITEM DESCRIPTION

RESISTORS, FIXED, WIRE WOUND,
POWER TYPE

The General Services Administration has authorized the use of this Commercial Item Description (CID) for all federal agencies.

The complete requirements for procuring fixed wire wound power resistors described herein, shall consist of this document and the issue in effect of CID A-A-59715.

CLASSIFICATION. This CID uses a classification system which is included in the Part Identification Number (PIN) (see 7.1). The PIN shall be AA5971503-******. Complete PIN example AA5971503-A1003J.

AA59715	03	-	*	****	*
CID number	Applicable CID sheet (two digits)		Resistor type (one digit)	Resistance	Resistance tolerance

SALIENT CHARTACTERISTICS.

Interface and physical dimensions. The resistors supplied to this CID shall meet the interface and physical dimensions as specified herein (see figure 1).

Resistor type. Designates the type and power rating of each resistor (see table 1).

Table 1 Resistor type.

Designation	Wattage (25^{O}C)	Resistance range (in ohms)
A	10.00	1.0 to 15,000
B	20.00	1.0 to 50,000
C	30.00	1.0 to 10,000
D	40.00	1.0 to 25,000
E	55.00	1.0 to 30,000

Resistance. The nominal resistance value expressed in ohms is identified by a four-digit number; the first three digits represent significant figures and the last digit specifies the number of zeros to follow. Resistance values for specific resistors are covered in the individual CID sheets. When the value of resistance is less than 100 ohms, or when fractional values of an ohm is required, the “R” will be substituted for one of the significant digits to represent the decimal point. When the letter “R” is used, succeeding digits of the group represent significant figures. The resistance value designations are shown in table II below.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:24Z
Check the source to verify that this is the current version before use.



Designation	Style	Dimensions	
		A	L
A	A	1.000	0.750
B	A	2.313	2.000
C	B	2.000	1.250
D	B	2.750	2.000
E	B	4.250	3.500

Inches	mm	Inches	mm	Inches	mm	Inches	mm
0.750	19.05	1.250	31.75	2.313	58.75	3.500	88.90
1.000	25.40	2.000	50.80	2.750	69.85	4.250	107.95

NOTES:
1. Dimensions are in Inches.
2. Metric equivalents are given for general information only.

FIGURE 1. Resistor, Fixed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:24Z
Check the source to verify that this is the current version before use.

Table II Designation of resistance values.

Designation	Resistance (in ohms)
1R00 to 9R99 incl.	1.0 to 9.99 incl.
10R0 to 99R8 incl.	10.0 to 99.9 incl.
1000 to 9990 incl.	100 to 999 incl.
1001 to 9991 incl.	1,000 to 9,990 incl.
1001 to 5002 incl.	10,000 to 50,000 incl.

Resistance tolerance. The resistance tolerance available is J (±5 percent).

Power rating. The power rating shall be specified in table I, at 25^{O}C, derated to zero at 350^{O}C.

Temperature coefficient of resistance (TCR). The temperature coefficient of resistance (TCR) is as follows:

Resistance	TCR (ppm/^{O}C)
5 ohms and under	±400
Above 5 ohms	±260

Marking. Resistors supplied to this CID shall be marked with the manufacturer's (MFR's) standard commercial PIN.

NOTES.

PIN. The PIN should be used for Government purposes to buy commercial products to this CID. See section 2 for PIN format example.

Commercial and Government Entity (CAGE) code. For ordering purposes, inventory control, and submission of these resistors to DSCC under the Military Parts Control Advisory Group (MPCAG) evaluation program, CAGE Code 58536 should be used.

Source of documents.

Commercial Item Description

A-A-59715 - Resistors, Fixed and Adjustable, Wire Wound, Power Type, General Requirement for.

(Copies of commercial item descriptions are available from the Document Automation and Production Service, Building 4D (DPM-DODSSP), 700 Robbins Avenue, Philadelphia, PA 19111-5094)

Ordering data. Ordering data is as specified in A-A-59715.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:24Z
Check the source to verify that this is the current version before use.

Commercial products. As part of the market analysis and research effort, this CID was coordinated with the following manufacturers of commercial products. At the time of the CID preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID. (NOTE: This information should not be considered as a list of approved manufacturers or be used to restrict procurement to only the manufacturers shown).

Manufacturer's CAGE	Manufacturer's name and address
44655	Ohmite Manufacturing Company 3603 Howard Street Skokie, IL 60076 Plant : Baja Oriente Calle 8 Esquina Calle Cuarta, S/N Parque Industiial Fondeport el Sauzal Ensenada, Baja California, Mexico, 22760

Part number (P/N) supersession data. This CID supersedes the following MFR's P/N as shown. This information is being provided to assist in reducing proliferation in the Government inventory system.

TABLE III. P/N supersession data.

MFR's CAGE	Designation	MFR's style 1/
44655	A	F10*-****
	B	F20*-****
	C	F30*-****
	D	F40*-****
	E	F55*-****

1/ The manufacturer's P/N shall not be used for procurement to the requirements of this CID. At the time of preparation of this CID, the aforementioned commercial products were reviewed and could be replaced by the CID P/N shown.

Government users. To acquire information on obtaining these resistors from the Government inventory system, contact Defense Supply Center, Columbus, ATTN: DSCC-CP, Post Office Box 3990, Columbus, OH 43213-5000, or telephone (614) 692-7684.

MILITARY INTERESTS:

Custodian

NAVY - EC
DLA - CC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - 7FXE

Preparing Activity:

DLA - CC

Project 5905-1651-03

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:24Z
Check the source to verify that this is the current version before use.