A-A-59732A
14 May 2003
SUPERSEDING
A-A-59732
11 July 2002

COMMERCIAL ITEM DESCRIPTION

SCALE, VEHICLE PLATFORM, 20,000 LBS., MAN-PORTABLE

The General Services Administration has authorized the use of this commercial item description (CID) for all federal agencies.

1. SCOPE. This Commercial Item Description covers a rugged, environmentally protected, commercial type, man-portable vehicle platform scale with a capacity of 20,000 pounds and a nominal inaccuracy of +/-1 percent of applied load. These scales are used to weigh wheeled military vehicles and cargo in remote areas, on unimproved and improved surfaces. Their purpose is to maximize flight safety and aircraft utilization at main operating bases, forward operating bases, landing zones, and under bare base operations.

2. SALIENT CHARACTERISTICS.

2.1 Design. The scale shall be fully electronic using shear beam load cells. The scale shall be NTEP Class IV Certified by the U.S. National Institute of Standards and Technologies (Ref. 2001 NIST Handbook 44).

2.2 Configuration. The scale shall be large enough to accommodate military vehicle wheels without requiring additional base supports when placed on unimproved ground of average density. The scale shall have organic ramps which are a structural part of the unit. The following dimensions are required to properly weigh vehicles in the military inventory; weighing surface 12 inches W x 12 inches L, overall dimensions of 16 inches L x 20 inches W. These dimensions are provided for information only; alternative dimensions may be used. The scale shall have a machined anti-skid base and top. A fixed carrying handle shall be located on the side of the scale. The handle shall be easily repaired or replaced. The scale shall have a weight indicating digital display. No portion of the scale shall sustain any damage when run over by a vehicle.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: WR-ALC/LEEC, 295 Byron St., Robins AFB, GA 31098-1611.

AMSC/N/A FSC 6670

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:25Z
Check the source to verify that this is the current version before use.

2.3 Power. The scale shall be powered by commercially available alkaline batteries and commercially available rechargeable Ni-CAD batteries. Batteries shall be capable of eight (8) hours of continued use without recharging. Recharging capabilities must be supplied to operate from a twelve (12) volt DC system. Scale shall be designed and manufactured to accomplish recharging of batteries without removing batteries from scale.

2.4 Performance. The scale shall have a performance range of 0 to 20,000 pounds. The indicated weight shall be repeatable with the indicating weight inaccuracy not exceeding +/-1 percent of the applied load, throughout the range, or +/-50 pounds, whichever is greater.

2.5 Weight Indicating. The scale shall contain a digital display at least 0.5 inches in height with a back light to improve visibility. The scale shall be graduated to 10 lb. increments. Individual push button controls for zero, peak hold, and local/total mode shall be included on the keypad. The peak hold mode shall indicate the maximum applied load. The load/total mode enables the wheel scales to be connected in a series to display axle and total weight.

2.6 Portability. The scale shall weigh no more than 37 pounds and be easily carried by one individual.

2.7 Tilted Position. The scale shall be accurate when operated up to and including 5 percent (approximately three degrees) out of level.

2.8 Environmental conditions.

2.8.1 Temperature. The scale shall operate repeatable with the accuracy specified in 2.4 over a temperature range of –15 degrees Fahrenheit (F) to +125 degrees F.

2.8.2 Water. The operation of the scale shall not be affected by the presence of water.

2.8.3 Dust. The operation of the scale shall not be affected by the presence of dust.

2.9 Overload. The scale shall be capable of withstanding 1.5 times the rated capacity, or 30,000 lbs., without sustaining structural damage or permanent degradation of performance.

2.10 Corrosion control. The scale shall be constructed of corrosion resistant materials and shall be suitable protected against corrosion.

2.11 Repair and calibration. The scale shall be designed so that minor repair and calibration can be performed at the field level.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:25Z
Check the source to verify that this is the current version before use.

2.12 Service life. The scale shall be designed for a minimum service life of 8 years.

3. REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation.

4. PRODUCT CONFORMANCE PROVISIONS.

4.1 Product Conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance. Minor changes to the commercial product, with respect to ruggedizing and environmental suitability and protection shall be permitted, subject to the approval of the procurement office, to satisfy the requirements of this commercial item description.

4.2 Market Acceptability. The following market acceptability criteria are necessary to document the quality of the product to be provided under this CID.

4.2.1 The manufacturer of the item must have been producing a product meeting the requirements of this CID for at least 2 years.

4.2.2 The manufacturer of the item must have sold at least 500 units meeting the requirements of this CID in the commercial market place over the last 2 years.

4.3 Operation and maintenance manual. One copy of the commercial operation and maintenance manual, including top level illustrated parts breakdown and calibration procedures and adjustments, as applicable, shall be shipped with each unit. One additional copy of the operation and maintenance manual per contract shall be mailed to the cognizant engineer at this address: FSC 6670 Engineer, WR-ALC/LEEG, 295 Byron Street, Robins AFB, GA 31098-1611.

4.4 Warranty. Each unit shall be supplied with the commercial warranty or a one year warranty on parts and labor, whichever is longer. Information of warranty duration and expiration date, conditions of the warranty and point of contact shall be shipped with each unit. One additional copy of the warranty information per contract shall be mailed to the cognizant engineer at this address: FSC 6670 Engineer, WR-ALC/LEEG, 295 Byron Street, Robins AFB, GA 31098-1611.

5. PACKAGING.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:25Z
Check the source to verify that this is the current version before use.

5.1 Packaging. The scale shall be packaged using standard commercial packaging.

5.2 Marking. The scale shall be marked with the following information: Part Number and/or Model Number, Serial Number, Scale Capacity, Contract Number, and National Stock Number (NSN).

6. NOTES.

6.1 Source of documents. NIST Handbook 44 may be obtained from : NIST Public Inquiries, NIST, 100 Bureau Drive, Stop 3460, Gaithersburg, MD 20899-3640.

6.2 Ordering data. Procurement documents must specify the title, number, and date of this CID, issue of DODISS to be cited in the solicitation, and preservation and packaging requirements.

6.3 Key Words:

Scale
Man-Portable

6.4 National Stock Numbers (NSNs). The following is a list of NSNs assigned that correspond with this CID. The list may not be indicative of all possible NSNs associated with the CID.

6670-01-381-4455

Custodian:
Army - GL
Navy – YD
DLA – GS

Preparing Activity:
Air Force – 84

Agent:
Air Force – 99

Project Number 6670-0223

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:25Z
Check the source to verify that this is the current version before use.