MILITARY SPECIFICATION SHEET

CONNECTOR, FIBER OPTIC, PLUG-RECEPTACLE-ADAPTER STYLE, FIXED SINGLE TERMINUS, THREADED, PLUG (STEP-DOWN NOSE INTERFACE), LENSLESS, EPOXY, FOR 50/125 µm AND 100/140 µm FIBER

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the connector described herein shall consist of this specification and the latest issue of MIL-C-83522.




FIGURE 1. Dimensions and configuration (step-down nose).

© denotes changes

AMSC N/A
FSC 6060

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:35Z
Check the source to verify that this is the current version before use.

	Min	Max
A	.3858 (9.804)	.3863 (9.812)
C	.080 (2.03)	.100 (2.543)
D	.179 (4.57)	.181 (4.62)
E	.220 (5.59)	.233 (5.74)
F	.485 (12.3)	
G	.183 (4.661)	.224 (5.700)
H		1.50 (38.1)
J	.015 (0.38)	.045 (1.14)
B	Plug must not enter .118 hole gauge	Plug must enter .124 dia. hole gauge


K dimension	
50/125 µm fiber	100/140 µm fiber
.130	.145
*.002	*.002


Inches	mm
.0002	0.005
.001	0.03
.002	0.05
.005	0.13
.0051	0.130
.0057	0.145
.010	0.25
.015	0.38
.027	0.69
.030	0.76
.039	0.99
.046	1.17
.0625	1.588
.0847	2.151
.0850	2.159
.123	3.12
.124	3.15
.127	3.23
.131	3.33
.250	6.35
.309	7.85
.312	7.93
.315	8.00

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Millimeters are in parentheses.
4. Dimensions for fiber optic cable shall be in accordance with DOD-C-85045.
5. K dimension is specified in µm. This dimension is critical to fiber alignment. Dimensions for fiber optic fiber shall be in accordance with DOD-F-49291.
6. Dimensions A are obtained after product has been assembled.
7. Ferrule may be integral part of component.
8. One full length sleeve to be used in conjuction with two step-down nose connectors.
9. One half length sleeve to be used in conjuction with one step-down nose connector and one receptacle (active device).
10. Three holes .016 (0.41 mm) minimum diameter, equally spaced, are required for safety wiring after mating. Location on the coupling nuts optional.
11. O-ring is required. Component shall be machined for either O-ring location A or location B.

FIGURE 1. Dimensions and configuration - Continued.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:35Z
Check the source to verify that this is the current version before use.






	A	
	Min	Max
Full sleeve (see note 4)	.240 (6.15)	.246 (6.25)
1/2 sleeve (see note 5)	.117 (3.07)	.123 (3.12)

Inches	mm
.001	0.03
.083	2.11
.084	2.13
.096	2.44
.102	2.59
.108	2.74
.112	2.85
.117	3.07
.122	3.10
.123	3.12
.125	3.18
.148	3.76
.152	3.86
.240	6.10
.246	6.25





SECTION A-A

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are in parentheses.
3. Metric equivalents are given for general information only.
4. One full length delrin sleeve to be used in conjunction with two step-down nose connectors.
5. One-half length delrin sleeve to be used in conjunction with one step-down nose connector and one receptacle (active device).
6. Dimensions apply to sleeve as manufactured. Sleeve material may be compressed when in use.

FIGURE 2. Alignment sleeves.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:35Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Metals: The plug housing shall be of corrosion resistant steel per QQ-S-763, class 303 or nickel plated brass per QQ-B-626. Other metal components shall be of corrosion resistant steel per QQ-S-763, class 303; nickel plated beryllium copper per QQ-B-530 or nickel plated brass per QQ-B-626.

Epoxies: Use Trabond 230, Eccobond 1448 or an equivalent epoxy approved by the qualifying activity.

Dimensions and configuration: See figure 1.

Fiber optic cable requirements:

Cable diameter: In accordance with DOD-C-85045.

Cable configuration: In accordance with DOD-C-85045.

Fiber diameter: 50/125 µm and 100/140 µm.

Fiber numerical aperture: In accordance with DOD-C-85045.

Fiber type: In accordance with DOD-C-85045.

Fiber optic contact:

Method of optical alignment: Ferrule/sleeve type (see figure 2).

Lens configuration: Not applicable.

Coating requirements: Not applicable.

Cleaning procedures: Dampen lens tissue (paper wipes or cotton swab) with a small amount of isopropyl alcohol or water. Gently wipe the face of the connector, removing any debris, particularly around the optical fiber, using clean lens tissue (paper wipes, cotton swab). Carefully dry the contact with a clean, dry tissue.

Optical requirements:

Number of optical termini: One.

Coupling loss (attenuation): 2 dB maximum per mated pair.

Weight: 4 grams maximum.

Polarization: Not applicable.

Safety wire holes: Required.

Force to engage and disengage:

Longitudinal force: 12 pounds maximum.

Torque: 7 inch-pounds maximum.

Coupling proof torque: 15 inch-pounds minimum.

Coupling mechanism retention force: 60 pounds minimum.

Ozone exposure: Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:35Z
Check the source to verify that this is the current version before use.

Military part numbers: See table I.

TABLE I. Part numbers.

Superseded part number M83522/1-	New part numbers M83522/1-	Safety wire holes	Fiber size
01	03	yes	50/125
02	04		100/140

Plug accessories: Each plug shall be supplied with a minimum of one crimp ferrule as needed (see figure 1); two alignment sleeves (see figure 2); one protective cable-end cap; one 1.5 inch length of heat-shrink tubing or one rubber boot; and one set of assembly instructions. The assembly instructions shall include a listing of the epoxies specified in this specification sheet and a cleaning procedure statement as follows:

Cleaning procedures: Dampen lens tissue (paper wipes or cotton swab) with a small amount of isopropyl alcohol or water. Gently wipe the face of the connector, removing any debris, particularly around the optical fiber, using clean lens tissue (paper wipes, cotton swab). Carefully dry the contact with a clean, dry tissue.

NOTE: The plug mates with MIL-C-83522/3 adapter, MIL-C-83522/4 receptacle (active device), and MIL-C-83522/5 receptacle, bulkhead.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Navy - SH
Air Force - 11, 17, 19, 80, 90, 99
DLA - ES

User activities:
Navy - AS, MC, OS
Air Force - 13, 14

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 6060-0059-1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:35Z
Check the source to verify that this is the current version before use.