MILITARY SPECIFICATION

BATTERY POWER SUPPLY PP-6607( )/VVG-1: 11738841

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of electronic assembly known as Battery Power Supply PP-6607( )/VVG-1: 11738841 (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-F-13926	Fire Control Materiel: General Specification Governing the Manufacture and Inspection of
MIL-I-45607	Inspection Equipment; Acquisition, Maintenance, and Disposition of
MIL-S-45743	Soldering, Manual Type, High Reliability, Electrical, Electronic, Instrument, Communication, and Radar for Aerospace and Control Systems, Procedure for
MIL-S-46844	Solder Bath Soldering of Printed Wiring Assemblies, Automatic Machine Type

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	Quality Assurance Terms and Definitions
MIL-STD-810	Environmental Test Methods

DRAWINGS

U.S. Army, Frankford Arsenal

F8565556	Pressure Tester
F11665527	Ballistic Cover
F11738841	Battery Power Supply: PP-6607( )/VVG-1

PACKAGING DATA SHEET

11738841	Packaging of Battery Power Supply PP-6607( )/VVG-1: 11738841

(Copies of specifications, standards, drawings, and packaging data sheets required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Fabrication. The Battery Power Supply PP-6607( )/VVG-1, herein referred to as the unit, shall be manufactured in accordance with Drawing F11738841 and drawings pertaining thereto.

3.2 General specification. The unit shall meet the following requirements, where applicable, of MIL-F-13926:

a. Order of precedence

b. Dimensions and tolerances

c. Inorganic protective surface finishes

d. Electrical and electronic assemblies

e. Part identification and marking

f. Workmanship

3.2.1 Soldering. Soldering shall be in accordance with MIL-S-45743 or MIL-S-46844, except that bare copper wire exposure shall be permitted at clipped ends of component leads.

3.3 Performance. Unless otherwise specified, the unit shall meet the performance requirements of this specification at standard ambient temperatures between 60 degrees Fahrenheit (^{o}F) and 90°F.

3.3.1 Loads, power, signals, and interconnections. The unit shall perform as specified herein when the loads, interconnections, power, and signals of table I are applied as specified.

3.3.1.1 System turn-on without tank power. With no external signal or power sources applied, the voltage at J1-K shall be within 3 Volts direct current (Vdc) of the voltage at J1-b.

3.3.1.2 Battery supplied Q-switch power. With no external signal or power sources applied, and with item 1.2 of table I connected as specified, the voltage at J1-P shall be within 2.0 Vdc of the voltage at J1-b.

3.3.1.3 Q-switch voltage supplied by tank power. With the signal source (item 3.1) of table I applied to J1-E and set to +38.0 ±1.0 Vdc, and with item 1.2 of table I connected, the output at J1-P shall be +37.0 ±1.5 Vdc.

3.3.1.4 Tank supplied primary power. With the signal source (item 3.1) of table I applied to J1-E and set for +24.0 ±2.0 Vdc, the voltage at J1-K shall be +23.0 ±3.5 Vdc. With J1-X disconnected from J1-M, the output at J1-K shall be +0.5 ±0.5 Vdc.

95

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

TABLE I
LOADS, POWER, SIGNALS, AND INTERCONNECTIONS

Item	Conditions	Characteristics	Connections
1.	Loads		Connected between the following pins of J1
1.1	Resistor	10 ohms (Ω) ±5%	K and M
1.2	Resistor	30Ω ±5%	P and M when specified herein
1.3	Resistor	620Ω ±5%	Y and T
1.4	Resistor	620Ω ±5%	V and T
1.5	Resistor	5.6 kilohm ±5%	a and R
2.	Power Sources		Applied between the following pins of J1 unless otherwise specified
2.1	+15 Vdc	Tolerance: ±0.7 Vdc Ripple: ≤ 25 mV p-p	T (+) and M (-)
2.2	+5 Vdc	Tolerance: ±0.2 Vdc Ripple: ≤ 25 mV p-p	R (+) and M (-)
2.3	-6 Vdc	Tolerance: ±0.2 Vdc Ripple: ≤ 25 mV p-p	S (-) and M (+)
3.	Signal Sources		
3.1	0 to +40 Vdc	Adjustable Ripple: ≤100 mV p-p Source impedance: ≤0.10Ω	Applied as specified herein with return to J1-G(-)
3.2	200 mA	Tolerance: ±20 mA Ripple: ≤ 5 mA p-p	Applied as specified herein with return to J1-M (-)
4.	Interconnections		Unless otherwise specified interconnect the following pins of J1: K to L E to F G to H M to N X to M

95

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

3.3.1.5 Battery supplied primary power. With the signal source (item 3.1) of table I applied to J1-E and set to +16.5 ±0.5 Vdc, the voltage at J1-K shall be within 3.0 Vdc of the voltage at J1-b.

3.3.1.6 Battery charge current level. With the signal source (item 3.1) of table I applied to J1-E and set to +24.0 ±2.0 Vdc, the current flowing to the battery positive terminal shall be 200 ±60 mAdc.

3.3.1.7 Malfunction 1 signal. With the signal source (item 3.1) of table I set to +24.0 ±2.0 Vdc and applied to and removed from J1-E, the outputs at J1-U shall be +5.0 ±1.0 Vdc and +0.2 ±0.2 Vdc, respectively. The output at J1-a shall be +5.0 ±1.0 Vdc.

3.3.1.8 Thermal switch (S1). With the signal source (item 3.1) of table I applied to J1-E and set to +24.0 ±2.0 Vdc and the thermal switch (S1) cooled to a temperature below -35°F, the output at J1-U and J1-a shall be +0.2 ±0.2 Vdc.

3.3.1.9 Thermal switch (S2). With the signal source (item 3.1) of table I applied and set to +24.0 ±2.0 Vdc, with switch A2S1 depressed, with the load (item 1.2) of table I disconnected, and with the thermal switch (S2) cooled to a temperature below -10°F, the voltage at J1-b shall be +36.0 ±3.0 Vdc.

3.3.1.10 Battery low light return. With the signal source (item 3.1) of table I applied to J1-E and set to +24.0 ±2.0 Vdc, and with J1-X disconnected from J1-M, the output at J1-V shall be +0.3 ±0.3 Vdc. Under these conditions, except with J1-X reconnected to J1-M, the output at J1-V shall be +15.0 ±1.0 Vdc provided that the voltage at J1-b is greater than +26 Vdc.

3.3.1.11 Battery drain light return. With the signal source (item 3.1) of table I applied to J1-E and set to +24.0 ±2.0 Vdc, and then to +16.5 ±0.5 Vdc, the voltage at J1-Y shall be +15.0 ±1.0 Vdc and +1.0 ±0.5 Vdc respectively.

3.3.1.12 Battery charge. With the current source (item 3.2) of table I applied to J1-Z and set for 200 ±20 mA dc, with J1-X disconnected from J1-M, and with no other signal or power source applied, the current flowing to the battery's positive terminal shall be 200 ±30 mAdc. With the thermal switch (S3) cooled to a temperature below -10°F, the current flow to the battery shall be 0 ±20 mA.

95

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

3.3.2 Environmental

3.3.2.1 Storage temperature. The unit shall meet the requirements of 3.3.1 at ambient temperature after exposure to and thermal stabilization at -80°F and +160°F.

3.3.2.2 Operating temperatures. The unit shall meet the requirements of 3.3.1, except 3.3.1.6, 3.3.1.9, and 3.3.1.12, while exposed to and thermally stabilized at -40°F, and shall meet the requirements of 3.3.1, except 3.3.1.6, 3.3.1.8, 3.3.1.9 and 3.3.1.12, while exposed to and thermally stabilized at +125°F, subsequent to which the requirements of 3.3.1 shall be met at ambient temperature.

3.3.2.3 Vibration. The unit shall show no physical failure and shall meet the requirements of 3.3.1 after being exposed to the following vibratory conditions:

a.	Amplitude:	1/64 inch, constant (1/32 inch double amplitude)
b.	Vibratory motion:	Simple harmonic
c.	Sweep time:	5 to 55 to 5 Hertz in a 5-minute period
d.	Vibration cycling:	Three linear or logarithmic sweeps applied to each of the three mutually perpendicular axes.

3.3.2.4 Shock. The unit shall meet the requirements of 3.3.1 after being exposed to a total of 18 shock impulses, three in each direction along the three mutually perpendicular axes. Each shock impulse shall be a half-sine wave with a time duration of 3.5 ±0.5 milliseconds and a peak amplitude of 100g.

3.3.3 Sealing. With the unit initially pressurized with nitrogen or air to 5 ±1 pounds per square inch gage (psig), the loss of pressure shall not exceed 0.055 psig in one-half hour, except for special sampling-environmental during which the loss of pressure shall not exceed 0.22 psig in two hours.

3.3.4 Internal pressure. Subsequent to meeting the sealing requirements, the unit shall be dry flushed with an internal atmosphere containing nitrogen or air having a dew point of at least -63.5°F, and an internal pressure of 3.5 ±0.5 psig shall be established.

3.3.5 Interface. The unit shall be capable of interfacing with the Ballistic Cover 11665527.

95

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 General provisions. The component and subassembly inspection requirements of MIL-F-13926 form a part of the quality assurance provisions of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109.

4.2 First article (initial production) approval. The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three units. The sample shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.2.1 Government testing. When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure conformance to all the requirements of the contract. A record of this inspection, including certificates of conformance for materials, shall be submitted with the sample.

4.2.2 Contractor testing. When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection.

95

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

4.3 Inspection provisions

4.3.1 Submission of product. Unless otherwise specified herein, or by the contracting officer, inspection lot size, lot formation and presentation of lots shall be in accordance with inspection and sampling procedures herein and submission of product provisions of MIL-STD-105.

4.3.2 Examination and tests

4.3.2.1 Components and subassemblies. All components and subassemblies shall be inspected in accordance with the inspection provisions contained the respective specifications and in Supplementary Quality Assurance Provisions (SQAP) listed in the technical data package (TDP). In the absence of SQAPs, the applicable quality assurance provisions of MIL-F-13926 shall apply.

4.3.2.2 First article testing. First article testing shall be conducted in accordance with tables II through IV to determine compliance with 4.2. All examinations and tests shall be witnessed by the Government Quality Assurance Representative. When manufacturing processes, materials, or inspection techniques previously applied are subject to change, or an adverse change occurs in performance capability of the unit, this shall be cause to cease those operations contributing to the change or failure until corrections have been made by the contractor and approved by the Government.

4.3.2.3 Functional tests. The requirements and tests in table II shall be inspected on a 100 percent basis. All examinations and tests shall be conducted at the standard ambient temperature.

S/S

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

TABLE II
FUNCTIONAL TESTS

Classification	Characteristic	Requirement	Test Paragraph
101	System turn-on without tank power	3.3.1.1	4.6.2
102	Battery supplied Q-switch power	3.3.1.2	4.6.3
103	Q-switch voltage supplied by tank power	3.3.1.3	4.6.4
104	Tank supplied primary power	3.3.1.4	4.6.5
105	Battery supplied primary power	3.3.1.5	4.6.6
106	Battery charge current level	3.3.1.6	4.6.7
107	$\overline{\text{Malfunction 1}}$ signal	3.3.1.7	4.6.8
108	Thermal switch (S1)	3.3.1.8	4.6.9
109	Thermal switch (S2)	3.3.1.9	4.6.10
110	Battery low light return	3.3.1.10	4.6.11
111	Battery drain light return	3.3.1.11	4.6.12
112	Battery charge	3.3.1.12	4.6.13
113	Sealing (1/2 hour)	3.3.3	4.6.15

95

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

TABLE III
SPECIAL SAMPLING - GENERAL

Classification	Control Test	Requirement	Test Paragraph
301	Fabrication	3.1	Applicable drawings - visual
302	General specification	3.2	MIL-F-13926 - visual

TABLE IV
SPECIAL SAMPLING - ENVIRONMENTAL

Classification	Control Test	Requirement	Test Paragraph
303	Storage temperature	3.3.2.1	4.6.14.1
304	Operating temperatures	3.3.2.2	4.6.14.1
305	Vibration	3.3.2.3	4.6.14.2
306	Shock	3.3.2.4	4.6.14.3
307	Sealing (2 hours)*	3.3.3	4.6.15
308	Interface	3.3.4	4.6.16
* To be performed after all environmental testing.			

4.4 Special sampling. The selection of samples shall be in accordance with section 7 of MIL-STD-105.

4.4.1 General. One unit shall be selected at random by a Government representative as a control sample from each 50 produced. The control sample shall meet the requirements and tests in table III.

4.4.2 Environmental. Three units shall be selected at random by a Government representative as a control sample from each 50 produced or from each month's production, whichever occurs first. The control sample shall meet the requirements and tests in table IV.

95

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

4.4.3 Acceptance and rejection. Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with the acceptance and rejection criteria specified in MIL-STD-105.

4.5 Inspection equipment. Except as otherwise provided for by the contract, the contractor shall supply and maintain inspection equipment in accordance with the applicable requirements of MIL-I-45607. The inspection equipment listed in table V shall be utilized in performirg the tests specified herein.

4.5.1 Government-furnished inspection equipment. Where the contract provides for Government-furnished inspection equipment, supply and maintenance of inspection equipment shall be in accordance with the applicable requirements specified in MIL-I-45607.

4.5.2 Contractor-furnished inspection equipment

4.5.2.1 Government design. Unless otherwise specified in the contract, all inspection equipment specified by drawing number in specifications or SQAPs forming a part of the contract shall be supplied by the contractor in accordance with applicable technical data listed in the TDP.

4.5.2.2 Contractor design. The contractor shall design and supply inspection equipment compatible with the test methods and procedures specified in 4.6 of this specification and with the component inspection procedures specified in examination and test facilities provisions of MIL-F-13926. Since tolerance of inspection equipment is normally considered to be within 10 percent of the product tolerance for which intended, this inherent error in the inspection equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions, and tolerances used in the design of inspection equipment shall be so selected and controlled as to insure that the inspection equipment shall reliably indicate acceptability of a product which does not exceed 90 percent of the prescribed tolerance limit and permit positive rejection when nonconforming. Construction shall be such as to facilitate routine calibration of inspection equipment.

4.5.2.2.1 Pressure tester. Special test equipment (STE) in accordance with Drawing F8565556, or equivalent, shall be provided to check the sealing of the unit.

95

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

TABLE V
INSPECTION EQUIPMENT

Item	Nomenclature	Description
1	DC power supply	0 to +40 Vdc adjustable Ripple: ≤100 mV p-p Source impedance: ≤0.01 ohm
2	DC power supply	+5.0 ±0.2 Vdc Ripple: ≤25 mV p-p
3	DC power supply	-6.0 ±0.2 Vdc Ripple: ≤25 mV p-p
4	DC power supply	200 ±20 mA dc
5	DC voltmeter	Range: 0 to 100 Vdc Accuracy: ±1%
6	DC ammeter	Range: 0 to 1 Amp dc, clip-on type. Accuracy: ±3%

4.6 Test methods and procedures

4.6.1 Test conditions. Unless otherwise specified, the test conditions shall be in accordance with the test facilities provisions of MIL-F-13926.

4.6.1.1 Initial conditions. Connect the loads and interconnect the pins specified in table I. Unless otherwise specified, apply the power sources of table I.

4.6.2 System turn-on without tank power test. With no external power applied, measure the voltages at J1-K and J1-b to determine compliance with 3.3.1.1.

4.6.3 Battery supplied Q-switch power test. With no external power applied, measure the voltages at J1-P and J1-b to determine compliance with 3.3.1.2.

95

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

4.6.4 Q-switch voltage supplied by tank power test. Apply the signal source (item 3.1) of table I to J1-E. Set the voltage to +38.0 ±1.0 Vdc. Measure the voltage at J1-P to determine compliance with 3.3.1.3.

4.6.5 Tank supplied primary power test. Apply the signal source (item 3.1) of table I to J1-E. Set the voltage to +24.0 ±2.0 Vdc. Measure the voltage at J1-K to determine compliance with 3.3.1.4. Disconnect J1-X from J1-M. Measure the voltage at J1-K to determine compliance with 3.3.1.4.

4.6.6 Battery supplied primary power test. Apply the signal source (item 3.1) of table I to J1-E. Set voltage to +16.5 ±0.5 Vdc. Measure the voltages at J1-K and J1-b to determine compliance with 3.3.1.5.

4.6.7 Battery charge current level test. Apply the signal source (item 3.1) of table I to J1-E. Set voltage to +24.0 ±2.0 Vdc. Verify that the requirements of 3.3.1.6 are met.

4.6.8 Malfunction 1 signal test. Set the signal source (item 3.1) of table I to +24.0 ±2.0 Vdc. First apply then remove the signal source from J1-E. Measure the outputs of J1-U and J1-a to determine compliance with 3.3.1.7.

4.6.9 Thermal switch (S1) test. Apply the signal source (item 3.1) of table I to J1-E. Set voltage to +24.0 ±2.0 Vdc. Cool the thermal switch (S1) to a temperature below -35°F. Measure the output at J1-U and J1-a to determine compliance with 3.3.1.8.

4.6.10 Thermal switch (S2) test. Apply the signal source (item 3.1) of table I to J1-E. Set voltage to +24.0 ±2.0 Vdc. Disconnect the load (item 1.2) of table I and depress A2S1. With S2 cooled to a temperature below -10°F, measure the output at J1-b to determine compliance with 3.3.1.9.

95

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

4.6.11 Battery low light return test. Apply the signal source (item 3.1) of table I to J1-E. Set voltage to +24.0 ±2.0 Vdc. Disconnect J1-X from J1-M. Measure the output of J1-V to determine compliance with 3.3.1.10. Reconnect J1-X to J1-M. Measure output at J1-V to determine compliance with 3.3.1.10.

4.6.12 Battery drain light return test. Apply the signal source (item 3.1) of table I to J1-E. Set voltage to +24.0 ±2.0 Vdc. Measure the output of J1-Y to determine compliance with 3.3.1.11. Readjust signal source to +16.5 ±2.5 Vdc. Measure the output of J1-Y to determine compliance with 3.3.1.11.

4.6.13 Battery charge test. Apply the current source (item 3.2) to J1-Z. Set to 200 ±20 mA dc. Disconnect J1-X from J1-M, and all other power or signal sources. Measure the current flowing to the positive terminal of the battery to determine compliance with 3.3.1.12. Cool thermal switch S3 to a temperature less than -10°F. Measure the current to the battery to determine compliance with 3.3.1.12.

4.6.14 Environmental tests

4.6.14.1 Temperature. The test apparatus shall be in accordance with the applicable test facilities provisions of MIL-F-13926 except that the unit may be mounted on the inside surface of the test chamber. Perform this test in accordance with Procedure I of MIL-F-13926, with conditions C (-40°F) and E (+125°F), and with the rate of temperature change during cycling not greater than 3°F per minute. At each of the specified operating temperatures, perform the tests of 4.6.2 through 4.6.13, except 4.6.7, 4.6.8, 4.6.10 and 4.6.13 at -40°F, and 4.6.7, 4.6.8, 4.6.10 and 4.6.13 at +125°F, to determine compliance with 3.3.2.1 and 3.3.2.2.

4.6.14.2 Vibration. Perform this test utilizing the apparatus specified in Method 514.1 of MIL-STD-810 and in accordance with Part I of Procedure I therein, except that the vibratory conditions of 3.3.2.3 shall apply. Following vibration exposure, examine the unit for structural failures, loose hardware, wire breakage, and abrasion. Perform the tests of 4.6.2 through 4.6.13 to determine compliance with 3.3.2.3.

4.6.14.3 Shock. Perform this test utilizing apparatus specified in Method 516.1 of MIL-STD-810, in accordance with Procedure I therein and with the conditions specified in 3.3.2.4, to determine compliance with 3.3.2.4.

95

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

4.6.15 Sealing. Perform this test utilizing the STE specified in 4.5.2.2.1. Pressurize the unit as specified in 3.3.3. Measure the pressure loss over the applicable time period to determine compliance with 3.3.3.

4.6.16 Internal pressure. Perform this test utilizing the STE specified in 4.5.2.2.1. Verify that the requirement of 3.3.4 is met.

4.6.17 Interface. Perform this test utilizing a limit gage to determine compliance with 3.3.5.

95

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing, and marking. Packaging, packing, and marking shall be in accordance with Packaging Data Sheet 11738841. The level of protection shall be as specified in the procurement document.

6. NOTES

6.1 Intended use. The Battery Power Supply PP-6607( )/VVG-1 is a functional part of the Fire Control Rangefinder AN/VVG-1( ). The function of the power supply is to provide primary power whenever there is a transient low voltage condition on the vehicle power or a complete removal of the vehicle power for a limited time period.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification

b. Applicable packaging data sheet number (see 5.1)

c. Selection of applicable levels of preservation, packaging and packing

d. Applicable stock number

e. Requirement for First Article Submission.

Custodian:

Army - MU

Preparing Activity:

Army - MU

PROJECT NO. 1240-A305

95

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.