MIL-S-48741 (PA)
28 March 1975

MILITARY SPECIFICATION

SHIPPING AND STORAGE CONTAINER, XM612

PARTS AND ASSEMBLING

This Specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not normally covered by the drawings and provides quality assurance provisions for the fabrication of parts and assembling of the Shipping and Storage Container, XM612.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals form a part of specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)

FSC: 8140

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

DRAWINGS

PICATINNY ARSENAL

PRODUCT AND PACKAGE DRAWINGS

9288556 - Shipping and Storage Container XM612

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

ASTM D 1505 - Density of Plastics by the Density Gradient Techniques
ASTM D 2765 - Degree of Crosslinking in Crosslinked Ethylene Plastics as Determined by Solvent Extraction

3. REQUIREMENTS

3.1 Materials.-Materials shall be in accordance with the applicable drawings and specifications.

3.2 Components and Assemblies.-The components and assemblies shall comply with all requirements specified on Drawing 9288556 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Assembly and disassembly.-The container shall accept the warhead section with spacer assembly attached, without evidence of excessive effort in assembly or disassembly, or closing and securing the cover. In addition, with the warhead assembled to the base a 1.44 ± .01 diameter by 4.37 ± .01 long cylinder shall fit without excessive effort between the warhead and the three (3) sling recesses in the base.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:38Z
Check the source to verify that this is the current version before use.

3.4 Performance characteristics.-The container shall comply with all the requirements specified on Drawing 9288556, and with all requirements specified in this specification, when loaded with a Warhead Section, without evidence of puncture, cracks or permanent distortion. In addition, the Warhead Section shall be operable after completion of the following tests. All tests shall be conducted at a temperature of plus (+) 80 degrees Fahrenheit (F), plus or minus (±) 20 degrees Fahrenheit.

3.4.1 Vibration.-The loaded container shall comply with the requirements of 3.4.

3.4.2 Edgewise drop.-The loaded container shall comply with the requirements of 3.4.

3.4.3 Cornerwise drop.-The loaded container shall comply with the requirements of 3.4.

3.4.4 Fork-lifting.-The loaded container shall be capable of being lifted by a suitable fork-type lift truck and meet the requirements of 3.4.

3.4.5 Stacking.-The loaded container shall be capable of supporting a simulated stacking load equal to two (2) times the weight of a loaded container and meet the requirements of 3.4.

3.5 Workmanship.-All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. All marking and stamping shall be neat and sharply defined.

3.6 Submission of results of contractor-conducted examinations and tests.-The contractor shall forward copies of the results of any of his examinations or tests to the designated address as required by the contract. (See 6.4)

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:38Z
Check the source to verify that this is the current version before use.

3.7 First Article Inspection.-This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection and Standard Quality Assurance Provisions.-Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of Inspection.-The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First Article Inspection.-

4.3.1 Submission.-The contractor shall submit a first article sample as designated by the Contractor for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing No.	Quantity
Shipping and Storage Container XM612	9288556	1
Base	9288553	1
Cover	9288554	1
Spacer Assembly	9288555	1
Pad	9294984	1

4.3.2 Inspections to be Performed.-See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection.-See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:38Z
Check the source to verify that this is the current version before use.

TABLE 1 - FIRST ARTICLE INSPECTION

MIL-S-48741 (PA)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Shipping and Storage Container XM612				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Shipping and Storage Container XM612 (Dwg. 9288556)				
	Examination For Defects	1		3.2	4.4.2.5
	Vibration			3.4.1	4.5.2.1
	Edgewise drop			3.4.2	4.5.2.2
	Cornerwise drop			3.4.3	4.5.2.3
	Fork-lifting			3.4.4	4.5.2.4
	Stacking			3.4.5	4.5.2.5
	Base (Dwg. 9288553) Examination for Defects	1			4.4.2.1
	Cover (Dwg. 9288554) Examination for Defects	1			4.4.2.2
	Spacer Assembly (Dwg. 9288555) Examination for Defects	1		3.2	4.4.2.3
	Pad (Dwg. 9254984) Examination for Defects	1		3.2	4.4.2.4

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection

4.1.1 Inspection Lot Formation.-Inspection lots shall comply with the lot formation provisions of MIL-A-48078 (PA).

4.4.2 Examination.-See MIL-A-48078 (PA).

a. Sampling Plans.-Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-S-48741 (PA)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.1	Base				9288553
					NEXT HIGHER ASSEMBLY
					9288556
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
116	Distance from outside shoulder to top of sealing lip		0.40%	3.2	Gage
117	Distance from top of sealing lip to inside horizontal surface		0.40%	3.2	Gage
118	Radius of sealing lip		0.40%	3.2	Gage
119	Radius at base of sealing lip		0.40%	3.2	Gage
120	Thickness of spacer assembly cavity max.		0.40%	3.2	Gage
121	Distance from spacer assembly cavity to largest sling groove		0.40%	3.2	Gage
122	Width of largest sling groove		0.40%	3.2	Gage
123	Distance from spacer assembly cavity to center sling groove		0.40%	3.2	Gage
124	Width of center sling groove		0.40%	3.2	Gage
125	Distance from spacer assembly cavity to smallest sling groove		0.40%	3.2	Gage
126	Weight		100%	3.2	Balance
Minor 201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:38Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-S-48741 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.1	Base				9288553
					NEXT HIGHER ASSEMBLY 9288556
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Anti-static agent missing		100%	3.2	Visual
Major A					
101	Drain holes blocked or missing		100%	3.2	Visual
102	Wall thickness		100%	3.2	Gage
103	Depth to foam, max		100%	3.2	Gage
104	Distance from side to center (both sides)		0.40%	3.2	Gage
105	Width of strapping recesses		0.40%	3.2	Gage
106	Depth of strapping recesses		0.40%	3.2	Gage
107	Distance from end to center of stacking indent		0.40%	3.2	Gage
108	Distance from center of first to center of second stacking indent		0.40%	3.2	Gage
109	Distance from center of first to center of third stacking indent		0.40%	3.2	Gage
110	Angle of stacking indent wall		0.40%	3.2	Gage
111	Radius at bottom of stacking indent (Detail A)		0.40%	3.2	Gage
112	Radius (smaller) at top of stacking indent (Detail A)		0.40%	3.2	Gage
113	Length of stacking indent		0.40%	3.2	Gage
114	Radius at bottom of stacking indent (View C-C)		0.40%	3.2	Gage
[illegible]	Radius (smaller) at top of stacking indent (View C-C)		0.40%	3.2	Gage

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:38Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48741 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9288555
4.4.2.3	Spacer Assembly				NEXT HIGHER ASSEMBLY 9288556
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
101	Any component missing, improperly assembled or damaged		100%	3.2	Visual
102	Height		0.40%	3.2	Gage
103	Width		0.40%	3.2	Gage
104	Thickness of spacer		0.40%	3.2	Gage
105	Thickness of side pad		0.40%	3.2	Gage
106	Thickness of top pad		0.40%	3.2	Gage
107	Thickness of bottom pad		0.40%	3.2	Gage
108	Diameter of recess for warhead		0.40%	3.2	Gage
109	Distance from center to T-bolt cutout radius centerline		0.40%	3.2	Gage
110	Distance from T-bolt cutout radius centerline to outside edge		0.40%	3.2	Gage
111	Radius of T-bolt cutout		0.40%	3.2	Gage
112	Radius of warhead washer cutout		0.40%	3.2	Gage
113	Depth of holes, min		0.40%	3.2	Gage
114	Diameter of holes, min		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-S-48741 (PA)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9288554
4.4.2.2	Cover				NEXT HIGHER ASSEMBLY 9288556
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
117	Radius at bottom of sealing lip groove		0.40%	3.2	Gage
118	Depth of sealing lip groove		0.40%	3.2	Gage
119	Radius of outside lip		0.40%	3.2	Gage
120	Radius of inside lip		0.40%	3.2	Gage
121	Thickness of spacer assembly cavity max		0.40%	3.2	Gage
122	Weight		100%	3.2	Balance
Minor 201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

10

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Spacer Assembly	1 OF 1	9288555
			NEXT HIGHER ASSEMBLY 9288556

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
101	Any component missing, improperly assembled or damaged		100%	3.2	Visual
102	Height		0.40%	3.2	Gage
103	Width		0.40%	3.2	Gage
104	Thickness of spacer		0.40%	3.2	Gage
105	Thickness of side pad		0.40%	3.2	Gage
106	Thickness of top pad		0.40%	3.2	Gage
107	Thickness of bottom pad		0.40%	3.2	Gage
108	Diameter of recess for warhead		0.40%	3.2	Gage
109	Distance from center to T-bolt cutout radius centerline		0.40%	3.2	Gage
110	Distance from T-bolt cutout radius centerline to outside edge		0.40%	3.2	Gage
111	Radius of T-bolt cutout		0.40%	3.2	Gage
112	Radius of warhead washer cutout		0.40%	3.2	Gage
113	Depth of holes, min		0.40%	3.2	Gage
114	Diameter of holes, min		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48741 (PA)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.2	Cover				9288554
					NEXT HIGHER ASSEMBLY
					9288556
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
117	Radius at bottom of sealing lip groove		0.40%	3.2	Gage
118	Depth of sealing lip groove		0.40%	3.2	Gage
119	Radius of outside lip		0.40%	3.2	Gage
120	Radius of inside lip		0.40%	3.2	Gage
121	Thickness of spacer assembly cavity max		0.40%	3.2	Gage
122	Weight		100%	3.2	Balance
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

21 of

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:38Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48741 (PA)

13

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Shipping and Storage Container XM612				9288556
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Assembly and disassembly		100%	3.3	4.5.1
102	Distance from spacer assembly cavity to pad		100%	3.2	Gage
103	Pad loose, damaged or improperly assembled		100%	3.2	Visual
104	Strapping improperly assembled or loose		0.40%	3.2	Visual/Manual
Minor					
201	Marking missing, incomplete or illegible		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.-

4.4.3.1 Percentage of extract, max of base (See Dwg. 9288553) Major A Defect.-One (1) sample from each eight (8) hours or less of production shall be selected and subjected to this test. If the sample fails to comply with the applicable drawing requirement, that quantity represented shall be rejected. The test shall be performed as specified in 4.5.3.

4.4.3.2 Density, max, of base (See Dwg. 9288553) Major A Defect.-Three (3) samples from each eight (8) hours or less of production shall be selected and subjected to this test. If any sample fails to comply with the applicable drawing requirement, that quantity represented shall be rejected. The test shall be performed as specified in 4.5.4.

4.4.3.3 Percentage of extract, max, of cover (See Dwg. 9288554) Major A Defect.-One (1) sample from each eight (8) hours or less of production shall be selected and subjected to this test. If the sample fails to comply with the applicable drawing requirement, that quantity represented shall be rejected. The test shall be performed as specified in 4.5.3.

4.4.3.4 Density, max, of cover (See Dwg. 9288554) Major A Defect.-Three (3) samples from each eight (8) hours or less of production shall be selected and subjected to this test. If any sample fails to comply with the applicable drawing requirement, that quantity represented shall be rejected. The test shall be performed as specified in 4.5.4.

4.4.4 Inspection Equipment.-The inspection equipment required to perform the examinations and tests presecribed herein is described in the "Paragraph Reference/ Inspection Method Column" in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test Methods and Procedures.-

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:38Z
Check the source to verify that this is the current version before use.

4.5.1 Assembly and disassembly.-The warhead section or fixture, with spacer assembly attached, shall be loaded into the container base. Inspection shall be made for proper fit of the cylindrical gage in the three (3) sling recesses in the base. Last, the cover shall be assembled and secured to the base.

4.5.2 Performance Characteristics.-The warhead section shall be loaded into the container. The container shall then be subjected to the tests listed in paragraphs 4.5.2.1 through 4.5.2.5. All test procedures and equipment shall be approved by the Contracting Officer. (See 4.3.4).

4.5.2.1 Vibration.-The loaded container shall be assembled to a suitable fixture with cover closed and strapping fastened in a normal manner. The container assembly shall then be subjected to the vibrations specified in Table A below. The vibrations shall be applied in the vertical axis at 80° ± 20°F. Adequate safety precautions shall be observed to preclude endangering personnel and equipment.

TABLE A

Frequency	Input	Logarithmic Sweep Rate	Total Time
5.5 - 38 Hz	1.5g	0.8 Octaves/min.	52 Min/ Axis
38 - 50 Hz	.02 In(da)		

4.5.2.2 Edgewise drop.-The loaded container shall be supported at one end of its base on a sill approximately five (5) inches in height and placed at right angles to its length. The other end of the container shall be raised and allowed to fall freely from a twenty-four (24) inch height to a concrete or similarly hard surface. This test shall be applied to both ends of the container.

4.5.2.3 Cornerwise drop.-The loaded container shall be supported at one corner of its base on a block approximately five (5) inches in height and with a block approximately twelve (12) inches high placed under the other corner of the same

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:38Z
Check the source to verify that this is the currentversion before use.

end of the container. The opposite end of the container shall be raised and allowed to fall freely from a twenty four (24) inch height, measured from the lower of the two (2) corners, to a concrete or similarly hard surface. The test shall then be applied to the diagonally opposite corner.

4.5.2.4 Fork-lifting.-The loaded container shall be lifted clear of another container (or equipment) when stacked, lowered to the floor by a fork-lift truck having forks forty (40) inches, minimum in length. The truck shall be cleared of the container, lifting position reassumed and restacked. This procedure shall then be performed from other side of container.

4.5.2.5 Stacking.-The required load shall be placed on top of the container.

4.5.3 Percentage of extract, max.-This test shall be performed in accordance with ASTM Method D 2765. Samples shall be obtained from access hole material. Readings shall not be averaged.

4.5.4 Density, max.-This test shall be performed in accordance with ASTM Method D 1505. Samples shall be obtained from access hole material. Readings shall not be averaged.

5. PREPARATION FOR DELIVERY

5.1 Marking.-Marking shall be in accordance with Dwg. 9288556.

5.2 Shipping.-When components from more than one lot are shipped as a carload, each lot shall be kept separate, and the divisions between lots clearly indicated to prevent mxing of the lots in transit.

6. NOTES

6.1 Intended Use.-The Shipping and Storage Container XM612 is intended for use with the Warhead Section, GM, Practice, Lightweight, M252.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

6.2 Ordering data.-See MIL-A-48078 (PA).

6.3 Submission of Inspection Equipment Designs for Approval.-See MIL-A--8078. Submit equipment designs as required, to Commander, Picatinny Arsenal, Attn: SARPA-QA-T, Dover, New Jersey 03801.

6.4 Submission of results of contractor-conducted examinations and tests.-Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to Commander, Picatinny Arsenal, Attn: SARPA-QA-A-S, Dover, New Jersey 07801.

6.5 Submission of data cards.-In addition to the normal distribution of records, when the container is procured by the U.S. Army Munitions Command, one (1) copy of the ammunition data cards shall be forwarded to: Commander, Picatinny Arsenal, Attn: SARPA-QA-A-S, Dover, New Jersey 07801.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 8140-A134

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:38Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO (If "Yes", in what way?)

4. REMARKS

SUBMITTED BY (Printed or typed name and address - Optional)

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:38Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-A
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.