
PERFORMANCE SPECIFICATION SHEET

COILS, RADIO FREQUENCY, CHIP, MAGNETICALLY SHIELDED, IRON CORE-IRON SLEEVE, AND IRON CORE-FERRITE SLEEVE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-83446.



	Inches	Millimeters
A	.300 to .325	7.62 to 8.26
B	.105 to .125	2.67 to 3.18
C	.125 to .145	3.18 to 3.68
D	.020 Min.	.508 Min.
E	.040 to .060	1.02 to 1.52
F	.190 Ref.	4.83 Ref.
G	.070 Ref.	1.78 Ref.

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.

FIGURE 1. Dimensions and configuration.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:12Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics (initial).

Dash Number	Inductance µH ±10%	Q (min)	Test Frequency (L and Q) MHz	Self Resonant Frequency MHz (min)	DC Resistance Ohms (max)	Current Rating mA (max)	Incremental current Dc (mA)	Material
-01	.10	45	25	1/ 490	.10	670	670	
-02	.12	45	25	1/ 430	.11	635	635	
-03	.15	45	25	1/ 415	.12	610	610	
-04	.18	45	25	1/ 375	.13	585	585	
-05	.22	45	25	1/ 330	.15	545	545	
-06	.27	45	25	1/ 300	.16	530	530	
-07	.33	44	25	1/ 260	.18	495	495	
-08	.39	42	25	230	.19	485	485	
-09	.47	41	25	220	.21	460	460	
-10	.56	41	25	210	.23	440	440	
-11	.68	39	25	180	.24	430	430	
-12	.82	38	25	165	.27	405	405	
-13	1.00	37	25	150	.30	385	385	2/
-14	1.20	40	7.9	130	.73	247	247	
-15	1.50	41	7.9	115	.86	228	228	
-16	1.80	43	7.9	105	.95	217	217	
-17	2.20	45	7.9	95	1.10	202	202	
-18	2.70	48	7.9	90	1.20	193	193	
-19	3.30	49	7.9	80	1.30	185	185	
-20	3.90	50	7.9	75	1.50	173	173	
-21	4.70	50	7.9	70	2.40	136	136	
-22	5.60	50	7.9	60	2.90	124	124	
-23	6.80	50	7.9	55	3.20	118	118	
-24	8.20	50	7.9	53	3.60	111	111	
-25	10.0	50	7.9	50	4.00	106	106	
-26	12.0	36	2.5	35	3.00	122	122	
-27	15.0	38	2.5	30	3.40	115	115	
-28	18.0	40	2.5	26	3.80	108	108	
-29	22.0	40	2.5	24	4.90	96	96	
-30	27.0	40	2.5	21	5.80	88	88	
-31	33.0	41	2.5	20	6.50	83	83	
-32	39.0	42	2.5	19	7.90	75	75	3/
-33	47.0	44	2.5	16	9.30	69	69	
-34	56.0	44	2.5	15	11.0	64	64	
-35	68.0	45	2.5	13	12.0	61	61	
-36	82.0	45	2.5	11	13.0	59	59	
-37	100.0	40	2.5	10.5	16.8	51	51	


1/ Estimate only.
2/ Material for PIN's MIL-PRF-83446/34-01 through MIL-PRF-83446/34-25 is iron core-iron sleeve.
3/ Material for PIN's MIL-PRF-83446/34-26 through MIL-PRF-83446/34-37 is iron core-ferrite sleeve.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:12Z
Check the source to verify that this is the current version before use.

TABLE II. Electrical characteristics (final).

Inspection group	Allowable percent variation from the initial measurement			
Qualification Inspection:	Inductance	Q	Self-resonant Frequency	DC resistance
Group II	±10	-20	-15	±3 (+.001 ohm)
Group IV	±10	-20	-15	±3 (+.001 ohm)
Group V	±10	-20	-----	-----
Quality Conformance Inspection:				
Group C				
Subgroup II	±10	-20	-15	±3 (+.001 ohm)
Subgroup IV	±10	-20	-15	±3 (+.001 ohm)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:12Z
Check the source to verify that this is the current version before use.







SHORTING BAR LOCATION DETAIL

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Shorting bar material is brass.
4. The total fixture and residual inductance is approximately .049µH (for references only).

FIGURE 2. General test fixture, (TF-388)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:12Z
Check the source to verify that this is the current version before use.





ENLARGED CUT-AWAY OF CLAMP

Legend	
LTR	Description
A	G-10 base
B	Upper V-block hold-down clamp
C	Clamp screws
D	Upper V-block (body contact)
E	End cap contact retaining wall
F	End cap contact V-block (in contact with E)
G	Lower V-block (body contact)
H	G-10 insulators (separating G from F/E)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Metric equivalents are in parentheses.

FIGURE 3. Test fixture for insulation resistance, dielectric withstanding voltage and barometric pressure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:12Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Bond strength: Force 2 pounds.

Weight: 0.30 gram maximum.

Operating temperature range: -55°C to +105°C.

Temperature rise (at +90°C): +15°C.

Maximum operating temperature: +105°C.

Altitude: 70,000 feet.

Dielectric withstanding voltage: Method 301 of MIL-STD-202, test voltage 200 volts rms.

Barometric pressure: Method 105, test condition C, MIL-STD-202, (70,000 feet), test voltage 80 volts rms.


Electrical characteristics (initial): See table I.

Percent coupling: 3 percent maximum.

Electrical characteristics (final): See table II.

Test fixture: Tests shall be performed using test fixtures shown on figure 2 and 3, or equivalent.

Part or Identifying Number (PIN): The PIN shall be in the following form:



Custodians:
Army - CR
Navy - EC
Air Force - 11

Preparing activity:
DLA - CC

(Project 5950-1050)

Review activities:
Army - MI
Navy - AS, OS
Air Force - 19

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:12Z
Check the source to verify that this is the current version before use.