A-A-51141A
February 14, 1990
SUPERSEDING
A-A-51141
October 31, 1984

COMMERCIAL ITEM DESCRIPTION

PLATE, LAPPING

The General Services Administration has authorized the use of this commercial item description.

Abstract. This description covers lapping plates of the standard, heavy duty, commercial type, which are used in a production environment.

Classification. The lapping plates shall be of the sizes specified in table I. The size to be furnished shall be as specified.

TABLE I. Dimensions and weights.

Working surface dimensions (approximate)				Top thickness (not less than)	Height, Overall (not less than)	Weight (not less than)
Size	Width Inches	Length Inches	Diameter Inches	Inches	Inches	Pounds
11	3	5		3/4	3/4	2
12	8	8		1	1	15
13	8	12		3/4	2-1/2	38
14	12	12		3/4	4	58
15	12	18		3/4	4	82
16	14	18		3/4	5	120
17	16	22		3/4	4	135
18	18	18		3/4	5	140
19	18	24		3/4	4	180
20	24	24		3/4	4	255
21	24	36		3/4	4	320
22	36	36		3/4	8	900
23			18	7/8	4	130
24			24	7/8	4	215

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: Defense Industrial Plant Equipment Center, ATTN: DIPEC-SSG, 2163 Airways Blvd., Memphis, TN 38114-5051.

AMSC N/A FSC 3460

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

SALIENT CHARACTERISTICS

1. Design. The lapping plate shall be new and of the manufacturer's commercial design in effect on the date of the solicitation. The lapping plate shall meet the requirements specified herein and conform to current industrial practices. The lapping plate shall have three point bearing support or other suitable means to ensure maximum stability. Lapping plates sizes 8 by 8 inches and smaller shall be a solid construction. Sizes greater than 8 by 8 inches shall have diagonal cross ribbing or other means to ensure maximum rigidity.

2. Materials. Materials used in the manufacture of the lapping plates shall be either steel, iron, or a combination thereof, or fine grain grey iron castings.

3. Castings. All castings shall be of uniform quality, free from defects, scale, and mismatching. In no event shall such processes as welding, peening, or filling with cold solders or metallic pastes be used for reclaiming any casting.

4. Grooves. The working surface shall have grooves 1/16 inch wide by 1/16 inch deep, and 1/2 inch apart in either a square or diamond pattern.

5. Accuracy. The accuracy of the working surface shall be such that no two points on that surface vary with each other by more than 0.0002 inch per linear foot of space separating the two points.

6. Hardness. The working surface shall have a Brinell hardness of not less than 170, when tested in accordance with ASTM-E-10.

7. Surface roughness. The maximum roughness average of the working surface shall be not more than 32 microinches (uin), and the sides of the top shall be not more than 125 uin, when tested in accordance with ANSI B46.1.

8. Painting. All surfaces not machined shall be painted in accordance with the manufacturer's standard practice and color.

9. Marking. The lapping plate shall be marked in a permanent manner with the manufacturer's name or trademark.

10. Covers. The lapping plate shall be furnished with a properly fitted wood or other adequate material cover to protect the working surfaces and edges during shipment and storage.

11. Workmanship. Workmanship of the lapping plate shall be of a quality equal to that of comparable products furnished to the commercial market.

Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this commercial item description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this commercial item description are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request shall be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials.

Environmental protection. During the manufacture of the lapping plate, materials hazardous to the ecological system as prohibited by the Federal, state, or local statutes in effect on the date of the contract shall not be used or emitted.

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection, examination, and test requirements specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections, examinations, or tests set forth in this description where such inspections, examinations, and tests are deemed necessary to assure supplies and services conform to prescribed requirements.

Responsibility for compliance. All items shall meet all requirements of salient characteristics paragraphs. The inspection set forth in this description shall become a part of the contractors' overall inspection system or quality program. The absence of any inspection requirements in the description shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

Sampling inspection. As a minimum sampling inspection, the supplier shall randomly select the number of samples in table II that is applicable to the quantity of items being purchased. Each sample item shall be inspected to determine conformance with the examination, the test, and the inspection. Should any of the sample items fail to meet either the examination or inspection below, the entire lot shall be considered defective and unsuitable for acceptance. A lot is defined as all items presented at one time for acceptance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

TABLE II. Sampling plan.

Quantity of items being purchased	Sample size	Quantity of items being purchased	Sample size
2 to 8	2	151 to 280	32
9 to 15	3	281 to 500	50
16 to 25	5	501 to 1,200	80
26 to 50	8	1,201 to 3,200	125
51 to 90	13	3,201 to 10,000	200
91 to 150	20		

Examination. Each lapping plate submitted for sample inspection shall be visually examined to determine conformance with all requirements of this description.

Preservation, packaging, packing, and marking. Preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Cross-reference of classification changes. Classification changes from the previous issue of this commercial item description are as listed in table III.

TABLE III. Cross-reference sizes of lapping plates.

A-A-51141	A-A-51141A
Size 1	(Deleted)
Size 2	(Deleted)
Size 3	(Deleted)
Size 4	(Deleted)
Size 5	(Deleted)
Size 6	(Deleted)
Size 7	(Deleted)
Size 8	(Deleted)
Size 9	(Deleted)
Size 10	(Deleted)
	Size 11 (New Size)
	Size 12 (New Size)
	Size 13 (New Size)
	Size 14 (New Size)
	Size 15 (New Size)
	Size 16 (New Size)
	Size 17 (New Size)
	Size 18 (New Size)
	Size 19 (New Size)
	Size 20 (New Size)
	Size 21 (New Size)
	Size 22 (New Size)
	Size 23 (New Size)
	Size 24 (New Size)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

CID based part identification number. The following part identification numbering procedure is for Government purposes and does not constitute a requirement for the contractor. Where applicable Arabic numbers shall be substituted for Roman numerals.

A-A-51141 XX

Size

CID number

Notes.

Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

a. Title, number, and date of this commercial item description.

b. Size and quantity required.

c. Other requirements.

Federal Standard FED-STD-376 is available from the Naval Publications and Form Center, 5801 Tabor Avenue, Philadelphia, PA 19120-5099.

ANSI B46.1 is available from the American National Standards Institute, 1430 Broadway, New York, NY 10018-3363.

ASTM E-10 is available from the American Society of Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.

MILITARY INTEREST:

Custodians

Army - AL
Navy - SH
Air Force - 99

Review

Air Force - 84
DLA - GS

CIVIL AGENCY COORDINATION ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

DLA - IP

Project 3460-0138

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE *(YYMMDD)*
3. DOCUMENT TITLE		
4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*		
5. REASON FOR RECOMMENDATION		

6. SUBMITTER		
a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE *(Include Area Code)* (1) Commercial (2) AUTOVON *(If applicable)*	7. DATE SUBMITTED *(YYMMDD)*

8. PREPARING ACTIVITY	
a. NAME	b. TELEPHONE *(Include Area Code)* (1) Commercial (2) AUTOVON
c. ADDRESS *(Include Zip Code)*	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.