MIL-C-63092 (PA)
28 July 1976

MILITARY SPECIFICATION

CARTRIDGE, 40MM, RED STAR, PARACHUTE, M662

METAL PARTS

AND

LOADING, ASSEMBLING AND PACKING

This specification is approved for use by Picatinny Arsenal, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the metal parts and loading, assembling and packing for one type of cartridge designated as Cartridge, 40MM, Red Star, Parachute, M662.

2. APPLICABLE DOCUMENTS

2.1 Issues of Documents - The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-223	- Black Powder
MIL-C-5541	- Chemical Films and Chemical Film Materials for Aluminum and Aluminum Alloys
MIL-P-22264	- Powders, Ignition, Gasless

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Picatinny Arsenal, Dover, NJ 07801 by using the self addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC: 1310

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:25Z
Check the source to verify that this is the current version before use.

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests for

MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

MIL-STD-1234 - Pyrotechnics Sampling, Inspection and Testing

DRAWINGS

PICATINNY ARSENAL

PRODUCT AND PACKING DRAWINGS

9255145 - Cartridge, 40MM, Red Star, Parachute, M662

9209204 - Box, Ammo, Metal for Cartridge, 40MM, White Star, Cluster or Smoke Canopy or Parachute

9209205 - Box, Wirebound, Packing, Ammunition for Cartridge, 40MM, White Star, Cluster or Smoke Canopy or Parachute

INSPECTION EQUIPMENT DRAWINGS

9202770 - Chamber Gage

9202783 - Alignment Check

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

8827895	- Limit Check
9201136	- Tunnel for Light Intensity Measurement
9201268	- Procedure for Light Output Measurement
9201390	- Photocell Checkout Procedure
9200964	- Photometer Head with Cell
9200965	- Tube, Sight
9200966	- Cover
9200967	- Bracket, Tube
9200968	- Gasket, Rear
9200969	- Gasket
9200970	- Cabinet
9200971	- Hood
9200972	- Brakcet
9200973	- Holder
9200974	- Spring
9201392	- Color Value
9247071	- Photocell

2.2 Other Publications - The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:25Z
Check the source to verify that this is the current version before use.

CODE OF FEDERAL REGULATIONS

TITLE 49 - Transportation, Parts 100-199

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. Orders should specify "49 CFR 100-199 (latest revision)").

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM B 117-73 - Standard Method of Salt Spray (Fog) Testing

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103)

3. REQUIREMENTS

3.1 Material - Materials shall be in accordance with the applicable drawings and specifications.

3.2 Cartridge - The cartridge shall comply with all requirements specified on Drawing (Dwg.) 9255145, all associated drawings, and with all requirements specified in applicable specifications.

3.3 Transportation Vibration - The cartridge shall comply with the following requirements:

3.3.1 The cartridge shall be safe to transport following this test (See 6.6).

3.3.2 There shall be no evidence of external damage to the cartridge that will affect the intended function (See 6.7).

3.4 Functioning - The cartridge shall comply with the following requirements;

3.4.1 Altitude - The projectile shall function at an average altitude of 600 ± 100 feet.

3.4.2 Burning of Illuminate Assembly - The illuminant assembly shall burn in the air for 30 seconds min. while suspended from the parachute.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

3.4.3 Parachute - The parachute shall not separate from the illuminant assembly at ejection or delay opening from time of ejection for more than 5 seconds.

3.4.4 Firing - No projectile shall stick in the gun bore.

3.4.5 Hot Temperature (160 degrees F. plus or minus 5 degrees F.) - The cartridge shall comply with the requirements of 3.4.1, 3.4.2, 3.4.3 and 3.4.4.

3.4.6 Ambient Temperature (70 degrees F. plus or minus 5 degrees F.) - The cartridge shall comply with the requirements of 3.4.1, 3.4.2, 3.4.3 and 3.4.4.

3.4.7 Cold Temperature (-65 degrees F. plus or minus 5 degrees F.) - The cartridge shall comply with the requirements of 3.4.1, 3.4.2, 3.4.3 and 3.4.4.

3.5 Workmanship - All parts and assemblies shall be fabricated, loaded and assembled in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous; however, a few light scratches not exposing base material may be permitted. All required marking and stamping shall be neat and sharply defined.

3.6 First Article Inspection - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection and Standard Quality Assurance Provisions - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of Inspections - The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:25Z
Check the source to verify that this is the current version before use.

4.3 First Article Inspection -

4.3.1 Submission - The contractor shall submit a first article as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing	Quantity
Body	9243900	25 (5 painted)
Ogive	9251920	25
Tube	9244311	25
Delay Carrier	9243886	25 (5 for Salt Spray)
Plug Anchors	9243907	25
Illuminant Loading Assembly	9252412	25
Cartridge	9255145	465 (440 to a Government Proving Ground for Ballistic Testing)
Delay Loading Assembly	9243885	25
Parachute Assembly	9243906	25

4.3.2 Inspections to be Performed - See MIL-A-48078 and Table I herein.

4.3.3 Rejection - See MIL-A-48078 and the following:

4.3.3.1 Proving Ground Tests -

a. Any critical defect occurs in any phase (see Table III).
b. Average altitude of the total sample fails the applicable requirement (see Table III and 3.4.1).
c. A total of eight (8) or more in the hot phase fail any of the following:
(1) Parachute failure (See 3.4.3).
(2) Item fails to function (See Table III).
(3) No illumination (See Table III).
Burning time should be recorded for informational purposes (average).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:25Z
Check the source to verify that this is the current version before use.

d. A total of twenty-two (22) or more in the ambient phase fail any of the following:

(1) Burning time incorrect (See 3.4.2) (Average).
(2) Parachute failure (See 3.4.3).
(3) Item fails to function (See Table III).

e. A total of eight (8) or more in the cold phase fail any of the following:

(1) Parachute failure (See 3.4.3).
(2) Item fails to function (See Table III).
(3) No illumination (See Table III).

Burning time should be recorded for informational purposes (Average).

f. Two (2) or more of the total sample are below an altitude of 350 ft (See Table III).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:25Z
Check the source to verify that this is the current version before use.

TABLE 1 - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C- 63092 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
	Cartridge and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Body (Dwg. 9243900)				
	Prior to painting				
	Examination for defects	20		3.2	4.4.2.1
	Salt Spray	5		3.2	4.5.3
	After painting				
	Examination for defects	5		3.2	4.4.2.2
	Ogive (Dwg. 9251920)				
	Examination for defects	25		3.2	4.4.2.3
	Tube (Dwg. 9244311)				
	Examination for defects	25		3.2	4.4.2.4
	Delay Carrier (Dwg. 9243886)				
	Examination for defects	20		3.2	4.4.2.5
	Salt Spray	5			4.5.3
	Plug Anchor (Dwg.9243907)				
	Examination for defects	25		3.2	4.4.2.6
	Illuminant Assembly (Dwg. 9252412)				
	Examination for defects	25		3.2	4.4.2.7
	Candle Power	25		3.2	4.5.4

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T04:25Z
Check the source to verify that this is the current version before use.

TABLE 1 - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63092 (PA)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	Cartridge and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Parachute Assembly (Dwg. 9243906)				
	Examination for defects	25		3.2	4.4.2.8
	Delay Loading Assembly (Dwg. 9243885)				
	Burn time	25		3.2	4.5.5
	Cartridge (Dwg. (9255145)				
	Examination for defects	25		3.2	4.4.2.12
	Pull test of projectile	25		3.2	4.5.6
	*Transportation-vibration	440		3.2	4.5.7
	*Air pressure	440		3.2	4.5.8
	Functioning				
	Hot	80		3.2	4.5.9.1
	Ambient	280		3.2	4.5.9.2
	Cold	80		3.2	4.5.9.3

NOTES: *Prior to submission of the 440 samples to a Gov't proving ground for functioning tests, the samples shall be inspected at the contractors plant for these tests.

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection -

4.4.1 Inspection Lot Formation - Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each inspection lot shall contain:

a. Projectile metal parts from one interfix lot number from one manufacturer.
b. Delay composition from not more than one lot number.
c. Igniter composition from not more than one lot number.
d. Black powder from not more than one lot number.
e. Illuminant composition produced by one manufacturer under one continuous set of operating conditions and which consist of one or more batches that have been subjected to the same unit chemical or physical mixing process intended to make the final product homogeneous.
f. Cartridge case loaded assemblies from one interfix lot number from one manufacturer.
g. Illuminant assemblies from one interfix lot number from one manufacturer.
h. Ignition composition from not more than one lot number.
i. Delay Assemblies from one interfix lot number from one manufacturer.

4.4.2 Examination - See MIL-A-48078.

a. Sampling Plans - Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:25Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63092 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.1	Body, prior to Painting				9243900-1
					NEXT HIGHER ASSEMBLY
					9252411
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Largest outside diameter		0.40%	3.2	Gage
102	Concentricity of largest outside diameter with second largest outside diameter		0.40%	3.2	Gage
103	Second largest outside diameter		0.40%	3.2	Gage
104	Concentricity of second largest outside diameter with smallest inside diameter		0.40%	3.2	Gage
105	Concentricity of largest inside diameter with smallest inside diameter		0.40%	3.2	Gage
106	Salt Spray	*	*	3.2	4.5.3
107	Pitch diameter of thread		0.40%	3.2	Gage
108	Minor diameter of thread, max.		0.40%	3.2	Gage
109	Perpendicularity of open end with smallest inside diameter		0.40%	3.2	Gage
110	Metal defective		0.40%	3.5 & 6.9	Visual
Minor					
201	Smallest outside diameter		0.65%	3.2	Gage
202	Groove diameter		0.65%	3.2	Gage
203	Width of rotating bands		0.65%	3.2	Gage
204	Total length		0.65%	3.2	Gage
205	Width of flange		0.65%	3.2	Gage
206	Distance to rotating band		0.65%	3.2	Gage

NOTES: * Sampling and rejection shall be in accordance with MIL-C-5541.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63092 (PA)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.1	Body, prior to Painting				9243900
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
207	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63092 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Body after Painting		9243900
			NEXT HIGHER ASSEMBLY 9252411

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Second largest outside diameter		0.40%	3.2	Gage
Minor 201	Color incorrect		0.65%	3.2	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Ogive		9251920
			NEXT HIGHER ASSEMBLY
			9252411

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Incorrect letter	(See 4.5.1)	100%	3.2	Visual
Major					
101	Large outside diameter		0.40%	3.2	Gage
102	Concentricity of large outside diameter with third largest outside diameter		0.40%	3.2	Gage
103	Second largest outside diameter		0.40%	3.2	Gage
104	Inside diameter		0.40%	3.2	Gage
Minor					
201	Total length		0.65%	3.2	Gage
202	Width of slots		0.65%	3.2	Gage
203	Diameter of groove		0.65%	3.2	Gage
204	Width of groove		0.65%	3.2	Gage
205	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T04:25Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63092 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9244311
4.4.2.4	Tube				NEXT HIGHER ASSEMBLY 9252412
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Wall thickness		0.40%	3.2	Gage
103	Perpendicularity of ends		0.40%	3.2	Gage
Minor					
201	Total length		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63092 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Delay Carrier		9243886
			NEXT HIGHER ASSEMBLY 9243885

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Salt Spray	*	*	3.2	4.5.3
102	Pitch diameter of thread		0.40%	3.2	Gage
103	Major diameter of thread		0.40%	3.2	Gage
104	Small inside diameter		0.40%	3.2	Gage
105	Concentricity of small inside diameter with large inside diameter		0.40%	3.2	Gage
106	Large inside diameter		0.40%	3.2	Gage
Minor					
201	Length to flange		0.65%	3.2	Gage
202	Concentricity of body diameter with large inside diameter		0.65%	3.2	Gage
203	Diameter of thread undercut		0.65%	3.2	Gage
204	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES: *Sampling and rejection shall be in accordance with MIL-C-5541.

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63092 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9243907
4.4.2.6	Plug Anchor				NEXT HIGHER ASSEMBLY 9252412
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Largest outside diameter		0.40%	3.2	Gage
102	Flange thickness		0.40%	3.2	Gage
103	Second largest outside diameter		0.40%	3.2	Gage
Minor					
201	Total length		0.65%	3.2	Gage
202	Holes missing		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.5	Visual
204	Width of slot incorrect		0.65%	3.2	Gage
205	Depth of slot incorrect		0.65%	3.2	Gage

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63092 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.7	Illuminant Loading Assembly		9252412
			NEXT HIGHER ASSEMBLY 9252411

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length from shoulder to end		0.40%	3.2	Gage
102	Diameter, max.		0.40%	3.2	Gage
103	Anchor plug insecure		0.40%	3.2	Manual-Visual
104	Assembly damaged to extent that function may be impaired		0.40%	3.2	Visual
105	Candle power			3.2	4.4.3.2, 4.4.3.3 and 4.5.4
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63092 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Parachute Assembly				9243906
					NEXT HIGHER ASSEMBLY 9252411
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Tears or holes in parachute		0.40%	3.2	Visual
102	Shroud lines not attached to parachute		0.40%	3.2	Visual
103	Shroud lines tangled		0.40%	3.2	Visual
104	Coupling not secure to shroud lines		0.40%	3.2	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63092 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Delay Assembly				9243885
					NEXT HIGHER ASSEMBLY
					9252411
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Static burn time	32	1.5%	3.2	9201136 9200973 9201268 9200974 9201390 9201392 9200964 9247071 9200965 4.5.5 9200966 9200967 9200968 9200969 9200970 9200971 9200972

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63092 PA)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Projectile assembly, prior to assembling illuminant assembly	1 OF 1	9252411
			NEXT HIGHER ASSEMBLY 9255145

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Coupling of illuminant assembly not secure to chain		0.40%	3.2	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63092 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.11	Projectile assembly, prior to assembling ogive		9252411
			NEXT HIGHER ASSEMBLY
			9255145

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Parachute missing		0.40%	3.2	Visual
102	O-ring missing		0.40%	3.2	Visual
103	Spring pin missing		0.40%	3.2	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63092 PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.12	Projectile Assembly		9252411
			NEXT HIGHER ASSEMBLY 9255145

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Gap present between delay assembly and body		0.40%	3.2	Visual
102	Color incorrect		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63092 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	Cartridge				9255145
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Chamber gage failure		100%	3.2	9202770 9202783 8827895
2	Incorrect ogive		100%	3.2	Visual
3	Marking incorrect		100%	3.2	Visual
Major					
101	Marking unidentifiable		0.40%	3.2	Visual
102	Pull test	50	2.50%	3.2	4.5.6
103	Transportation-vibration			3.3	4.4.3.5, 4.4.3.8 and 4.5.7
104	Air pressure			3.2	4.4.3.4, 4.4.3.6, 4.4.3.9 and 4.5.8
105	Functioning			3.4	4.4.3.7, 4.4.3.10 and 4.5.9
Minor					
201	Total length		0.65%	3.2	Gage

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T04:25Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63092 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.14	Unsealed Metal Box		9209204
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Incorrect number of cartridges		0.40%	3.2	Visual
102	Desiccant bags missing		0.40%	3.2	Visual
103	Rubber gasket damaged or improperly assembled		0.40%	3.2	Visual
Minor					
201	Fillers missing		0.65%	3.2	Visual
202	Tube missing		0.65%	3.2	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63092 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.15	Sealed Metal Box		9209204
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Air pressure	*	*	3.2	4.5.10
Minor					
201	Marking misleading or unidentifiable		0.65%	3.2	Visual
202	Contents loose		0.65%	3.2	Manual

NOTES: *One (1) packed, sealed box shall be selected from each twenty (20) boxes packed. If one (1) box fails, the quantity represented by the sample shall be rejected.

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63092 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.16	Sealed Wooden Packing Box				9209205
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Minor					
201	Marking misleading or unidentifiable		0.65%	3.2	Visual
202	Contents loose		0.65%	3.2	Manual
203	ICC nomenclature missing		0.65%	3.2	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

27

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

4.4.3 Testing -

4.4.3.1 Moisture Content (See Table 1), Major -

TABLE I

Material	Drawing
Delay Composition	9243885
Igniter Composition	9243885
Ignition Composition	9252412
Black Powder	9252412
Illuminant Composition	9252412

The contractor shall provide adequate controls to insure compliance with the requirements and shall test for verification at least one (1) sample of each material from each eight hour's production of cartridges. Composite samples shall not be used. If the moisture content of a sample exceeds the requirement and loading has not begun, that quantity of material represented by the sample shall be rejected. If assemblies have been loaded with material containing excessive moisture, the remaining material that is represented by the sample together with all cartridges loaded with the non-forming material shall be rejected.

4.4.3.2 Candle Power of Illuminant Assembly - Beginning with the first lot produced and continuing until three (3) acceptable lots (lots not accepted by disposition) have been accepted, eighty (80) assemblies shall be selected from each lot for this test. If three (3) or more assemblies fail to comply with the requirement specified on the applicable drawing, the lot shall be rejected.

4.4.3.3 Candle Power of Illuminant Assembly, Regular Production - After three (3) acceptable lots have met the criteria of 4.4.3.2, the Government Inspector shall select thirty-two (32) assemblies from each lot for this test. If two (2) or more assemblies fail to comply with the requirement specified on the applicable drawing, the lot shall be rejected.

At the start of production, or when there has been a lapse of 90 days, or when a major design change occurs as determined by the Government inspector, the criteria of 4.4.3.2 shall apply.

4.4.3.4 Air Pressure - This test shall be conducted 100 percent. Any cartridge which fails to comply with the requirement specified on the applicable drawing shall be classified defective and removed from the lot.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:25Z
Check the source to verify that this is the current version before use.

4.4.3.5 Transportation-Vibration - After completion of the 100 percent air pressure test and beginning with the first lot produced and continuing until three (3) acceptable lots (lots not accepted by disposition) have complied with the acceptance criteria specified in TABLE II, two-hundred and sixty-four (264) cartridges shall be selected from each lot, packed in their regular shipping containers and subjected to this test. The cartridges shall be observed and examined visually without disassembly for any evidence of failure to comply with the requirements of TABLE II.

TABLE II

Defect	Drawing
Cartridge not safe to transport following test	Critical
Cartridge damaged after test	Major

The lot shall be rejected if any defect as classified in TABLE II occurs.

4.4.3.6 Air Pressure - After completion of the transportation-vibration test, the two-hundred and sixty-four (264) samples from each lot shall be subjected to this test. If nine (9) or more cartridges fail to comply with the requirement specified on the applicable drawing, the lot shall be rejected. Cartridges which fail this test shall be discarded and replaced with units which have been successfully subjected to transportation-vibration test prior to subsequent testing.

4.4.3.7 Functioning - After completion of the air pressure test and beginning with the first lot produced and continuing until three (3) acceptable lots (lots not accepted by disposition) have complied with the criteria of TABLE III, the two-hundred and sixty-four (264) samples from each lot shall be packed and shipped to a Government proving ground and tested as follows:

4.4.3.7.1 Hot - Forty-four (44) samples shall be subjected to this test.

4.4.3.7.2 Ambient - One-hundred and seventy-six (176) samples shall be subjected to this test.

4.4.3.7.3 Cold - Forty-four (44) samples shall be subjected to this test.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:25Z
Check the source to verify that this is the currentversion before use.

4.4.3.7.4 Rejection - The lot shall be rejected if:

a. Any critical defects occur in any phase (see Table III).
b. Average altitude of the total sample fails the applicable requirement (see Table III).
c. A total of six (6) or more in the hot phase fail any of the following:
(1) Parachute failure (see 3.4.3)
(2) Item fails to function (see Table III).
Burning time should be recorded for informational purposes. (Average).
d. A total of fifteen (15) or more in the ambient phase fail any of the following:
(1) Burning time incorrect (see 3.4.2). (Average)
(2) Parachute failure (see 3.4.3).
(3) Item fails to function (see Table III).
e. A total of six (6) or more in the cold phase fail any of the following:
(1) Parachute failure (see 3.4.3).
(2) Item fails to function (see Table III).
Burning time should be recorded for informational purposes. (Average)
f. Two (2) or more of the total samples have an altitude less than 350 ft (see Table III).

TABLE III

Defect	Classification
Incorrect color	Critical
Burst or ejects	Critical
Illuminant within 50 feet of the launcher	
Any projectile assembly sticks in the gun bore	Critical
Burning time incorrect (see 3.4.2)	Major
The first emission of light shall be at an average altitude of 600 ± 100 ft	Major
Parachute failure (see 3.4.3)	Major
Altitude less than 350 ft	Major
Item fails to function	Major

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:25Z
Check the source to verify that this is the currentversion before use.

4.4.3.8 Transportation-Vibration, Regular Production - After three (3) acceptable lots have complied with 4.4.3.5 and 4.4.3.7, one-hundred and thirty-two (132) of the samples subjected to the 100% air pressure test shall be selected from each lot, packed in their regular shipping containers and subjected to this test. The lot shall be rejected if any defect as classified in TABLE II occurs.

4.4.3.9 Air Pressure, Regular Production - After completion of the transportation-vibration test, the one-hundred and thirty-two (132) samples shall be removed from their shipping containers and subjected to this test. If eight (8) or more samples fail to comply with the requirement specified on the applicable drawing, the lot shall be rejected. Cartridges which fail this test shall be discarded and replaced with units which have been successfully subjected to transportation-vibration test prior to subsequent testing.

4.4.3.10 Functioning, Regular Production - After three (3) acceptable lots have complied with 4.4.3.7, the one-hundred and thirty-two (132) samples subjected to the air pressure test shall be packed and shipped to a Government proving ground and tested as follows:

4.4.3.10.1 Hot - Twenty-six (26) samples shall be subjected to this test.

4.4.3.10.2 Ambient - Eighty (80) samples shall be subjected to this test.

4.4.3.10.3 Cold - Twenty-six (26) samples shall be subjected to this test.

4.4.3.10.4 Rejection - The lot shall be rejected if:

a. Any critical defect occurs in any phase (see Table III).
b. Average altitude of the total sample fails the applicable requirement (see Table III).
c. A total of four (4) or more in the hot phase fail any of the following:
(1) Parachute failure (see 3.4.3).
(2) Item fails to function (see Table III).
Burning time should be recorded for informational purposes. (Average).
d. A total of eight (8) or more in the ambient phase fail any of the following:

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:25Z
Check the source to verify that this is the current version before use.

(1) Burning time incorrect (see 3.4.2). (Average)
(2) Parachute failure (see 3.4.3).
(3) Item fails to function (see Table III).

e. A total of four (4) or more in the cold phase fail any of the following:

(1) Parachute failure (see 3.4.3).
(2) Item fails to function (see Table III).

Burning time should be recorded for informational purposes. (Average).

f. Two (2) or more of the total samples have an altitude less than 350 ft (see Table III).

If any lot fails, the consecutive lots thereafter shall revert to the critieria of 4.4.3.5.

4.4.3.11 Suitability Test Plan (Information Test Only) - Beginning with the first lot produced by each producer and continuing until that producer has submitted three (3) acceptable lots (lots not accepted by disposition) that are accepted in accordance with 4.4.3.7.1, 4.4.3.7.2 and 4.4.3.7.3, and extra sample of eighty-eight (88) rounds shall be selected from each lot and preconditioned and tested as follows:

a. The eighty-eight (88) rounds shall be packaged in their regular shipping containers and subjected to transportation vibration environmental in accordance with MIL-STD-331, Test No. 104.

b. After transportation vibration, the rounds shall be unpacked and subjected to the JAN temperature and humidity cycle (14 days) specified in MIL-STD-331, Test No. 105.

c. After temperature and humidity cycle, the rounds shall be temperature conditioned and fired as follows:

30 rounds + 165 degrees F. $\pm$ 5 degrees F.
28 rounds ambient (between $\mp$ 40 and + 110 degrees F.)
30 rounds - 65 degrees F. $\pm$ 5 degrees F.

d. Fire the rounds in accordance with paragraph 4.5.9 and with TECOM Material Test Procedure, TECP 700-700 Volume 4. Test results, failure analysis reports and other information as requested shall be forwarded to Picatinny Arsenal, ATTN: SARPA-QA-A-S.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:25Z
Check the source to verify that this is the current version before use.

4.4.4 Inspection Equipment - The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method column in the tables starting with Paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test Methods and Procedures -

4.5.1 Dimensional Control of Molded or Plastic Parts - In place of the normal sampling and inspections associated with the Classification of Defects, and after a curing time (3) parts (as molded) from each cavity shall be fully inspection dimensionally to qualify a new or reworked cavity for use in production. The molded parts shall carry the individual cavity identification. As a control of each cavity during production, theabove quantity of parts from each cavity shall be inspected for at least the defects listed in paragraphs 4.4.2.1 and 4.4.2.5 after continuous production of each 5,000 parts or at the end of each week, whichever occurs first. Of the three (3) samples, one (1) sample shall be the last part produced. If any defective parts are found during qualification of the cavity, the cavity producing the defective part will not be used in production. If any defective parts are found when inspection is performed for the control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for inspection for each separate type of defect according to MIL-STD-105, using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. All cavities removed from production because of some fault may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request. Contractor designs of gages and test equipment required to perform the inspections listed herein shall be forwarded to Commander, Picatinny Arsenal, Dover, New Jersey 07801, Attn: SARPA-QA-T, for approval prior to manufacture of equipment. The noted sub-paragraphs identify those items and minimum inspections subject to the requirements of this paragraph.

NOTE 1: In establishing a cure time, dimensionally ccheck ten (10) parts from each cavity at periodic intervals (e.g. every 30, 60, etc. mins) until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:25Z
Check the source to verify that this is the currentversion before use.

dimensional stability is attained. The inspection data in determining the curing time shall be sent to Picatinny Arsenal, Dover New Jersey 07801, Attn: SARPA-QA-A-S. If there is a change in material, or in the cycle time, or if a cavity is reworked, or a new cavity is used, a new curing time shall be established and approved.

4.5.2 Moisture Content -

4.5.2.1 Delay Composition - The moisture content of the delay composition at the time and place of loading shall be determined in accordance with Method 102.1 of MIL-STD-1234.

4.5.2.2 Black Powder - The moisture content of the black powder at the time and place of loading shall be determined in accordance with 4.4.3 of MIL-P-223.

4.5.2.3 Ignition Composition - The moisture content of the ignition composition at the time and place of loading shall be determined in accordance with Method 101.4 of MIL-STD-1234 using methyl alcohol as an extraction solvent.

4.5.2.4 Illuminant Composition - The Karl Fischer method as stated in Standard MIL-STD-1234, Method 101.2 up to paragraph 5.3 shall be used. A fifty-gram sample plus or minus 0.1 gram shall be added to a 500 milliliter (ml) volumetric flash containing approximately 300 to 400 ml. methanol and 25 grams of dry sodium nitrate. The flask shall be stoppered and the contents swirled cautiously for several minutes until the material is thoroughly dispersed. The sample shall be allowed to remain in contact with the methanol for approximately two hours. Then the 500 ml. volumetric flash shall be filled up to the 500 ml. mark with methanol and swirled again. A blank without the sample shall be put through the same procedure. After the sample has settled, a 50 ml. aliquot of the clear supernatant liquid shall be withdrawn and immediately transferred to the standard titration vessel containing approximately 100 ml. of methanol which has just been titrated to the preliminary end point as described in Standard MIL-STD-1234, Method 101.2, paragraph 5.1. The final end point shall be reached in 3.5 minutes in the manner described in Standard MIL-STD-1234, Method 101.2, paragraph 5.4. A 50 ml. aliquot of the blank shall be titrated in the same manner. The water content shall be calculated as follows:

$$\% \text{ Water} = \frac{100F\,[(VR-S) - (V'R-S)]}{W}$$

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

Where:

F = grams of water per ml. of standard water in methanol solution

V = ml of Karl Fischer reagent added to the sample

V' = ml of Karl Fischer reagent added to the blank

R = ml of standard water in methanol solution per ml. of Karl Fischer reagent

S - ml of standard water in methanol solution for titration of sample

S' = ml of standard water in methanol solution with back titration of blank

W = weight of sample in grams

4.5.2.5 Igniter Composition - The moisture content of the igniter composition at the time and place of loading shall be determined in accordance with 4.6.4 of MIL-P-22264.

4.5.3 Salt Spray - This test shall be conducted in accordance with ASTM B 117-73.

4.5.4 Candle Power of Illuminant Assembly - This test shall be conducted in accordance with equipment drawings 9201136, 9201268, 9201390, 9200965, 9200966, 9200967, 9200968, 9200969, 9200970, 9200971, 9200972, 9200973, 9200974, 9201392, and 9247071.

4.5.5 Static Burn Time of Delay Assembly - This test shall be conducted in accordance with the equipment specified in 4.4.2.9.

4.5.6 Pull Test of Cartridge - The cartridge shall be placed in an approved fixture and the axial force specified on the applicable drawing shall be applied. Cartridge shall be pulled until total separation occurs and data shall be recorded. This test is a destructive test. Parts so tested shall not be returned to the lot.

4.5.7 Transportation Vibration - The cartridges shall be packaged and packed in accordance with dwgs. 9209204 and 9209205 and tested in accordance with Test No. 104 of MIL-STD-331, except that each box shall be vibrated at the specified amplitudes for four (4) hours in each of three (3) different positions (i.e., box positioned so that the cartridges are vertical with case end down, box positioned so that the cartridges are horizontal, and box positioned so that the cartridges are vertical with case end up. After the test, the box packing and the cartridges shall be examined to determine compliance with the requirements. Cartridges shall be used for subsequent tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

4.5.8 Air Pressure - The cartridge shall be placed in an approved fixture and a measured quantity of air shall be applied to produce the required air pressure. Cartridges shall be used for subsequent testing.

4.5.9 Functioning - The following tests shall be performed at a Government-owned proving ground:

4.5.9.1 Hot Temperature (160 degrees F. plus or minus 5 degrees F.) - The cartridges shall be packed in their regular shipping containers and conditioned for a minimum of 16 hours at a temperature of 160 degrees F. plus or minus 5 degrees F. The cartridge shall be taken from the conditioning chamber, removed from the packing container, and fired from an approved launcher placed on an approved mount at 90 degrees quadrant within approximately 2 minutes. Observation shall be made for proper functioning and the requirements of 3.4.5.

4.5.9.2 Ambient Temperature (70 degrees F. plus or minus 5 degrees F.) - The cartridges shall be pakced in their regular shipping containers and conditioned for a minimum of 16 hours at a temperature of 70 degrees F. plus or minus 5 degrees F. The cartridge shall be taken from the conditioning chamber, removed from the packing container, and fired from an approved launcher placed on an approved mount at 90 degrees quadrant within approximately 2 minutes. Observation shall be made for proper functioning and the requirements of 3.4.6.

4.5.9.3 Cold Temperature (-65 degrees F. plus or minus 5 degrees F.) - The cartridges shall be packed in their regular shipping containers and conditioned for a minimum of 16 hours at a temperature of -65 degrees F. plus or minus 5 degrees F. The cartridge shall be taken from the conditioning chamber, removed from the packing container, and fired from an approved launcher placed on an approved mount at 90 degrees quadrant within approximately 2 minutes. Observation shall be made for proper functioning and the requirements of 3.4.7.

4.5.10 Air Pressure of Packed Sealed Metal Box - The sealed metal box shall be placed in an approved fixture and a measured quantity of air shall be applied to produce the required air pressure. Observation shall be made for leakage. This test is a non-destructive test. Boxes so tested may be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:25Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging -

5.1.1 Level A - The cartridges shall be preserved and packaged in accordance with dwg. 9209204.

5.1.2 Level C - The metal parts shall be preserved and packaged in accordance with MIL-STD-1169.

5.2 Packing -

5.2.1 Level A - The cartridges, preserved and packaged as specified in 5.1.1, shall be packed in accordance with dwg. 9209205.

5.2.2 Level C - The metal parts, preserved and packaged as specified in 5.1.1, shall be packed for shipment in accordance with MIL-STD-1169.

5.3 Marking - Marking shall be in accordance with Dwgs. 9209204, 9209205, MIL-STD-1169 and Code of Federal Regulations, Title 49, Parts 100-199.

5.4 Shipping - When shipments from more than one lot are shipped as a carload, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended Use - This specification covers the metal parts and loading, assembling and packing for Cartridge, 40MM, Red Star Parachute, M662.

6.2 Ordering Data - See MIL-A-48078.

6.3 Submission of Inspection Equipment Designs for Approval - See MIL-A-48078. Submit equipment designs as required to Commander, Attn: SARPA-QA-T, Picatinny Arsenal, Dover, NJ 07801.

6.4 Submission of Results of Contractor-conducted Examinations and Tests - Data shall be submitted in accordance with data item DI-R-1721 on the DD Form 1423 for the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

6.5 Submission of Test Data - In addition to the normal distribution of records, when the cartridge is procured by the US Army Armament Command, one (1) copy of all ballistic data and ammunition data cards shall be forwarded to: Commander, Picatinny Arsenal, Attn: SARPA-QA-A-S.

6.6 The cartridges will be considered safe to transport providing no evidence exists of loose powder or composition in the box.

6.7 The cartridges will be considered free of damage that will affect the intended function provided the top seal has not been broken by movement or displacement of the top, or the case side has not been distorted sufficiently to prevent ejection of the illuminant assembly.

6.8 Proving Ground Test - Initial production testing shall be conducted in accordance with US Army Test and Evaluation Command Initial Production Test Plan No. CART-40GL-VAR.

6.9 Metal Defective - Nick, crack, dent or sharp edge which might interfere with the proper assembly or end item performance of the item.

6.10 Proving Ground Test Summary:

TEST	SAMPLE SIZE	REQUIREMENTS
Functioning		
(1) First Article		
a. Hot	80	See 3.4.5 & 4.3.3.1
b. Ambient	280	See 3.4.6 & 4.3.3.1
c. Cold	80	See 3.4.7 & 4.3.3.1
(2) First 3 lots		
a. Hot	44	See 3.4.5 & 4.4.3.7
b. Ambient	176	Se3 3.4.6 & 4.4.3.7
c. Cold	44	See 3.4.7 & 4.4.3.7
(3) Regular Production		
a. Hot	26	See 3.4.5 & 4.4.3.10
b. Ambient	80	See 3.4.6 & 4.4.3.10
c. Cold	26	See 3.4.7 & 4.4.3.10

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1310-A094

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-C-63092

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:25Z
Check the source to verify that this is the current version before use.