NOT MEASUREMENT SENSITIVE

MIL-S-62052C
22 August 1989
SUPERSEDING
MIL-S-62052B(AT)
5 October 1981

MILITARY SPECIFICATION

SEMITRAILER, VAN; AIR TRANSPORTABLE, 5-1/2 TON, AIR CONDITIONED, COMMERCIAL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a 5-1/2 ton capacity semitrailer equipped with a demountable suspension system for aircraft loading. The semitrailer shall be air conditioned and shall be equipped with a single axle, dual wheel suspension system. Semitrailers procured under this specification are commercial items which shall be warranted by the manufacturer as specified in acquisition documents.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS), and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS
FEDERAL
L-F-475 - Floor Covering, Vinyl, Surface (Tile and Roll) With Backing.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-UED, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC-2330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

MILITARY
MIL-P-514 - Plates, Identification, Instruction and Marking, Blank.

STANDARDS
FEDERAL
* FED-STD-297 - Rustproofing of Commercial (Nontactical) Vehicles.

MILITARY
MIL-STD-171 - Finishing of Metal and Wood Surfaces.
MIL-STD-1223 - Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking and Data Plate Standards.
* MIL-STD-1791 - Designing for Internal Aerial Delivery in Fixed Wing Aircraft.

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

* "DODISS - Department of Defense Index of Specifications and Standards.

(Copies of the DODISS are available on a yearly subscription basis either from the Government Printing Office for hard copy, or microfiche copies are available from the Director, Navy Publication and Printing Service Office, 700 Robbins Avenue, Philadelphia, PA 19111-5093.)"

DEPARTMENT OF TRANSPORTATION (DOT)
Federal Motor Carrier Safety Regulations.
Federal Motor Vehicle Safety Standards.

(Applications for copies of DOT publications should reference the Code of Federal Regulations, 49 CFR, and the Federal Register, and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

* 2.2 Non-Government publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are issues of the documents cited in the solicitation (see 6.2).

THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)
ASME Boiler and Pressure Vessel Code, Section VIII.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

(Application for copies of ASME publications should be addressed to the American Society of Mechanical Engineers, United Engineering Center, 345 East Forty-Seventh Street, New York, NY 10017.)

* THE EUROPEAN TYRE AND RIM TECHNICAL ORGANISATION (ETRTO)
Standards Manual

(Application for copies of the European Tyre and Rim Technical Organisation publications should be addressed to the European Tyre and Rim Technical Organisation, 32, Avenue Brugmann, 1060 Brussels, Belgium.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)
NFPA No. 70 - National Electrical Code.

(Application for copies of NFPA publications should be addressed to National Fire Protection Association, 470 Atlantic Avenue, Boston, MA 02110.)

* SAE, Inc.
SAE Standards and Recommended Practices

*	J318	- Air Brake Gladhand Service (Control) and Emergency (Supply) Line Couplers - Trucks, Truck-Tractors, and Trailers (DOD adopted).
	J478	- Slotted and Recessed Head Screws.
*	J551	- Performance Levels and Methods of Measurement of Electromagnetic Radiation from Vehicles and Devices (30-1000 MHz).
	J560	- Seven-Conductor Electrical Connector for Truck-Trailer Jumper Cable.
	J588	- Turn Signal Lamps.
*	J682	- Rear Wheel Splash and Stone Throw Protection (DOD adopted).
*	J700	- Upper Coupler Kingpin - Commercial Trailers and Semitrailers.
	J702	- Brake and Electrical Connection Locations - Truck-Tractor and Truck-Trailer.
	J1292	- Automobile, Truck, Truck Tractor, Trailer, and Motor Coach Wiring.

(Application for copies of SAE publications should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC.
Yearbook.

(Application for copies of Tire and Rim Association publications should be addressed to the Tire and Rim Association, Inc., 3200 W. Market Street, Akron, OH 44313.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Standard semitrailer, components, and accessories. Except as specified in 3.1.1 through 3.1.1.9, the semitrailer, components, and accessories shall be standard or optional items which meet or exceed the requirements of this specification. All items shall be as represented and rated in the manufacturer's technical data, including special or mounted equipment. Technical data shall be limited to specifications and technical material identical to that furnished to the authorized company representatives for selection of semitrailer models and components, and shall be available to the engineering offices of the procuring activity prior to delivery of the items. The semitrailer and furnished accessories shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture.

3.1.1 Special requirements. In addition to the standard semitrailer and components specified in 3.1, the semitrailer shall be furnished with special equipment as specified herein.

* 3.1.1.1 Painting and marking. Treatment, painting, marking and data plates shall be in accordance with MIL-STD-1223. The exterior color and the identification markings shall be in accordance with the requirements of MIL-STD-1223 for the military service identified by the procuring activity (see 6.2). The body interior color shall be the manufacturer's standard gloss white.

3.1.1.1.1 Instruction plates. At least the following equipment operating instruction plates shall be furnished:

(a) Electrical circuits controlled by switches
(b) Air line outlets
(c) Air conditioning controls
(d) Heating controls
(e) Schematic of interior electrical circuits
(f) Schematic of air lines
(g) Complete operating instructions for preparing the vehicle for air transport.

Instruction plates, schematics, and control devices shall be depicted on photoetched, corrosion-resistant plates. Control device plates shall be secured to the area adjacent to the control. Instruction and schematic plates shall be located on the curbside wall near the electrical distribution boxes. Operating instructions for preparing the vehicle for air transport shall be located near or on the interior of the curbside door.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

* 3.1.1.2 Wood treatment. Wood shall be treated in accordance with MIL-STD-1223 except interior paneling may be resin impregnated with an overlaid surface on one side of resin treated cellulose fiber and interior floor may be laminated hardwood in lieu of MIL-STD-1223 treatment.

3.1.1.3 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with FED-STD-297.

3.1.1.4 Drain plugs. All drain plugs installed throughout the vehicle for the purpose of draining lubricants shall be of the permanent magnet type.

3.1.1.5 Radio interference suppression. The vehicle shall be suppressed to limit electromagnetic radiation in accordance with SAE J551. Any body equipment emitting electromagnetic radiation shall be suppressed to the same level as the semitrailer.

* 3.1.1.6 Air transportability. The semitrailer, complete with all components and accessories, exclusive of the demountable components specified herein, shall be air transportable in accordance with MIL-STD-1791 in C-130 aircraft, equipped with A/A32H-4A Cargo Handling System. Preparation for air transport shall be accomplished by the removal of the running gear assembly and removal or folding up of landing gear, leveling jacks, spare tire carrier, spare wheel assembly and rear bumper assembly. All fastening devices shall be corrosion-resistant. All fastening devices except common bolts and nuts shall be secured with corrosion-resistant security chains to prevent loss. Spring loaded dowel pins, alinement pins, and other quick release methods of alining removable components shall be provided. Torque requirements for threaded fasteners shall be provided for installation purposes. The demountable body shall be capable of being winched to and from aircraft when supported on its skid frame. The vehicle shall be designed so that preparation for air transport can be accomplished in not more than two manhours.

* 3.1.1.7 Tiedown devices. The body shall be provided with tiedown devices to permit the tiedown of the body to the floor or deck of the transportation medium in such a manner as to prevent shifting or movement in any direction. The tiedown devices shall be in accordance with MIL-STD-1791. Each device shall be designed to accept its proportionate share of the loads imposed. The devices shall be designed to withstand thrusts of the magnitudes specified therein. Tiedown devices shall be located so as to permit easy attachment of cables or turnbuckles. Tiedown devices, fasteners, or attachments shall not project below the bottom of the body and shall not interfere during aircraft loading. Tiedown devices shall be indicated by an information plate conforming to MIL-P-514 except copper base alloy is not required. This information plate shall be mounted adjacent to the operating instruction plate specified in 3.1.1.1.1(g). Tiedown devices shall be located by stenciling, as specified in MIL-STD-1791. Markings shall clearly indicate that the device is intended for the tiedown of the body on the carrier when shipped.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

3.1.1.8 Towing devices. Two towing devices shall be provided on the front and two on the rear of the body. Towing devices shall be capable of pulling the body on its skid into an aircraft and of pulling the body from the aircraft.

3.1.1.9 Lifting pads. Lifting pads shall be provided at the rear end and on each side rearward of the gooseneck or landing gear, as applicable. Lifting pads shall protect the underside of the semitrailer and shall be capable of accepting their portion of the gross weight when lifting the body with a fork lift tractor for removal and installation of the rear axle assembly and the landing gear assembly, if not retractable. Skid rails at the rear of the body shall serve as the rear lifting pads. A minimum size of 8 inches wide by 30 inches long lifting pads shall be installed on each side of the body. The side lifting pads shall be located on the outside edge of the vehicle body 31 inches rearward from the edge of the gooseneck for gooseneck semitrailers or from the landing gear centerline for semitrailers without a gooseneck, measured to the centerline of the lifting pad. The bottom of the lifting pads shall be on the same horizontal plane as the bottom of the skid rails.

* 3.1.1.10 Asbestos. Asbestos materials shall not be used in any form in any part of the vehicle.

3.2 Semitrailer weights, loads and ratings.

3.2.1 Curb weight. The curb weight shall include the weight of the semitrailer with installed equipment, all attachments, and accessories and shall not exceed 14,000 pounds.

3.2.2 Payload. The rated payload shall be not less than 11,000 pounds.

3.2.3 Gross weight. The gross weight shall consist of the curb weight and the specified payload evenly distributed in the semitrailer rear compartment load area.

3.2.4 Ratings. The semitrailer and component ratings shall be the manufacturer's published ratings. The component and semitrailer ratings shall not be raised to meet the requirements of this specification. When ratings are not published, verification of the ratings shall be available to the engineering office of the procuring activity.

3.3 Performance. Semitrailer performance requirements as specified in 3.3.1 through 3.3.5 shall be met by the semitrailer when fully equipped, completely serviced, coupled to the towing vehicle, and towed over improved and unimproved, hard, uneven terrain. The semitrailer shall show no evidence of failure or malfunction of any components, attachments, or accessories.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

* 3.3.1 Towing speed and trailing ability. The semitrailer shall follow the towing vehicle at sustained speeds of 55 miles per hour (mph), over smooth prepared hard surfaced roads and at not less than 10 mph over gravel roads. The semitrailer shall follow the towing vehicle without exceeding the tracking deviations specified in Federal Motor Carrier Safety Regulation 393.70(a).

* 3.3.2 Turning ability. The semitrailer when coupled to the towing vehicle shall be capable of assuming an angle of 90 degrees to the towing vehicle without cramping or damage to the semitrailer or the towing vehicle.

3.3.3 Brake performance. The service brakes shall stop the tractor-semitrailer combination, with the semitrailer loaded with specified payload, within the stopping distance requirements of Federal Motor Carrier Safety Regulation 393.52.

3.3.4 Air conditioning and heating.

* 3.3.4.1 Air conditioning. The air conditioner shall be capable of maintaining not more than 80 degrees Fahrenheit (°F) dry bulb and a 68°F wet bulb temperature in the vehicle in an ambient air temperature of 110°F under full solar radiation and peak heat load. The worst condition shall be with a 5-kilowatt (kW) peak heat load, four people, and full solar radiation.

* 3.3.4.2 Heating. The heating unit of the system shall be capable of maintaining a 55°F temperature in the vehicle in a minus 50°F ambient air temperature when the semitrailer is exposed to a 50 mph wind.

* 3.3.5 Waterproofness. The vehicle shall be waterproof to prevent entrance of water when exposed to a spray of 25 pounds per square inch (psi) located two feet from the vehicle for at least 15 minutes. The spray shall be projected on all sides of the vehicle.

3.4 Design and construction. The vehicle shall have a fully inclosed van type body, with removable chassis components to provide loading into a C-130 type aircraft. The semitrailer shall have a straight frame with a single level floor, or shall have a gooseneck type frame with a single or two-level floor. When an inside air conditioner is furnished (see 3.7.1), a transverse partition shall be furnished over the gooseneck or forward of the landing legs. The vehicle shall be equipped with double rear doors and a curbside door adjacent to the landing legs. The vehicle shall be equipped with a vertical heating and air conditioning system, mounted to the floor on the streetside at the forward left corner of the front compartment or outside mounted on the front wall.

3.4.1 Body types. Unless otherwise specified (see 6.2), the following body types, as specified, shall be furnished. When body types are at the option of the manufacturer, all bodies shall be of the same design:

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

(a) Chassis frame
(b) Trussed body side members
(c) Stressed-skin (monocoque or semi-monocoque).

3.4.1.1 Body exterior and framing. Body exterior, except front and doors, shall be corrugated aluminum alloy sheets having corrugation on 4-inch centers for the side walls or shall be smooth skin, stretcher level aluminum alloy sheets. Body, underbody, and roof framing shall be constructed of steel or aluminum section. Steel or aluminum structural members shall be arc welded and reinforced at joints to fulfill the dynamic and static loading requirements specified herein. When splices are necessary, they shall be designed to avoid stress concentration. Splice welds shall be continuous. Welding material shall be compatible to the material being welded. Structural members shall be designed to accept the loads imposed by the factors specified in 3.1.1.6, 3.1.1.7, 3.1.1.8, 3.1.1.9 and 3.6.13.3. The roof shall be of one-piece construction of aluminum alloy sheet.

3.4.1.2 Materials. Materials shall be free of any defects or imperfections that may affect the performance and appearance of the vehicle.

3.4.1.3 Dissimilar metals. When parts of dissimilar metals are in contact, the contact faces shall be primed with a highly alkaline resistant primer and faced with mylar barrier tape or the contact surfaces shall be primed with zinc chromate primer to effectively prevent galvanic or electrolytic action. Materials used shall be compatible with each other in accordance with MIL-STD-171.

3.4.2 Design load and stresses. The design load shall be equal to the product of 1.5 times the algebraic sum of the vehicle curb weight minus the unsprung weight of the suspension system plus the rated design payload uniformly distributed over the load area. Expressed as an equation:

Design load = 1.5 (curb weight - unsprung weight + rated design payload).

The 1.5 factor shall include and adjust the effect of a shock load (0.50) in stress calculations. When subjected to the computed design load, the normal stress (variously designated as the principal, bending, flexural, or fiber stress) in the load carrying members shall not exceed 50 percent of the material yield strength. The stress in the compression members shall not exceed the following, whichever is less:

(a) 1/2 of critical stress based on Euler column formula.

$$SCR = {}^{2} E (r/L)^{2}$$

(b) 2/3 of the material yield strength, or
(c) 1/3 of the material ultimate strength.

3.5 Dimensions and clearances. The exterior dimensions and clearances shall be as specified in table I when measured with the vehicle uncoupled from the prime mover, resting on the landing gear and tires, with the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

interior floor horizontal to the ground level; when in air transport position; and without payload. The overall length includes the front mounted air conditioner. The overall width excludes the handles, lights, and other appurtenances.

TABLE I. Dimensions and clearances.

General location	Inches
Overall length, (plus 0, minus 6 inches)	384
Overall width (plus 1 inch, minus 0)	95
Overall height (maximum)	140
Upper fifth wheel height (plus or minus 1 inch) (distance from ground to underside of fifth wheel plate at centerline of kingpin)	48
Kingpin to front of vehicle (plus or minus 3 inches):	33
Swing radius (maximum)	58
Landing wheel clearance (distance from centerline of kingpin to any point on the vehicle 6 inches or more below upper fifth wheel plate), not less than	82
Ground clearance (minimum)	9.5
Overall height of vehicle, resting on skid rails in air transport position (maximum)	102

3.6 Semitrailer components.

3.6.1 Underbody. The underbody load carrying longitudinal members shall be one piece, without splices except at the kickup for gooseneck semitrailer. Tire clearance shall be not less than 4-1/2 inches and shall not extend into the frame member areas.

3.6.1.1 Platform. The platform shall be flat with no protrusions or wheelhousings, shall be of the single deck type for semitrailers without gooseneck and of the two level type for semitrailers with gooseneck. When a semitrailer with gooseneck is furnished, the step to the front of the vehicle over the gooseneck shall not exceed a vertical height of 12 inches. The floor shall be insulated as specified in 3.6.2.6. The U-shaped channel and interior tiedown rings specified in 3.6.13.2 and 3.6.13.3 shall be secured so as to minimize the transfer of heat.

3.6.1.2 Floor pan. A floor pan shall be provided to protect the complete underside of the vehicle. The floor pan shall be not less than 18 gage (0.0478 inch) stainless steel sheet or 0.050 inch aluminum. The floor pan shall rise above the loadspace of the floor level and shall have a flanged perimeter except when the body rails are flanged so as to prevent the entrance of water. The floor pan shall be primed (see 3.4.1.3) and painted to prevent galvanic and electrolytic action. The floor pan shall be watertight to prevent contamination of the insulation cavity (see 3.6.2.6).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

3.6.1.3 Floor. A full length, single level or, for a gooseneck semitrailer a two level subfloor shall be provided. The subfloor support members shall be of nonconductive material, primed (see 3.4.1.3), and painted to prevent galvanic or electrolytic action; or may be oak batten strips treated in accordance with MIL-STD-1223. Insulation as specified in 3.6.2.6 shall be provided on top of the floor pan and between the nonconductive material. The insulation cavity shall be covered with exterior AC grade plywood, not less than 3/4 inch in thickness, seven-ply, treated in accordance with MIL-STD-1223, and sealed around the perimeter. The subfloor shall be secured to the nonconductive members. The floor shall be capable of withstanding a vertical load of 200 pounds per square foot. The interior tiedown devices and U-shaped channel as specified in 3.6.13.2 and 3.6.13.3 shall be flush mounted. The subfloor nonconductive members or oak batten strips shall be secured to the crossmembers by slotted or torx head, flat head, self-tapping (thread cutting), phosphate coated or other corrosion-resistant material machine screws of appropriate size and length conforming to SAE J478, Table 4 for slotted screws and recessed head screws. The interior tiedown devices and the U-shaped channel shall be secured to the main frame crossmembers with corrosion-resistant bolts, washers, lock washers, and nuts. An insulation insert shall be placed between the members and the tiedowns and the U-shaped channel to minimize transfer of heat. When oak batten support members are furnished, it shall be acceptable to secure the interior tiedown devices and U-shaped channels directly to the oak batten support members using corrosion-resistant wood screws of appropriate size and length. Floor seams shall be filled. The subfloor shall be secured with slotted flat head or torx head screws as specified herein. The tiedown devices and the U-shaped channel shall be installed so that when the floor covering is installed, the top edge of the U-shaped channel and the top surface of the mounting plate of the tiedown devices are flush mounted.

3.6.1.4 Skid rails. Skid rails shall be furnished, or the lower edge of the floor structure may be used as skid rails to provide a skid surface when components have been removed for air transport. Skid rails shall be not less than 12 inches in width and shall mate with the conveyor rollers on the floor of the aircraft (see 3.1.1.6). Skid rails shall be of one continuous length from the rear of the gooseneck to the rear of the vehicle except for interruption at the wheelwells. Interruption shall be chamfered to prevent damage during loading and unloading. The front and rear of each skid rail shall have a chamfered face of the same transverse width as the skid rail. The chamfered face shall be not less than 27 degrees and shall have a vertical rise measured from the bottom edge of the skid rail of not less than 1-5/16 inches. Chamfered edges shall have smooth surfaces that are tangent to the conveyor rollers of the aircraft. The skid rails shall mate with at least the outside pair of aircraft rollers. Skid rail faces in contact with the aircraft rollers shall have a flat, smooth, uninterrupted surface, so that the entire contact surface of each skid rail is in contact with the rollers on the aircraft. Covered, clad or laminated contact surfaces of the skid rails are not acceptable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

3.6.2 Body exterior. Body construction shall be of a trussed or monocoque type design. The longitudinal upper rails at the roof level shall be continuous, without splices, extending the full length between the front and rear walls of the vehicle, and designed for attachment of full width roof bows, located on not more than 12-inch centers. All vertical structural members shall be one piece without splice. The corner posts shall be such as to present nominal square, rounded or chamfered corners on the vehicle. The contact face on noncompatible metals shall be protected from corrosion (see 3.4.1.3).

3.6.2.1 Trussed body. Trussed body framing structure shall include at least the following: Vertical members, consisting of corner and intermediate posts, shall be inserted between the roof structure and the chassis frame, and employed to combine the roof structure to the chassis frame. The corner and intermediate posts shall be continuous without splice between the roof structure and chassis frame except at door opening areas and shall be spaced on not more than 12-inch centers, except different intervals shall be permitted at door opening regions. The vertical posts may be used to add to the rigidity of the truss.

* 3.6.2.2 Monocoque or semi-monocoque body. The stressed skin monocoque or semi-monocoque body unitized structure shall be constructed to prevent buckling of the skin sheets when the vehicle is operating under the intended service. The monocoque design shall incorporate a rubrail feature in the lower structural rail.

3.6.2.3 Body attachments. Body attachments shall be fastened together in a manner which shall prevent loosening of bolts, screws and rivets, as well as cracking of welded joints when the vehicle is properly maintained and operated under the intended service conditions. Fasteners shall be compatible to the metal being secured. Self-tapping screws shall not be used in areas subjected to stress and wood shall not be utilized for structural framing.

3.6.2.4 Body side panels. Corrugated body side panels, when furnished, shall be provided with a flat sheet of proper size to accommodate markings (see 3.1.1.1).

3.6.2.5 Body roof panels. Body roof panels shall be stretcher leveled and secured to the roof bows to prevent panel vibration. The roof shall be capable of withstanding a static load of 30 pounds per square foot. The roof shall be crowned to permit drainage.

3.6.2.6 Insulation. Body insulation shall have a "K" factor of not more than 0.12 and a density of not less than 2.00 pounds per cubic foot. The "K" factor of the insulation shall not increase to more than 0.15 in a four-year period. Insulation shall not support combustion or sustain flame, mold, rot,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

or vermin; shall not corrode metals, absorb odors, disintegrate under vibration, or settle and leave voids; and shall be essentially odorless. Condensation in the insulation cavity shall not exceed 0.50 pound per hour. Unless foamed-in-place insulation is used, means shall be provided to drain condensation to the ground. Insulation material shall be homogenous and uniform in density and thermal efficiency. Insulation material shall be capable of flexing more than its containing structure without tendency to crack or rupture. Material performance shall be certified.

3.6.2.7 Drip moldings. Drip moldings shall be furnished over at least all windows and doors.

3.6.2.8 Rub rails. Rub rails of sheet steel, not less than 10 gage (0.1345 inch), or fluted aluminum rub rails not less than 1/8 inch thick backed by a minimum 10 gage (0.1345 inch) steel rub rail shall be provided along the streetside and curbside of the body.

3.6.2.9 Double rear doors. Double rear doors shall provide full interior width opening for access into the body rear compartment. Interior door opening height shall be not less than 72 inches. The doors shall be hung between box posts with not less than three heavy duty strap hinges on each door. Doors shall be hung to permit folding back against body sides. Means shall be provided to retain doors in fully opened position. Doors shall be insulated (see 3.6.2.6). The door clearance shall not exceed 3/8 inch. A center door post shall not be acceptable.

* 3.6.2.10 Side door. A side door located on the curbside rearward of the gooseneck or landing legs and located as near the gooseneck or landing legs as construction permits shall be furnished. The door shall open to the front of the vehicle. The door opening shall be not less than 28 inches in width and 72 inches in height. Door shall be hung to permit the door to fold back against the body side. Means shall be provided to retain the door in a fully opened position. The door shall be insulated (see 3.6.2.6). The door clearance shall not exceed 3/8 inch. The door shall be hung between box posts with not less than three heavy duty strap hinges.

3.6.2.10.1 Side door window. A fixed window shall be installed in the side door, located centrally and approximately 60 inches from the floor. The window shall be glazed to provide for a 6-inch diameter, shatterproof glass or plexiglass window, 1/4 inch in thickness. The window shall be provided with a spring-loaded hinge with a cover on the interior and operable from the interior only. The cover shall have a spring-retention latch. A rubber gasket shall be provided on the edge of the perimeter of the cover that faces the interior door surface to assure that light does not pass through.

* 3.6.2.11 Rear door hardware. Each door shall lock independently of each other in the closed position. The curbside rear door shall be designed to open from inside or outside the vehicle. Each door shall be provided with

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

cam type locks with top and bottom vertical drawbolts. The curbside rear door shall be provided with interior and exterior handles enabling the closing and opening of the doors from inside and outside the vehicle by personnel with arctic gloves, and shall be operable in ambient air temperature of minus 50°F. The rear curbside door shall be provided with a handle having a provision on the exterior to accommodate locking the door with a padlock. Locking mechanism shall have an internal safety release handle to enable doors to be unlocked from the inside of the van when locked from the outside.

* 3.6.2.12 Side door hardware. The side door shall be capable of being locked from the inside or outside of the vehicle. A cam type lock with top and bottom vertical drawbolts located on the interior of the door shall be furnished. The lock shall be recessed within the door. The exterior handle shall be provided with a provision to accommodate locking the door with a padlock. Lock mechanism shall have an internal safety release handle to enable the door to be unlocked from the inside of the van when locked from the outside. The door hardware shall be operable by personnel wearing arctic gloves, and shall be operable in an ambient air temperature of minus 50°F.

3.6.2.13 Door gaskets. Doors shall be provided with weatherproof, nonabsorbent, light-tight, rubber sealing gaskets. Gaskets shall be fitted around the door openings and between the doors. Gaskets shall have appropriate flexural and compressibility characteristics and shall not absorb moisture. When doors are closed, light, wind, or rain shall not penetrate. Gaskets shall withstand an ambient air temperature range of minus 50°F to plus 160°F.

3.6.2.14 Detachable ladder. A detachable ladder of the flatstep type and of lightweight construction shall be provided for the right rear and side doors for use by personnel in entering and leaving the van body. Ladder steps shall be self-cleaning with an antiskid surface. The ladder shall support a static load of 350 pounds centrally located on any single step without failure. The ladder side members shall be designed to provide not less than 30 degrees slope from the vertical. The steps shall provide approximately equal risers, of not more than 8 inches between the ground and the vehicle floor level, and shall furnish sufficient tread width of not less than 8 inches to minimize tripping hazards. A removable hand rail with provisions for locking in a stationary position shall be furnished for use with the ladder. Detachable ladders shall be provided for the side entrance door and the rear curbside service door. In addition, means may be added to position the ladder in the center of the rear doors. Means shall be provided to retain detachable ladders at the door sills when in use.

3.6.2.15 Detachable ladder carrier(s). Detachable ladder carrier(s) shall be furnished. Carrier(s) shall be removable for aircraft transport (see 3.1.1.6). Carrier(s) shall be located in an accessible location under the body.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:22Z
Check the source to verify that this is the current version before use.

3.6.3 Suspension and axle. The suspension and axle shall be removable as a unit assembly and shall be as specified in 3.1.1.6.

3.6.3.1 Suspension system. The vehicle shall be equipped with a spring suspension system, with each component having a rated capacity at least equal to the load imposed, measured at the ground, with the vehicle loaded as specified in 3.2.3. The vertical tire clearance shall be not less than 4-1/2 inches.

3.6.3.2 Axle. Axle rating shall be at least equal to the load imposed, measured at the ground, with the vehicle loaded as specified in 3.2.3. Axle spindles shall be hardened and ground. The hub caps shall have a metal body and a window for visual determination of the oil supply and shall incorporate provisions for venting and replenishing the oil supply.

* 3.6.4 Brakes. Full air, internal expanding type brakes shall be furnished on all wheels of the vehicle. The brakes shall conform to Federal Motor Carrier Safety Regulations 393.40 through 393.43, 393.45 through 393.50, and 393.52. Brake linings shall be of nonasbestos material. The brake system shall include piping, hose connections, gladhands with cover assembly, air reservoirs, automatic slack adjusters, relay emergency valve, and all other associated parts and connections required for a complete air brake system. Location of air fittings shall be in accordance with SAE J702. Air fittings shall be mounted in a recessed location. Front air hose connections shall be provided with gladhands, spring loaded dust covers, or dummy gladhands equipped with security chains. Gladhands shall conform to SAE J318. All components of the brake system shall be installed in such a manner as to provide adequate road clearance when traveling over uneven or rough terrain, including objects liable to strike and cause damage to the brake system components. No part of the braking system shall extend below the bottom of the wheel rims. The removable running gear assembly shall be provided with air hoses with air couplings that connect to fixed air couplings with spring loaded dust cover on the vehicle chassis. Disconnect is required for air transport. Fixed dummy couplings shall be provided on the running gear frame for use during air transport.

3.6.4.1 Parking brakes. The semitrailer shall be equipped with spring or air diaphragm mechanical lock type parking brakes. The parking brakes shall hold the semitrailer, with rated payload on a 10 percent grade despite the depletion of the compressed air supply. The parking brakes shall be automatically applied upon disconnection of the emergency air line and under emergency conditions. The parking brakes shall conform to Federal Motor Carrier Safety Regulation 393.41.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

3.6.5 Wheels, rims, tires, and tubes.

3.6.5.1 Wheels and rims. The vehicle shall be equipped with dual wheels. Wheel bearings shall be of the antifriction roller bearing type and shall be oil lubricated. The hubs shall be provided with seals. Rims and tire ratings shall conform to Tire and Rim Assocation recommendations for the type and size of tires furnished. Tire size, load range (ply rating), tread design, and manufacturer shall be the same for all wheels on the semitrailer. Rim sizes shall be the same for all wheels on each vehicle.

* 3.6.5.2 Tires. Unless otherwise specified (see 6.2), tires shall be tube or tubeless steel belted radial ply type with highway tread. Tires shall be of a rated capacity at least equal to the loads imposed on each tire, measured at each wheel, at the ground, with the vehicle loaded as specified in 3.2.3. The manufacturer's current size of tires conforming to specified requirements may be furnished. Tires shall conform to Tire and Rim Association Recommendations, or European Tyre and Rim Technical Organisation recommendations.

3.6.5.3 Inner tubes. For tube type tires, inner tubes shall be of the heavy duty type and shall be proper size for the tire furnished. Tire flaps shall be provided for tube type tires in accordance with Tire and Rim Association recommendations.

* 3.6.5.4 Spare wheel or rim. Unless otherwise specified (see 6.2), a spare wheel or rim shall be mounted on a carrier located forward of the axle, readily accessible from the curbside. The carrier shall be readily removable for air transport and shall be bolted to the vehicle or mounted to the removable running gear. Threaded fasteners, when used to secure the spare tire in the carrier, shall be constructed of or plated with corrosion-resistant material.

3.6.5.5 Spare tire. Unless otherwise specified (see 6.2), an inflated spare tire shall be mounted on the spare wheel or rim. The spare tire shall be of the same size, load range (ply rating), and tread design as the tires furnished on the vehicle.

* 3.6.6 Upper fifth wheel plate. The upper fifth wheel plate shall be of the one-piece rigid type, not less than 1/4 inch in thickness, reinforced, having a minimum dimension of 45 inches in length and 36 inches in width, and shall conform to Federal Motor Carrier Safety Regulation 393.70(b). A 2-inch kingpin conforming to SAE J700 shall be provided. The forward end of the upper fifth wheel plate shall have a minimum 1-inch long lip turned up at 45 degrees or a 1-inch rolled lip, for ease of loading onto the towing vehicle.

3.6.7 Electrical system. The electrical system shall be 12-volt direct current (dc). Wiring shall be in accordance with the applicable portion of SAE J1292, and Federal Motor Carrier Safety Regulations 393.27, 393.28, 393.29, 393.32 and 393.33. All wiring exposed to possible physical damage

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

shall be protected by use of a heavy wall thermoplastic insulated cable or rigid conduit. Wiring within the body area that is not readily accessible for service shall be in a rigid conduit. The conduit shall be provided with vents. All wiring shall be tagged and color-coded in accordance with SAE J560. The conduit shall be adequately and properly secured to prevent possible physical damage by the employment of chafeproof clamps and grommets.

* 3.6.7.1 Lighting. An electrical lighting system shall be provided. The lighting system shall conform to Federal Motor Carrier Safety Regulations 393.14, 393.20, 393.22, 393.23, 393.25 through 393.29, 393.32 and 393.33. When available as the manufacturer's standard or optional feature, the brake lights shall override the four-way emergency flasher. All lights and reflectors shall be mounted in recessed locations or in guarded locations to provide protection from operational hazards. Lights and reflectors shall not be mounted on vertical surfaces of rub rails (unless recessed and fully protected), or mounted on vehicle bumpers. Turn signal lamps shall be in accordance with SAE J588.

3.6.7.2 Lighting receptacle. The vehicle shall be equipped with a lighting receptacle mounted in a recessed or protected location at the front of the vehicle. The receptacle shall be in accordance with SAE J560, with a spring loaded cover assembly.

3.6.8 Landing gear. The vehicle shall have two vertical lift, telescoping, nonrotating landing legs with two-speed gears and a hand-crank for each landing leg. The landing legs shall be equipped with steel wheels or self-leveling skid pads. A holder shall be provided for each handcrank. A corrosion-resistant security chain, secured to the landing leg, shall be provided except when permanently attached crank handles are used. The landing gear assembly shall be capable of operating independently from either side of the vehicle for side-to-side leveling. The landing gear assembly and its components, accessories, and attachments shall withstand, without deformation, the combined static and dynamic forces due to the portion of the gross weight sustained, and the additional forces resulting from impact during coupling and uncoupling operations. When placed in travel position, the landing gear assembly shall remain locked. When the landing gear is in a retracted position, the ground clearance shall be not less than 12 inches. The landing gear assembly shall have sufficient vertical travel to vary the height of the upper fifth wheel plate, measured at the vertical centerline of the kingpin, from at least 44 inches to not less than 52 inches above ground level. The landing gear assembly shall be protected to prevent the entrance of foreign matter which would impair its functioning or mechanical efficiency. A lubrication fitting shall be furnished. The landing gear assembly shall be fully retractable above the skid rails specified in 3.6.1.4 or removable for air transport as specified in 3.1.1.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

3.6.9 Leveling jacks. Four manually operated leveling jacks shall be furnished. The leveling jacks shall be retractable or removable for highway and air transport. When the leveling jacks are used, they shall be installed in each extreme rear corner and at each extreme front corner of the vehicle. The leveling jack contact surfaces at the inside of the vehicle frame member corners shall meet or exceed the requirements of 3.4.1.1. The leveling jacks shall be capable of leveling the vehicle and shall insure stability under wind velocities of 50 mph. The leveling jacks shall be Westran Model No. 6439 or equal, having a total expanded length of 60 inches, providing a total lift on the front coupler height of approximately 12 inches above ground level. When a clevis and yoke are used to secure leveling jacks to the vehicle, the fastening devices shall be secured by a corrosion-resistant security chain to prevent loss of the fasteners. The operating mechanism shall be enclosed to prevent contamination. Means shall be provided for lubrication.

3.6.10 Bumper. Rear end protection shall conform to Federal Motor Carrier Safety Regulation 393.86. The vehicle shall be furnished with a folding or demountable type bumper for air transport (see 3.1.1.6). The bumper shall be furnished with corrosion-resistant security chains and corrosion-resistant alinement pins. Alinement pins are for locating purposes. The bumper may be permanently attached to the bogie assembly and be removable along with the bogie itself.

3.6.11 Rear wheel splash protection. Rear wheels shall have rubber mud flaps at the rear of the rear wheels. Mud flaps may be bolted to the bogie frame. A metal strip not less than 1/8 inch thick and not less than one inch wide, extending the entire width of the mud flap, shall be installed to prevent the bolt heads or bolt nuts from damaging the mud flap. Splash and stone throw protection shall conform to SAE J682. Rubber mud flaps when secured to the vehicle chassis shall be removable for aircraft transport (see 3.1.1.6).

3.6.12 Partition. When the air conditioner specified in 3.7 is located inside, a partition shall be furnished at the front of the vehicle between the rear and front compartments at the kickup or forward of the landing legs. A sliding door shall be furnished (see 3.6.12.1), and located transversely 26 inches from the curbside interior wall. A sliding door shall provide a clear opening of 30 inches in width and 60 inches in height. When an outside front air conditioner is provided (see 3.7), the partition shall not be furnished.

3.6.12.1 Sliding door hardware. The sliding door hardware shall enable the door to remain in the open position or the closed position during highway or aircraft travel. The sliding door track shall provide positive alinement and prevent separation of track sections at the joints. End stops with padded faces to prevent vibration shall be furnished. Door roller guides with nylon rollers to prevent side-to-side vibration shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

Door hangers shall be furnished with double nylon rollers. Door hangers shall be furnished with a mechanical means to adjust door alinement. The door bottom face parallel to the floor shall be provided with nylon roller guides operating in a sliding door track with wipers to prevent contamination of the door sill track. The track shall be flush mounted with the vehicle body floor. A sliding door lock with pillar type locking features shall be furnished. The lock shall be furnished with handles on each side of the door. When a handle is installed, the handle shall face down to prevent unlatching of door lock. Striker plates shall be furnished. Locks shall be of the slam type for sliding doors.

3.6.13 Vehicle body interior. When a semitrailer with gooseneck is furnished, the vehicle body over the gooseneck shall have a finished floor-to-ceiling height of not less than 69 inches, except with the air dampers and lighting fixtures installed, the height shall be not less than 65 inches. The full length of the trailer with a single level floor, and the length to the rear of the gooseneck for a two-level platform, shall have a floor-to-ceiling height of not less than 80 inches, except that with the air dampers and lighting fixtures installed or mounted within the ceiling, the height shall be not less than 76 inches. Under the duct work, within the first 5 feet from the front, the height shall be not less than 48 inches. The following components shall be recessed or mounted within the vehicle body walls, ceiling and floor:

(a) U-channel (see 3.6.13.2)
(b) Interior tiedown rings (see 3.6.13.3)
(c) Air distribution ducts and dampers (see 3.7.5)
(d) Compressed air system (see 3.8)
(e) Electrical conduit and receptacles (see 3.9).

3.6.13.1 Interior paneling. The interior walls, ceiling, and partition shall be lined with not less than 1/4-inch exterior grade plywood. Plywood shall be treated as specified in MIL-STD-1223 or the plywood shall be resin impregnated with an overlaid surface on one side of resin treated cellulose fiber. The structural members of the body interior walls and ceiling, except partition, shall have oak batten strips, not less than nominal 2 inch by 2 inch, or nonferrous upright stringers secured to high impact plastic spacers and screws. Space shall be provided for the flush mounted components specified herein. The interior finish paneling shall be secured to the oak batten strip, or the nonferrous uprights, by use of countersunk screws of a length that shall not penetrate through batten strips.

* 3.6.13.2 U-channel. A U-shaped channel having a minimum dimension of 12 gage (0.1046 inch), by 1-3/8 inches in depth, 1-5/8 inches in width, with an opening of 7/8 inch shall be furnished. The channel, for reference purposes, shall be model P-3000, manufactured by Unistrut Corporation or equal. The channels shall be the full length of the body and shall be recessed and flush

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

mounted to the finished floor, side walls, and ceiling. The U-shaped channel shall be installed to minimize the transfer of heat at the points of attachment (see 3.6.1.3). The channel shall be of corrosion-resistant material. An end cap shall be furnished in the end of each row.

3.6.13.2.1 Channel locations. The U-shaped channels shall be located in two longitudinal rows recessed in the ceiling and in the floor. Channels shall be parallel to each other. Channels shall be measured from the centerline of the channel. The floor and ceiling channels shall be measured 24 inches from the side walls. Each side wall shall have three longitudinal rows. One row shall be measured 4 inches from the floor, one row shall be 4 inches from the ceiling, and one row shall be spaced equally between the top and bottom channel.

3.6.13.3 Interior tiedown rings. Tiedown rings shall be furnished. Tiedown rings, for reference purposes, shall be model 170 or model 172 recessed rope ring, as manufactured by Eberhard Manufacturing Company, or equal. Each tiedown ring and its attachment shall be capable of withstanding a 2,000 pound pull in the vertical position and in a 45 degree angle to the vertical position. Tiedown rings shall be so installed as to minimize transfer of heat (see 3.6.1.3) and shall be mounted flush with the floor. Tiedown rings shall be corrosion resistant.

3.6.13.3.1 Tiedown ring locations. Tiedown rings shall be located in two longitudinal rows flush mounted in the floor as specified herein. Tiedown ring locations shall be 12 inches from the longitudinal centerline of the vehicle to the centerline of the ring of the tiedown plate. Tiedown rings shall be longitudinally spaced 24 inches apart on the centerline of the ring. The first tiedown ring in each row shall be located on the first crossmember that is closest to 6 feet from the rear of the vehicle, with six tiedown rings in each row, and rings shall be perpendicular to each other on the transverse plane, i.e., the opening direction of the tiedown rings in the left and right rows of tiedowns shall be to the left and right side walls of the body respectively.

* 3.6.13.4 Floor covering. The complete floor area and any steps over the gooseneck shall be covered with vinyl conforming to L-F-475. Unless otherwise specified (see 6.2), the color of the floor covering shall be light tan. Floor covering shall be installed with waterproof cement and shall lay flat with no air pockets. Seams shall be tight to one another. Entrance doors and steps shall have corrosion-resistant, extruded metal moldings to protect edges of floor covering. Floor covering shall be sealed around its perimeter to prevent water entrapment and to prevent corrosion.

3.7 Air conditioner and heater.

3.7.1 Air conditioner. An air conditioner shall be furnished. The air conditioner shall meet the requirements specified in 3.3.4.1. The air conditioner shall have a rated capacity of not less than 36,000 British

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

thermal units per hour (Btu per hr). Air conditioners shall be located either on the outside front or in the forward compartment in the left front streetside of the vehicle. The air conditioner shall be of vertical design. The electric supply shall be 208-volt, 3-phase, 60 hertz (Hz), 4-wire alternating current (ac). The air conditioner shall be mounted and insulated to prevent transfer of vibration under any of the operating conditions specified herein. When an inside mounted air conditioner is furnished, it shall be capable of being removed for service through the partition sliding door (see 3.6.12). When an outside front air conditioner is furnished, the partition specified in 3.6.12 shall not be furnished.

3.7.1.1 Heaters. When the air conditioning system is being used for heating the vehicle, the heating system shall meet the requirements specified in 3.3.4.2.

3.7.2 Controls. Air conditioning and heating controls shall be provided. Controls shall be located near the air return opening and at a point to allow easy reading and adjusting, or may be combined with the thermostat and located as specified in 3.7.3. Controls shall be capable of changing from cooling to heating.

3.7.3 Thermostat. A thermostat shall be furnished to maintain heating and cooling and shall be manually adjusted within plus or minus 4°F. The thermostat shall have an index range from 50°F to 90°F. The thermostat shall be located in the forward section of the van near the air return opening. The thermostat shall not be located near an air outlet.

3.7.4 Condenser air opening. When an inside mounted air conditioner is furnished, the condenser air opening shall be provided in the vehicle wall for flow of air to and from the condenser and to the fresh air inlet. The opening shall be air and watertight between the walls of the vehicle and around the opening. The opening shall have automatically operated louvers with screens.

3.7.5 Air distribution system. An air distribution system shall be furnished which recirculates conditioned air and warmed air through air ducts into the front and rear of the vehicle, and returns the air to the air conditioner and heater unit. Heating and cooling air ducts protruding from the ceiling shall be insulated on the topside and covered with a nonabsorbent type of waterproof covering on either exterior or interior surface areas that protrude below the ceiling. However, ductwork need not be insulated when it is located below an insulated ceiling. The covering shall prevent condensation forming on the exterior surfaces. The floor to ceiling height may be reduced by the thickness of the covering. The air conditioning and heating unit shall be provided with a plenum chamber connecting the unit and the external opening (see 3.7.7) with the conditioned air system. A damper shall be furnished for operating the unit. The air distribution system shall be corrosion-resistant. The system shall be so installed as to prevent transfer of vibration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

3.7.5.1 Conditioned air discharge. The cooled and warmed air distribution system shall extend from the front to the rear of the vehicle. The system shall be provided with dampers in the duct system to regulate the air velocity. Dampers shall indicate the open or closed position. The cooled and warmed air shall discharge through manually operated damper diffusers.

3.7.5.2 Discharge dampers. Discharge air dampers shall be installed in the ceiling. The dampers shall have adjustable diffusers to regulate the flow of air. The damper diffusers shall direct the air movement toward the sides of the body. Dampers shall be manually operated and shall provide a floor-to-damper height as specified in 3.6.13.

3.7.6 Pressure drop. The air distribution system shall have a pressure drop of not more than 0.75 inch of water.

3.7.7 External air distribution connection. Two heavy duty, 8-inch outer diameter (od), sheet metal connectors, with a rolled lip on the outer edge covered with an airtight and watertight hinged cover, shall be provided. The external input duct connection shall be connected to the plenum chamber (see 3.7.5). A damper shall be provided adjacent to the interior wall which shall indicate the opened or closed position. The hinged cover shall have a rubber gasket with a standard, commercial, corrosion-resistant, spring loaded latch. The latch shall be designed to hold the cover closed so that the cover is watertight, rattle-free, and does not come open or loosen during transport of the semitrailer. The external duct connector shall supply warm or cool air from an external source in lieu of the air conditioning and heating unit. Connections shall be located near the left front of the vehicle.

* 3.8 Compressed air supply system. A compressed air supply system shall be furnished for receiving and distributing compressed air from a Government supplied external source. This source will be connected to the compressed air system and receiver tank of the semitrailer by means of an external air intake coupling located in the 8-inch by 8-inch opening described in 3.8.1. The system shall conform generally to figure 1 and shall include a compressed air intake coupler, air lines, air receiver tank, valves, pressure gages, strainer (filter), and 1/4-inch compressed air outlets in the front equipment area and rear working area. The air supply lines to the 1/4-inch compressed air outlets on the curbside and streetside of the vehicle shall be recessed within the vehicle body walls and suspended to prevent vibration and chafing. The air supply system shall be accessible for service without loss of insulation. Metals shall be compatible to one another to prevent galvanic or electrolytic action.

3.8.1 Compressed air intake. The vehicle shall be furnished with a compressed air intake located in the front or curbside wall of the semitrailer as near the front curbside corner as practical. The air intake coupler connection shall be located in an 8-inch by 8-inch compartment,

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:22Z
Check the source to verify that this is the currentversion before use.

located not less than 12 inches above floor level, and of sufficient depth for the air line coupler. The compartment shall be furnished with a hinged external door with a rubber gasket and a standard commercial spring loaded latch designed to hold the cover closed, so that the cover is weathertight and will not open or work loose during transport of the semitrailer. The compartment shall be lined with a nonferrous sleeve and shall be airtight and watertight.

* 3.8.1.1 Air line coupler. A 1/2-inch quick disconnect air fitting shall be furnished in the 8-inch by 8-inch compartment. The fitting shall be of the plug-in type which opens when plugged in and closes when pulled out, and shall be provided with both male and female fittings. The coupler shall be mounted to 3/4-inch seamless, heavy duty, copper tubing, projecting into the interior walls. The copper tubing shall have a working pressure of not less than 400 psi and a wall thickness of not less than 0.065 inch.

3.8.2 Coupler to receiver tank. The air supply from the coupler to the receiver tank shall be through the 3/4-inch heavy duty, seamless copper tubing. This air line shall be furnished with a 3/4-inch brass air shutoff valve.

* 3.8.3 Air receiver. The air receiver tank shall be a commercial tank adequate to meet specified requirements and shall have a nominal capacity of 30 gallons. The tank shall be of the horizontal type with sufficient capacity to provide 200 psi pressure to the 1/4-inch outlets specified in 3.8.7. The tank shall be constructed in accordance with the ASME Boiler and Pressure Vessel Code, Section VIII. Certification shall be furnished that the receiver tank meets the requirements specified herein. The tank shall be mounted on a substantial bedplate and the bedplate secured to the platform with corrosion-resistant bolts, nuts, washers, and lock washers. An air strainer, with water trap and water reservoir to collect moisture, shall be furnished. The air strainer shall be adjacent to either the 3/4-inch air shutoff valve in the air receiver inlet line or in the air receiver discharge line. The water reservoir shall be furnished with an exhaust valve and a line to expel water through the floor to the vehicle exterior. Felt or sintered metal filters and a screen to prevent air line contamination shall be provided.

3.8.3.1 Air receiver components. Air receiver components shall include at least the following:

(a) Receiver safety and relief valve(s)
(b) Drain valve and line to expel water through the floor
(c) Service valve
(d) Shockproof pressure gage.

3.8.4 Receiver discharge air line. The air receiver discharge shall be connected to a 3/4-inch air supply line. The connection shall include a 3/4-inch brass union and a 3/4-inch brass air shutoff valve.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the currentversion before use.

3.8.5 Air supply lines. Air supply lines shall be furnished to each side of the vehicle. The main air line shall be 3/4-inch, heavy duty, copper tubing having a working pressure of not less than 400 psi and a wall thickness of not less than 0.065 inch. The 3/4-inch air line shall be connected to at least 5/8-inch service air lines with a union and a 3/4-inch brass valve on each side of the vehicle to permit personnel to shut off the air supply on either side of the vehicle. The 5/8-inch service air lines shall extend from near the receiver tank at the front of the vehicle to within 4 feet of the rear service doors on each side of the vehicle. The service air lines shall be located 48 ± 2 inches above floor level and shall be recessed into the body wall. The air lines on each side of the vehicle shall be provided with at least 5/8-inch air pressure regulator as specified in 3.8.6. The air supply lines shall be secured to prevent vibration within the wall and shall be accessible for service. Clamps, when employed, shall be chafeproof.

3.8.6 Air pressure regulators. An air pressure regulator with gage shall be provided for each of the minimum 5/8-inch service supply lines on the streetside and the curbside of the semitrailer. The air pressure regulators shall be adjustable to operate at 150 psi to 10 psi. The air pressure gage shall be shockproof against both vibration and line pressure shock. The gages shall indicate air pressure to the service lines on each side of the vehicle. An air pressure regulator shall also be supplied in the 3/4-inch main air supply line, if required to maintain constant pressure in the system.

* 3.8.7 Compressed air outlets. The service air lines shall be connected to the 1/4-inch, wall mounted compressed air outlets. Not less than four 1/4-inch compressed air outlets shall be furnished on each side to the rear of the gooseneck, landing legs, or partition, located 48 ± 2 inches from floor level and 12 ± 2 inches forward of each duplex electrical convenience receptacle (see 3.9.2.3.1 and 3.9.2.3.2). One 1/4-inch compressed air outlet shall be furnished in the front equipment area, on the streetside wall above the air receiver tank. Each compressed air outlet shall be furnished with a 1/4-inch swivel adapter and a check unit for quick disconnect of a hose line. Outlets shall be mounted as flush to the wall as practicable while still facilitating the use of the swivel adapter quick disconnects.

* 3.9 Interior electrical system. The vehicle shall be furnished with three electrical systems as follows:

(a) 12-volt dc system (see 3.6.7 and 3.9.1)
(b) 110-volt ac, single-phase, 60 Hz system
(c) 208-volt ac, three-phase, 60 Hz, four-wire system.

The vehicle interior electrical system shall be in E. M. T. (thinwall) conduit (galvanized electrical metallic tubing) with compression type connectors. Joints shall be threaded with connections at all lamps and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

junction boxes, excluding boxes around the lights. Junction boxes shall be accessible and provided with junction box covers. Wiring shall be color-coded at junction boxes and at the distribution panel(s) for identification purposes. The conduit shall be recessed within the vehicle body wall, supported with locktight conduit clamps having chafeproof faces and so installed as to prevent vibration. All electrical assemblies, wiring, components and parts shall be weatherproof and shall meet the operating conditions specified herein. Conduits shall be provided with vents in a weather-protected location except when electrical insulation is of the type that is fungus and moisture resistant. Wiring shall conform to SAE J1292 and shall be of sufficient size and gage to accept the loads imposed in operating the electrical system without loss of dielectric strength. The 110-volt ac and 208-volt ac systems shall receive power from an outside source. Wiring shall be accessible for service. The electrical system shall be in accordance with the requirements of NFPA No. 70.

3.9.1 Interior lamps, 12-volt. Two 12-volt lamps shall be provided. Lamps shall be mounted in the ceiling. The lamps shall be provided with a white nonglare reflector. One lamp shall be located over the curbside entrance door and one lamp shall be located to provide light to the 110/220-volt power distribution panel(s). Both lamps shall be serviced with a single on-and-off switch, located at the curbside door.

3.9.2 Electrical system, 110-volt. The vehicle shall be equipped with a 110-volt, single-phase, 60 Hz electrical system for interior lighting and for the electrical duplex outlets.

3.9.2.1 Distribution panel, 110-volt. A distribution panel for the 110-volt electrical system shall be furnished. The panel shall be rated for not less than 100 amperes. The panel shall be equipped with automatic circuit breakers and shall be grounded. The panel shall be provided with not less than 10 circuits. In addition, two 15-ampere circuits shall be furnished for future expansion purposes. The panel door shall be hinged and provided with a combination latch, and shall be capable of locking with a padlock. The distribution panel shall be furnished with a main breaker or throw switch. A circuit diagram shall be furnished in addition to that specified in 3.1.1.1.1. The 110-volt distribution panel may be combined with the 208-volt, three-phase panel (see 3.9.3), providing specified circuit breaker protection is furnished for all circuits.

3.9.2.1.1 Distribution panel mountings. The 110-volt or combination 110/208-volt electrical distribution panel shall be located on the interior as close as practicable to the curbside front corner.

3.9.2.2 Electrical lighting and switches, 110-volt.

3.9.2.2.1 Lighting, fluorescent. Fluorescent lamps and fixtures shall be furnished. The lamps shall be located in two longitudinal rows, spaced 30 inches from the curbside and streetside walls. There shall be not less than five double lamp fixtures per row. Each lamp shall be 48 inches in length

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

and of 40-watt rating. The lamps shall provide a broad distribution of light. Lamps shall be white. A nonglare reflector and tube guard shall be provided. Lamps shall be so installed as to provide a headroom of not less than 76 inches, except for the frontmost lamps when a gooseneck is furnished.

* 3.9.2.2.2 Lamp switches. Two light switches shall be furnished for the fluorescent lights. One switch shall operate the six fluorescent lights (located in two rows) at the rear of the vehicle and the other switch shall operate the four fluorescent lights (located in two rows) at the front of the vehicle. The switches shall be flush mounted on the curbside partition wall facing the rear compartment, or adjacent to the curbside door. Switches shall be grounded.

3.9.2.3 Electrical wall receptacles, 110-volt.

3.9.2.3.1 Electrical wall receptacle (rear working area). Not less than four electrical duplex wall receptacles shall be furnished on both curbside and streetside of the vehicle. Receptacles shall be flush mounted. Receptacles shall be located 48 ± 2 inches from the finished floor, with the first curbside receptacle being 3 feet rearward of the curbside entrance door. The first streetside receptacle shall be located 4 feet rearward of the gooseneck step, landing legs or partition, whichever is the most rearward. The last receptacle on each side shall be located 3 feet forward of the rear service doors. The intermediate receptacles shall be equally spaced. Receptacles shall be grounded.

3.9.2.3.2 Electrical wall receptacle (front equipment area). An electrical duplex wall receptacle shall be furnished. The receptacle shall be flush mounted and shall be located 48 ± 2 inches above the finished floor and adjacent to the 110-volt distribution box. The receptacle shall be grounded.

3.9.2.4 Circuits, 110-volt. The electrical circuits for the lighting and receptacles shall be grouped as follows:

(a) Fluorescent lamp, two circuits of not less than 20 amperes each (one circuit for each row of lamps)
(b) Duplex wall receptacles, two circuits of not less than 15 amperes for each side
(c) Duplex receptacle and ceiling lighting fixtures over the gooseneck (or forward of the landing legs) and entrance light, one circuit of not less than 20 amperes.

The wall switches shall have a capacity of not less than the ampere rating of the circuits.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

3.9.2.5 Receptacle face plates. Receptacle face plates shall be of nonconductive and noncombustible material. Each wall switch shall be marked for its purpose and each duplex receptacle marked for its nominal voltage rating (e.g. "110-volts").

3.9.3 Distribution panel, 208-volt. A distribution panel for the 208-volt ac, three-phase, 60 Hz, four-wire system shall be furnished. The distribution panel shall provide 208-volt ac, three-phase, 60 Hz to the air conditioner and heater (see 3.7) and shall also include two additional circuits for future expansion. In addition, the distribution panel shall provide 110-volt ac, single-phase, 60 Hz power to the 110-volt distribution panel (see 3.9.2.1). The 208-volt distribution panel may be combined with the 110-volt distribution panel (see 3.9.2.1). The panel shall receive power from an external power source. Automatic circuit breakers shall be furnished. The panel shall have sufficient capacity to meet the electrical requirements of the vehicle specified herein and an allowance for the two additional circuits. The panel shall be grounded. The panel door shall be hinged and provided with a combination latch, and shall be capable of being locked with a padlock. A throw switch shall be furnished. The circuit diagram shall be furnished in addition to that specified in 3.1.1.1.1.

3.9.3.1 Panel mounting. The 208-volt panel shall be combined with or mounted adjacent to the 110-volt panel specified in 3.9.2.1.

* 3.9.4 Power supply receptacle. A 25-kW three-phase, four-wire, 208- to 220-volt receptacle shall be furnished. The receptacle shall be mounted on the front of the semitrailer or flush mounted on the exterior side, on the curbside of the vehicle below the 208-volt distribution panel (see 3.9.3). The receptacle shall be furnished with a screw cover (threaded) attached with corrosion-resistant chain and shall be waterproof. The receptacle shall be grounded to the vehicle chassis. The receptacle shall have sufficient dielectric capacity to meet the imposed loads.

* 3.9.4.1 Power supply cable. A power supply cable of neoprene rubber, not less than 25 feet in length, shall be furnished. The cable shall have a plug and cap with corrosion-resistant chain on one end and a polarized twist lock fastener and mating connector (for installation by the using activity) on the opposite end. The cable shall be of sufficient dielectric strength to meet the loads imposed. The power supply cable shall be for a 208 to 220-volt, 60 Hz, three-phase, four-wire system.

* 3.10 Fire extinguishers. Two Halon 1301 fire extinguishers, NSN 4210-00-555-8837, shall be furnished. One extinguisher shall be located adjacent to the curbside door and one extinguisher shall be located adjacent to the rear doors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

* 3.11 Tools. Special tools that are required for disassembly and assembly of components for aircraft transport shall be provided. Tool stowage shall be provided in the vehicle in the front equipment area. The stowage compartment shall be furnished with a hinged cover, a hasp for a 3/4-inch padlock and a drain hole. The stowage compartment shall have bins with retaining clamps to retain tools during aircraft and road travel. The stowage compartment shall be of not less than 16 gage (0.0598 inch) sheet steel. The compartment shall be reinforced. The stowage compartment shall be demountable.

3.12 Servicing and adjusting. Prior to acceptance of the vehicle by the Government inspector, the contractor shall service and adjust each semitrailer and its mounted equipment for operational use, including at least the following: adjustment of the brake system, compressed air lines, air conditioning and heating systems; inflation of all tires; and complete lubrication of chassis and components.

3.13 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished. The welded, bolted, and riveted construction utilized in vehicle manufacture shall be in accordance with the highest standards of the industry.

3.13.1 Dissimilar metals. All dissimilar metals used throughout the vehicle shall be insulated from one another to prevent galvanic or electrolytic action. Contact faces shall be primed and faced with mylar barrier tape as specified herein. All crevices shall be primed with a highly alkaline resistant primer that resists corrosion and shall be sealed to prevent corrosion.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility for

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods, and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

4.3 First vehicle preliminary inspection. The first in-process vehicle inspection shall be performed by the Government to evaluate workmanship and to determine conformance with contractual requirements.

4.3.1 Treatment of materials. Each vehicle shall be inspected to verify that dissimilar materials have been treated as specified in 3.4.1.3 and 3.13.1.

4.3.2 Installation of recessed components. The first in-process vehicle shall be inspected to verify that the following recessed components are furnished and installed as follows:

(a) Insulation (see 3.6.2.6)
(b) Partition if air conditioner is mounted inside (see 3.6.12)
(c) U-channel (see 3.6.13.2)
(d) Interior tiedown ring(s) (see 3.6.13.3)
(e) Air distribution system (see 3.7.5)
(f) Compressed air supply system (see 3.8)
(g) Interior electrical system (see 3.9).

4.3.3 Water spray test. Each vehicle shall be subjected to a 100 percent water spray test before the installation of the insulation and subfloor. The test shall be as specified in 4.4.3.

4.3.4 In-process inspection of vehicle and components. The first complete assembled vehicle and components shall receive an in-process inspection by the Government prior to installation of the vinyl or linoleum and the prime painting of the interior and exterior of the vehicle. The inspection shall be conducted to evaluate workmanship and to determine conformance to contractual requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

4.4 First production vehicle inspection. The first vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformance with the requirements of the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

* 4.4.1 Weight and payload capacity. The first production vehicle shall be weighed to determine the curb weight and distribution of the curb weight on the axle and kingpin. The total imposed loading on the axle and kingpin shall be computed by the contractor and verified by the Government using the curb weight and payload as specified. Calculated imposed loads on the axle shall be compared to the suspension, axle and tire load capacity ratings to determine if these components are of adequate capacity to meet contractual requirements.

* 4.4.2 Road test. The first production semitrailer shall be examined and road tested with and without payload for a total of 200 miles. The road test shall be conducted by the contractor under the direction and surveillance of Government representatives to assure that the semitrailer will operate in accordance with contractual requirements. The distance traveled shall consist of improved (see 6.3.1) and unimproved roads (see 6.3.2) with sharp turns and rocks. The semitrailer (with payload), coupled to a truck tractor, shall be driven at speeds of 55 mph for 100 miles over improved roads, and at speeds of 20 to 25 mph for 50 miles over unimproved roads. The semitrailer (without payload), coupled to a truck tractor, shall be driven 25 miles over improved roads and 25 miles over unimproved roads. For each 25 miles of travel, at least one sudden stop shall be accomplished. During the road test the semitrailer shall be observed to determine conformance to 3.3.2. Upon completion to the road test, the vehicle shall be inspected for leakage, weld quality, permanent deformation, misalinement or any other defects, and refurbished prior to offering for Government acceptance.

4.4.3 Water spray test. The first production vehicle shall be water spray tested after the road test. Each vehicle on the contract shall be subjected to a water spray test and shall be free of leakage after exposure to a 100 percent water spray for not less than 15 minutes. Test may be conducted in sections. The spray shall be delivered by nozzles operating at not less than 25 psi water pressure, sufficient in number and so placed (approximately 2 feet from the body) to afford full coverage of the sides, roof, front, rear, and undercarriage of the body. During the test, doors shall be closed as in normal travel position.

4.4.4 Tiedown devices. Exterior and interior tiedown devices shall be as specified in 3.1.1.7 and 3.6.13.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

4.4.5 Air conditioning. Air conditioning shall be as specified in 3.3.4.1 and 3.7. The inside and outside of the vehicle shall be exposed to a 110°F ambient air temperature for a minimum of four hours with doors open. The vehicle doors shall then be closed. When the inside and outside temperatures are equalized, the air conditioner shall be operated. Within 30 minutes of air conditioner operation, the recorded temperature inside the semitrailer shall be not greater than 80°F dry bulb and 68°F wet bulb.

4.4.6 Heating. Heating shall be demonstrated as specified in 3.3.4.2.

4.4.7 Rear axle and suspension system. The rear axle and suspension system shall be removable from the vehicle for aircraft transport (see 3.1.1.6). Removal and replacement of the rear axle and suspension system shall be demonstrated by use of the lifting pads (see 3.1.1.9). The system shall be easily removable and replaceable in the correct alinement position by the use of dowel pins, and shall be secured with fasteners. The connection of the air brake system with the detachable air brake hose connections specified in 3.6.4 shall be accomplished.

4.4.8 Electrical system. The electrical system shall be checked for conformance to the requirements of 3.9. The electrical system shall be demonstrated with the air conditioner operating and all lighting on. The lighting shall be observed for fade during the phase-in period of the air conditioning compressor. The power and electrical circuits shall be verified to ascertain that the power load is in accordance with the specification requirements and the loads imposed.

4.4.9 Compressed air supply system. The compressed air supply system shall be checked for requirements as specified in 3.8.

4.4.10 Landing gear. The landing gear shall be checked for conformance to the requirements of 3.6.8.

4.4.11 Leveling jacks. Leveling jacks shall be checked for conformance to the requirements of 3.6.9.

4.4.13 Wood treatment certification. Manufacturer's records shall be available to verify that all wood requiring treatment in accordance with MIL-STD-1223 has been treated.

4.4.14 First production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample and shall be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

4.4.14.1 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under contract until corrective action has been taken.

4.5 Inspection of production semitrailer. The contractor's inspection system shall, as a minimum, assure that the semitrailer conforms to the physical and dimensional requirements and is capable of meeting the performance requirements contained herein.

4.6 Inspection of the preparation for delivery. Vehicle preparation for delivery shall be inspected to verify conformance to the requirements specified in 5.1.

5. PACKAGING

5.1 Vehicle processing. Semitrailers shall be processed for shipment, from the manufacturer's plant to the initial receiving activity, in accordance with the manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use. The vehicles covered by this specification are intended for use by the Government for transporting equipment by air transport.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Identification of appropriate service for exterior color for painting and marking (see 3.1.1.1).
(c) Rustproofing, if required (see 3.1.1.3).
(d) Body type, if other than as specified (see 3.4.1).
(e) Other type of tires, if required (see 3.6.5.2).
(f) If spare wheel or rim is not required (see 3.6.5.4).
(g) If spare tire is not required (see 3.6.5.5).
(h) Color of floor covering if other than as specified (see 3.6.13.4).

6.3 Definitions.

6.3.1 Improved roads. An improved road is a smooth, hard surfaced road, such as a concrete or asphalt paved highway.

6.3.2 Unimproved roads. An unimproved road is an unpaved, unstabilized road with an undulating surface, having occasional chuckholes and exposed rocks.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

* 6.4 Subject term (key word) listing.
Semitrailer van
Air transportable semitrailer van.

* 6.5 Identification of changes. The margins of this specification are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document regardless of the marginal notations and relationship to the last previous issue.

Custodians:
Army - AT
Air Force - 99

Review activities:
Air Force - 84

Preparing activity:
Army - AT

Project No.2330-A968

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.




Figure 1 Compressed Air System Typical Schematic

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
U.S. Army Tank-Automotive Command
ATTN: AMSTA-UED
Warren, MI 48937-5000

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. *Fold on lines on reverse side*, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If *there are additional papers*, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or *clarification of specification* requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the *referenced document(s)* or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-S-62052C SEMITRAILER, VAN: AIR TRANSPORTABLE, 5½ TON, AIR CONDITIONED, COMMERCIAL

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSF OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.