NOT MEASUREMENT SENSITIVE

MIL-S-62080D
1 October 1991
SUPERSEDING
MIL-S-62080C
28 October 1987

MILITARY SPECIFICATION

SEMITRAILERS, TANK: POTABLE WATER, 2,000 TO 5,500 GALLON, COMMERCIAL

This specification is approved for use by all departments and agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers 2,000 to 5,500 gallon, single and tandem axle, tank type semitrailers for transporting potable water. Vehicles procured under this specification are commercial items which are warranted by the manufacturer as specified in acquisition documents.

1.2 Classification.

1.2.1 Sizes. The semitrailer shall be one of the following sizes, as specified (see 6.2):

Size 2 - 2,000 gallon tank
Size 3 - 3,000 gallon tank
Size 4 - 4,000 gallon tank
Size 5 - 5,500 gallon tank.

1.2.2 Style. The semitrailer shall be one of the following styles, as specified (see 6.2):

Style A - Gravity discharge
Style B - Forced discharge.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-UED, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC-2330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS), and supplement thereto, cited in the solicitation (see 6.2).

	SPECIFICATIONS	
	FEDERAL	
*	W-B-131	- Battery Storage: Vehicular, Ignition, Lighting and Starting.
	MILITARY	
*	MIL-P-514	- Plates, Identification, Instruction and Marking, Blank.
	STANDARDS	
	FEDERAL	
*	FED-STD-297	- Rustproofing of Commercial (Nontactical) Vehicles.
	MILITARY	
	MIL-STD-1223	- Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking and Data Plate Standards.
*	MIL-STD-1474	- Noise Limits for Army Materiel.
	MS 75021	- Connector, Receptacle, Electrical: 12-Contact, Intervehicular, 28-Volt, Waterproof.

* (Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, Military Specifications and Standards, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

* DEPARTMENT OF DEFENSE
Department of Defense Index of Specifications and Standards (DODISS).

(Copies of the DODISS are available on a yearly subscription basis either from the Government Printing Office for hard copy, or microfiche copies are available from the Director, Navy Publication and Printing Service Office, 700 Robbins Avenue, Philadelphia, PA 19111-5093.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF TRANSPORTATION (DoT)
Federal Motor Carrier Safety Regulations.
Federal Motor Vehicle Safety Standards.

(Application for copies of DoT publications should reference the code of Federal Regulations, 49 CFR, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

FOOD AND DRUG ADMINISTRATION (FDA)
Indirect Food Additives: Polymers (21 CFR 177).

(Application for copies of FDA publications should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

* 2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN NATIONAL STANDARD INSTITUTE, INC. (ANSI)
American National Standard Pipe Thread Series.

(Application for copies of ANSI publications should be addressed to the American National Standard Institute, 1430 Broadway, New York, NY 10018.)

* THE EUROPEAN TYRE AND RIM TECHNICAL ORGANISATION (ETRTO)
Standards Manual

(Application for copies of the ETRTO publications should be addressed to the European Tyre and Rim Technical Organisation, 32, Avenue Brugmann, 1060 Brussels, Belgium.)

SAE, INC.
SAE Standards and Recommended Practices

	J318	- Air Brake Gladhand Service (Control) and Emergency (Supply) Line Couplers - Trucks, Truck-Tractors, and Trailers (DOD adopted).
*	J551	- Performance Levels and Methods of Measurement of Electromagnetic Radiation from Vehicles and Devices (30-1000 MHz).
	J560	- Seven-Conductor Electrical Connector for Truck-Trailer Jumper Cable.
	J682	- Rear Wheel Splash and Stone Throw Protection (DOD adopted).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

J700	- Fifth Wheel Kingpin - Commercial Trailers and Semitrailers (DOD adopted).
J702	- Brake and Electrical Connection Locations - Truck-Tractor and Trailer (DOD adopted).
J1292	- Automobile, Truck, Truck-Tractor, Trailer and Motor Coach Wiring.

(Application for copies of SAE publications should be addressed to SAE, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

* THE TIRE AND RIM ASSOCIATION, INC.
Year Book.

(Application for copies of Tire and Rim Association publications should be addressed to The Tire and Rim Association, Inc., 175 Montrose West Ave., Copley, OH 44321.)

* (Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.4, the vehicle, components, assemblies, and accessories to be delivered under the contract shall be standard or optional items, which meet or exceed the requirements of this specification. All items shall be as represented and rated in the vehicle manufacturer's technical data book. Special bodies or mounted equipment shall be as represented in the body and equipment manufacturer's technical data. Technical data shall be limited to specifications and technical material identical to that furnished to the authorized company representatives for selection of vehicle models and components, and shall be available to the engineering offices of the procuring activity, prior to delivery of the items. The model furnished shall be not older than the manufacturer's current model on the date of invitation for bids.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 3.1.1.1 Treatment and painting. The vehicle shall be treated and painted in accordance with MIL-STD-1223. As specified by the procuring activity for the appropriate service (see 6.2), the exterior color shall be in accordance with MIL-STD-1223. The exterior of the tank stainless steel members shall be unpainted, with a 2B or better finish, free of blemishes, discoloration and other visible defects (see 3.22.2). The frame and undercarriage shall be treated and painted in accordance with MIL-STD-1223 in a gloss black color.

* 3.1.1.2 Marking and data plates. As specified by the procuring activity for the appropriate services (see 6.2), identification marking and data plates shall be in accordance with MIL-STD-1223.

* 3.1.1.3 Rustproofing. When specified (see 6.2), the semitrailer shall be rustproofed in accordance with FED-STD-297.

3.1.1.4 Toxic products and formulations. The materials used in the construction or treatment of surfaces, which may be in contact with potable water during use, shall have no adverse effect on the health of personnel. Materials used shall be non-toxic, relatively non-absorbent, resistant to fat and normal cleaning with bactericidal solutions, and shall not contaminate the water or affect the smell or taste of the water. Nozzle and faucet seals shall be free of asbestos impregnated materials. Parts, fittings, pumps, and piping in contact with water shall be of corrosion-resistant material not affecting the potability of water. Fabrication of the tank and piping system shall be such that it shall not cause or result in contamination of drinking water. Rubber or plastic materials used on the interior surfaces of gaskets or hoses that contact potable water shall meet the requirements of 21 CFR part 177, except materials constructed of acrylonitrile and co-polymers shall not be used. Manufacturers shall submit evidence to this effect for review and approval by the procuring activity. Such evidence shall be submitted within 10 days from date of receipt of contract and shall identify all materials that come in contact with potable water. Materials shall withstand handling and usage in ambient temperatures of minus 40 degrees Fahrenheit (°F) to plus 135°F.

* 3.1.1.15 Brake lights. At least one pair of brake lights shall override the four-way emergency flasher or the two systems shall be independent of each other. Modifications to the manufacturer's standard product to accommodate this requirement shall not compromise conformance to any Federal Motor Carrier Safety Regulation referenced herein or to any Federal Motor Vehicle Safety Standard. If additional lights are added to the vehicle, the lights shall be selected from the chassis manufacturer's standard matching hardware.

3.2 General design.

3.2.1 Federal Motor Vehicle Safety Standards. The vehicle and furnished accessories shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 3.2.2 Dissimilar metals. All dissimilar metals used throughout the vehicle shall be insulated from one another to prevent galvanic or electrolytic action.

3.2.3 Ratings. Vehicle ratings shall be the manufacturer's published ratings. Component and vehicular ratings shall not be raised to meet the requirements of this specification. When published ratings are not available, verification of ratings must be submitted to the engineering office of the procuring activity. Minimum payload shall conform to 1.2 for the specified size of the vehicle.

* 3.2.4 Accessibility. The design of the vehicle and optional equipment shall permit access for routine servicing and shall permit access for replacement and adjustment of component parts and accessories with minimal disturbance of other components and systems.

* 3.2.5 Prohibited materials. Asbestos materials shall not be used in any form in any part of the vehicle. No item, part or assembly shall contain radioactive materials in which the specific activity is greater than 0.002 microcurie per gram or activity per item equals or exceeds 0.01 microcuries.

* 3.3 Performance. The semitrailer, fully equipped, with and without rated payload, shall evidence no part failure or permanent set when towed at speeds as great as 25 miles per hour over unimproved roads, and when towed at speeds as great as 60 miles per hour over improved roads.

3.3.1 Turning ability. The semitrailer shall be capable of assuming a 90 degree angle to the towing vehicle without cramping or damage to the semitrailer or the towing vehicle.

3.3.2 Tracking ability. The semitrailer shall conform to the tracking ability requirements of Federal Motor Carrier Safety Regulation 393.70(a) when towed under the conditions specified in 3.3.

3.3.3 Service brakes. The service brakes shall control, decelerate and stop the semitrailer-tractor combination, with the semitrailer loaded with specified payload, within the stopping distance requirements of Federal Motor Carrier Safety Regulation 393.52.

3.4 Payload capacity. The rated payload capacity shall be not less than the weight computed from the rated liquid volume, using 8.3 pounds per gallon.

3.4.1 Weight distribution. Load bearing members shall be rated for the loads imposed with the tank in a horizontal position, and the payload uniformly distributed in the tank. The gross weight on the axle(s) shall not exceed 18,000 pounds for single axle semitrailers, and 34,000 pounds for tandem axle semitrailers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

3.5 Dimensions and clearances. The semitrailer, uncoupled from the truck tractor, resting on its landing legs on level ground, without payload, and with the tank body within 1 percent of level, shall conform to the dimensions specified in table I.

TABLE I. Dimensions and clearances.

Requirement	Value
Overall length (maximum)	35 feet
Overall width (maximum)	96 inches
Ground clearance (minimum)	12 inches
Upper fifth wheel height, from the ground to the underside of the upper fifth wheel plate, plus or minus 1 inch	48 inches for sizes 2, 3 and 4. 52 inches for size 5
Distance from vertical centerline of kingpin to front end of semitrailer (plus 1 inch minus 2 inches)	36 inches
Landing wheel clearance. Radius from vertical centerline of kingpin to any point 6 inches or more below upper fifth wheel plate (minimum)	82 inches
Forward swing radius. From vertical centerline of kingpin to most distant point on semitrailer nose (maximum)	56 inches

3.6 Chassis components.

3.6.1 Frame. The semitrailer shall be of the frame or frameless type.

3.6.2 Stress analysis. The contractor shall perform a stress analysis. This analysis shall verify compliance with the requirements specified and shall include at least the following calculations and diagrams:

(a) The sprung gross weight distribution diagram;
(b) The vertical shear diagram for the length of the vehicle;
(c) The bending moment diagram for the length of the vehicle;
(d) The loads, sections, and stresses in members that carry maximum shear and moment, to include the analysis of the stresses in attaching weldments or other fastenings;

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

(e) The loads, sections, shear, and bending moment diagrams at kingpin and rear-underconstruction subframe members, and for the drop section when drop frame trailers are provided;
(f) The load, section, shear, and bending moment diagram for the most critical crossmember, to include the analysis of stresses in attaching weldments or other fastenings;
(g) The loads, sections, and stresses in members that carry maximum compression;
(h) A listing of all assumptions and references used to provide required data.

* 3.7 Tank body and equipment. The semitrailer shall be designed and constructed to meet the requirements of DOT Safety Regulation 178.345, MC306 for material, structural integrity, joints, supports and anchoring, circumferential reinforcement and minimum thickness, except in no case shall the minimum thickness of any part of the tank be less than 12 gage (0.1046 inch). Minimum thickness requirements shall be based on a product density of 8.3 pounds per gallon.

* 3.7.1 Material. The tank shell, baffles, bulkheads, pads, manholes, catwalk, access steps, grab handles, access ladders, fenders, insulation jacket, outlets, underslung cabinets, and hose tubes shall be of type 304 stainless steel. Thickness of shell, head and baffle sheets shall be not less than 12 gage (0.1046 inch) stainless steel. Tank combinations of mild steel, high strength low alloy steel, and austenitic stainless steel, as permitted by DoT Safety Regulation 178.345, shall not be furnished. All hose couplings, dust caps, dust plugs, dust cap and dust plug security chains or cables, valves, piping, tubing and strainers shall be of stainless steel. Faucets and nozzles shall be of stainless steel or brass. Where dissimilar materials are used, effective means shall be taken to impede electrolytic action. Teflon packing and tape shall not be used on adjacent parts that are of aluminum content.

3.7.2 Capacity. The liquid capacity of the tank shall be not less than that specified in 1.2.1 for the size of semitrailer required, plus at least 3 percent expansion space by volume. The tank shall have a single compartment.

3.7.3 Tank configuration. The tank shall have an elliptical, circular or modified rectangular section. The tank body may be provided with a slope to ensure the complete removal of liquids. When a slope is provided, it shall not exceed one percent of the tank body length.

* 3.7.4 Baffles. Where the provisions of DoT Safety Regulation 178.345 would require circumferential reinforcements, baffles shall be used in lieu of ring stiffeners. Baffles shall be flanged and dished. A half round or full round opening, of not less than 3-inch radius, shall be provided at the bottom of the baffles. Openings of equivalent size shall be provided at the top of the baffles. Each baffle shall also be provided with not less than an 18-inch diameter manway opening. The edges of the half round or full round openings and the manway opening shall have flanges of approximately 1 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 3.7.5 Manhole. The tank shall be equipped with a round or oval manhole opening not less than 19 inches in major diameter. Manhole sides and lip shall be constructed of stainless steel having a carbon content of not more than type 304 sheet steel. A lightweight, liquid-tight, easy opening, self-latching manhole cover, or a bolted cover with a liquid-tight, easy opening, self-latching fill cover not less than 10 inches in diameter, shall be supplied. Hinged covers shall be hinged at the forward edge. All metal parts of the cover exposed to contact with water in the tank shall be fabricated of type 304 stainless steel. Gaskets and seals shall conform to 3.1.1.4.

* 3.7.6 Vents. Air vents shall be provided to allow for expansion of the water in the tank and discharging the tank at maximum rate with the manhole and fill cover sealed. Vents shall be adequate to limit the tank pressure and vacuum under these conditions to those permitted by DOT Safety Regulation 178.346. Vents shall remain sealed when not fulfilling their purpose of equalizing internal and external pressures. The vents shall be easily removable for cleaning.

* 3.7.7 Catwalk. A flat catwalk, not less than 24 inches wide, running the full length of tank body, shall be provided at the top of the tank body. The catwalk shall be of stainless steel. The catwalk shall be of grip-strut material or shall be of the open grating type. The catwalk shall be flanged at the sides to form handholds for personnel. Unless an open grating type catwalk is furnished, drains shall be provided at the lowest points of the catwalk. Access steps and grab handles, or access ladders, shall be provided to assist personnel in reaching the catwalk from the ground.

* 3.7.8 Fenders. The semitrailer shall be provided with stainless steel fenders encircling at least the top half of the wheels. Rubber mud flaps shall be installed to the rear of the wheels. The mud flap installation shall conform to SAE J682. A metal strip not less than 0.125 inch thick and not less than one inch wide, extending the entire width of the mud flap, shall be installed to prevent the bolt heads or bolt nuts from damaging the mud flap. As an alternate method of attaching the mud flaps, tabs or clips with minimum surface contact dimensions of 1 inch high by 1.25 inch wide by 0.094 inch thick shall be furnished at each bolt.

3.7.9 Insulated tank. The tank and all piping shall be completely covered with a minimum of 2 inches of fiberglass insulation material. External rings shall be welded to the exterior of the inner tank to provide insulation space between the inner tank and the outer insulation jacket. The insulation jacket shall be not less than 0.036 inches thick. The insulation jacket shall completely enclose the tank, including the front, rear, top, sides and bottom. The insulation jacket shall be waterproof. A watertight double cover with insulation shall be provided over the manhole.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

3.8 Style A semitrailer (gravity discharge). In addition to the general requirements specified, style A semitrailers shall conform to 3.8.1 through 3.8.5.

3.8.1 Underslung cabinets. Underslung cabinets, constructed of stainless steel not less than 16 gage (0.0598 inch) in thickness, shall be provided on both sides of the semitrailer, extending from the rear wheelhousing forward to the gooseneck area. Each cabinet shall be of the full flanged, flush type. Cabinets shall have wooden tray shelves suitable for stowing strainers, couplings, and tools. Shelving in the curbside cabinet shall be removable. Racks or shelves for the discharge hose (see 3.8.3) shall be provided in the street side cabinet. Doors shall be side hung and equipped with hinges. Hinges shall have stainless steel hinge pins, and stainless steel, bronze, nylon or nylon insert sockets. Cabinets shall have provisions for flushing, draining, and for ventilation through fixed louvers. The cabinets shall be stormproof. Cabinet doors shall be provided with rubber bumpers and door retainers. The doors shall have latches and locking handles, keyed alike. Each cabinet shall be provided with a light. The cabinet interior shall have an unpainted, 2B or better finish.

3.8.2 Hose tubes. Stainless steel hose tubes of the dimensions required to stow the suction hose specified in 3.8.4 shall be provided on each side of the semitrailer. The hose tubes shall have drainage provisions and spring loaded dust tight stainless steel doors. Theftproof locking devices shall be provided on each tube cover, keyed the same as the cabinet doors.

3.8.3 Discharge hose. Three lengths of flexible hose, each 25 feet in length and 4 inches in nominal diameter, shall be furnished. Male and female couplings shall be furnished on each length of hose and shall be of the camlock type. A dust cap or dust plug shall be provided for each end of each hose length. Discharge hose shall be stowed in racks or shelves in the street side cabinets. Hoses and fittings shall conform to 3.1.1.4.

3.8.4 Suction hose. Four lengths of suction hose, each not less than 15 feet in length and 4 inches in nominal diameter, shall be furnished. The hose shall be noncollapsible and wire reinforced. Male and female couplings shall be furnished on each length of hose and shall be of the camlock type. A dust cap or dust plug shall be provided for each end of each hose length. The hoses and fittings shall conform to 3.1.1.4. The suction hose shall be stowed in the hose tubes.

3.8.5 Discharge outlet. The tank shall be provided with a 4-inch gravity discharge outlet located at the lowest point in the tank. The discharge outlet shall provide for complete discharge of the tank through a 4-inch pipe extending to the rear. The discharge plumbing shall consist of at least the following:

(a) An outlet valve, 4-inch, with slotted stops to meter flow of water;
(b) A mesh screen in the discharge outlet, ahead of the outlet valve, removable and accessible for cleaning purposes;

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

(c) A faucet with a cam-lock coupler, 4-inch, to mate with the suction and discharge hoses. The faucet shall be protected by the rear bumper, but shall be readily accessible for attaching the hoses;
(d) A dust cap with security chain for the faucet.

3.9 Style B semitrailer (forced discharge). In addition to the general requirements, style B semitrailers shall conform to 3.9.1 through 3.9.11.

3.9.1 Underslung cabinets for style B semitrailers. Underslung cabinets, constructed of stainless steel not less than 16 gage (0.0598 inch) thick, shall be provided on both sides of the semitrailer, extending from the rear wheelhousing forward to the gooseneck area. Each cabinet shall be of full flanged, flush type construction. The right (curbside) cabinet shall house the plumbing system, hose, hose reel, pump and pump engine. The left (streetside) cabinet shall be provided with a full-length, removable type, stainless steel shelf not less than 12 inches wide. Wooden trays suitable for stowing strainers, couplings, and tools shall be provided. Doors shall be side hung and equipped with hinges. Hinges shall have stainless steel hinge pins, and stainless steel, bronze, nylon or nylon insert sockets. Cabinets shall have provisions for flushing, draining, and for ventilation through fixed louvers. The cabinets shall be stormproof. Cabinet doors shall be provided with rubber bumpers and door retainers. The doors shall have latches and locking handles, keyed alike. Each cabinet shall be provided with a light. The cabinet interior shall have an unpainted, 2B or better finish.

3.9.2 Hose tubes for style B semitrailers. Stainless steel hose tubes, of the dimensions required to stow the suction hose specified in 3.9.4, shall be provided on both sides of the semitrailer. The hose tubes shall have drainage provisions and dust tight stainless steel doors. Theftproof locking devices shall be provided on each tube cover, keyed the same as the cabinet doors.

3.9.3 Pressure discharge hose, reel and nozzle. A hose reel with swivel valve shall be furnished with 100 feet of 1.5 inch inside diameter hose. A crank shall be provided for hand rewind of the winding mechanism. A ratchet device shall be provided to prevent tension or looseness on the hose. Four-way roller guides shall be provided to prevent damage to the hose when used other than straight out. The hose and reel shall be mounted in the right (curbside) cabinet. The free end of the hose shall be fitted with a delivery nozzle or a quick opening and closing faucet with a 1.5 inch diameter rigid spout. The nozzle, if furnished, shall be trigger action operated and shall be equipped with a 1.5 inch diameter rigid spout. A dust cap shall be furnished for the nozzle or faucet spout. The discharge hose, fittings, valve, nozzle, faucet and spout shall conform to 3.1.1.4.

3.9.4 Suction hose for style B semitrailers. Four lengths of suction hose, each not less than 15 feet in length, and a minimum of 2.5 inches in inside diameter, shall be furnished. Male and female couplings shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

furnished on each length of hose and shall be of the camlock type. A dust cap or dust plug shall be provided for each end of each hose length. The hose and fittings shall conform to 3.1.1.4. The suction hoses shall be stowed in the hose tubes.

3.9.5 Tank outlet valve. Not less than a 2-inch diameter flanged type outlet valve shall be installed at the lowest point in the bottom of the tank. The valve shall be attached to a flanged outlet welded to the bottom of the tank. The valve and installation shall permit complete removal of the valve body. A mesh screen to protect the valve shall be installed ahead of the outlet valve. The screen shall be removable for cleaning. Piping from the valve to the plumbing system in the right underslung cabinet shall be provided.

3.9.6 Valve control. A remote control for the outlet valve shall be located in the right (curbside) underslung cabinet. The control shall be provided with a stop to hold the valve in open position. The control shall be readily accessible and when in closed position, the outlet valve shall be effectively sealed.

* 3.9.7 Piping and couplings. All piping shall be not less than 2-inch inside diameter stainless steel tubing with long sweep bends or 2-inch nominal diameter stainless steel pipe with long sweep elbows. Piping shall be installed to withstand expansion and vibration without failure and shall conform to the strength requirements of DOT specification DOT 406. All portions of the discharge system, including the pump, which are not self-draining, shall be equipped with marked drain plugs located to assure complete removal of water.

3.9.8 Plumbing system. A plumbing system shall be installed in the right underslung cabinet and shall incorporate the following equipment functionally arranged:

(a) Gravity discharge faucet, 2.5 inch, with camlock coupler for gravity discharge through the suction hose (see 3.9.4) and for suction loading of the tank from a nonpressurized source (with the outlet valve closed, in through the gravity discharge faucet, through the pump, out through the 1.5 inch pressure discharge hose and nozzle and into the tank through the manhole fill cover opening). Bottom loading capability shall not be furnished.
(b) Piping to the hose reel swivel valve
(c) A dust cap with corrosion resistant security chain or cable for the gravity discharge faucet
(d) When specified (see 6.2), a meter located to measure the flow through the gravity discharge faucet and the hose reel. The meter shall be of the positive displacement type with built in strainer and air release. The meter shall be calibrated for handling water and shall have a flow rating equaling or exceeding the maximum flow rate the pump is capable of producing. The meter shall have a

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

2-inch inlet and outlet. The meter shall be accurate within 1 percent at a flow rate of 75 gallons per minute and shall be accurate within 2 percent at all other pump flow rates. The meter shall have a seven figure totalizer and a four figure set back counter, both with figures not less than 0.75 inch high. The meter shall be located to facilitate reading of the numerals. The meter shall conform to 3.1.1.4.

3.9.9 Pump. An engine driven, self-priming centrifugal pump shall be installed in the right (curbside) cabinet. Pump materials shall be constructed of or plated with corrosion-resistant materials. The pump shall be capable of lifting water from 18 feet below ground level through the 60 feet of 2.5 inch inside diameter suction hose into the top of the tank. The rate of flow under these conditions shall be not less than 75 gallons per minute (gpm). The pump shall be capable of discharging water from the tank through the tank outlet valve at the rate of not less than 75 gpm against a head of not less than 25 feet plus the 100 feet of 1.5 inch pressure discharge hose. The suction intake and pressure discharge ports of the pump shall be not less than 2 inches in diameter. A check valve shall be provided in the pump. A line strainer shall be furnished at the suction port of the pump. The line strainer shall be capable of removing any contamination, dirt and debris that would interfere with the pump's operation. Drains in the system shall be provided to allow the drainage of water from the complete system. The pump shall conform to 3.1.1.4.

* 3.9.10 Engine. An air cooled, four-stroke cycle, diesel engine shall be furnished to drive the pump. The engine shall have adequate horsepower, torque and speed characteristics to meet the performance requirements of 3.9.9. The engine shall be furnished complete with all accessories required for operation including a fuel tank with not less than a 3-gallon capacity; a 12-volt starting battery with the maintenance-free characteristics listed in W-B-131; a battery charging alternator; throttle, air cleaner, fuel gage, battery charging indicator, engine start and stop controls and all other components required to power the pumping system. The engine oil drain shall be located so that the engine can be drained, without spillage, into a container sitting on the ground.

* 3.9.10.1 Radio interference suppression. The engine shall be suppressed to limit electromagnetic radiation in accordance with SAE J551.

* 3.9.10.2 Engine sound level. The engine noise level during operation shall be not more than 84db(A) when measured in accordance with MIL-STD-1474. The noise level shall be measured at the operator's station adjacent to the controls with the operator standing on the ground.

* 3.9.11 Instruction plate. A plate, showing a schematic of all valves, components and accessories with operating instructions shall be fastened in a visible location inside the curbside cabinet door. The plate shall conform to composition A (class 1 or 2) or composition C of MIL-P-514.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

3.10 Gage rod. One gage rod of stainless steel shall be furnished and shall be calibrated in increments of 25 gallons on three sides. The gage rod shall be securely stowed in the left (streetside) cabinet.

3.11 Stowage of on vehicle equipment. Provisions shall be made for securing all equipment on the semitrailer.

3.12 Suspension system. The semitrailer shall be equipped with a suspension system, with components having a rated capacity at least equal to the load imposed upon each member, measured at the ground, with the semitrailer loaded with specified payload. When suspension is rated at the spring pads, unsprung weight shall be deducted.

* 3.12.1 Air suspension system. When specified (see 6.2), an air suspension system shall be furnished. The suspension system shall have not less than 60 percent of the sprung weight carried on the air springs. The air suspension system shall incorporate at least two track bars to control lateral movement. Each end of the track bars and of the torque rods, if so equipped, shall be equipped with rubber bushings that do not require periodic lubrication. The suspension system shall incorporate leveling valve(s) with time delay or other devices to minimize constant air consumption. The air suspension system shall include mechanisms to prevent damage from excessive extension when lifting and towing the vehicle. The suspension shall be provided with a mechanism at each wheel to assure lifting of the wheel and axle when jacking the vehicle from the applicable jacking location.

3.13 Axle(s). Size 2 and size 3 semitrailers shall be provided with a single axle. Size 4 and size 5 semitrailers shall be provided with tandem axles. Axle rating shall be at least equal to the load imposed on the axle(s), measured at the ground, with the semitrailer loaded with specified payload. The wheel bearings and axle spindles shall be oil lubricated. The hubs shall be fitted with seals. The hub caps shall have a window and shall incorporate provisions for venting or equivalent method of withstanding internal pressure buildup without leakage.

* 3.14 Wheels, rims, tires and tubes. The semitrailer shall be equipped with dual wheels on each axle. Multi-piece rims shall not be furnished. Rims and tire ratings shall conform to Tire and Rim Association or European Tyre and Rim Technical Organisation recommendations for the type and size of of tires furnished. Rim sizes shall be the same for all wheels on the semitrailer. Tire size and load range (ply rating) shall be the same for all tires on the semitrailer. When specified (see 6.2), disc type wheels shall be furnished.

* 3.14.1 Tires. Tires shall be tubeless type with highway tread. Tires shall be of the steel belted radial type. Tires shall have a rated capacity at least equal to the load imposed on each tire, measured at each wheel at the ground, with the semitrailer loaded with specified payload. Tires shall conform to Tire and Rim Association or to the European Tyre and Rim Technical Organisation recommendations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

3.14.2 Inner tubes. When tube type tires are specified in procurement documents, the inner tubes shall be of the heavy duty type, and shall be of proper size for the tires furnished. Tire flaps shall be provided in accordance with Tire and Rim Association recommendations.

* 3.14.3 Carrier for spare tire assembly. Unless otherwise specified (see 6.2), a carrier for a spare wheel or rim and tire assembly shall be installed in a readily accessible location. The carrier shall permit removal or installation of a spare wheel assembly, using only tools furnished with the semitrailer. Threaded fasteners, when used to secure the spare tire in the carrier, shall be constructed of or plated with corrosion-resistant material. The carrier shall enable the safe removal and installation of the spare tire assembly from and to the vehicle and carrier without personnel positioning themselves or any part of their body under the spare tire assembly.

3.14.4 Spare wheel or rim. When specified (see 6.2), a spare wheel or rim shall be mounted and secured on the carrier. When a spare tire assembly is specified (see 3.14.5), a spare wheel or rim shall be furnished.

3.14.5 Spare tire assembly. When specified (see 6.2), a spare tire assembly shall be furnished. The spare tire assembly shall include an inflated spare tire mounted on the spare wheel or rim. The spare tire shall be of the same size, load range and tread design as the tires installed on the semitrailer.

3.15 Brakes.

* 3.15.1 Service brakes. The service brakes shall be of the full air, internal expanding type, and shall conform to Federal Motor Carrier Safety Regulations 393.40 through 393.43, 393.45 through 393.47, and 393.52. Brake linings shall be of nonasbestos material. The braking system shall include automatic slack adjusters, standard breakaway features, relay emergency valve, air reservoirs, piping, hose connections, gladhands, spring loaded dust covers or dummy gladhands equipped with security chains, and all other components required for a complete air brake system. The location of the gladhands shall comply with SAE J702. The gladhands shall conform to SAE J318. The braking system shall be installed in a manner which provides road clearance for travel over uneven terrain and protection against damage caused by objects striking the components. No part of the braking system shall extend below the bottom of the wheel rims.

3.15.2 Parking brakes. The semitrailer shall be equipped with spring applied or air diaphragm type parking brakes. The parking brakes shall be automatically applied upon disconnection of the emergency air line and under emergency braking conditions, and shall remain applied with no additional application despite the depletion of all air pressure. The parking brakes shall conform to Federal Motor Carrier Safety Regulation 393.41.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 3.16 Upper fifth wheel. The upper fifth wheel plate shall completely cover a 36 inch diameter lower fifth wheel when the lower fifth wheel is coupled to the kingpin of the upper fifth wheel and the semitrailer is turned at all angles. The upper fifth wheel shall conform to Federal Motor Carrier Safety Regulation 399.70(b).

* 3.16.1 Upper fifth wheel plate. The upper fifth wheel plate shall be not less than 0.25 inch thick. The plate shall be reinforced on the upper surface through the use of commercial steel angles, channels and ribs. The plate shall include an access hole to permit servicing the brake connections and electrical connectors when these components are not serviceable from the top.

* 3.16.2 Pickup plate. A turned up lip pickup plate, compatible with the size (payload) of the semitrailer, shall be provided as an extension of the upper fifth wheel plate. The pickup plate shall have a turned up lip not less than 2 inches high. The pickup plate shall extend sufficiently forward to protect the semitrailer from damage during coupling and uncoupling operations to and from a truck tractor. The pickup plate shall be integral with the upper fifth wheel plate.

* 3.16.3 Kingpin. A 2-inch diameter kingpin conforming to SAE J700 shall be furnished. The kingpin shall be fabricated of heat treated alloy steel.

3.17 Landing gear. The semitrailer shall have two vertical lift, telescopic, nonrotating landing legs with two-speed gears, and a handcrank on the curbside. The landing legs shall be provided with steel wheels or self-leveling skid pads. A holder shall be provided for the handcrank when not in use. The landing gear shall withstand, without deformation, the combined static and dynamic forces due to the portion of the gross weight sustained, and the additional forces resulting from impact during coupling and uncoupling operations. When placed in travel position, the landing gear legs shall remain positively locked. The landing gear shall be protected to prevent the entrance of foreign matter which would impair its functioning or mechanical efficiency.

3.17.1 Range of adjustment. The landing gear shall have a range of adjustment sufficient to vary the height of the upper fifth wheel plate at the kingpin from 45 inches to not less than 52 inches from the ground for the size 2 and 3 semitrailers and 46 inches to not less than 54 inches from the ground for the size 4 and 5 semitrailers. The minimum ground clearance with the landing gear retracted shall be 14 inches.

3.18 Lubrication system. A lubrication system shall be furnished with fittings for all bearings and other working parts which require relubrication for continued service. Vehicles shall be lubricated, prior to delivery, with applicable grade of standard lubricant for the ambient air temperature encountered at the delivery point.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 3.19 Lighting. All lights and reflectors shall be protected from operational hazards by mounting in recessed or otherwise guarded locations. Lights and reflectors shall not be mounted on vertical surfaces of rub rails (unless recessed and fully protected) or on the semitrailer bumper. All electrical wiring shall conform to SAE J1292. Clearance and identification lights shall be constructed for easy removal and replacement of lamps and lenses without the use of hand tools.

3.19.1 Receptacle, 12-volt. The front of the semitrailer shall be equipped with a 7-contact receptacle conforming to SAE J560 with the connectors connected and color coded as specified therein. The receptacle shall be provided with a spring loaded cover. The receptacle shall be located in accordance with SAE J702.

3.19.2 Twelve-volt dc system. A 12-volt direct current (dc) lighting system conforming to 3.19 and 3.19.1 shall be provided. The 12-volt dc lighting system shall conform to Federal Motor Carrier Safety Regulations 393.14, 393.20, 393.22, 393.23, 393.25 through 393.29, 393.32 and 393.33.

3.19.3 Independent 24-volt dc system. When specified (see 6.2), a 24-volt dc lighting system independent of the 12-volt dc lighting system shall be provided. Separate wiring and bulbs shall be provided for the 24-volt dc system. The system shall conform to 3.19. The 24-volt dc system shall also conform to the Federal Motor Carrier Safety Regulations referenced in 3.19.2, except the 24-volt dc stop and turn lamps shall be combined.

3.19.4 Interconnected 24-volt dc system. When specified (see 6.2), capability of operating the 12-volt dc system (see 3.19.2) from a towing vehicle equipped with a nominal 24-volt dc electrical system shall also be provided.

3.19.5 Receptacle, 24-volt dc. When either an independent or interconnected 24-volt dc system is specified, the front of the semitrailer shall also be equipped with a 12-contact receptacle and cover conforming to MS 75021, part number MS 75021-1. The receptacle shall be located in accordance with SAE J702. The 24-volt dc 12-contact receptacle shall be connected to the lights as follows:

Contact B. Connect to left-hand turn signal and stop lamp (yellow)
Contact D. Connect to ground (white)
Contact E. Connect to clearance, side marker, identification, and tail lamps (black and brown)
Contact J. Connect to right-hand turn signal and stop lamp (green)
Contact L. Connect to ground (white).

The rest of the contacts shall not be connected. Circuits B and J on tactical trucks are combination stop and turn indicator circuits. On the interconnected 24-volt system, the normal 12-volt dc turn signal lights will

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:23Z
Check the source to verify that this is the current version before use.

function both as turn signals and stop lights, and the normal 12-volt dc stop lights will not be operational when the semitrailer is connected to a towing vehicle with a 24-volt dc power supply. Because of this condition, the stop light (red) circuit is not connected to the 24-volt dc 12-contact receptacle.

3.19.6 Resistors. When an interconnected 24-volt dc system is specified (see 3.4.19.4), the 12-contact receptacle shall be provided with resistance in each circuit to reduce the voltage of the tactical (military design) towing vehicle from a nominal 28 volts dc to 12 volts dc. Each circuit resistor shall be selected to reduce the 28-volt dc regulated voltage of the tactical truck to within the maximum rated voltage of the semitrailer electrical components. The resistor assembly shall be located in a protective housing and provided with adequate ventilation or a heat sink to prevent overheating and any damage to resistors, wiring, or adjacent components.

3.20 Rear end protection. Semitrailer rear end protection shall be provided in accordance with Federal Motor Carrier Safety Regulation 393.86.

3.21 Servicing and adjusting. Prior to acceptance of each vehicle by the Government inspector, the contractor shall service and adjust each vehicle and its mounted equipment for operational use including at least the following: adjustment of engine, electrical and brake systems; alinement of wheels; inflation of all tires; complete lubrication of chassis, engine, running gear, and mounted equipment with grades of lubricant recommended for the ambient air temperature at the delivery point.

3.22 Workmanship. The quality and workmanship of all component parts, including fabricated parts, machined parts and castings shall be commensurate with sound manufacturing standards for similar equipment. The vehicles shall be free from all burrs, sharp edges, die, tool and metal handling marks, rust, scale and cracks. All materials used shall be free from delamination defects, and shall be of prime material. Improper manufacturing or assembling practices, defective components or parts and assemblies which have been modified to overcome deficiencies shall not be furnished.

3.22.1 Welding. Adequate preparation of metal prior to welding shall be provided. Surface of parts to be welded shall be free of rust, scale, paint, grease and other foreign matter. Welding rods shall be compatible with the metal being used. All critical arc welds shall be magnaflux or dye penetrant inspected. The following defects shall not be acceptable:

(a) Welds which are ground flush with metal;
(b) Slug or plug welding;
(c) Undersized fillet welds, overlaps, inadequate fusion or penetration, undercutting of weldments and vertical down welding;
(d) Unremoved slag and spatter;
(e) Cracks;
(f) Spot, tack or intermittent welds for strength.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:23Z
Check the source to verify that this is the current version before use.

Weld penetration shall be such as to provide transference of maximum design stress through the base metal juncture.

3.22.2 Visible stainless steel surfaces. Stainless steel used in visible areas shall be provided from the mill paper-coated to prevent blemishes. Care shall be exercised in handling. All visible stainless steel welds shall be polished with a stainless steel brush. The exterior of the vehicle shall reflect great exercise of care in all handling and fabrication techniques and the best workmanship in the industry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility for ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods, and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

4.3 First production vehicle inspection. The first vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformance with the requirements of the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:23Z
Check the source to verify that this is the current version before use.

4.3.1 Vehicle weight. The first production vehicle shall be weighed to determine net weight and distribution of net weight on the kingpin and the rear axles. The imposed loading on the kingpin and rear axles will be computed using the net weight and the payload (see 3.4) distributed in the tank. The calculated imposed load on the rear axles will be used to ascertain that the suspension, axles and tires are of adequate capacity to meet contractual requirements.

4.3.2 Leakage test. Each completely assembled tank body, including all piping, shall be tested for leaks at its design pressure in accordance with DoT Safety Regulation 178.346. The tank of the first production vehicle shall be tested for leaks both before and after the road test.

* 4.3.3 Road test. The first production vehicle shall be coupled to a truck tractor and road tested with and without rated payload for a distance of not less than 50 miles. Ten miles shall be accomplished with rated payload on unimproved roads and 15 miles on improved roads (25 miles total). The remaining 25 miles shall be performed without payload. The vehicle shall be examined and tested to determine conformance to performance requirements specified herein.

4.3.4 Pump test. On style B semitrailers, the vehicle pumping equipment shall be tested to determine conformance to all requirements.

4.3.5 Electrical test. An electrical test shall be conducted on the first production vehicle to determine that all vehicle lights are functioning. In addition, when an interconnected 24-volt system is furnished, the circuits of the 12-contact receptacle shall be energized with not less than 28 volts dc regulated voltage for a time sufficient to stabilize the temperature of the resistor assembly for not less than 30 minutes in an ambient temperature of not less than 77°F. After the test, the resistor assembly, including resistors, wiring and adjacent components shall be examined for evidence of overheating, deterioration or damage.

4.3.6 Availability of regulations. The contractor shall make available to the Government at the point of final acceptance a current copy of DOT Safety Regulation 178.345 and DoT Safety Regulation 178.346. The documents shall be surrendered to the Government representatives for use in conjunction with the contract for the duration of the contract.

4.3.7 Joint specimens. The contractor shall offer for Government inspection and approval the joint test specimens subjected to the tensile test required by DoT Safety Regulation 178.345, together with certification regarding the date of preparation and testing. The test specimens shall be current in accordance with 178.345.

4.3.8 Toxic data and formulations. The supplier shall furnish a copy of the approval by the procuring activity of the materials used in the construction of the vehicle (see 3.1.1.4). The vehicle shall be inspected

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

and the manufacturer shall provide evidence that only the approved materials were used in the construction and treatment of the affected parts of the vehicle.

4.3.9 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and shall be the last vehicle shipped on the contract. The manufacturer shall maintain the vehicle in a serviceable condition for the duration of the contract.

* 4.3.10 Test failure. The vehicle shall successfully complete the entire test. Failure of the vehicle to successfully complete the test shall be cause for nonacceptance of any of the contract quantity, pending correction of deficiencies and evidence of corrective action which shall prevent the recurrence of similar deficiencies in the contract quantity. Failure of the vehicle to successfully complete the test shall not constitute an excusable delay in meeting scheduled deliveries. The equipment shall be closely monitored throughout the test for interference with towing operations, and for instability as evidenced by poor tracking or uncontrollable sideslipping, skidding, swerving, or tilting. The equipment also shall be closely monitored for loosening of parts, interference between parts, leakage of fluids or lubricants, overheating of components, and for damage, permanent distortion, or excessive wear of parts and components. The equipment shall be disassembled to the extent necessary for inspection for unusual wear or damage to components. Substitution of a new semitrailer or replacement of a major component may require complete retest at the discretion of the Government representatives. Rejection of the test semitrailer shall be for damage or deficiencies, including but not limited to the following:

(a) Damage caused by collision
(b) Failure of any major component
(c) Vibration due to misalinement of wheels or frame
(d) Vibration due to the type of construction or mounting
(e) Evidence of abnormal tire wear due to misalinement or unbalance
(f) Failure of any vehicular safety device such as brakes or electrical circuits
(g) Evidence of structural weakness in any part of the vehicles, vehicle components, accessories or welds.
(h) Loose mountings of parts or accessories due to workmanship or vehicular operation.

4.4 Inspection of production vehicles. The contractor's inspection system shall, as a minimum, assure that the vehicle conforms to the physical and dimensional requirements and is capable of meeting performance requirements contained herein. All semitrailers under contract shall be tested as specified in 4.3.2. For each vehicle under contract, the contractor shall make available to the Government, at the point of final acceptance, records acceptable to the Government indicating that the servicing and adjusting required by 3.15 has been accomplished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Vehicle processing. The vehicle shall be processed for shipment, from manufacturer's plant to initial receiving activity, in accordance with the manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use. The vehicles covered by this specification are intended for general nontactical use by the Government in transporting potable water.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Size and style of vehicle required (see 1.2.1 and 1.2.2).
* (c) Issue of DODISS to be cited in the solicitation and, if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
(d) Identification of appropriate service for painting (see 3.1.1.1).
* (e) Identification of appropriate service for marking (see 3.1.1.2).
(f) Rustproofing, if required (see 3.1.1.3).
(g) Meter, if required (see 3.9.8(d)).
* (h) Air suspension system, if required (see 3.12.1).
(i) Disc type wheels, if required (see 3.14.4).
(j) If a carrier for a spare tire assembly is not required (see 3.14.3).
(k) Spare wheel or rim, if required (see 3.14.4).
(l) Spare tire assembly, if required (see 3.14.5).
(m) Independent 24-volt dc lighting system, if required (see 3.19.3).
(n) Interconnected 24-volt dc lighting system, if required (see 3.19.4).

* 6.3 Subject term (key word) listing.

Baffles
Catwalk
Dissimilar metals
Plumbing system
Suspension system
Welding.

6.4 Identification of changes. The margins of this specification are marked with asterisks (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content regardless of the marginal notations and relationship to the previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AT
Navy - YD

User activity:
Army - ME

Preparing activity:
Army - AT

Project No. 2330-A091

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER (Number) AND TITLE MIL-S-62080D SEMITRAILERS, TANK: POTABLE WATER, 2,000 TO 5,500 GALLON, COMMERCIAL

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY (Printed or typed name and address — Optional)

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
U.S. Army Tank-Automotive Command
ATTN: AMSTA-UED
Warren, Michigan 48397-5000

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.