MIL-T-62126C(AT)
9 May 1988
SUPERSEDING
MIL-T-62126B(AT)
26 June 1981

MILITARY SPECIFICATION

TRUCKS, EQUIPMENT TRANSPORT, TILT PLATFORM, DIESEL AND GASOLINE ENGINE DRIVEN, 24,000 GVW, 4X2, AND 44,500 GVW, 6X4, COMMERCIAL

This specification is approved for use by the US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers diesel and gasoline engine driven, four-wheel, two-rear-wheel drive and six-wheel, four-rear-wheel drive equipment transport trucks with a hydraulic operated rear tilt platform and loading winch. Trucks have a minimum gross vehicle weight (GVW) of either 24,000 pounds or 44,500 pounds for normal operating conditions. Vehicles procured under this specification are commercial items which shall be warranted by the manufacturer as specified in acquisition documents.

* 1.2 Classification. The vehicle shall be one of the types shown below, as specified (see 6.2):

Type I - 24,000 GVW, 4x2
Type II - 44,500 GVW, 6x4.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS), and supplement thereto, cited in the solicitation.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-UED, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC-2320

DISTRIBUTION STATEMENT A. Approved for public use; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS
FEDERAL

	W-B-131	- Battery, Storage: Vehicular, Ignition, Lighting and Starting.
*	ZZ-T-381	- Tires, Pneumatic, Vehicular (Highway).

STANDARDS

	FED-STD-297	- Rustproofing of Commercial (Nontactical) Vehicles.

MILITARY

*	MIL-STD-1223	- Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking and Data Plates Standards.
	MS51118	- Pintle Assembly, Towing: 40,000 Lbs. Capacity, Manual Release.
	MS51317	- Light, Warning, Vehicular, Rotating, D.C.

* 2.1.2 Other Government documents. The following other Government documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DEPARTMENT OF TRANSPORTATION (DoT)
Federal Motor Carrier Safety Regulations.
Federal Motor Vehicle Safety Standards.

(Application for copies of DoT publications should be addressed to the Department of Transportation, Federal Highway Administration, Washington, D.C. 20591.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)
Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines.
Noise Emission Standards for Transportation Equipment - Medium and Heavy Trucks.

(Application for copies of EPA publications should reference the Code of Federal Regulations, 40 CFR, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

(Copies of specifications, standards and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the non-Government document which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM) Standards:
ASTM Designation: A120 - Pipe, Steel, Black and Hot-Dipped Zinc-Coated (Galvanized) Welded and Seamless, for Ordinary Uses (DoD adopted).

(Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

SAE, INC.
SAE Standards and Recommended Practices

	J318	- Air Brake Gladhand Service (Control) and Emergency (Supply) Line Couplers - Trucks, Truck-Tractors, and Trailers (DoD adopted).
*	J350	- Spark Arrester Test Procedure for Medium Size Engines (DoD adopted).
	J537	- Storage Batteries.
	J551	- Performance Levels and Methods of Measurement of Electromagnetic Radiation from Vehicles and Devices (30-1000 MHz).
	J560	- Seven-Conductor Electrical Connector for Truck-Trailer Jumper Cable.
	J588	- Turn Signal Lamps.
	J589	- Turn Signal Switch.
	J682	- Rear Wheel Splash and Stone Throw Protection (DoD adopted).
*	J683	- Tire Chain Clearance - Trucks, Buses, and Combinations of Vehicles (DoD adopted).
	J688	- Truck Ability Prediction Procedure. (DoD adopted).
	J704	- Openings for Six- and Eight-Bolt Truck Transmission Mounted Power Take-Offs (DoD adopted).
	J706	- Rating of Winches.
	J844	- Nonmetallic Air Brake System Tubing (DoD adopted).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* J1349 = Engine Power Test Code - Spark Ignition and Diesel.

(Application for copies of SAE publications should be addressed to SAE, INC., 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC.
Yearbook.

(Application for copies of Tire and Rim Association publications should be addressed to the Tire and Rim Association, Inc., 3200 W. Market Street, Akron, OH 44313.)

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.7, the vehicle, components, assemblies and accessories to be delivered under the contract shall be standard or optional items which meet or exceed the requirements of this specification. All chassis items shall be as represented in the chassis manufacturer's technical data, and special bodies or mounted equipment shall be as represented in the body and equipment manufacturer's technical data. Technical data shall be limited to specifications and technical material identical to that furnished to the authorized company representatives for selection of vehicle models and components, and shall be available in the engineering offices of the procuring activity prior to delivery of the items. The chassis model furnished shall be not older than the chassis manufacturer's current model on the date of invitation for bids.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

* 3.1.1.1 Painting and marking. Treatment, painting, marking and data plates shall be in accordance with MIL-STD-1223. The exterior color and the identification markings shall be in accordance with the requirements of MIL-STD-1223 for the military service identified by the procuring activity (see 6.2). When specified (see 6.2), concealed markings shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 3.1.1.2 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with FED-STD-297. When specified (see 6.2), tropical rustproofing in accordance with FED-STD-297 shall be furnished.

3.1.1.3 Drain plugs. Drain plugs installed in manual transmissions and in rear axles for the purpose of draining lubricants shall be of the permanent magnet type.

3.1.1.4 Towing devices. Not less than two hooks, loops, or pins or a single, center-mounted towing eye for towing the vehicle shall be furnished on the front of the vehicle.

* 3.1.1.5 Trailer towing package. When specified (see 6.2), a trailer towing package consisting of a pintle, safety chain attachment devices, a lighting receptacle, a trailer brake control system, and associated reinforcements and wiring shall be installed on the rear of the vehicle. The pintle shall be of the rotating type conforming to MS51118. The pintle shall be installed on the chassis frame with reinforcements to transfer a vertical tongue load of not less than 4,000 pounds and a horizontal drawbar load of not less than 40,000 pounds directly to the chassis frame rails. The rearmost portion of the pintle shall be forward but not more than 4 inches forward of the rearmost part of the vehicle. Two trailer safety chain attachment devices, one adjacent to each side of the pintle, shall be provided. Each attachment device shall provide an ultimate strength of not less than 40,000 pounds. The attachment devices shall be capable of accommodating a standard grab hook (4-9/16 inches wide, 1-3/16 inches thick, 25/32-inch throat width) for a 5/8-inch chain. The lighting receptacle, conforming to SAE J560 with its conductors connected and color coded as specified therein, shall be mounted in a readily accessible location near the pintle. The trailer brake control system shall conform to 3.4.11.2.

* 3.1.1.6 Rear wheel splash and stone throw protection. Rear wheels shall have rigid splash shields in front and rubber mud flaps at the rear. Splash and stone throw protection shall be in accordance with SAE J682. A metal strip not less than 1/8 inch thick and not less than one inch wide, extending the entire width of the mud flap, shall be installed to prevent the bolt heads or bolt nuts from damaging the mud flap.

* 3.1.1.7 Brushguard. The vehicle shall be equipped with a radiator and headlamp brushguard. When the headlamps are recessed into and protected by the front bumper, a headlamp brushguard is not required.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:23Z
Check the source to verify that this is the currentversion before use.

3.2 General design.

3.2.1 Federal Motor Vehicle Safety Standards. The vehicle and furnished accessories shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture.

3.2.2 Air pollution control. The vehicle shall comply with EPA Regulations governing Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines in effect on the date of manufacture. In addition, vehicles destined for California shall comply with State of California regulations governing air pollution control in effect on the date of manufacture.

3.2.3 Sound level. The interior sound level shall conform to Federal Motor Carrier Safety Regulation 393.94. The vehicle exterior sound level shall conform to the Environmental Protection Agency Noise Emission Standards for Transportation Equipment - Medium and Heavy Trucks.

3.2.4 Curb weight. The curb weight shall include the weight of the chassis and cab with all attachments, accessories, and equipment; the body; and a full complement of fuel, lubricants and coolant.

3.2.5 Gross vehicle weight. Gross vehicle weight (GVW) shall consist of curb weight, operator weight (computed at 175 pounds), and a payload to provide not less than 24,000 pounds GVW for type I vehicles and 44,500 pounds GVW for type II vehicles.

3.2.6 Weight distribution. The distribution of GVW for the purpose of establishing suspension, axle, and tire capacities shall be determined with the payload uniformly distributed over the load area.

3.2.7 Ratings. Vehicle ratings shall be manufacturer's published ratings. Component and vehicular ratings shall not be raised to meet the requirements of this specification. When published ratings are not available, verification of ratings shall be available to the engineering office of the procuring activity. The minimum GVW rating shall be 24,000 pounds for type I vehicles and 44,500 pounds for type II vehicles.

* 3.2.8 Overall width. The overall width of the vehicle, exclusive of mirrors, lights, reflectors and tires, shall be not more than 96 inches. The width over the tires shall be not more than 100 inches.

* 3.2.9 Accessibility. The design of the vehicle and optional equipment shall permit access for routine servicing and shall permit access for replacement and adjustment of component parts and accessories with minimal disturbance of other components and systems.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

3.3 Performance.

3.3.1 Speeds and gradeability. High and low speed requirements shall be met with the truck loaded to the specified GVW.

3.3.1.1 High speed gradeability. The vehicle shall ascend at 50 miles per hour (mph) a 1.0 percent grade for type I vehicles and a 0.50 percent grade for type II vehicles. Gradeability requirements shall be met with the main transmission in direct drive and, when a multispeed axle or auxiliary transmission is furnished, with the axle or auxiliary transmission in high speed range. Gradeability shall be verified with calculations in accordance with SAE J688 (see 6.3).

* 3.3.1.2 Low speed. Low speed for vehicles with a manual transmission shall be calculated with the engine operating at not less than 35 percent of the recommended governed speed, and shall provide a vehicle speed of not more than 4 mph for type I vehicles and not more than 2.5 mph for type II vehicles.

* 3.3.1.3 Maximum geared speed. The maximum geared speed at engine governed speed shall be not less than 58 mph. Conformance to geared speed specified shall be determined by calculating in accordance with the following formula:

$$\text{Maximum geared speed (mph)} = \frac{\text{Governed speed (rpm)}}{\text{Total gear reduction x tire factor (see 6.3)}}.$$

* 3.3.2 Service brakes. The service brakes shall control and hold the vehicle, when loaded to its specified GVW on a 30 percent grade. The service brakes shall stop the vehicle, loaded to specified GVW, within the stopping distance requirements of Federal Motor Carrier Safety Regulation 393.52.

3.4 Chassis components.

3.4.1 Engine. The engine furnished shall be the chassis manufacturer's standard or optional engine for the commercial model truck which meets or exceeds the requirements of this specification.

* 3.4.1.1 Diesel engine. Unless otherwise specified (see 3.4.1.2), the vehicle shall be equipped with a liquid cooled, compression ignition, two-stroke or four-stroke cycle diesel engine, with not less than four cylinders for type I and six cylinders for type II vehicles. Engine net horsepower figures used in performance prediction calculations shall be determined in accordance with SAE J1349.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 3.4.1.2 Gasoline engine. When specified (see 6.2), the vehicle shall be equipped with a liquid cooled, internal combustion, four-stroke cycle gasoline engine with not less than six cylinders. The engine furnished shall produce the required vehicle performance when operated on unleaded fuel with a research octane rating of 91, at engine speeds not more than the manufacturer's recommended operating speed. The engine shall be capable of warranted operation on unleaded fuel when used in accordance with the operator's manual. Engine net horsepower figures used in performance prediction calculations shall be determined in accordance with SAE J1349.

3.4.1.3 Oil filter. A full flow type oil filter shall be furnished.

3.4.1.4 Governor. An engine governor shall be furnished and set and sealed to limit the engine to the engine manufacturer's maximum recommended operating speed.

* 3.4.1.5 Cooling system. The cooling system shall maintain the engine coolant at a temperature below the boiling point with the vehicle loaded to rated GVW and operated at an altitude of 10,000 feet above sea level or in an ambient air temperautre of not less than 125 degrees Fahrenheit (°F). The coolant system shall include a surge tank or a coolant recovery reservoir of not less than two-quart capacity. A high coolant temperature or a low coolant level alarm buzzer and a red indicator warning light shall be provided on the instrument panel. On tilt cab models, a radiator servicing access door shall be provided to allow verification of the coolant level.

3.4.1.6 Coolant temperature control. Thermostatic control of the engine coolant temperature shall be provided. On diesel engine driven vehicles, the control shall include partial thermostatic control of the coolant flow through the radiator and thermostatically controlled radiator shutters or complete thermostatic control of all coolant flow through the radiator.

* 3.4.1.7 Fan clutch. A fan clutch shall be provided. The fan clutch shall reduce the fan speed automatically when the fan is not required for engine cooling.

* 3.4.1.8 Power plant heaters and fuel warmer. When specified (see 6.2), a coolant heater, an engine oil heater and a fuel warmer (diesel engine driven vehicle only) shall be provided. Unless otherwise specified (see 6.2), a battery heater shall be provided when power plant heaters are specified. Heaters shall operate on 120-volt alternating current (ac), and shall be wired through a junction block to a single

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

three-pronged (male), weatherproof, slave receptacle for receiving external power and grounding vehicle. A three-wire connecting cable, 25 feet long and of adequate line capacity to supply power for all heater units simultaneously, shall be furnished. The connecting cable shall include a matching female connector at the vehicle end and a standard, weatherproof, three-pronged (two power plus one ground) male connector at the other end. Electrical apparatus shall conform to Federal Motor Carrier Safety Regulation 393.77(c)(7). Electrical insulation of the connecting cable shall withstand normal operating ambient air temperatures (down to minus 60°F) without cracking or loss of dielectric capacity. All heater lead wires shall be installed without interfering with vehicle component operation, and without loose excess wire. A carrier for the connecting cable shall be mounted within the cab or engine compartment and shall provide positive cable retention during vehicle operation. Heaters shall be furnished as follows:

(a) Coolant heaters, 1500-watt minimum rating, shall be installed in the engine block or lower coolant inlet hose. An engine thermostat with an operating range of 170°F to 195°F shall be installed

(b) Immersion type engine oil heater, 300-watt minimum rating, with 170°F to 195°F thermostat, shall be installed in the oil pan through any convenient opening

(c) The battery heater shall have a capacity adequate to maintain the battery electrolyte at a temperature of not less than 10°F during vehicle exposure in ambient air temperatures as low as minus 60°F, and shall embody a thermostat to limit the temperature of the electrolyte to not more than 80°F

(d) When an automatic transmission is provided, a 300-watt immersion type heater with 170°F to 195°F thermostat shall be installed in the transmission oil pan through any convenient opening

(e) For diesel engine driven vehicles, a fuel warmer or preheater shall be provided to prevent clogging of fuel filters due to wax crystallization in the fuel. The fuel warmer shall use engine coolant to transfer sufficient heat to the diesel fuel to heat it from an inlet temperature of minus 40°F to an outlet temperature of plus 9°F, with a flow rate of not less than the maximum fuel demand of the engine fuel system. A coolant shutoff valve shall be provided for the coolant inlet side of the fuel warmer unit.

3.4.2 Electrical systems. Electrical systems shall be in accordance with Federal Motor Carrier Safety Regulations 393.27 through 393.31 and 393.33.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 3.4.2.1 Starting system. For diesel engine driven vehicles, a 12- or 24-volt direct current (dc) starting system, with 12-volt dc lighting system, shall be furnished. A minimum 60-ampere alternator shall be furnished. Engine starting equipment shall include an ether starting system or glow plug. If an ether system is furnished in lieu of a glow plug, it shall be of the measured shot type. The measured shot type ether system shall be key operated or manually operated from the driver's compartment and shall be inoperative with the engine warm. Complete provisions for a replaceable ether reservoir of not less than 12 fluid ounces shall be furnished. A reservoir need not be furnished.

* 3.4.2.2 Ignition system. For gasoline engine driven vehicles, a 12-volt dc ignition system shall be furnished. An alternator of not less than a 40-ampere rated capacity and which provides not less than 16 amperes of dc output at normal engine idle speed shall be furnished.

* 3.4.2.3 Lighting. All vehicle lights, reflectors, and wiring shall conform to Federal Motor Carrier Safety Regulations 393.12, 393.13, 393.19, 393.20, and 393.22 through 393.26(d). When available as the manufacturer's standard or optional feature, the brake lights shall override the four-way emergency flashers. Lights and reflector shall not be mounted on vertical surfaces of rub rails or mounted on vehicle bumpers (unless recessed or fully protected).

* 3.4.2.4 Turn signals. Turn signal lamps shall conform to SAE J588. Operating units shall conform to SAE J589, class A, and shall be mounted on the steering column. The vehicle shall be provided with double-faced front signal units and with single-faced rear signal units installed in accordance with SAE J588, except that turn signals shall not be mounted on the engine compartment hood. Turn signal operating units shall have visible and audible type flash indicators.

3.4.2.5 Batteries. Each battery shall be of 12-volt potential. The total reserve capacity ratings and the total cold cranking ampere ratings at 0°F, both measured in accordance with SAE J537, shall be not less than specified in table I. The batteries shall be of the maintenance-free type having the maintenance-free characteristics listed in W-B-131.

TABLE I. Batteries.

Engine type	Reserve capacity (minutes)	Cold cranking (amperes)
Diesel engine (less than 220 gross horsepower)	320	1,200
* Diesel engine (220 gross horsepower and over)	480	1,740
Gasoline engine	100	450

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

3.4.2.6 Rotating warning light. When specified (see 6.2), an amber, rotating, vehicular warning light conforming to MS51317-4 shall be provided. The rotating light shall be mounted with reinforcement at the point of attachment on the cab roof centerline for 360-degree visibility. The rotating light shall be operated by means of a separate switch with a red indicator light located on the instrument panel and marked to indicate the function of the switch.

3.4.2.7 Spotlights. When specified (see 6.2), two 6-inch diameter, chrome plated spotlights shall be installed through the upper left and right front corners of the cab with controls inside the cab.

* 3.4.2.8 Radio interference suppression. The vehicle shall be suppressed to limit electromagnetic radiation in accordance with SAE J551. Any body equipment emitting electromagnetic radiation shall be suppressed to the same level as the vehicle chassis.

3.4.3 Fuel system. The fuel system shall conform to Federal Motor Carrier Safety Regulations 393.65 and 393.67.

* 3.4.3.1 Air cleaner. An air cleaner shall be furnished.

* 3.4.3.2 Fuel tanks. The fuel tank(s) shall be of not less than a 50-gallon capacity (43 gallons for vehicles destined for California). When more than one tank is furnished on diesel engine driven vehicles, means shall be provided to assure equalized fuel levels in both tanks. When more than one tank is furnished on gasoline engine driven vehicles, a selector valve connecting either tank to the engine fuel intake shall be provided, and means shall be provided to monitor the fuel level of either tank from a single fuel gage.

* 3.4.4 Exhaust system. The exhaust system shall conform to Federal Motor Carrier Safety Regulation 393.83. If furnished, vertical exhaust mufflers capable of being reached easily by personnel entering or leaving either side of the cab shall be provided with a heat shield. Vertical exhaust mufflers shall be provided with a hinged rain cap.

* 3.4.4.1 Spark arrester. When specified (see 6.2), a spark arrester shall be furnished, except on vehicles with turbocharged engines. The spark arrester shall have an 80 percent arresting efficiency when rated in accordance with SAE J350.

* 3.4.5 Transmission. Unless otherwise specified (see 3.4.5.2), a manually shifted transmission with not less than five forward speeds for type I and nine forward speeds for type II shall be provided. The input torque capacity of the transmission shall be at least equal to the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

maximum torque delivered by the engine. When more than five forward speeds are required, a multispeed transmission, auxiliary transmission, or two-speed axle(s) may be provided. Gear ratios in the transmissions and axle(s) shall be matched to provide a progressive shifting pattern throughout the complete range, and shall provide the required vehicle performance (see 3.3.1 through 3.3.1.3). The transmission shall be provided with an SAE J704 power takeoff opening on both right and left sides. The transmission shall provide for maximum ease of shifting in all speeds.

3.4.5.1 Clutch. The clutch shall be the largest capacity clutch offered for the type and class vehicle and engine furnished, with the clutch torque capacity exceeding the maximum delivered engine torque.

* 3.4.5.2 Automatic or semiautomatic transmission. When specified (see 6.2), the vehicle shall be provided with an automatic or semiautomatic transmission. The transmission shall include a hydraulic torque convertor and not less than four forward gear ratios for type I vehicles and five forward gear ratios for type II vehicles. The normal driving range selector position shall provide not less than four gear ratios without movement of the selector. The transmission shall be provided with an SAE J704 power takeoff opening. The input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine.

3.4.5.3 Power takeoff. The power takeoff shall be of a rated capacity to operate powered equipment. Controls to operate the power takeoff shall be located in the truck cab accessible to the seated driver. A caution plate or decal reading "DO NOT OPERATE VEHICLE AT HIGHWAY SPEEDS WITH POWER TAKEOFF ENGAGED" shall be provided and installed so as to be visible to the seated driver.

3.4.6 Driveline components. Driveline components shall be adequate to transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction.

* 3.4.7 Frame. The chassis frame shall be the manufacturer's standard for the type of vehicle furnished. Frame rails shall not project beyond the rear end of the body. The chassis shall have a heavy duty main frame or frame reinforcements. The heavy duty frame shall have frame rails of greater section modulus than the manufacturer's standard and shall provide structural strength at least equivalent to the reinforced frame specified herein. Reinforcements shall extend at least from the rear of the front suspension, rear hanger bracket to the front of the rear spring, front hanger bracket. Reinforcements shall provide sufficient structural strength in the chassis frame through

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

increased resisting bending moment to at least equal the loads imposed, with the vehicle loaded to specified GVW. For type II vehicles, the combined strength of the frame and reinforcements shall be not less than 2,200,000 inch-pounds resisting bending moment.

3.4.8 Suspension. The vehicle shall be equipped with a suspension system with components having a rated capacity at least equal to the load imposed on each member, measured at the ground, with the vehicle loaded to the specified GVW. When suspension is rated at the spring pads, unsprung weight shall be deducted. The vehicle shall be equipped with hydraulic, double-acting shock absorbers at the front wheels.

* 3.4.9 Axles. Axle ratings shall be at least equal to the load imposed on each axle, measured at the ground, with the vehicle loaded to specified GVW. When specified (see 6.2), the wheel bearings and axle spindles shall be oil lubricated. The hubcaps shall have a window for visual determination of oil level. Provisions for venting or withstanding internal pressure buildup and for replenishing the oil supply shall be provided.

3.4.9.1 Two-speed axle. When specified (see 6.2), a two-speed axle shall be furnished, equipped with an electric, vacuum or air shift and provided with ratios which will permit proper gear splitting. The gear ratio shall provide the performance specified in 3.3.1 through 3.3.1.3.

3.4.9.2 Rear bogie. For type II vehicles, the rear bogie shall be of the four-wheel type, complete with axles, springs, torque rods and all other necessary parts. The bogie shall be provided with means permitting differential action between the two axles, and a manually or automatically controlled lockout assuring equal power to each rear axle. The manual lockout control used shall be located in the truck cab. Axle gear ratios shall provide the performance specified in 3.3.1 through 3.3.1.3.

* 3.4.9.3 Traction control. When specified (see 6.2), the vehicle shall be furnished with a traction control. For type II vehicles the traction control shall be on either rear axle. The traction control shall actuate automatically to ensure that power is transmitted to the wheels having traction when the opposite wheel loses traction. Maximum traction capabilities shall be maintained at all times under each drive wheel for the life of the vehicle.

* 3.4.10 Wheels, rims, tires and tubes. Unless wide base tires are specified, the vehicle shall be equipped with single front and dual rear wheels. Except as specified herein, rims and tire ratings shall conform to Tire and Rim Association recommendations for the type and size of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

tires furnished. Rim and disc wheel sizes shall be the same for all wheels. Tire size and load range (ply rating) shall be the same for all tires. When specified (see 6.2), wide base type tires and wheels for the front and rear axles shall be provided in lieu of conventional front and dual rear wheels and tires. Wide base wheels shall be interchangeable without the use of an adapter. When specified (see 6.2), disc type wheels shall be furnished.

* 3.4.10.1 Tires. Tires shall be steel belted radial or, when specified (see 6.2), bias ply. Tires shall be tube or tubeless type with highway tread on the front and nondirectional mud and snow tread on the rear. Tires shall be of a rated capacity at least equal to the load imposed on each tire, measured at each wheel, at the ground, with the vehicle loaded to specified GVW. Tires shall conform to Tire and Rim Association recommendations, or to ZZ-T-381 with a size designation system the same as the Tire and Rim Association.

3.4.10.2 Inner tubes. When tube type tires are furnished, inner tubes shall be of the heavy duty type and shall be of the proper size for the tires furnished. Tire flaps shall be provided for tube type tires in accordance with Tire and Rim Association recommendations.

* 3.4.10.3 Carrier for spare tire assembly. When specified (see 6.2), a carrier for a spare wheel or rim or a spare tire assembly shall be installed in a readily accessible location on the vehicle. Threaded fasteners, when used to secure the spare tire in the carrier, shall be constructed of or plated with corrosion-resistant material. The carrier design shall enable removal or mounting of the spare tire assembly using only the tools specified in 3.4.16.1.

3.4.10.4 Spare wheel or rim. When specified (see 6.2), a spare wheel or rim shall be furnished. When a spare tire assembly is specified, a spare wheel or rim shall be furnished.

* 3.4.10.5 Spare tire assembly. When specified (see 6.2), a spare tire assembly shall be furnished. The spare tire assembly shall include an inflated spare tire mounted on the spare wheel or rim. The spare tire shall be of the same size, tread design and load range (ply rating) as the tires furnished on the vehicle.

* 3.4.10.6 Tire chain clearance. Tire chain clearance in accordance with SAE J683 shall be provided. Allowance for spring deflection shall be included.

* 3.4.11 Brakes. Brakes shall conform to Federal Motor Carrier Safety Regulations 393.40 through 393.43, and 393.45 through 393.52. When available as the manufacturer's standard or as an option, brake linings shall be of nonasbestos material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 3.4.11.1 Service brakes. The vehicle shall be equipped with full air brakes on all wheels. The braking system, complete with all necessary components, shall include:

(a) Air compressor, unloader-head type, engine driven and engine lubricated, air or water cooled, and having a capacity of not less than 7-1/4 cubic feet per minute (cfm) for type I vehicles and 12 cfm for type II vehicles
(b) Air storage reservoir(s), each tank equipped with drain, and with safety and check valves between compressor and last reservoir tank
(c) Foot control, suspended or treadle type
(d) Air control valves
(e) Air pressure gage, visible to the driver
(f) Low-air pressure warning, visible and audible
(g) Service brake stop lamp switch
(h) Automatic moisture ejector
(i) Automatic slack adjusters.

* 3.4.11.1.1 Air dryer. A replaceable cartridge desiccant type air dryer shall be installed in the air brake system. The dryer shall have the capability of removing a minimum of 95 percent of the moisture in the air being dried. The dryer shall have a precooler and a filter to screen out oil and solid contaminants. The dryer shall have an automatic self-cleaning cycle and a thermostatically controlled heater to prevent icing of the purge valve.

3.4.11.2 Trailer brake control system. When a trailer towing package is specified (see 3.1.1.5), in addition to the components specified in 3.4.11.1 and 3.4.11.1.1, a trailer brake control system shall be furnished. The trailer brake control system shall include:

(a) Identification of emergency and service lines
(b) Coincident control of trailer brakes with prime mover foot control
(c) Independent hand control for trailer brakes
(d) Prime mover protection valve with dash control and automatic breakaway feature
(e) Trailer stoplight control operable with foot brake and with hand control for trailer brakes
(f) Two SAE J844 coiled air hoses, not less than 110 inches long when fully extended, with SAE J318 gladhand couplers on both ends of hoses. The hoses shall be packaged and stowed in the vehicle tool compartment for shipment
(g) Air connectors for trailers with SAE J318 gladhand couplers mounted at the rear of the vehicle located to prevent interference with the trailer

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

(h) Dummy gladhand couplers with chains
(i) Prime mover only parking brake valve to permit prime mover parking brakes to be applied while charging the trailer air brake system.

3.4.11.3 Brake controls for use from a towing vehicle. When specified (see 6.2), the vehicle shall be furnished with a system for controlling the brakes from a towing vehicle (wrecker). The installation shall be complete with air brake couplers, a relay emergency valve with no-bleed-back feature (except when a spring applied emergency brake is furnished), additional air lines and fittings. The service and emergency couplers shall be mounted on the front in a protected position providing for ready attachment of air hoses from a towing vehicle. The service and emergency couplers shall be identified and provided with dummy gladhand couplers with chains. The system shall not compromise conformance to any Federal Motor Carrier Safety Regulation referenced herein or to any Federal Motor Vehicle Safety Standard.

* 3.4.12 Cab. Unless otherwise specified, the chassis manufacturer shall furnish any type of his standard or optional full-width cab. When specified (see 6.2), a cab with a forward tilting hood and fender assembly, including tilting and locking mechanism, shall be furnished. When specified (see 6.2), a tilt type cab, with tilting and locking mechanism, shall be furnished. Tilt cab features shall be in accordance with the Employee Safety and Health Standards of Federal Motor Carrier Safety Regulation 399, including the first step height which shall be not more than 24 inches. Cab doors shall be equipped with locks, operable from inside the cab through mechanical linkage, and with at least the curbside door equipped with an external, key operated lock. Drip rails shall be installed above the cab doors. The cab shall have an upholstered, full-width, adjustable seat and back or an individual, adjustable, driver's seat and individual passenger seat. When specified (see 6.2), an individual adjustable driver's seat and an individual passenger's seat shall be furnished. The color of the upholstery and the interior finish shall be compatible with the exterior color (see 3.1.1.1). White upholstery shall not be furnished. Interior lighting shall be provided. Manufacturer's standard fastenings and two pairs of seat belts shall be installed. For tilt type cabs, provisions to facilitate cleaning the windshield shall be provided by means of a bumper step, or bumper step cutouts, and a grab handle located under the windshield. Safety grips shall be provided on each side of the cab to assist personnel in entering and leaving the cab.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

3.4.13 Steering. Power steering shall be furnished.

3.4.14 Windshield wipers and washers. The vehicle shall be equipped with dual windshield wipers, wiper blades, and windshield washers. Windshield wipers shall be of the multispeed type and operated by either air or electric motor(s).

3.4.15 Bumper. Unless the front bumper is an integral part of the vehicle cab, a channel type front bumper shall be provided.

3.4.15.1 Rear end protection. The rear end of the vehicle shall be protected in accordance with Federal Motor Carrier Safety Regulation 393.86.

* 3.4.16 Tool stowage. Stowage space of sufficient size to accommodate a vehicle jack, hand tools, antiskid chains and emergency reflective triangles shall be furnished for retaining equipment during vehicle operation. Stowage space for these tools may be furnished inside the cab. When stowage space for these tools is located outside of cab, it shall be weatherproof and shall provide for locking with a padlock.

3.4.16.1 Tools. When specified (see 6.2), each vehicle shall be furnished with tools required for exchanging a mounted tire assembly with the spare assembly, and shall include at least a hydraulic jack, a jack handle and a wheelnut wrench. The jack shall be of such closed height as to permit its location under the axle, or other satisfactory lift point, at any wheel with the tire flat. The jack, without blocking, shall be capable of raising any wheel of the loaded vehicle to a height adequate to permit removal and replacement of the wheel and tire assembly.

3.4.17 Heater and defroster. The vehicle shall be provided with a hot water heater with fresh air intakes and discharge outlets to the floor and to the windshield defroster louvers. The heater shall be complete with blower and mounted controls convenient to the driver.

3.4.18 Controls and operating mechanisms. All controls and operating mechanisms shall be located for left hand drive. Controls shall be complete and conveniently operable by the driver. Lever controls shall be designed and located to permit easy entrance and exit of the operator to and from the driver's compartment. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. All instruments shall be visible to the driver when seated in the driving position.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T04:23Z
Check the source to verify that this is the currentversion before use.

free from slag (except mill assembly. After welding, all weldments shall be

3.4.19 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

(a) Key operated ignition switch
(b) Ammeter, charging indicator, or voltmeter
(c) Fuel gage
(d) Oil pressure gage or indicator
(e) Engine temperature gage or indicator
(f) Speedometer with recording odometer
(g) Ash receptacle
(h) Dual sunvisors
(i) Driver's compartment ventilator other than window
* (j) Tachometer
(k) Dash mounted hand throttle.

* 3.4.20 Rearview mirrors. Outside rearview mirrors shall be mounted on each side of the cab. Combination (flat and convex) mirrors, enclosed in a common housing, shall be furnished. Each combination mirror shall have at least 50 square inches of flat reflective area and a convex surface having at least 20 square inches of reflective area. The mirrors shall have not less than two supports.

3.4.21 Horn. The manufacturer's standard electric horn shall be furnished.

* 3.4.22 Engine hour meter. When specified (see 6.2), an engine hour meter having a totalizing mechanism of not less than 9,999 hours shall be furnished for the chassis engine to register accurately the number of hours of operating time. The meter shall be of rugged construction to ensure continuous trouble-free performance under severe operating conditions. The engine hour meter shall be mounted on the cab instrument panel or in the engine compartment in a readable location.

* 3.4.23 Back-up alarm. When specified (see 6.2), the vehicle shall be provided with an audible, pulsating, signaling device (electric or mechanical) to caution personnel when the vehicle is in reverse gear operation.

* 3.4.24 Air conditioning. When specified (see 6.2), the vehicle shall be equipped with the manufacturer's standard air conditioning system. The air conditioning system shall include a tinted windshield and tinted glass.

* 3.4.25 Front mounted winch. When specified (see 6.2), a winch assembly, mounted on the front of the vehicle and powered by the manufacturer's standard power takeoff or powered hydraulically, shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

provided. The winch shall conform to SAE J706. The winch shall be of the single drum type and shall have one forward and one reverse speed. All winch controls shall be mounted inside the cab. The winch controls shall be located to provide no interference with the entrance or exit of the driver. The winch shall have a rated single line pull capacity of not less than 20,000 pounds pull on the bare drum. The winch line speed on the bare drum shall be between 15 and 30 feet per minute at an engine speed equal to 35 percent of engine governed speed. The winch shall be wound with not less than 185 feet of 5/8-inch diameter, preformed, 6x37, improved plow steel, wire strand core and shall be equipped with an end chain and hook. An integral, adjustable, automatic safety brake shall be provided. The winch shall be equipped with a roller guide.

* 3.4.25.1 Winch drum guard. A winch drum guard shall be furnished. The guard shall confine the cable to the area between the drum flanges. The guard shall consist of not less than 1/4-inch vertical side plates, conforming to the outside radius of the drum flanges. Six bars, 3/8-inch by 1-1/4 inches, shall be welded to the vertical side plates. Three bars shall be located on the top and spaced equally on the top radius, and three bars shall be located on the bottom and spaced equally on the bottom radius. The vertical distance between the vertical side plate and the drum flanges shall be not more than half the specified cable diameter. Angles of the winch driveline U-joints shall be not more than 16-1/2 degrees.

* 3.4.25.2 Front bumper. The bumper shall be mounted forward of the winch. The open area on either side of the winch shall be covered with a combination step plate and gravel guard. The bumper shall be either a channel (see 3.4.15) or a pipe type. When a pipe type front bumper is furnished, the nominal diameter shall be not less than three inches, and the wall thickness shall be not less than that specified in Schedule 40 of ASTM A120. The pipe type front bumper shall have half-round ball ends.

* 3.4.25.3 Combination step plate and gravel guard. A combination step plate and gravel guard shall be furnished. The step plate shall be fabricated of not less than 14 gage (0.0747 inch) steel tread plate exclusive of projections. The step plate shall be secured to the front bumper and shall be not less than 1/4 inch or not more than 3/8 inch from the chassis sheet metal. The step plate shall be capable of supporting 300 pounds per square foot. The step plate shall not deflect more than 1/8 inch under the loads imposed.

* 3.5 Body. The vehicle shall be equipped with a hydraulically operated, rear tilt platform and a loading winch. The body shall be of all steel construction with a safety tread steel plate floor not less than 3/16 inch thick, exclusive of the raised tread. The vehicle and

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:23Z
Check the source to verify that this is the currentversion before use.

the contractor's standard ... shall be ... in accordance with

platform dimensions shall be as specified in table II. The tilt platform shall provide a level loadspace, with no kick-up over the wheels. A subframe or mounting plates shall be provided. The platform understructure, subframe or mounting plates, and reinforcements shall be not less than that required to provide rigid and safe support for hoisting and transporting a minimum payload of 12,000 pounds for type I and 30,000 pounds for type II. When tilted and touching the ground at the rear, the angle of the platform with the ground shall be not more than 17 degrees.

* TABLE II. Dimensions.

Body dimensions	Type I Inches	Type II Inches
Cab-to-axle	124 min.	—
Cab-to-trunnion	—	138 min.
Wheelbase	189 min.	204 min.
Overall length of platform, with folding ramp down	240 min.	260 min.
Overall width of platform (+1 in. - 0 in.)	95	95
Chassis frame height measured from top of frame to ground - unloaded	38 max.	38 max.
Chassis frame height measured from top of frame to ground - loaded	34-1/2 max.	37 max.

3.5.1 Header. A full width steel header, not less than 42 inches high, shall be attached in a manner to provide rigidity. A window opening shall be provided in the header, alining with the rear window in the truck cab. The window opening shall have an expanded metal coverguard.

3.5.2 Guide rails. When specified (see 6.2), four nine-foot longitudinal guide rails shall be installed along the top of the floor, starting from approximately 43 inches behind the header and running to the rear of the platform. The guide rails shall be 3 inches by 3 inches by 1/4 inch, "L" shaped structural members. The four guide rails shall be equally spaced with the outer rails running along the outer edge of the body. The lower flange of the outer guide rails shall be to the outside of the platform. The lower flange of the inner guide rails shall be to the inside of the platform.

3.5.3 Folding ramp. If a ramp is supplied, it shall be of the folding type. The ramp shall be not less than 24 inches high, of not less than 3/16-inch thick safety tread steel plate with a suitable understructure, and shall be installed completely across the rear of the platform. The ramp shall act as an approach ramp when the platform is

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

tilted for loading or unloading and as a vertical 24-inch rear bumper when the tilt platform is in the horizontal (travel) position. The ramp-bumper combination shall fold and unfold hydraulically or the hinges shall be spring loaded to assist raising. Holes in the ramp shall be provided, where necessary, for visibility of the rear lights and reflectors.

3.5.4 Platform locking device. A positive locking device, either hydraulic or mechanical, for holding down the platform in a level position, shall be provided. The device shall lock the platform down automatically when the platform is lowered to travel position.

3.5.5 Cable hook retainer. A means for retaining the hook end of the winch cable shall be provided on the floor at the left rear corner of the platform.

3.5.6 Stake pockets. The platform shall contain not less than 6 stake pockets on each side. When guide rails are specified, stake pockets need not be furnished.

3.5.7 Hydraulic system. A hydraulic pump, driven by a power takeoff, shall be provided and shall be of a capacity adequate to furnish power for the hoist and the winch.

3.5.8 Lift frame and hoist. A lift frame and hydraulic hoist shall be provided and shall be capable of raising and lowering the platform loaded with not less than 12,000 pounds for type I vehicles and not less than 30,000 pounds for type II vehicles.

3.5.9 Winch and cable. A hydraulic winch and cable shall be provided. The hydraulic winch shall be used to draw equipment, not operating under its own power, aboard the tilted platform and for controlling the descent of the equipment during unloading. The winch shall conform to SAE J706. The capacity of winch, cable, chain and hook assembly shall be adequate for loads weighing not less than 12,000 pounds for type I vehicles and not less than 30,000 pounds for type II vehicles. The winch shall have one forward and one reverse speed. The cable, not less than 50 feet in length, shall be of 5/8-inch diameter, preformed, 6x37 improved plow steel, wire core for type I vehicles and of 3/4-inch diameter, preformed, 6x37 extra-improved plow steel, interwoven rope core for type II vehicles. A 6-foot winch chain, steel loading, 3/8-inch, with hook, shall be furnished at the end of the cable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 3.5.10 Winch and tilting platform controls. Controls shall be installed to permit operation of the tilt platform and the winch from a recessed control box located on the streetside to the rear of the rear axle. When a hydraulically operated folding ramp is furnished, its controls also shall be so located.

3.5.11 Safety lock. A mechanical safety lock permanently affixed to the lift body shall be provided. The safety lock shall provide positive retention of the body in the up position for servicing and repair. The safety lock mechanism shall not interfere with the operation of the body under any operating condition.

3.5.12 Tool box. Manufacturer's standard tool box shall be provided. The tool box shall be located on the streetside of the vehicle rearward of the cab, and shall be secured to the vehicle frame members. The tool box shall be provided with two side-hinged double panel doors. A recessed handle shall be furnished. The tool box shall be not less than 20 inches deep, 20 inches in height, and 36 inches in length and shall be constructed of not less than 12 gage (0.1046 inch) sheet steel. Provisions for locking shall be furnished.

* 3.5.13 Hydraulic fluid identification plate. A corrosion resistant identification plate indicating the type of hydraulic fluid to be used shall be installed near the filler cap.

* 3.6 Servicing and adjusting. Prior to acceptance of the vehicle by the Government inspector, the contractor shall service and adjust each vehicle for operational use including at least the following: alinement of lights; adjustment of engine and brake systems; filling and charging of the batteries; alinement of front wheels; inflation of all tires; complete lubrication of the chassis, engine and running gear with grades of lubricants recommended for the ambient air temperature at the delivery point; servicing of the cooling system with a solution of ethylene glycol type antifreeze and water in equal parts by volume; and servicing of the windshield washer reservoir with water and appropriate additives. Cables, where used, shall be lubricated with proper lubricants to resist corrosion.

3.7 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished. Welded, bolted and riveted construction utilized shall be in accordance with the highest standards of the industry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility for assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of the product to specification criteria has been demonstrated.

4.3 First production vehicle inspection. The first vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformance to the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

* 4.3.1 Vehicle weight. The first production vehicle shall be weighed to determine the curb weight and the distribution of the curb weight on front and rear axles. The total imposed loading on front and rear axles shall be computed by the contractor and verified by the Government, using the curb weight, the operator weight at 175 pounds, and the payload (see 3.2.4) to provide the specified GVW. The calculated imposed loads on the front and rear axles shall be compared to the suspension, axle and tire load capacity ratings to determine if these components are of adequate capacity to meet contractual requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 4.3.2 Road test. The first production vehicle shall be examined and road tested by the contractor with full rated payload. The road test shall be for not less than 50 miles at speeds up to 55 mph, with a sudden stop after each 10 miles traveled. The distance traveled shall consist of highway, rough dirt roads, puddles and sharp turns. The platform, loading winch and ramp shall be operated for 10 cycles, loading and then unloading a forklift truck or similar vehicle of a weight equal to payload capacity.

* 4.3.3 Truck body treatment and painting. A certification regarding the body cleaning, treating, prime painting and salt spray resistance testing required by MIL-STD-1223 shall be made to the Government representatives at the first production vehicle inspection.

4.3.4 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample and shall be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

4.3.5 Failure. Failure of the first production vehicle to meet the requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under contract until corrective action has been taken.

* 4.4 Inspection of production vehicles. The contractor's inspection system shall, as a minimum, assure that the vehicle conforms to the physical and dimensional requirements and is capable of meeting performance requirements contained herein. For each vehicle under contract, the contractor shall make available to the Government, at the point of final acceptance, records acceptable to the Government indicating that the servicing and adjusting required by 3.6 have been accomplished.

5. PACKAGING

5.1 Vehicle processing. The vehicle shall be processed for shipment from the manufacturer's plant to the initial receiving activity in accordance with the manufacturer's standard commercial practice.

6. NOTES

* 6.1 Intended use. The vehicles covered by this specification are intended for the loading and transporting of forklift trucks and similar equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type of vehicle required (see 1.2).
(c) Identification of appropriate service for painting and marking (see 3.1.1.1).
(d) Concealed markings, if required (see 3.1.1.1).
(e) Rustproofing, if required (see 3.1.1.2).
(f) Tropical rustproofing, if required (see 3.1.1.2).
(g) Trailer towing package, if required (see 3.1.1.5).
(h) Gasoline engine, if required (see 3.4.1.2).
(i) Power plant heaters, if required (see 3.4.1.8).
(j) If a battery heater is not required with power plant heaters (see 3.4.1.8).
(k) Rotating warning light, if required (see 3.4.2.6).
(l) Front spotlights, if required (see 3.4.2.7).
(m) Spark arrester, if required (see 3.4.4.1).
(n) Automatic or semiautomatic transmission, if required (see 3.4.5.2).
* (o) Oil lubricated wheel bearings and axle spindles, if required (see 3.4.9.).
(p) Two-speed axle, if required (see 3.4.9.1).
(q) Traction control, if required (see 3.4.9.3).
(r) Wide base type tires and wheels, if required (see 3.4.10).
(s) Disc type wheels, if required (see 3.4.10).
(t) Bias ply tires, if required (see 3.4.10.1).
(u) Spare tire carrier, if required (see 3.4.10.3).
(v) Spare wheel or rim, if required (see 3.4.10.4).
(w) Spare tire assembly, if required (see 3.4.10.5).
(x) Brake controls for use from a towing vehicle, if required (see 3.4.11.3).
(y) Tilting hood and fender assembly, if required (see 3.4.12).
(z) Tilt type cab, if required (see 3.4.12).
(aa) Individual driver and passenger seats, if required (see 3.4.12).
(ab) Tools, if required (see 3.4.16.1).
(ac) Engine hour meter, if required (see 3.4.22).
(ad) Back-up alarm, if required (see 3.4.23).
(ae) Air conditioning, if required (see 3.4.24).
(af) Front mounted winch, if required (see 3.4.25).
(ag) Guide rails, if required (see 3.5.2).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:23Z
Check the source to verify that this is the current version before use.

6.3 Performance prediction. The SAE Truck Ability Prediction Procedure computations and computations for low speed and maximum geared speed will be required by the contract. The SAE Work Sheet Item 1 should include vehicle model number, engine model number and vehicle type. Unless other conditions are cited in the contract, computations should be made for normal atmospheric pressure, in normal ambient air temperature and still, dry air. The factors to be used in predicting truck ability (see 3.3.1.1) are established as follows for the corresponding SAE Truck Ability Prediction Tables:

Table 1	- Tire Factor. This factor must relate to the size of tires furnished by the contractor in accordance with this specification.
Table 2	- Altitude Factor. 1.00
Table 3	- Rolling Factor. 1.613
Table 4	- Area Factor. 0.173
Table 5	- Velocity Factor. 250.0
Table 6	- Altitude Factor. 1.00
Table 7	- Chassis Friction Horsepower. Use applicable power unit GVW (to nearest, higher, 1,000 pounds) and the engine rpm (to nearest 100 revolutions) which is required for 50 mph geared speed. For GVW and engine speed beyond the range of this table, factors shall be extrapolated.
Table 8	- Grade Factor. 0.75
Table 8A	- Correction Factor. Not required.
Table 9	- Road Factor. 0.0.

* 6.4 Subject term (key word) listing.
Hydraulic winch
Radio interference suppression
Rotating warning light
Spark arrester
Traction control.

6.5 Identification of changes. The margins of this specification are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

document based on the entire content regardless of the marginal notations and relationship to the last previous issue.

Custodian:
Army - AT

Preparing Activity:
Army - AT
Project Number 2320-A324

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
U.S. ARMY NAVY-AUTOMOTIVE COMMAND
ATTN: AMSTA-UED
WARREN, MICHIGAN 48397-5000

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE MIL-T-62126C(AT) TRUCKS, EQUIPMENT TRANSPORT, TILT PLATFORM, DED/GED, 24,000 GVW, 4x2, AND 44,500 GVW, 6x4, COMMERCIAL

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.