NOT MEASUREMENT SENSITIVE

MIL-T-62318C
16 April 1990
SUPERSEDING
MIL-T-62318B
28 September 1984

MILITARY SPECIFICATION

TRUCK, MULTISTOP DELIVERY: FORWARD CONTROL AND CHASSIS, TRUCK: FORWARD CONTROL, DIESEL AND GASOLINE ENGINE DRIVEN, 13,000 TO 21,000 POUNDS GVW, 4x2, COMMERCIAL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

* 1.1 Scope. This specification covers diesel and gasoline engine driven, four-wheel, two-rear wheel drive, multistop delivery trucks and truck chassis, having minimum gross vehicle weights (GVW) of 13,000 to 21,000 pounds, for normal operating conditions. Vehicles procured under this specification are commercial items which shall be warranted by the manufacturer as specified in acquisition documents.

1.2 Classification. The vehicle shall be one of the types and classes shown in table I, as specified (see 6.2):

TABLE I. Vehicle classification.

Type	Nomenclature	Class
I	Truck, multistop delivery, forward control	A - - -
II	Chassis, truck, forward control	A B C D
III	Chassis, truck, forward control, with front section	A B C D

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-UEL, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC-2320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

1.2.1 Class. Class of vehicle shall be determined by minimum gross vehicle weight rating as follows:

Class A - 13,000 pounds
Class B - 16,000 pounds
Class C - 19,000 pounds
Class D - 21,000 pounds.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS), and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS
FEDERAL

	W-B-131	- Battery, Storage: Vehicular, Ignition, Lighting and Starting.
*	VV-F-800	- Fuel Oil, Diesel.

MILITARY

*	MIL-P-514	- Plates, Identification, Instruction and Marking, Blank.
*	MIL-T-5624	- Turbine Fuel, Aviation, Grades JP-4 and JP-5.
	MIL-B-46176	- Brake Fluid, Silicone, Automotive All Weather, Operational and Preservative.
*	MIL-T-83133	- Turbine Fuel, Aviation, Kerosene Type, Grade JP-8.

STANDARDS
FEDERAL

	FED-STD-297	- Rustproofing of Commercial (Nontactical) Vehicles.

STANDARDS
MILITARY

	MIL-STD-1223	- Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking and Data Plate Standards.

* (Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from the Naval Publications and Forms Center, Military Specifications and Standard, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

* DEPARTMENT OF DEFENSE
Department of Defense Index of Specifications and Standards (DODISS).

(Copies of the DODISS are available on a yearly subscription basis either from the Government Printing Office for hard copy, or microfiche copies are available from the Director, Navy Publication and Printing Service Office, 700 Robbins Avenue, Philadelphia, PA 19111-5093.)

DEPARTMENT OF TRANSPORTATION (DoT)
Federal Motor Carrier Safety Regulations.
Federal Motor Vehicle Safety Standards.

(Application for copies of DOT publications should reference the Code of Federal Regulations, 49 CFR, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)
Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines.
Noise Emission Standards for Transportation Equipment - Medium and Heavy Trucks.

(Application for copies of EPA publications should reference the Code of Federal Regulations, 40 CFR, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

* 2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

* THE EUROPEAN TYRE AND RIM TECHNICAL ORGANISATION (ETRTO)
Standards Manual

(Application for copies of the ETRTO publications should be addressed to the European Tyre and Rim Technical Organisation, 32, Avenue Brugmann, 1060 Brussels, Belgium.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* NORTH ATLANTIC TREATY ORGANIZATION (NATO)
Allied Engineering Publication (AEP-5)
Part II - NATO Standard Diesel and Spark Ignition Engines Laboratory Test, dated January 1984.

(Application for copies of NATO publications should be addressed to North Atlantic Treaty Organization, Military Agency for Standardization, 1110 Brussels, Belgium.)

SAE, INC.
SAE Standards and Recommended Practices.

J537	- Storage Batteries.
J551	- Performance Levels and Methods of Measurement of Electromagnetic Radiation from Vehicles and Devices (30-1000 MHz).
J588	- Turn Signal Lamps.
J589	- Turn Signal Switch.
J682	- Rear Wheel Splash and Stone Throw Protection (DoD adopted).
* J683	- Tire Chain Clearance - Trucks, Buses, and Combinations of Vehicles.
J688	- Truck Ability Prediction Procedure (DoD adopted).
J704	- Openings for Six- and Eight-Bolt Truck Transmission Mounted Power Take-Offs (DoD adopted).
J1349	- Engine Power Test Code - Spark Ignition and Diesel.

(Application for copies of SAE publications should be addressed to SAE, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC.
Year Book.

(Application for copies of Tire and Rim Association publications should be addressed to the Tire and Rim Association, Inc., 3200 W. Market Street, Akron, OH 44313.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

* 3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.9, the vehicle, components, assemblies, and accessories to be delivered under the contract shall be standard or optional items, which meet or exceed the requirements of this specification. Except as specified in 3.1.1 through 3.1.1.9, no removal, substitution or alteration of the chassis manufacturer's standard or optional chassis model components shall be made. All chassis items shall be as represented in the chassis manufacturer's technical data book. Special bodies or mounted equipment shall be as represented in the body and equipment manufacturer's technical data. Technical data shall be limited to specifications and technical material identical to that furnished to the authorized company representatives for selection of vehicle models and components, and shall be available to the engineering offices of the procuring activity, prior to delivery of the items. The chassis model furnished shall be not older than the chassis manufacturer's current model on the date of invitation for bids.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

* 3.1.1.1 Painting and marking. Treatment, painting, marking and data plates shall be in accordance with MIL-STD-1223. The exterior color and the identification markings shall be in accordance with the requirements of MIL-STD-1223 for the military service identified by the procuring activity (see 6.2). When specified (see 6.2), concealed markings shall be furnished.

* 3.1.1.2 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with FED-STD-297. When specified (see 6.2), tropical rustproofing in accordance with FED-STD-297 shall be furnished.

3.1.1.3 Towing devices. Towing devices consisting of two hooks, loops, eyes or pins or the manufacturer's standard single center mounted eye or pin, for towing the vehicle, shall be furnished on the front of the vehicle.

3.1.1.4 Rear end splash shields. Rear end splash shields for type I multistops (see 3.5.1.3) shall be provided. All splash shield and mud flap installations, front and rear, shall conform to the rear wheel splash and stone throw protection provisions of SAE J682.

3.1.1.5 Silicone brake fluid. When specified (see 6.2), and if available as the manufacturer's standard or optional brake fluid, brake fluid conforming to MIL-B-46176 shall be provided in the hydraulic brake system. A decal or plate shall be placed near the master cylinder stating "CAUTION: USE SILICONE BRAKE FLUID ONLY, MIL-B-46176."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 3.1.1.6 Hydraulic fluid identification plate. When a body hydraulic system is furnished and the hydraulic system requires fluid replenishment, a decal or plate shall be installed near the filler cap and shall identify the type of hydraulic fluid to be used. (See 3.1.1.7.)

* 3.1.1.7 Decals and data plates. The hydraulic tailgate operating instructions and the hydraulic fluid identification information and the power takeoff caution notice shall conform to type I or type II, class 1 of MIL-M-43719 or composition A (class 1 or 2) or composition C of MIL-P-514.

* 3.1.1.8 Drain plugs. All drain plugs installed in manual transmissions and rear axles shall be of the permanent magnet type.

* 3.1.1.9 Brake lights. At least one pair of brake lights shall override the four-way emergency flasher. Modifications to the manufacturer's standard product to accommodate this requirement shall not compromise conformance to any Federal Motor Carrier Safety Regulation referenced herein or to any Federal Motor Vehicle Safety Standard. If additional lights are added to the vehicle, the lights shall be selected from the chassis or body manufacturer's standard matching hardware.

3.2 General design.

3.2.1 Federal Motor Vehicle Safety Standards. The vehicle and furnished accessories shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture.

3.2.2 Air pollution control. The vehicle shall comply with EPA regulations governing Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines in effect on the date of manufacture. In addition, vehicles destined for California shall comply with State of California regulations governing air pollution control in effect on the date of manufacture.

3.2.3 Sound level. The interior sound level shall conform to Federal Motor Carrier Safety Regulation 393.94. The vehicle exterior sound level shall conform to EPA Noise Emission Standards for Transportation Equipment - Medium and Heavy Trucks.

3.2.4 Curb weight. The curb weight shall include the weight of the chassis with all attachments, accessories, and equipment; the body (except for types II and III); and a full complement of fuel, lubricants, and coolant.

3.2.5 Gross vehicle weight. Gross vehicle weight (GVW) shall consist of curb weight, operator weight (computed at 175 pounds), and a payload to provide not less than the specified GVW.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

3.2.6 Weight distribution. For type I multistop, the gross axle weight ratings (GAWR) shall be not less than 4,000 pounds on the front and 10,000 pounds on the rear. For types II and III chassis, the distribution of specified GVW for the purpose of establishing suspension, axle and tire rating requirements shall be determined with the payload (difference between specified GVW and curb weight including operator) evenly distributed over the specified body load area (see 3.5.2 or 3.5.3).

3.2.7 Ratings. Vehicle ratings shall be the manufacturer's published ratings. Component and vehicular ratings shall not be raised to meet the requirements of this specification. When published ratings are not available, verification of ratings shall be available to the engineering office of the procuring activity. Minimum GVW ratings shall conform to table II for the specified class of vehicle.

TABLE II. GVW minimum ratings.

Class	GVW, pounds
A	13,000
B	16,000
C	19,000
D	21,000

* 3.2.8 Accessibility. The design of the vehicle and optional equipment shall permit access for routine servicing and shall permit access for replacement and adjustment of component parts and accessories with minimal disturbance of other components and systems.

* 3.2.9 Asbestos. Asbestos materials shall not be used in any part of the vehicle.

3.3 Performance.

3.3.1 Speeds and gradeability. High and low speed requirements shall be met with the truck loaded to specified GVW.

3.3.1.1 High speed gradeability. The vehicle shall ascend continuous grades specified in table III at 50 miles per hour (mph). Gradeability requirements shall be met with the main transmission in direct drive. Gradeability shall be verified with calculations in accordance with SAE J688 (see 6.4).

TABLE III. Gradeability.

Class	Percent grade
A	2.2
B	2.5
C	1.5
D	1.5

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 3.3.1.2 Low speed. Low speed for vehicles with a manual transmission shall be calculated with the engine operating at not less than 35 percent of recommended governed speed, and shall provide not more than the vehicle speed specified in table IV for the corresponding number of available forward speeds.

TABLE IV. Vehicle low speed requirements.

Number of forward speeds	Maximum low speed (mph)
4 or 5	4.5
6	3.5
9 or 10	3.0

3.3.1.3 Maximum geared speed. The maximum geared speed at engine governed speed shall be not less than 58 mph. Conformance to geared speed specified shall be determined by calculating in accordance with the following formula:

$$\text{Maximum geared speed (mph)} = \frac{\text{Governed speed (rpm)}}{\text{Total gear reduction x tire factor (see 6.3)}}$$

3.3.2 Service brakes. The service brakes shall control and hold the vehicle, when loaded to its specified GVW, on a 30 percent grade. The service brakes shall stop the vehicle, loaded to specified GVW, within the stopping distance requirements of Federal Motor Carrier Safety Regulation 393.52.

3.4 Chassis components.

3.4.1 Engine. The engine furnished for the specified vehicle class shall be the chassis manufacturer's standard or optional engine for the commercial model truck which meets or exceeds the requirements of this specification.

* 3.4.1.1 Diesel engine. Unless otherwise specified (see 3.4.1.2), the vehicle shall be equipped with a liquid cooled, compression ignition, two-stroke or four-stroke cycle diesel engine, with not less than four cylinders. Engine net horsepower used in performance prediction calculations shall be determined in accordance with SAE J1349. The engine shall demonstrate the performance characteristic specified herein when using diesel fuel conforming to VV-F-800. In addition, when specified (see 6.2), the engine shall operate satisfactorily on grade JP-4 and grade JP-5 fuel conforming to MIL-T-5624 under emergency, short duration conditions and on grade JP-8 fuel conforming to MIL-T-83133 under normal conditions. A power loss when operating on JP-4, JP-5 or JP-8 is acceptable. A test report shall be available showing that a representative engine has been tested and certified to meet the requirements of NATO AEP-5 test procedures (400 hours dynamometer test to assure JP-8 compatibility).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 3.4.1.2 Gasoline engine. When specified (see 6.2), the vehicle shall be equipped with a liquid cooled, internal combustion, four-stroke cycle gasoline engine with not less than six cylinders. The engine furnished shall produce the required vehicle performance when operated on unleaded fuel with a research octane rating of 91, at an engine speed not more than the manufacturer's recommended operating speed. The engine shall be capable of warranted operation on unleaded fuel, when used in accordance with the operator's manual. Engine net horsepower used in performance prediction calculations shall be determined in accordance with SAE J1349. Unless otherwise specified or required by foreign laws, vehicles for overseas use shall be capable of accepting and operating on leaded gasoline.

3.4.1.3 Oil filter. A full flow type oil filter shall be furnished.

* 3.4.1.4 Cooling system. The cooling system shall maintain engine coolant at a temperature below the boiling point with the vehicle loaded to rated GVW and operated at an altitude of 10,000 feet above sea level or in an ambient air temperature of not less than 125 degrees Fahrenheit (°F). The coolant system shall include a surge tank, or a coolant recovery reservoir of not less than two-quart capacity.

3.4.1.5 Coolant temperature control. Thermostatic control of engine coolant temperature shall be provided. On diesel engine driven vehicles, the control shall include partial thermostatic control of coolant flow through the radiator and thermostatically controlled radiator shutters or complete thermostatic control of all coolant flow through the radiator.

3.4.1.6 Governor. For class C and D vehicles, an engine governor shall be furnished, set and sealed to limit the engine to the engine manufacturer's maximum recommended operating speed.

* 3.4.1.7 Fan clutch. A fan clutch shall be provided. The fan clutch shall reduce the fan speed automatically when the fan is not required for engine cooling. The fan clutch shall be asbestos free.

* 3.4.1.8 Power plant heaters. When specified (see 6.2), a coolant heater, an engine oil heater, and a fuel warmer (diesel engine driven vehicles only) shall be provided. Unless otherwise specified (see 6.2), a battery heater shall be provided when power plant heaters are specified. Heaters shall operate on 110-volt alternating current (ac), and shall be wired through a junction block, including a fuse or circuit breaker, to a single three-pronged (male), weatherproof slave receptacle for receiving external power and grounding the vehicle. A three-wire connecting cable, 25 feet long and of adequate line capacity to supply power for all heater units simultaneously, shall be furnished. Connecting cable shall include a matching female connector at the vehicle end and a standard, three-pronged (two power plus one ground) male connector at the other end. Electrical apparatus shall conform to Federal Motor Carrier Safety Regulation 393.77(c)(7). Electrical insulation of the connecting cable shall withstand

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

normal operating stresses in low ambient air temperature (down to minus 60°F) without cracking or loss of dielectric capacity. All heater lead wires shall be installed without interfering with vehicle component operation and without loose excess wire. Provisions for stowage of the cable shall be provided in the vehicle cab. Heaters shall be provided as follows:

(a) Coolant heaters, 1500-watt minimum rating, shall be installed in the engine block or lower coolant inlet hose. Engine thermostat with an operating range of 170°F to 195°F shall be installed
(b) An immersion type engine oil heater, 300-watt minimum rating, with 170°F to 195°F thermostat, shall be installed in the oil pan through any convenient opening
(c) The battery heater shall have a capacity adequate to maintain the battery electrolyte at a temperature of not less than 10°F during vehicle exposure in ambient air temperature as low as minus 60°F, and shall embody a thermostat to limit the temperature of the electrolyte to not more than 80°F
(d) A fuel warmer or preheater shall be provided on diesel engine driven vehicles to prevent clogging of fuel filters due to wax crystallization in the fuel. The fuel warmer shall use engine coolant to transfer sufficient heat to the diesel fuel to heat it from an inlet temperature of minus 40°F to an outlet temperature of plus 9°F, with a flow rate not less than the maximum fuel demand of the engine fuel system. A coolant shutoff valve shall be provided for the coolant inlet side of the fuel warmer unit.

* 3.4.1.9 Silicone rubber hose. When specified (see 6.2), silicone rubber radiator and heater hoses shall be furnished.

3.4.2 Electrical system. The electrical system shall be in accordance with Federal Motor Carrier Safety Regulations 393.27 through 393.31 and 393.33.

* 3.4.2.1 Starting system. For diesel engine driven vehicles, a 12- or 24-volt direct current (dc) starting system, with a 12-volt dc lighting system, and not less than a 60-ampere alternator, shall be furnished. Engine starting equipment shall include an ether starting system, glow plug or electric grid heater. If an ether system is furnished in lieu of a glow plug or grid heater, it shall be of the measured shot type. The measured shot type ether system shall be key operated or manually operated from the driver's compartment, and shall be inoperative with the engine warm. Complete provisions for a replaceable reservoir of not less than 12 fluid ounces shall be furnished. A reservoir need not be furnished.

3.4.2.2 Ignition system. For gasoline engine driven vehicles, a 12-volt dc ignition system shall be furnished. An alternator of not less than 40 amperes rated capacity and which provides not less than 16 amperes dc output at normal engine idle speed shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

3.4.2.3 Lighting. All vehicle lights, reflectors, and wiring shall conform to Federal Motor Carrier Safety Regulations 393.12, 393.13, 393.19, 393.20 and 393.22 through 393.26(d). Type II and III chassis need not be furnished with rear identification lamps or clearance lamps and reflectors. Lights and reflectors shall not be mounted on vertical surface of rub rails (unless recessed and fully protected) or mounted on vehicle bumpers. On type I multistops, the taillights, stoplights and rear turn signals shall be located to avoid obstruction by the rear doors when the doors are in the fully opened position.

3.4.2.4 Turn signals. Turn signal lamps shall conform to SAE J588. Operating units shall conform to SAE J589, class A, and shall be mounted on the steering column. Type I multistop and type III chassis shall have lights integrally mounted in the body. Type II chassis shall be provided with single-faced front and rear signal units. Turn signal units shall be installed in accordance with SAE J588. Turn signal operating units shall be of the self-cancelling type with visible and audible type flash indicator. Temporary mounting for the rear signal units shall be provided on type II and type III vehicles.

3.4.2.5 Batteries. Each battery shall be of 12-volt potential. The total reserve capacity rating and the total cold cranking rating at 0°F, both measured in accordance with SAE J537, shall be not less than as specified in table V. Batteries shall be of the maintenance-free type having the maintenance-free characteristics listed in W-B-131.

* TABLE V. Batteries.

Engine type	Reserve capacity (minutes)	Cold cranking (amperes)
Diesel	320	1,200
Gasoline	100	450

3.4.2.6 Radio interference suppression. The vehicle shall be suppressed to limit electromagnetic radiation in accordance with SAE J551. Any body equipment emitting electromagnetic radiation shall be suppressed to the same level as the vehicle chassis.

3.4.3 Fuel system. The fuel system shall conform to Federal Motor Carrier Safety Regulations 393.65 and 393.67.

* 3.4.3.1 Air cleaner. An air cleaner shall be furnished.

3.4.3.2 Fuel tank. A fuel tank of not less than 24 gallons capacity shall be furnished for type I. A fuel tank of not less than 30 gallons total capacity shall be furnished for types II and III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

3.4.4 Exhaust system. The exhaust system shall conform to Federal Motor Carrier Safety Regulation 393.83. On type I multistops, the exhaust system shall discharge at the rear of the vehicle or to the side behind the rear wheels.

* 3.4.5 Transmission. The input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine. Transmission and axle gear ratios shall be selected to provide the performance specified in 3.3.1 through 3.3.1.3.

* 3.4.5.1 Automatic or semiautomatic transmission. Unless otherwise specified (see 3.4.5.2), the vehicle shall be provided with automatic or semiautomatic transmission. The transmission shall include a hydraulic torque convertor and not less than three forward gear ratios for type I multistops and four forward gear ratios for all other types. The normal driving range selector position shall provide not less than four gear ratios without movement of the selector (three on type I).

3.4.5.2 Manually shifted transmission. When specified (see 6.2), a manually shifted transmission shall be furnished. The manually shifted transmission for class A, B, and C vehicles shall have not less than four forward and one reverse speed, with SAE J704 power takeoff opening provided. For class D vehicle, the transmission shall have not less than five forward and one reverse speed with SAE J704 power takeoff openings on both right and left sides. The transmission shall provide for synchronized shift for at least the three highest forward speeds, or for class D, vehicle constant mesh transmission may be provided.

3.4.5.2.1 Clutch. The clutch shall be of the largest capacity offered for the type and class vehicle and engine furnished, with the clutch torque capacity exceeding the maximum delivered engine torque. The clutch lining shall be asbestos free.

* 3.4.5.3 Power takeoff. When a power takeoff is furnished, it shall be of a rated capacity to operate powered equipment. Controls to operate the power takeoff shall be located in the truck cab accessible to the seated driver. A caution decal or plate reading "DO NOT OPERATE VEHICLE AT HIGHWAY SPEEDS WITH POWER TAKEOFF ENGAGED" shall be installed, readily visible to the seated driver. (See 3.1.1.7.)

3.4.6 Driveline components. Driveline components shall be adequate to transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction.

3.4.7 Frame. The chassis frame shall be the manufacturer's standard for the type and class vehicle furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

3.4.8 Suspension. The vehicle shall be equipped with a suspension system with components having a rated capacity at least equal to that specified in 3.2.6 for type I multistop and to the load imposed on each member, measured at the ground, with the vehicle loaded to specified GVW for all other vehicle types. When suspension capacity is rated at the spring pads, unsprung weight shall be deducted. The vehicle shall be equipped with hydraulic, double-acting shock absorbers at the front wheels.

3.4.9 Axles. Axle ratings shall be at least equal to that specified in 3.2.6 for type I multistop and to the load imposed on each axle, measured at the ground, with the vehicle loaded to specified GVW for all other vehicle types. A single reduction rear axle shall be furnished. A vehicle provided with an automatic or semiautomatic transmission shall be equipped with a single-speed axle.

3.4.9.1 Traction control. When specified (see 6.2), the vehicle shall be furnished with a traction control on the rear axle. The traction control shall actuate automatically to ensure that power is transmitted to the wheel having traction when the opposite wheel loses traction. Maximum traction capabilities shall be maintained at all times under each drive wheel for the life of the vehicle.

* 3.4.10 Wheels, rims, tires, and tubes. The vehicle shall be equipped with single front and dual rear wheels. Rims and tire ratings shall conform to Tire and Rim Association or European Tyre and Rim Technical Organisation recommendations for the type and size of tires furnished. Multi-piece rims shall not be furnished. Rims and disc wheel sizes shall be the same for all wheels on each vehicle. Tire size and load range (ply rating) shall be the same for all tires on each vehicle. When specified (see 6.2), disc type wheels shall be furnished.

* 3.4.10.1 Tires. Tires shall be tube or tubeless type with highway tread. Tires for class C and D vehicles shall be of the steel belted radial type, or when specified (see 6.2), bias ply. Tires shall be of rated capacity at least equal to that specified in 3.2.6 for type I multistop and to the load imposed on each tire, measured at each wheel, at the ground, with the vehicle loaded to specified GVW for all other vehicle types. Tires and tire size designations shall conform to Tire and Rim Association or to the European Tyre and Rim Technical Organisation recommendations.

3.4.10.2 Inner tubes. When tube type tires are specified in procurement documents, the inner tubes shall be of heavy duty type, and shall be of proper size for tires furnished. Tire flaps shall be provided for tube type tires in accordance with Tire and Rim Association recommendations.

3.4.10.3 Carrier for spare tire assembly. When specified (see 6.2), a carrier for a spare wheel or rim and tire assembly shall be installed in a readily accessible location on the vehicle. Threaded fasteners, when used to

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

secure the spare tire in the carrier, shall be constructed of or plated with corrosion-resistant material. The carrier design shall enable removal or mounting of spare wheel assembly using only the tools specified in 3.4.15.1.

3.4.10.4 Spare wheel or rim. When specified (see 6.2), a spare wheel or rim shall be furnished. When a spare tire assembly is specified (see 3.4.10.5), a spare wheel or rim shall be furnished.

3.4.10.5 Spare tire assembly. When specified (see 6.2), a spare tire assembly shall be furnished. The spare tire assembly shall include an inflated spare tire mounted on the spare wheel or rim. The spare tire shall be of the same size, tread design and load range (ply rating) as the tires furnished on the vehicle.

* 3.4.10.6 Tire chain clearance. Tire chain clearance in accordance with SAE J683 shall be provided. Allowance for spring deflection shall be included.

* 3.4.11 Brakes. Brakes shall conform to Federal Motor Carrier Safety Regulations 393.40 through 393.43 and 393.45 through 393.52. Brake linings shall be of nonasbestos material.

3.4.11.1 Power hydraulic brakes. The vehicle shall be equipped with power-assisted, hydraulically actuated, four-wheel service brakes.

3.4.11.1.1 Split hydraulic brake system. The power-hydraulic brake system shall be so arranged as to provide separate systems for at least two wheels and so designed and constructed that rupture or leakage type failure of any single pressure component of the service brake system, except structural failures of the brake master cylinder body, effectiveness indicator body, or other housing common to the divided system, will not result in complete loss of function of the vehicle brakes when force on the brake pedal is continued. "Pressure component" means any internal component of the brake master cylinder or master control unit, wheel brake cylinder, brake line, brake hose, or equivalent, except power assist components.

3.4.11.1.2 Indicator light. The split hydraulic brake system shall be equipped with an electrically operated red light mounted on the instrument panel to indicate system effectiveness. The light shall have an area of not less than 0.196 square inch. It shall illuminate before or upon application of the brakes when an actuating pressure component of the system has sustained a loss of pressure. The indicator light system shall include a means for testing by the vehicle operator to assure that the light bulb is operable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

3.4.12 Steering. Power steering shall be furnished.

3.4.13 Windshield wipers and washers. Type I and type III vehicles shall be equipped with dual windshield wipers and windshield washers. Windshield wipers shall be multispeed type and operated by electric motor(s).

3.4.14 Bumper. A channel type front bumper shall be provided on Type II and type III vehicles. The manufacturer's standard front bumper shall be furnished on type I multistops.

3.4.14.1 Rear end protection. The rear end of the type I vehicle shall be protected in accordance with Federal Motor Carrier Safety Regulation 393.86. A rear bumper shall be provided as specified herein for the various vehicle types.

3.4.15 Tool stowage. On type I vehicle, stowage space of sufficient size to accommodate a vehicle jack, hand tools, antiskid chains and emergency reflective triangles shall be furnished for retaining equipment during vehicle operation.

3.4.15.1 Tools. When specified (see 6.2), each vehicle shall be furnished with tools required for exchanging a mounted tire assembly with the spare assembly, and shall include at least a jack, jack handle and wheelnut wrench. The jack shall be of such closed height as to permit its location under an axle, or other satisfactory lift point, at any wheel with the tire flat. The jack, without blocking, shall be capable of raising any wheel of the loaded vehicle to a height adequate to permit removal and replacement of the wheel and tire assembly.

3.4.16 Heater and defroster. A hot water heater shall be provided. The heater shall have fresh air intakes. Discharge outlets shall be provided to direct heated air to the floor and to defroster louvers. The heater shall be complete with blower and mounted controls convenient to the driver.

3.4.17 Controls and operating mechanisms. All controls and operating mechanisms shall be located for left-hand drive. Controls shall be complete and conveniently operable by the driver. Lever controls shall be designed and located to permit easy entrance and exit of the operator to and from the driver's compartment. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. Instruments shall be panel mounted and visible to the driver when seated in the driving position.

3.4.18 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. Except for type II chassis which shall not require additional equipment and type III chassis which will not require sunvisors, the following minimum equipment shall be furnished:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

(a) Key-operated ignition switch
(b) Ammeter, charging indicator or voltmeter
(c) Fuel gage
(d) Oil pressure gage or red indicator warning light
* (e) Engine coolant temperature gage or high coolant temperature or low coolant level red indicator warning light
* (f) High coolant temperature or low coolant level alarm buzzer
(g) Speedometer with recording odometer
(h) Ash receptacle
(i) Dual sunvisors
(j) Driver's compartment ventilator other than window
(k) Tachometer (diesel engine driven vehicles only).

* 3.4.19 Rearview mirrors. On type I and type III vehicles, outside rearview mirrors shall be mounted on each side of the vehicle. The mirrors shall be of the combination type having flat and convex areas enclosed in a common housing. The flat portion shall have not less than 50 square inches of reflective area. The convex portion shall have not less than 25 square inches of reflective area. The mirrors shall have not less than two supporting arms.

3.4.20 Horn. The manufacturer's standard electric horn shall be furnished.

3.4.21 Engine hour meter. When specified (see 6.2), an engine hour meter having a totalizing mechanism of not less than 9,999 hours shall be furnished for the chassis engine to register accurately the number of hours of operating time. The meter shall be of rugged construction to ensure continuous trouble-free performance under severe operating conditions. The engine hour meter shall be mounted on the instrument panel or in the engine compartment in a readable location.

3.4.22 Back-up alarm. When specified (see 6.2), the vehicle shall be provided with an audible, pulsating, signaling device (electric or mechanical) to caution personnel when the vehicle is in reverse gear operation.

3.5 Vehicle types.

3.5.1 Type I (multistop delivery, forward control). Type I vehicle shall be built on a forward control chassis and shall have an integral driver's compartment and an enclosed body. An upholstered, bucket type driver's seat with pedestal shall be furnished. The seat shall be adjustable fore and aft and for height. The driver's seat pedestal shall be provided with a positive locking mechanism to secure the seat in place when in use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

3.5.1.1 Body materials. Except as otherwise specified herein, the body shall be constructed of sheet metal having minimum gages specified for carbon steel; high tensile steel utilized may be two gages lighter weight in accordance with US Standard gages. Aluminum alloys of equal strength may be furnished.

3.5.1.2 Steps, doors and windows. Inset steps shall be provided at both front entrances. External inset steps shall be provided with a step height of not more than 21 inches above ground level. The body shall have sliding type front doors with door openings not less than 24 inches wide by 66 inches high. Sliding windows with not less than 360 square inches of clear glass area shall be provided in the front doors. Double rear doors with side mounted hinges and centered door opening not less than 60 inches high shall be furnished. The total width of the rear door opening shall be not less than 34 inches or, when specified (see 6.2), not less than 64 inches. Two fixed windows, each with not less than 168 square inches of clear glass area, shall be provided in the rear doors. Rear doors shall have door operating handles inside and outside. All doors shall be provided with means for locking. All door windows shall be of safety glass, mounted in molded rubber in the upper section of the doors. Windows shall be watertight. All windows shall be of first quality, as used by quantity commercial builders of multistop bodies, and not of the type used in motor or mobile home construction.

* 3.5.1.3 Van body roll-up overhead rear door. When specified (see 6.2), a roll-up overhead rear door shall be provided. The door shall provide a clear opening of not less than 80 inches in width and not less than 71 inches in height, measured from the top of the floor to the underside of the header. The door shall be of the sectional type, having not less than five sections. Door sections shall incorporate joints of the tapered tongue-and-groove type or of the ship-lap type. Door shall be plastic covered or aluminum covered, 0.750 inch marine plywood construction. Door section corrosion-resistant hinges shall be mounted on the inside of the door, not less than four hinges at each section joint. The door track shall be the manufacturer's standard corrosion-resistant type equipped with a positive stop at the end of the track. Door rollers, counterbalance unit and cables of corrosion-resistant construction shall be the manufacturer's standard. The door shall be weathertight. A heavy duty, corrosion-resistant, cam operated, lever type lock shall be provided, equipped with provisions for use of a padlock. One heavy duty corrosion-resistant grab handle, closed type, shall be provided on the outside bottom of the door. One nylon double loop pull-down strap, not less than 1.500 inches wide and 12 inches in length, shall be provided and located adjacent to the door lock.

* 3.5.1.4 Hydraulic rearfold lift tailgate. When specified (see 6.2), the vehicle shall be equipped with an electric motor driven hydraulic rearfold lift tailgate. Unless otherwise specified (see 6.2), the hydraulic tailgate shall have a rated capacity of not less than 1,500 pounds. All hydraulic

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

cylinders shall be provided with flow restrictors in the down port of the cylinders to prevent the tailgate from falling rapidly in the event of hydraulic system failure. The tailgate platform shall be of the ramping type and shall have a depth of not less than 32 inches exclusive of the ramp and shall be not less than 64 inches in width. The ramp shall taper down to ground level to facilitate loading with wheeled hand carts. Platform loading area shall be of nonskid sheet steel. The tailgate shall fold vertically against the rear of the vehicle and shall have devices for holding the platform in the stowed position for vehicle travel. When the tailgate is in the loading position, the clearance between the rear edge of the vehicle and the tailgate shall be not more than 0.750 inch. The rear bumper, specified in 3.4.14.1 need not be furnished. Controls shall be mounted outside the body on the curbside of the vehicle. All tailgate operations shall be hydraulically powered or metered, providing for raising, lowering, folding, and unfolding without manual assistance. The vehicle ignition switch or a spearate switch in the driver's compartment shall allow the driver to disconnect the power source to the tailgate. A decal or plate describing operation of the hydraulic tailgate shall be provided and shall be in close proximity to the hydraulic tailgate controls.

3.5.1.5 Rear step and splash shields. A safety-tread, steel plate step, integrated with the rear bumper and extending not less than 35 inches in width, shall be furnished. Rear end splash shields shall be provided (see 3.1.1.4). When a hydraulic rearfold lift tailgate is furnished, a rear step bumper and step plate is not required.

3.5.1.6 Framing. Not less than six full-width crossmembers (including end sills) shall be furnished. Stub crossmembers, as required for wheelhousing to provide required strength, shall be furnished.

3.5.1.7 Side panels and roof. Side panels shall be constructed of stretcher-leveled or equivalent flat or formed sheet steel of not less than 20 gage (0.0359 inch) thickness, except manufacturer's standard design in upper section may be furnished. The roof shall be one piece or shall have a one-piece center section with caps at the front, rear and sides, all of not less than 20 gage (0.0359 inch) sheet steel or not less than 0.032 inch thick aluminum. Rain gutters shall be furnished at least over all doors. All body seams and joints shall be dust and weather sealed.

3.5.1.8 Floor. The floor shall be of wood and metal, or all metal construction. For wood and metal floor, wood flooring shall extend the full length and width of the loadspace between the wheelhousings. Not less than 0.055 inch steel shall be utilized for the remainder of the floor area. Wood flooring shall be not less than 0.375 inch thick planking or 0.50 inch laminated, exterior grade plywood, metal covered, with not less than 24 gage (0.0239 inch) steel, or provided with recessed, steel skid-strips, installed flush with ends of flooring and protruding not more than 0.0625 inch above the floor surface. All metal floor, where smooth sheet steel is used, shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

be not less than 14 gage (0.0747 inch) sheet steel. All metal floor, where ribbed sheet steel is used, shall be not less than 18 gage (0.0478 inch). The floor and support members shall sustain an evenly distributed load of 125 pounds per square foot of floor area.

3.5.1.9 Interior. The roof shall be lined and completely insulated (see 3.5.1.7.2). The headliner for the roof and side lining, when furnished, shall be sheet metal, 0.1250 inch thick tempered masonite, or 0.250 inch thick exterior grade plywood. The interior body sides, whether lined or not, shall be smooth or ribbed with no other protrusions except fasteners and corner posts. The fasteners shall project not more than 0.1093 inch into the interior and shall be blended and smooth. Side lining panels adjacent to the floor, the headliner, and each other shall line the body without areas that are not structurally supported and areas that are not completely fastened. Side lining panels furnished shall completely line the body without gaps between panels, except at the roof line. All interior panels shall be removable to facilitate body repair. Each sheet metal headliner and side lining panel shall be rigid, shall have no sharp edges exposed to the touch, and shall be fastened so as to prevent scalloping and edge ridges in the panels. Each masonite and wood headliner and side lining panel shall be free of defects, sanded smooth (wood only) and flush with adjacent panels. At least two domelights shall be installed, one in the driver's compartment and one approximately in the center of the cargo space. Minimum dimensions (with side panels installed) shall be as specified in table VI.

TABLE VI. Type I loadspace dimensions.

Feature	Inches
Length, back of seat to rear doors, measured at floor	141
Width, exclusive of wheelhousings and door pockets	70
Height, floor to ceiling at center	71

3.5.1.9.1 Bulkhead. When specified (see 6.2), a steel bulkhead with a sliding open mesh type center section door and solid side panels shall be provided between the driver's area and the cargo space. The bulkhead shall be secured to the body interior with easily removable, corrosion-resistant fasteners. The door shall slide open on the front side of the bulkhead, towards the curbside of the vehicle.

3.5.1.9.2 Insulation. Insulation shall be provided in the ceiling of the body and shall provide resistance to transfer of heat equivalent to the protection afforded by a 1-inch thick batt having a thermal conductivity of 0.24 in normal ambient air temperatures. Insulation shall be either foamed-in-place, flexible or batt type, fibrous or cellular material, having a moisture absorption capacity of less than 2 percent by weight. Materials shall be odorless and fire-retardant. Insulation shall not breed or promote the growth of fungus and shall neither cause nor accelerate corrosion of steel, copper, or aluminum. Insulation shall be cemented to inner side of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

roof and provided with means to retain insulation under all operating conditions. Cement shall be waterproof and the resulting bond shall provide shear strength sufficient to prevent sag of the insulation when the assembled vehicle is operated at speeds up to 60 mph over improved roads.

3.5.2 Type II (chassis, forward control). Type II vehicle shall have a forward control chassis with not less than a 130-inch wheelbase. The load area for the purpose of determining weight distribution (see 3.2.6) shall be as specified (see 6.2). The chassis shall be suitable for subsequent mounting of the make, model and type of body specified (see 6.2).

3.5.3 Type III (chassis, forward control with front section). The front section of type III vehicle shall consist of cowl, windshield, and side windows. An adjustable, post type, upholstered driver's seat shall be furnished. The wheelbase shall be not less than 130 inches. The load area for the purpose of determining weight distribution (see 3.2.6) shall be as specified (see 6.2). The chassis shall be suitable for subsequent mounting of the make, model and type of body specified (see 6.2).

3.6 Servicing and adjusting. Prior to acceptance of the vehicle by the Government inspector, the contractor shall service and adjust each vehicle for operational use including at least the following: alinement of lights; adjustment of the engine and brake systems; filling and charging of battery; alinement of front wheels; inflation of all tires; complete lubrication of the chassis, engine, and running gear with grades of lubricants recommended for the ambient air temperature at the delivery point; servicing of the cooling system with a solution of ethylene glycol type antifreeze and water in equal parts by volume; and servicing of the windshield washer reservoir with water and appropriate additives.

3.7 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished. Welded, bolted, and riveted construction utilized shall be in accordance with the highest standards of the industry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements, (examination and tests) as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility for ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods, and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification has been demonstrated.

4.3 First production vehicle inspection. The first vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformance to the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

* 4.3.1 Vehicle weight. The first production vehicle shall be weighed to determine curb weight and distribution of curb weight on front and rear axle. The total imposed loading on front and rear axles shall be computed by the contractor and verified by the Government, using the curb weight, the operator weight at 175 pounds, and the payload (see 3.2.5) to provide the specified GVW. Except for type I multistops, the calculated imposed loads on front and rear axles shall be compared to the suspension, axle and tire load capacity ratings to determine if these components are of adequate capacity to meet contractual requirements.

4.3.2 Road test. The first production vehicle will be examined and road tested (less payload) by the contractor at speeds up to 55 mph to assure that the vehicle will operate in accordance with the contractual requirements.

4.3.3 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and shall be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

4.3.4 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under contract until corrective action has been taken.

4.4 Inspection of production vehicles. The contractor's inspection system shall, as a minimum, assure that the vehicle conforms to the physical and dimensional requirements and is capable of meeting the performance requirements contained herein. For each vehicle under contract, the contractor shall make available to the Government, at the point of final acceptance, records acceptable to the Government indicating that the servicing and adjusting required by 3.6 have been accomplished.

5. PREPARATION FOR DELIVERY

5.1 Vehicle processing. The vehicle shall be processed for shipment, from the manufacturer's plant to the initial receiving activity, in accordance with the manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use. The vehicles covered by this specification are intended for general nontactical use by the Government in transporting personnel or cargo, or for the mounting of special bodies or equipment.

* 6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number and date of this specification.
(b) Type and class of vehicle required (see 1.2).
* (c) Issues of DODISS to be cited in the solicitation and if required, the specific issues of individual documents referenced (see 2.1.1 and 2.2).
(d) Identification of appropriate service for painting and marking (see 3.1.1.1).
(e) Concealed markings, if required (see 3.1.1.1).
(f) Rustproofing, if required (see 3.1.1.2).
(g) Tropical rustproofing, if required (see 3.1.1.2).
(h) Silicone brake fluid, if required (see 3.1.1.5).
(i) Gasoline engine, if required (see 3.4.1.2).
(j) Power plant heaters, if required (see 3.4.1.8).
(k) If battery heaters are not required with the power plant heaters (see 3.4.1.8).
* (l) Rubber hoses, if required (see 3.4.1.9).
(m) Manual transmission, if required (see 3.4.5.2).
(n) Traction control, if required (see 3.4.9.1).
(o) Disc type wheels, if required (see 3.4.10).
(p) Other than highway tread tires, if required (see 3.4.10.1).
(q) Bias ply tires, if required (see 3.4.10.1).
(r) A carrier for a spare tire, if required (see 3.4.10.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

(s) A spare wheel or rim, if required (see 3.4.10.4).
(t) A spare tire assembly, if required (see 3.4.10.5).
(u) Tools, if required (see 3.4.15.1).
(v) Engine hour meter, if required (see 3.4.21).
(w) Back-up alarm, if required (see 3.4.22).
(x) Extra width rear doors, if required (see 3.5.1.2).
* (y) Roll-up overboard rear door, if required (see 3.5.1.3).
* (z) Hydraulic rearfold lift tailgate, if required (see 3.5.1.4).
* (aa) Hydraulic tailgate capacity, if not 1,500 pounds (see 3.5.1.4).
(ab) Bulkhead for type I, if required (see 3.5.1.9.1).
(ac) Load area and body mounting requirements for type II chassis (see 3.5.2).
(ad) Load area and body mounting requirements for type III chassis (see 3.5.3).

6.3 Performance prediction. SAE Truck Ability Prediction Procedure computations and computations for low speed and maximum geared speed will be required by the contract. The SAE Work Sheet Item 1 should include vehicle model number, engine model number, and vehicle type and class. Unless other conditions are cited in the contract, computations should be made for normal atmospheric pressure, normal ambient air temperature, and still, dry, air. The factors to be used in predicting truck ability (see 3.3.1.1) are established as follows for the corresponding SAE Truck Ability Prediction Procedure Tables:

Table 1	- Tire Factor. This factor must relate to the size of tires furnished by the contractor in accordance with this specification.
Table 2	- Altitude Factor. 1.00
Table 3	- Rolling Factor. 1.613
Table 4	- Area Factor. 0.173
Table 5	- Velocity Factor. 250.0
Table 6	- Altitude Factor. 1.00
Table 7	- Chassis Friction Horsepower. Use applicable power unit GVW (to nearest, higher, 1,000 pounds) and the engine rpm (to nearest 100 revolutions) which is required for 50 mph geared speed. For GVW and engine speed beyond the range of this table, factors shall be extrapolated.
Table 8	- Grade Factor. 0.75
Table 8A	- Correction Factor. Not required.
Table 9	- Road Factor. 0.0.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 6.4 Subject term (key word) listing.

Commercial vehicle
Delivery truck
Nontactical vehicle.

6.5 Identification of changes. The margins of this specification are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content regardless of the marginal notations and relationship to the last previous issue.

Custodians:
Army - AT
Navy - YD
Air Force - 99

Preparing Activity:
Army - AT

Project No. 2320-0437

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER (Number) AND TITLE MIL-T-62318C Truck, Multi-stop Delivery: Forward Control and Chassis, Truck: Forward Control, DED and GED, 13,000 To 21,000 Pounds GVW, 4x2, Commercial

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY (Printed or typed name and address — Optional)

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

U.S. MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
U.S. Army Tank-Automotive Command
ATTN: AMSTA-UED
Warren, Michigan 48397-5000

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.