MILITARY SPECIFICATION

TRUCK, FLATBED: RIGGER MAINTENANCE, 28,000 GVW, 4x2 AND 4x4, COMMERCIAL

This specification is approved for use by the US Army Tank-Automotive Materiel Readiness Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers diesel and gasoline engine driven, four-wheel, two-rear-wheel drive and four-wheel, four wheel drive, 28,000 pounds gross vehicle weight (GVW) commercial trucks equipped with a flatbed rigger maintenance body. Vehicles procured under this specification are commercial items which shall be warranted by the manufacturer as specified in procurement documents.

1.2 Classification. The vehicle shall be one of the following types, as specified (see 6.2).

Type I - Flatbed body, with a winch mounted behind the cab and a tail roller mounted on the rear of the body.
Type II - Flatbed body, with a hydraulic crane mounted behind the cab.

1.2.1 Model. The vehicle shall be further classified by model. The model of the vehicle shall be determined by the number of wheels and the number of driving wheels as follows:

4x2 Model - 4 wheel, 2 wheel drive
4x4 Model - 4 wheel, 4 wheel drive

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: DRSTA-GBS.1, Warren, MI 48090, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS
FEDERAL

W-B-131	- Battery, Storage: Vehicular, Ignition, Lighting and Starting.

STANDARDS
MILITARY

MIL-STD-1223	- Administrative Wheeled Vehicles Treatment, Painting, Rustproofing, Identification Marking, Data Plates and Warranty Notice Standards.
MS51118	- Pintle Assembly, Towing: 40,000 Lbs. Capacity, Manual Release.
MS51317	- Light, Warning, Vehicular, Rotating, D.C.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)
ASTM Standards.

ASTM Designation: 120-65	- Black and Galvanized Welded Seamless Steel Pipe for Ordinary Uses.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

DEPARTMENT OF TRANSPORTATION (DoT)
Federal Motor Carrier Safety Regulations.
Federal Motor Vehicle Safety Standards.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:24Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines.

Noise Emission Standards for Transportation Equipment - Medium and Heavy Trucks.

(Application for copies should reference the Code of Federal Regulations 40 CFR and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Standards and Recommended Practices.

J245	- Engine Rating Code - Spark Ignition.
J318	- Air Brake Gladhand Service (Control) and Emergency (Supply) Line Couplers - Trucks, Truck-Tractors and Trailers.
J537	- Storage Batteries.
J551	- Limits and Methods of Measurement of Radio Interference Characteristics of Vehicles and Devices (20-1000 MHz).
J552	- External Electromagnetic Radiation Suppressors.
J555	- Truck, Truck-Tractor, Trailer and Motor Coach Wiring.
J560	- Seven Conductor Electrical Connector for Truck Trailer Jumper Cable.
J588	- Turn Signal Lamps.
J589	- Turn Signal Switch.
J682	- Rear Wheel Splash and Stone Throw Protection.
J688	- Truck Ability Prediction Procedure.
J704	- Transmission Mounted Power Take-Offs.
J706	- Rating of Winches.
J816	- Engine Test Code - Spark Ignition and Diesel.
J844	- Nonmetallic Air Brake System Tubing.
J1067	- Seven Conductor Jacketed Cable for Truck and Trailer Connectors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASOCIATION, INC.
Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron, OH 44313.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.9 vehicles, components, assemblies, and accessories to be delivered under the contract shall be standard or optional items which meet or exceed the requirements of this specification. All chassis items shall be as represented in the chassis manufacturer's technical data, and special bodies or mounted equipment shall be as represented in the body and equipment manufacturer's technical data. Technical data shall be limited to specifications and technical material, identical to that furnished to the authorized company representatives for selection of vehicle models and components, and shall be on file in the engineering offices of the procuring activity, prior to delivery of the items.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

3.1.1.1 Painting and marking. As specified by the procuring activity for the appropriate service (see 6.2), treatment, painting, identification marking, data plates and warranty notice shall be in accordance with MIL-STD-1223.

3.1.1.2 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with MIL-STD-1223.

3.1.1.3 Drain plugs. All drain plugs installed in manual transmissions, transfer cases, rear axles, and for the purpose of draining hydraulic fluid shall be of the permanent magnet type.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.1.1.4 Heavy duty cooling system. When specified (see 6.2), a heavy duty cooling system shall be furnished. The system shall maintain engine coolant at a temperature below the boiling point with the vehicle loaded to rated GVW and operated at an altitude of 10,000 feet above sea level or in an ambient air temperature of not less than 125 degrees Fahrenheit (°F).

3.1.1.5 Coolant recovery system. A de-aeration system, a surge tank or a coolant recovery reservoir with not less than 2 quart capacity shall be furnished. A high coolant temperature or a low coolant level alarm buzzer and a red indicator warning light shall be provided on the dash instrument panel.

3.1.1.6 Towing devices. Not less than two hooks, loops or pins, for towing the vehicle, shall be furnished on front of the vehicle.

3.1.1.7 Drive hubs. When specified for 4x4 model vehicles (see 6.2), manually operated drive hubs, for disengaging front wheels from the power train, shall be provided, except for vehicles equipped with interaxle compensating devices between the front and rear axles (see 3.4.5.1.2).

3.1.1.8 Trailer towing package. When specified (see 6.2), a trailer towing package shall be furnished. The trailer towing package shall consist of a pintle, safety chain attachment devices, a lighting receptacle, a trailer brake control system (see 3.4.11.2), and associated reinforcements and wiring. The pintle shall be of the rotating type conforming to MS51118-1. The pintle shall be installed on the chassis frame with reinforcements to transfer pintle loads directly to the chassis rails. The rearmost portion of the pintle shall be forward, but not more than four inches forward, of the rearmost part of the vehicle and completely forward of the tail roller (see 3.5.4.2). Two trailer safety chain attachment devices, one adjacent to each side of the pintle, shall be provided. Each attachment device shall provide an ultimate strength at least equal to the GVW of the truck furnished. The lighting receptacle, conforming to SAE J560, with its conductors connected and color coded as specified therein, shall be mounted in a readily accessible location near the pintle.

3.1.1.9 Wheel splash and stone throw protection. The vehicle shall have rigid splash shields ahead of the rear wheels and rubber mud flaps to the rear of the rear wheels. All splash shield and mud flap installations, front and rear, shall conform to the rear wheel splash and stone throw protection provisions of SAE J682.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.2 General design.

3.2.1 Federal Motor Vehicle Safety Standards. The vehicle and furnished accessories shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture.

3.2.2 Air pollution control. The vehicle shall comply with the EPA Regulations governing Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines in effect on the date of manufacture. In addition, vehicles destined for California shall comply with State of California Regulations governing air pollution control in effect on the date of manufacture.

3.2.3 Sound level. The interior sound level shall conform to Federal Motor Carrier Safety Regulation 393.94. The vehicle exterior sound level shall conform to the EPA Noise Emission Standards for Transportation Equipment, Medium and Heavy Trucks.

3.2.4 Curb weight. Curb weight shall include the weight of the chassis and cab, with all attachments, accessories, and equipment; body; and full complement of fuel, lubricants and coolant.

3.2.5 Gross vehicle weight. Gross vehicle weight (GVW) shall consist of curb weight, operator (weight computed at 175 pounds) and a payload distributed throughout the length of vehicle body, to provide not less than the specified GVW. Vehicles with crew (four-door) cab shall have GVW computed with 525 pounds of payload in the rear seat.

3.2.6 Weight distribution. The distribution of GVW for the purpose of establishing suspension, axle and tire capacities shall be determined with the payload uniformly distributed over the load area.

3.2.7 Ratings. Vehicle ratings shall be manufacturer's published rating. Component and vehicular ratings shall not be raised to meet the requirements of this specification. When published ratings are not available, verification of ratings must be submitted to the engineering office of the procuring activity. Minimum GVW ratings shall be not less than 28,000 pounds. The ratings shall be established by the manufacturer of the equipment being verified.

3.2.8 Cab-to-axle. The cab-to-axle dimension shall be not less than 102 inches, measured from the back of the cab or crew cab to the center of the axle, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.3 Performance.

3.3.1 Speeds and gradeability. High and low speed requirements shall be met with the vehicle loaded to specified GVW.

3.3.1.1 High speed gradeability. The vehicle shall ascend a continuous grade of 1.0 percent at 50 miles per hour (mph). Gradeability requirements for 4x2 model vehicles shall be met with the main transmission in direct drive and, when a multi-speed axle or auxiliary transmission is furnished, with the axle or auxiliary transmission in the high speed ratio. In addition, 4x4 model performance requirements shall be met with the front wheel drive disengaged, except that when equipped with interaxle compensating devices, the vehicle shall meet the performance requirements with the front wheel drive engaged. Gradeability shall be verified with calculations in accordance with SAE J688 (see 6.3).

3.3.1.2 Low speed. Low speed shall be calculated with the engine operating at not less than 35 percent of the recommended governed speed, and shall provide a vehicle speed of not more than 5 mph for 4x2 model and 2.5 mph for 4x4 model vehicles.

3.3.1.3 Maximum geared speed. For 4x2 model vehicles, maximum geared speed at engine governed speed shall be not less than 55 mph (minus 1 percent). Conformance to geared speed specified shall be determined by calculating in accordance with the following formula:

$$\text{Maximum geared speed (mph)} = \frac{\text{Governed speed (rpm)}}{\text{Total gear reduction x tire factor (see 6.3)}}$$

3.3.2 Service brakes. The service brakes shall control and hold the vehicle, when loaded to its specified GVW, on a 30 percent grade. The service brakes shall stop the vehicle, loaded to specified GVW, within the stopping distance requirements of Federal Motor Carrier Safety Regulation 393.52.

3.4 Chassis components.

3.4.1 Engine. The engine furnished shall be the chassis manufacturer's standard or optional engine for the commercial model truck which meets or exceeds the requirements of this specification.

3.4.1.1 Diesel engine. Unless otherwise specified (see 3.4.1.2), the vehicle shall be equipped with a liquid cooled, compression ignition, two-stroke or four-stroke cycle diesel engine, with not less than six cylinders. Engine net horsepower figures used in performance

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

prediction calculations shall be determined in accordance with SAE J816. A fan clutch to reduce fan speed automatically, when not required for engine cooling, shall be provided.

3.4.1.2 Gasoline engine. When specified (see 6.2), the vehicle shall be equipped with a liquid cooled, internal combustion, four-stroke cycle gasoline engine with not less than six cylinders. The engine furnished shall produce the required vehicle performance when operated on unleaded fuel with a research octane rating of 91, at engine speed not more than manufacturer's recommended operating speed. The engine shall be capable of continuous, warranted operation on unleaded fuel. Unless otherwise specified, vehicles for overseas use shall be capable of accepting and operating on leaded gasoline. The rated net torque output of the engine shall be not less than 295 pound-feet. Engine net torque ratings and net horsepower figures used in performance prediction calculations shall be determined in accordance with SAE J245. A fan clutch to reduce fan speed automatically, when not required for engine cooling, shall be provided.

3.4.1.3 Oil filter. A full-flow type oil filter shall be furnished.

3.4.1.4 Governor. An engine governor shall be furnished and set and sealed to limit engine to maximum recommended operating speed.

3.4.1.5 Coolant temperature control. Thermostatic control of engine coolant temperature shall be provided. On diesel engine driven vehicles, control shall include partial thermostatic control of coolant flow through the radiator and thermostatically controlled radiator shutters or complete thermostatic control of all coolant flow through the radiator.

3.4.1.6 Power plant heaters and fuel warmer. When specified (see 6.2), coolant heater; engine oil heater; and a fuel warmer (diesel engine driven vehicles only), shall be provided. Unless otherwise specified (see 6.2), a battery heater shall be provided when power plant heaters are specified. Heaters shall operate on 120-volt alternating current (ac), and shall be wired through a junction block to a single three-pronged (male), weatherproof, slave receptacle for receiving external power and grounding vehicle. A three-wire connecting cable, 25 feet long and of adequate line capacity to supply power for all heater units simultaneously, shall be furnished. Connecting cable shall include a matching female connector at the vehicle end and a standard, weatherproof, three pronged (two power plus one ground) male connector at the other end. Electrical apparatus shall conform to Federal Motor

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

Carrier Safety Regulation 393.77(c)(7). Electrical insulation of connecting cable shall withstand normal operating stresses in low ambient air temperatures (down to minus 60°F) without cracking or loss of dielectric capacity. All heater lead wires shall be installed without interfering with vehicle component operation, and without loose excess wire. Provisions for stowage of the cable shall be provided in the vehicle cab. Heaters shall be furnished as follows:

(a) Coolant heater, 1500-watt minimum rating, shall be installed in the engine block or lower, coolant, inlet hose. Engine thermostat with an operating range of 170°F to 195°F shall be installed;

(b) Immersion type engine oil heater, 300-watt minimum rating, with 170°F to 195°F thermostat, shall be installed in oil pan through any convenient opening;

(c) Battery heater shall have a capacity adequate to maintain the battery electrolyte at a temperature of not less than 10°F during vehicle exposure in ambient air temperatures as low as minus 60°F and shall embody a thermostat to limit the temperature of the electrolyte to not more than 80°F;

(d) For diesel engine driven vehicles, a fuel warmer or pre-heater shall be provided to prevent clogging of fuel filters due to wax crystallization in the fuel. The fuel warmer shall use engine coolant to transfer sufficient heat to the diesel fuel to heat it from an inlet temperature of minus 40°F to an outlet temperature of plus 9°F, with a flow rate of not less than the maximum fuel demand of the engine fuel system. A coolant shutoff valve shall be provided for the coolant inlet side of the fuel warmer unit.

3.4.2 Electrical systems. The electrical system shall be in accordance with Federal Motor Carrier Safety Regulations 393.27 through 393.31 and 393.33.

3.4.2.1 Starting system. For diesel engine driven vehicles, a 12- or 24-volt dc starting system with 12-volt dc lighting system, and with not less than a 60 ampere alternator, shall be furnished. Engine starting equipment shall include an ether starting system or glow plug. When specified (see 6.2), if an ether system is furnished in lieu of a glow plug, it shall be of the measured shot type. Measured shot type systems shall be key operated or manually operated from the driver's compartment, shall have a reservoir of not less than 12 fluid ounces, and shall be inoperative with the engine warm.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.4.2.2 Ignition system. For gasoline engine driven vehicles, an ignition system of 12-volt direct current (dc) potential shall be furnished. An alternator of not less than 40 amperes rated capacity and which provides not less than 16 amperes dc output at normal engine idle speed shall be furnished.

3.4.2.3 Lighting. All vehicle lights, reflectors, and wiring shall be as specified herein and shall conform to Federal Motor Carrier Safety Regulations 393.12, 393.19, 393.20 and 393.22 through 393.26(d). Lights and reflectors shall not be mounted on vertical surface of rub rails (unless recessed and fully protected) or mounted on vehicle bumpers.

3.4.2.4 Turn signals. Turn signal lamps shall conform to SAE J588. Operating units shall conform to SAE J589, class A, and shall be mounted on the steering column. Vehicles shall be provided with double-faced front signal units and with single-faced rear signal units installed in accordance with SAE J588. Turn signals shall not be mounted on engine compartment hood. Turn signal operating units shall have a visible and audible flash indicator.

3.4.2.5 Batteries. Each battery shall be of 12-volt potential. The total reserve capacity ratings and the total cold cranking ratings at 0°F, both measured in accordance with SAE J537, shall be not less than specified in table I. The batteries shall be of the maintenance free type having the maintenance free characteristics listed in W-B-131.

TABLE I. Batteries.

Engine type	Reserve capacity (minutes)	Cold cranking (amperes)
Diesel	320	1200
Gasoline	110	450

3.4.2.6 Lighting cable. When specified (see 6.2), a lighting cable, conforming to SAE J1067, shall be furnished. The cable shall be coiled and shall be not less than 110 inches long when fully extended. Both ends of the cable shall be equipped with a round plug conforming to SAE J560. The plugs shall be equipped with a grip for withdrawing from the connector sockets. The cable shall be packaged and stowed in the vehicle tool compartment.

3.4.2.7 Radio interference suppression. The vehicle shall be suppressed to limit electromagnetic radiation in accordance with SAE J551. Suppressors used shall conform to SAE J552. Any body equipment emitting electromagnetic radiation shall be suppressed to the same level as the vehicle chassis.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.4.3 Fuel system. The fuel system shall conform to Federal Motor Carrier Safety Regulations 393.65 and 393.67.

3.4.3.1 Air cleaner. An air cleaner shall be furnished. When equipped with an oil-bath type, oil capacity shall be not less than 1 quart.

3.4.3.2 Fuel tank(s). Fuel tank(s) shall be the manufacturer's standard for the vehicle furnished with a total capacity of not less than 43 gallons. When more than one tank is furnished on diesel engine driven vehicles, means shall be provided to assure equalized fuel level in both tanks. When more than one tank is furnished on gasoline engine driven vehicles, a selector valve connecting either tank to engine fuel intake shall be provided.

3.4.4 Exhaust system. The exhaust system shall conform to Federal Motor Carrier Safety Regulation 393.83. Exhaust mufflers, when stacked, shall be furnished with a heat shield and a hinged rain cap.

3.4.5 Gear train.

3.4.5.1 Transmission. Unless otherwise specified (see 3.4.5.3), a manually shifted transmission shall be provided on the vehicle. Input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine. Gear ratios in the transmission and axles shall be matched to provide a progressive shifting pattern throughout the complete range, and shall provide required vehicle performance (see 3.3.1). The transmission shall be provided with SAE J704 power takeoff openings at right and left sides. The transmission shall provide for maximum ease of shifting in all speeds.

3.4.5.1.1 Speeds. The vehicle shall be provided with not less than five forward speeds for 4x2 model and not less than 10 forward speeds for 4x4 model. The vehicle may be furnished with an auxiliary transmission.

3.4.5.1.2 Transfer case. Model 4x4 vehicles shall be equipped with a transfer case. Unless the transfer case is equipped with devices which compensate for differential torque and speeds between the front and rear axles, the transfer case shall provide for driver selection of either two-wheel or four-wheel drive. When furnished, interaxle compensating devices shall provide for positive transfer of power to all driving axles.

3.4.5.2 Clutch. The clutch shall be the largest capacity clutch offered for the type vehicle and engine furnished with torque capacity exceeding maximum delivered engine torque.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.4.5.3 Automatic or semiautomatic transmission. When specified (see 6.2), the vehicle shall be provided with automatic or semiautomatic transmission. The transmission shall provide continuous drive. The transmission shall include a hydraulic torque convertor and not less than four forward gear ratios. Normal driving range selector position shall provide not less than four gear ratios without movement of the selector. The transmission shall be provided with SAE J704 power takeoff opening(s).

3.4.5.4 Power takeoff. The power takeoff shall be of a rated capacity to operate powered equipment. Controls to operate the power takeoff shall be located in the truck cab accessible to the seated driver. A caution plate or decal reading "DO NOT OPERATE VEHICLE AT HIGHWAY SPEEDS WITH POWER TAKEOFF ENGAGED" shall be provided and installed so as to be readily visible to the seated driver.

3.4.6 Drive line components. Drive line components shall be adequate to transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction, in proportion to the number of driving axles furnished.

3.4.7 Frame. The chassis frame shall be the manufacturer's standard for the vehicle furnished. Chassis frame rails shall not project beyond the rear end of the body.

3.4.8 Suspension. The vehicle shall be equipped with a suspension system with components having a rated capacity at least equal to the load imposed on each member, measured at the ground, with the vehicle loaded to specified GVW. When suspension capacity is rated at the spring pads, unsprung weight shall be deducted. The vehicle shall be equipped with hydraulic double-acting shock absorbers at the front wheels.

3.4.9 Axles. Axle ratings shall be at least equal to the load imposed on each axle, measured at the ground, with the vehicle loaded to specified GVW. Gear ratios shall provide performance specified in 3.3.1 and shall be of the single reduction type.

3.4.9.1 Traction control. When specified (see 6.2), a traction control shall be furnished on the rear axle. The traction control shall actuate automatically to insure that power is transmitted to the wheel having traction when the opposite wheel loses traction. Maximum traction capabilities shall be maintained at all times under each drive wheel for the life of the vehicle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.4.9.2 Two-speed axle. When specified for model 4x2 vehicles (see 6.2), a two-speed axle shall be furnished, equipped with electric, vacuum, or air shift and provided with ratios which will permit proper gear splitting. Gear ratio shall provide performance specified in 3.3.1.

3.4.10 Wheels, rims, tires, and tubes. Unless otherwise specified, the vehicle shall be equipped with single front and dual rear wheels. Rims and tire ratings shall conform to Tire and Rim Association recommendations for the type and size of tires furnished. Tire type and size, load range (ply rating), and rim sizes shall be the same for all wheels on each vehicle. When specified (see 6.2), the vehicle shall be equipped with wide base type tires and wheels in lieu of dual wheels and tires. When wide base tires are furnished, the wheels shall be interchangeable without the use of an adapter. When specified (see 6.2), disc type wheels shall be furnished.

3.4.10.1 Tires. Tires shall be tube or tubeless steel-belted radial ply type with highway tread on 4x2 model vehicles and with non-directional mud and snow tread on 4x4 model vehicles. Tires shall be of rated capacity at least equal to the load imposed on each tire, measured at each wheel, at the ground, with the vehicle loaded to specified GVW.

3.4.10.2 Inner tubes. When tube type tires are furnished, inner tubes shall be of heavy duty type, and shall be of proper size for tires furnished. Tire flaps shall be provided for tube type tires in accordance with Tire and Rim Association recommendations.

3.4.10.3 Carrier for spare tire assembly. Unless otherwise specified (see 6.2), a carrier for a spare wheel or rim and tire assembly shall be installed in a readily accessible location on the vehicle. The carrier design shall enable removal or mounting of spare wheel assembly using only the tools specified in 3.4.16.1.

3.4.10.4 Spare wheel or rim. When specified (see 6.2), a spare wheel or rim shall be furnished.

3.4.10.5 Spare tire. When specified (see 6.2), an inflated spare tire mounted on the spare wheel or rim shall be furnished. The spare tire shall be of the same size, type, tread design, and ply rating furnished on the vehicle.

3.4.11 Brakes. Brakes shall conform to Federal Motor Carrier Safety Regulations 393.40 through 393.43 and 393.45 through 393.52.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.4.11.1 Service brakes. The vehicle shall be equipped with full air brakes. The braking system, complete with all necessary components, shall include:

(a) Air compressor, unloader-head type, engine driven and engine lubricated, air or water cooled, and having a capacity of not less than 7 1/4 cubic feet per minute (cfm)
(b) Air storage reservoir(s) with not less than 2,000 cubic inches total capacity, each tank equipped with drain, and with safety and check valves between compressor and last reservoir tank
(c) Foot control, suspended or treadle type
(d) Air control valves
(e) Air pressure gage, visible to the driver
(f) Low-air-pressure warning, visible and audible
(g) Service brake stop lamp switch
(h) Alcohol aspirator with unbreakable transparent container
(i) Automatic moisture ejector.

3.4.11.2 Trailer brake control system. In addition to components specified in 3.4.11.1, a trailer brake control system shall be furnished when a trailer towing package is required (see 3.1.1.8). The trailer brake control system shall include:

(a) Identification of emergency and service lines
(b) Coincident control of trailer brakes with prime mover foot control
(c) Independent hand control for trailer brakes
(d) Prime mover protection valve with dash control and automatic break-away feature
(e) Trailer stoplight control operable with foot brake and with hand control for trailer brakes
(f) Air connectors for trailers with SAE J318 gladhand couplers mounted at the rear of the vehicle located to preclude interference with trailer
(g) Two SAE J844 coiled air hoses, not less than 110 inches long when fully extended, with SAE J318 gladhand couplers on both ends of hoses. The hoses shall be packaged and stowed in the vehicle tool compartment for shipment;
(h) Dummy gladhand couplers with chains
(i) Prime mover only parking brake valve to permit prime mover parking brakes to be applied while charging the trailer air brake system.

3.4.11.2.1 Brake control from a towing vehicle. When specified, the vehicle shall be furnished with a system for controlling the brakes

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

from a towing vehicle (wrecker). The installation shall be complete with air brake couplers, relay emergency valve with no-bleed-back feature (except when spring-applied emergency brake is furnished), additional air lines and fittings. The service and emergency couplers shall be mounted on the front in a protected position providing for ready attachment of air hoses from a towing vehicle. The service and emergency couplers shall be identified and provided with dummy gladhand couplers with chains. The system shall not compromise conformance to any Federal Motor Carrier Safety Regulation referenced herein or to any Federal Motor Vehicle Safety Standard.

3.4.12 Cab. Unless otherwise specified, the manufacturer may furnish any standard non-tilting, full-width model cab. Cab doors shall be equipped with locks, operable from inside the cab through mechanical linkage, and with at least the curbside door equipped with an external, key-operated lock. Full length drip rails shall be installed above the cab doors. Unless otherwise specified, the cab shall have upholstered, full-width, adjustable seat and back or individual, adjustable, driver's seat and individual passenger seat. When specified (see 6.2), an individual adjustable driver's seat and an individual passenger seat shall be provided. The color of the upholstery and the interior finish shall be compatible with the exterior color (see 3.1.1.1). White upholstery shall not be furnished. Safety grips shall be provided on each side of the cab to assist personnel in entering and leaving the cab. Interior lighting shall be provided. Manufacturer's standard fastenings and two pairs of seat belts shall be installed on the vehicle.

3.4.12.1 Crew cab. When specified (see 6.2), in addition to the requirements of 3.4.12, a four-door crew cab having two full-width upholstered seats with backs shall be furnished. Six pairs of seat belts shall be installed. All cab doors shall be equipped with locks, operable from inside the cab through mechanical linkage. Both front doors shall be equipped with external, key-operated locks. Cab doors shall have safety glass windows with crank-operated window regulators. A rear window shall be provided. The cab roof shall be of one piece construction; or if welded, the roof shall give the appearance of one piece, with weld seams being continuous, waterproof, and free of visible seams, bumps, or protrusions. Full length drip mouldings shall be mounted above doors. A dome light shall be furnished in the cab. When a crew cab is furnished, the cab-to-axle dimension shall be measured from the back face of the crew cab.

3.4.12.1.1 Seat spacing. With the front seat adjusted to the extreme forward position, there shall be not less than 30 inches, measured in a horizontal plane, between the front of the rear seat back

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

and the rear of the front seat back. A kick-space height of not less than 2 3/4 inches shall be maintained between the floor and the rear of the front seat in all positions of adjustment. Leg room and space forward of the front seat shall be equivalent to that provided ahead of the seat in a two-door standard cab.

3.4.13 Steering. Power steering shall be furnished.

3.4.14 Windshield wipers and washers. The vehicle shall be equipped with dual windshield wipers and windshield washers. Windshield wipers shall be multispeed type and operated by air or electric motor(s).

3.4.15 Bumper. Unless the bumper is an integral part of the vehicle cab, a channel type front bumper shall be provided, except when a front mounted winch is furnished (see 3.4.22).

3.4.15.1 Rear end protection. The rear end of the vehicle shall be protected in accordance with Federal Motor Carrier Safety Regulation 393.86.

3.4.16 Tool stowage. Stowage space of sufficient size to accommodate vehicle jack, hand tools, antiskid chains, and emergency reflective triangles shall be furnished for retaining equipment during vehicle operation. Stowage space for these tools may be furnished inside the cab. When stowage space for these tools is located outside of cab, it shall be waterproof and shall provide for locking with a padlock.

3.4.16.1 Tools. When specified (see 6.2), each vehicle shall be furnished with tools required for exchanging mounted tire assembly with the spare assembly, and shall include at least a hydraulic jack, jack handle, and wheelnut wrench. The jack shall be of such closed height as to permit its location under axle or other satisfactory lift point, at any wheel with the tire flat. The jack, without blocking, shall be capable of raising any wheel of the loaded vehicle to a height adequate to permit removal and replacement of wheel and tire assembly.

3.4.17 Heater and defroster. A hot water heater shall be provided. The heater shall have fresh air intakes. Discharge outlets shall be provided to direct heated air to floor and to defroster louvers. The heater shall be complete with blower and mounted controls convenient to the driver.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

3.4.18 Controls and operating mechanisms. All controls and operating mechanisms shall be located for left-hand drive. Controls shall be complete and conveniently operable by the driver. Lever controls shall be designed and located to permit easy entrance and exit of operator to and from driver's compartment. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. All instruments shall be visible to the driver when seated in the driving position.

3.4.19 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

(a) Key-operated ignition switch
(b) Ammeter, charging indicator or voltmeter
(c) Fuel gage
(d) Oil pressure gage or indicator
(e) Engine temperature gage or indicator
(f) Speedometer with recording odometer
(g) Dual sunvisors
(h) Front door mounted armrest on driver's side
(i) Driver's compartment ventilator other than window
(j) Tachometer (for diesel engine driven vehicles only).

3.4.20 Rearview mirrors Outside rearview mirrors shall be mounted on each side of the cab. The mirrors shall be of the combination type having flat and convex areas inclosed in a common housing. The flat portion shall have not less than 50 square inches of reflective area. The convex portion shall have not less than 20 square inches of reflective area. The mirrors shall have not less than three supporting arms.

3.4.21 Horn. Manufacturer's standard electric horn shall be furnished. When specified (see 6.2), in addition, an air operated horn shall be furnished.

3.4.22 Front mounted winch. When specified (see 6.2), the vehicle shall be furnished with a winch assembly mounted on the front of the vehicle. The winch shall be powered by the manufacturer's standard power takeoff or, when furnished, by the vehicle hydraulic system. The winch shall conform to SAE J706. The winch shall be single drum type and shall have one forward and one reverse speed. All winch controls shall be mounted inside the cab. Winch controls shall be located to provide no interference with the entrance or exit of the driver. The winch shall have a rated single line pull capacity of not less than 20,000 pounds pull on the bare drum. Winch shall be wound with not less

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

than 185 feet of 5/8 inch diameter, preformed 6x37, improved plow steel, wire strand core and shall be equipped with end chain and hook. An integral, adjustable, automatic safety brake shall be provided. The winch shall be equipped with a roller guide. When the winch is driven by a power takeoff unit, angles of the winch drive line U-joints shall be not greater than 16 1/2 degrees.

3.4.22.1 Winch drum guard. A winch drum guard shall be furnished. The guard shall confine the cable to the area between the drum flanges. The guard shall consist of not less than 1/4 inch vertical side plates, conforming to the outside radius of the drum flanges. Six bars, 3/8 inch by 1 1/4 inches, shall be welded to the vertical side plates. Three bars shall be located on the top and spaced equally on the top radius, and three bars shall be located on the bottom and spaced equally on the bottom radius. The vertical distance between the vertical side plates and the drum flanges shall be not greater than one half the specified cable diameter.

3.4.22.2 Front bumper. When a front mounted winch is specified (see 3.4.22), the bumper shall be mounted forward of the winch. The open area on either side of the winch shall be covered with a combination step plate and gravel guard. The bumper shall be either a channel type (see 3.4.15) or a pipe type front bumper. When a pipe type front bumper is furnished, the nominal diameter shall be not less than three inches, and the wall thickness shall be not less than that specified in Schedule 40 of ASTM 120-65. The pipe type front bumper shall have half-round ball ends.

3.4.22.3 Combination step plate and gravel guard. When a front-mounted winch is specified, a combination step plate and gravel guard shall be furnished. The step plate shall be fabricated of not less than 14 gage (0.0747 inch) steel tread plate exclusive of projections. The step plate shall be secured to the front bumper and shall be not less than 1/4 inch and not greater than 3/8 inch from the chassis sheet metal. The step plate shall be capable of supporting 300 pounds per square foot. The step plate shall not deflect more than 1/8 inch under the loads imposed.

3.4.23 Engine hour meter. When specified (see 6.2), an engine hour meter having a totalizing mechanism of not less than 9,999 hours shall be furnished for the chassis engine to register accurately the number of hours of operating time. The meter shall be of rugged construction to insure continuous, trouble free performance under severe operating conditions. The engine hour meter shall be mounted on the cab instrument panel.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:24Z
Check the source to verify that this is the currentversion before use.

3.4.24 Back-up alarm. When specified (see 6.2), the vehicle shall be provided with an audible, pulsating, signaling device (electric or mechanical) to caution personnel when the vehicle is in reverse gear operation.

3.5 Body. The vehicle shall be equipped with a flatbed type body designed for rear loading of heavy equipment. Type I vehicle shall be furnished with a winch and tail roller assembly (see 3.5.4). Type II vehicle shall be furnished with a hydraulic crane (see 3.5.5). When a type II vehicle is furnished, the body shall be mounted to provide a space between the cab and body of 26 plus 0 minus 2 inches for mounting of the crane.

3.5.1 Body construction. The body understructure shall be constructed with not less than seven full width crossmembers. The crossmembers shall be fabricated from 6-inch steel channel with a density of 8.2 pounds per foot. Longitudinal rails shall be tied into each of the crossmembers using not less than 3- by 3-inch angle iron. On vehicles equipped with a tail roller, the rear crossmember shall be an 8-inch H-section, with end plates for supporting the tail roller and support bearings. The body sides shall be of not less than 10 gage (0.1345 inch) steel and the front head shall be of not less than 8 gage (0.1644 inch) steel. The front head shall be capable of withstanding a horizontal static load equal to 1/2 the payload capacity of the vehicle without permanent distortion. Not less than three triangular or box section side braces per side, of not less than 10 gage (0.1345 inch) steel, shall be equally spaced, between the front head and rear corner post, and welded to the side plates. The front head sheet shall be formed or reinforced for rigidity. Chain hooks shall be mounted at the front, center, and rear on each side of the body. A recessed loop or pin, attached to framing at the rear of the body, shall be provided for mounting a snatch block. The body shall have the minimum dimensions specified in table II. The floor shall be 1/8 inch, one or two piece, diamond tread steel plate with additional lateral supports provided at the wheel wells.

TABLE II. Body dimensions (minimum).

Nomenclature	Dimension
Overall body length, inches	144
Overall body width, inches	96
Side plate height, inches	12

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

3.5.1.1 Underslung storage compartments. Underslung storage compartments shall be furnished. The storage compartments shall extend from the front of the body to the rear wheels, and shall provide sufficient tire clearance. The storage compartments shall be capable of supporting a load of not less than 50 pounds per square foot of area and shall include provisions for locking with a padlock.

3.5.2 Body mounting. The body shall be secured with U-bolts, twin studs, or brackets and shall include a wood breaker strip.

3.5.2.1 U-bolts or twin studs. When U-bolts or twin studs are used, there shall be not less than four U-bolts or twin studs per side, each having 9/16 inch body diameter with 5/8 inch minimum thread diameter. Tie-plates shall be not less than 1/2 inch thick. The vehicle chassis frame shall be braced, using wood blocks at each mounting point, unless mounting point is located at a full depth, frame crossmember. Blocks shall incorporate a keeper strap or groove for mounting bolt, and shall be of a width and thickness to assure retention. Two tie-back straps shall be provided, one bolted to each side of the rear portion of the body subframe, to maintain body alinement on the vehicle chassis. Forward body mounting bolts shall be located to the rear of the tapered portion of breaker strips (see 3.5.2.3).

3.5.2.2 Brackets. When brackets are used, they shall be bolted to the web of the chassis frame rails. The body mounting brackets shall provide means for drawing down the body on the chassis rails, and provisions shall be made to prevent lateral shifting of the breaker strips. When additional holes are required to secure mounting brackets to chassis frame rails, they must be located within the area of the rail which is designated as being safe for drilling in accordance with the chassis manufacturer's body builders layouts. Attachments shall not interfere with nor obstruct chassis components.

3.5.2.3 Breaker strips. A hardwood or dense southern yellow pine breaker strip of not less than 1 1/16 inches finished thickness, shall be installed between longitudinal sills and vehicle chassis frame. Breaker strips shall have a taper of 1 inch in 18 inches at the forward end.

3.5.3 Lights. In addition to the lighting specified in 3.4.2.3, the following lighting shall be furnished:

(a) Two 4 1/2 inch minimum diameter sealed beam floodlights, with universal mounts, shall be furnished. The lights shall be mounted to the rear of the cab roof on each side, providing for illumination of the work area. The controls shall be

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currenversion before use.

accessible to an operator inside the cab through an open window;

(b) An amber, rotating, vehicular, warning light in accordance with MS51317-4 shall be provided. The rotating light shall be mounted on the roof of the cab in a location providing 360 degree visibility. The rotating light shall be operated by means of a separate switch with an indicator light located on the instrument panel and marked to indicate the function of the switch;

(c) Wiring for the body shall be in accordance with the applicable portion of the General Section, SAE J555 and all wiring exposed to possible physical damage shall be protected by the use of heavy wall thermoplastic insulated cable.

3.5.4 Type I. Type I vehicles shall be equipped with a winch mounted behind the cab and a tail roller mounted at the rear of the body. Controls for the winch shall be located in the cab.

3.5.4.1 Winch. The winch shall be of the heavy duty, single drum type. The winch shall have a rated single line pull capacity of not less than 30,000 pounds on the bare drum. The winch shall have two forward and two reverse speed ranges. A worm gear shall provide a reduction of not less than 29 to 1. An integral, adjustable, automotive safety brake, and an extended shaft equipped with detachable capstan, shall be provided. The winch shall be wound with 250 feet of 5/8 inch, preformed, 6X37, improved plow steel, regular-lay wire rope having a nominal breaking strength in excess of the winch rating. The winch shall be equipped with an end chain and hook.

3.5.4.2 Tail roller. The tail roller shall have an outside diameter of approximately 8 5/8 inches, and shall be of the heavy duty type weighing approximately 43 pounds per foot. The roller shall extend the full width of the body. The roller shall be supported at each end in bronze bushings attached to end plates. Additionally, the roller shall be supported by four exterior roller-type, bronze-bushed bearings, two mounted under, and two mounted forward of the roller. The exterior roller support bearings shall be mounted in line with the truck frame, on the 8-inch H-section, at the rear of the body. All bearings shall be equipped with high-pressure lubrication fittings.

3.5.5 Type II. Type II vehicles shall be furnished with a one-man-operated, fully hydraulic, articulated boom-type crane, mounted on the truck frame between the cab and the platform (see 3.5). The boom shall consist of an upper and lower section and a hydraulically operated extendable jib capable of extending not less than 33 inches. Double-acting hydraulic outriggers, independently controlled and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

integrally mounted to the crane base, shall be furnished. With the outriggers in the down position, the crane shall be capable of lifting a minimum load of 6,000 pounds when the load is located at a radius of 5 feet; and 2,500 pounds when the load is located at a radius of 16 feet, without causing the vehicle to become unstable. Vehicle shall be deemed unstable when any one of the vehicle wheels lift off the ground. The boom, when fully extended, shall have a normal lifting range of 25 feet above ground level and shall fold to a nestable travel height, between body and truck cab, not more than 78 inches above the truck chassis frame. Crane controls shall be provided on each side of the vehicle. Crane and outrigger controls shall be accessible from ground level. Each outrigger control shall be located on the same side of the vehicle as the outrigger. Each outrigger landing pad shall be not less than 140 square inches.

3.5.5.1 Hydraulic system. A hydraulic pump driven from a power takeoff controlled from inside the truck cab shall be provided to furnish power for the crane and front mounted winch, when furnished (see 3.4.22). The pump shall be of the positive displacement type and shall provide a working pressure of not less than 1,800 pounds per square inch (psi). Controls shall be of the self-centering, fail-safe type with hydraulic by-pass overload valves, and check valve type locking system in boom and outriggers to prevent load dropping due to hydraulic or power failure. Controls shall have fine metering qualities to provide infinitely variable raising, lowering, and rotating motions of the crane boom. Crane hydraulic system shall contain the following minimum safety features:

(a) Check valve system in boom and outrigger system to prevent load drop due to hydraulic system failure
(b) Constant flow valve in hydraulic lines to preclude boom damage due to sudden load-lowering stops
(c) Cushioning valves in boom rotating hydraulic system to preclude damage due to sudden stops
(d) Pressure relief valve to preclude loading beyond lifting capacity
(e) Devices to limit vertical creep of the boom to not more than one inch per hour
(f) Signs with 1-inch lettering visible to the operator at both sets of controls: "OUTRIGGERS MUST BE IN PLACE BEFORE LIFT IS MADE."

3.6 Dissimilar metals. All dissimilar metals throughout the vehicle shall be insulated from one another to preclude galvanic action or electrolytic action.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

3.7 Lubrication system. A lubrication system shall be furnished with fittings for all bearings and other working parts which require relubrication for continued service. Vehicles shall be lubricated, prior to delivery, with an applicable grade of standard lubricant for the ambient air temperatures encountered at the delivery point.

3.8 Servicing and adjusting. Prior to acceptance of each vehicle by the Government inspector, the contractor shall service and adjust each vehicle and its mounted equipment for operational use including at least the following: alinement of lights; adjustment of engine; adjustment of brake system; filling and charging of batteries; alinement of front wheels; inflation of all tires; complete lubrication of chassis, engine, running gear, and mounted equipment with grades of lubricants recommended for the ambient air temperature at the delivery point; and servicing of cooling system with a solution of ethylene glycol and water in equal parts by volume. Cable, where used, shall be lubricated with proper lubricants to resist corrosion.

3.9 Workmanship. The quality and workmanship of all component parts, including fabricated parts, machined parts, and castings shall be commensurate with sound manufacturing standards for similar equipment. The vehicle shall be free from all burrs, sharp edges, die, tool, and metal handling marks, rust, scale, and cracks. Improper manufacturing or assembling practices, defective components, or parts and assemblies, which have been modified to overcome deficiencies shall not be furnished.

3.9.1 Recovered materials. All equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products is allowed under this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Government verification. Quality assurance operations performed by the contractor shall be subject to Government verification at unscheduled intervals. Verification shall consist of observation of the operations to determine that practices, methods, and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

4.3 First production vehicle inspection. The first production vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformity to the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

4.3.1 Vehicle weight. The first production vehicle shall be weighed to determine curb weight and distribution of curb weight on the front and rear axles. The imposed loading on front and rear axles shall be computed using the curb weight, the operator weight at 175 pounds, and the payload (see 3.2.5), to provide the specified GVW. Calculated imposed loads on front and rear axles shall be utilized to ascertain that the suspension, axles, and tires furnished are of adequate capacity to meet contractual requirements.

4.3.2 Road test. The first production vehicle shall be examined and road tested (less payload) by the contractor to assure that the vehicle shall operate in accordance with contractual requirements.

4.3.3 Radio frequency suppression verification. The vehicle manufacturer shall furnish, with the questionnaire (commercial vehicle engineering data), a description of all interference suppression devices used to suppress vehicle electromagnetic radiation in accordance with SAE J551. Data shall be sufficient for visual determination that all required suppression devices are installed on the vehicle.

4.3.4 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample and be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

4.3.5 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under contract until corrective action has been taken.

4.4 Inspection of production vehicles. The contractor's inspection system shall as a minimum, assure that the vehicle conforms to the physical and dimensional requirements and is capable of meeting performance requirements contained herein. For each vehicle under contract, the contractor shall make available to the Government, at the point of final acceptance, records acceptable to the Government indicating that the servicing and adjusting required by 3.8 has been accomplished.

5. PACKAGING

5.1 Vehicle processing. The vehicle shall be processed for shipment from the manufacturer's plant to the initial receiving activity in accordance with manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use. The vehicles covered by this specification are intended for general administrative use by the Government in transporting heavy equipment and for use in the performance of maintenance tasks.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification
(b) Type and model of vehicle required (see 1.2)
(c) Identification of appropriate service for painting and marking (see 3.1.1.1)
(d) Concealed marking, if required (see 3.1.1.1)
(e) Rustproofing, if required (see 3.1.1.2)
(f) Heavy duty cooling system, if required (see 3.1.1.4)
(g) Drive hubs, if required for 4x4 model vehicles (see 3.1.1.7)
(h) A trailer towing package, if required (see 3.1.1.8)
(i) Gasoline engine, if required (see 3.4.1.2)
(j) Power plant heaters, if required (see 3.4.1.6)
(k) If a battery heater is not rquired (see 3.4.1.6)
(l) A measured shot type ether system, if required (see 3.4.2.1)
(m) Lighting cable, if required (see 3.4.2.6)
(n) Automoatic or semiautomatic transmission, if required (see 3.4.5.3)
(o) Traction control, if required (see 3.4.9.1)
(p) Two-speed axle, if required for 4x2 model vehicles (see 3.4.9.2)

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

(q) Wide base type tires and wheels in lieu of dual wheels and tires, if required (see 3.4.10)
(r) Disc type wheels, if required (see 3.4.10)
(s) If a carrier for the spare tire assembly is not required (see 3.4.10.3)
(t) Spare wheel or rim, if required (see 3.4.10.4)
(u) Spare tire, if required (see 3.4.10.5)
(v) Brake control for use from a towing vehicle, if required (see 3.4.11.2.1)
(w) Individual driver's and passenger seats, if required (see 3.4.12)
(x) Crew cab, if required (see 3.4.12.1)
(y) Tools, if required (see 3.4.16.1)
(z) Air operated horn, in addition, if required (see 3.4.21)
(aa) Front mounted winch, if required (see 3.4.22)
(ab) Engine hour meter, if required (see 3.4.23)
(ac) Back-up alarm, if required (see 3.4.24).

6.3 Performance prediction. Completed copies of SAE Truck Ability Prediction Procedure Form and computation for low speed requirement for each vehicle model furnished under contract should be submitted as specified in the contract. The SAE Work Sheet Item 1 should include vehicle model number, wheelbase, and engine model number. Unless other conditions are cited in the contract, computations should be made for normal atmospheric pressure, normal ambient air temperature, and still, dry air. The factors to be used in predicting truck ability (see 3.3.1.1) are established as follows for the corresponding SAE Truck Ability Prediction Procedure Tables:

Table 1 - Tire Factor. This factor must relate to the size of tires furnished by the contractor in accordance with this specification;
Table 2 - Altitude Factor. 1.00
Table 3 - Rolling Factor. 1.613
Table 4 - Area Factor. 0.173
Table 5 - Velocity Factor. 250.0
Table 6 - Altitude Factor. 1.00
Table 7 - Chassis Friction Horsepower. Use applicable power unit GVW (to nearest, higher, 1,000 pounds) and the engine rpm (to nearest 100 revolutions) which is required for 50 mph geared speed. For GVW and engine speed beyond the range of this table, factors shall be extrapolated;
Table 8 - Grade Factor. 0.75
Table 8A - Correction Factor. Not required
Table 9 - Road Factor. 0.0.

Custodian:
Army - AT

Preparing activity:
Army - AT
Project No. 2320-AB90

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE MIL-T-62339(AT) TRUCK, FLATBED: RIGGER MAINTENANCE, 28,000 GVW, 4x2 AND 4x4, COMMERCIAL

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.