MIL-T-62351A
28 May 1986
SUPERSEDING
MIL-T-62351
8 October 1982

MILITARY SPECIFICATION

TRUCKS, VAN: MAINTENANCE, WITH CREW CAB, DIESEL AND GASOLINE ENGINE DRIVEN, 19,000 POUNDS GVW, 4x2, COMMERCIAL

This specification is approved for use by all departments and agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers diesel and gasoline engine driven, four-wheel, two-rear-wheel drive maintenance van trucks with an interior electrical system and a crew cab, and having a minimum gross vehicle weight (GVW) of 19,000 pounds, for normal operating conditions. The vehicles procured under this specification are commercial items which shall be warranted by the manufacturer as specified in acquisition documents.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

W-B-131	- Battery, Storage: Vehicular, Ignition, Lighting and Starting.
ZZ-T-381	- Tires, Pneumatic, Vehicular (Highway).

MILITARY

MIL-B-46176	- Brake Fluid, Silicone, Automotive All Weather, Operational and Preservative.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-UED, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

* AMSC N/A

FSC-2320

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-297	- Rustproofing of Commercial (Nontactical) Vehicles.

MILITARY

MIL-STD-1223	- Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking, and Data Plate Standards.
MS51335	- Pintle Assembly, Towing - 18,000 Lbs. Capacity, Manual Release.
MS75020	- Connector, Plug, Electrical - 12 Contact, Intervehicular, 28-Volt, Waterproof.
MS75021	- Connector, Receptacle, Electrical - 12 Contact, Intervehicular, 28-Volt, Waterproof.

* 2.1.2 Other Government documents. The following other Government documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DEPARTMENT OF TRANSPORTATION (DoT)
Federal Motor Carrier Safety Regulations.
Federal Motor Vehicle Safety Standards.

(Application for copies of DoT publications should be addressed to the Department of Transportation, Federal Highway Administration, Washington, D.C. 20591.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)
Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines.
Noise Emission Standards for Transportation Equipment - Medium and Heavy Trucks.

(Application for copies of EPA publications should reference the Code of Federal Regulations, 40 CFR, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

(Copies of specifications, standards and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:24Z
Check the source to verify that this is the current version before use.

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DoDISS shall be the issue of the nongovernment document which is current on the date of the solicitation.

NATIONAL ELECTRICAL MANUFACTURER'S ASSOCIATION (NEMA)
PRACTICE 5

(Application for copies of NEMA publications should be addressed to National Electrical Manufacturer's Association, 155 East 44th Street, New York, NY 10017).

SAE, INC.
SAE Standards and Recommended Practices

*	J245	- Engine Rating Code - 5 Spark Ignition
	J318	- Air Brake Gladhand Service (Control) and Emergency (Supply) Line Couplers - Trucks, Truck-Tractors, and Trailers.
	J350	- Spark Arrester Test Procedure for Medium Sized Engines (DoD adopted).
	J537	- Storage Batteries (DoD adopted).
*	J551	- Performance Levels and Methods of Measurement of Electromagnetic Radiation from Vehicles and Devices (20-1000 MHz).
	J560	- Seven-Conductor Electrical Connector for Truck-Trailer Jumper Cable.
	J588	- Turn Signal Lamps.
	J589	- Turn Signal Switch.
	J682	- Rear Wheel Splash and Stone Throw Protection (DoD adopted).
	J683	- Tire Chain Clearance - Trucks, Buses, and Combinations of Vehicles. (DoD adopted).
	J688	- Truck Ability Prediction Procedure. (DoD adopted).
	J704	- Openings for Six- and Eight-Bolt Truck Transmission Mounted Power Take-Offs. (DoD adopted).
*	J816	- Engine Test Code - Spark Ignition and Diesel.
	J844	- Nonmetallic Air Brake System Tubing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

J1067 - Seven-Conductor Jacketed Cable for Truck-Trailer Connections.
J1349 - Engine Test Code - Spark Ignition and Diesel.

(Application for copies of SAE publications should be addressed to SAE, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC. (T&RA)
Yearbook.

(Application for copies of T&RA publications should be addressed to The Tire and Rim Association, Inc., 3200 W. Market Street, Akron, OH 44313.)

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.12, vehicles, components, assemblies, and accessories to be delivered under the contract shall be standard or optional items, which meet or exceed the requirements of this specification. All chassis items shall be as represented in the chassis manufacturer's technical data, and special bodies or mounted equipment shall be as represented in the body and equipment manufacturer's technical data. Technical data shall be limited to specifications and technical material identical to that furnished to the authorized company representatives for selection of vehicle models and components, and shall be on file in the engineering offices of the procuring activity, prior to delivery of the items. The chassis model furnished shall be not older than the chassis manufacturer's current model on the date of invitation for bids.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

* 3.1.1.1 Painting and marking. Treatment, painting, marking and data plates shall be in accordance with MIL-STD-1223. The exterior color and the identification markings shall be in accordance with the requirements of MIL-STD-1223 for the military service identified by the procuring activity (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

* 3.1.1.2 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with FED-STD-297. When specified (see 6.2), tropical rustproofing in accordance with FED-STD-297 shall be furnished.

3.1.1.3 Drain plugs. Drain plugs installed in manual transmissions and rear axles shall be of the permanent magnet type.

3.1.1.4 Heavy duty cooling system. When specified (see 6.2), a heavy duty cooling system shall be furnished that will maintain engine coolant at a temperature below the boiling point with the vehicle loaded to rated GVW and operated at an altitude of 10,000 feet above sea level or in an ambient air temperature of not less than 125 degrees Fahrenheit (°F).

3.1.1.5 Coolant system and indicators. The coolant system shall include a de-aeration system, a surge tank, or a coolant recovery reservoir of not less than two-quart capacity. A high coolant temperature or low coolant level alarm buzzer and red indicator warning light shall be provided on the dash instrument panel.

* 3.1.1.6 Wood treatment. As specified herein (see 3.5.6), wood shall be treated in accordance with MIL-STD-1223.

* 3.1.1.7 Towing devices. Not less than two hooks, loops, or pins, or a single center mounted towing eye for towing the vehicle shall be furnished on the front of the vehicle. When specified (see 6.2), not less than two hooks, loops, or pins shall be furnished on the rear.

* 3.1.1.8 Wheel splash and stone throw protection. The vehicle shall have rigid splash shields ahead of the rear wheels and rubber mud flaps to the rear of the rear wheels. A metal strip, not less than 1/8 inch thick and not less than one inch wide, extending the entire width of the mud flap, shall be installed to prevent bolt heads or bolt nuts from damaging the mud flap. All splash shield and mud flap installations, front and rear, shall conform to the rear wheel splash and stone throw protection provisions of SAE J682.

* 3.1.1.9 Trailer towing package. When specified (see 6.2), a trailer towing package consisting of a pintle, safety chain attachment devices, a lighting receptacle, a trailer brake control system and associated reinforcements and wiring shall be installed on the rear of the vehicle. The pintle shall be of the rotating type conforming to MS51335-1. The pintle shall be installed on the chassis frame with reinforcements to transfer a tongue load of not less than 1,800 pounds and a drawbar load of not less than 18,000 pounds directly to the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

chassis rails. The rearmost portion of the pintle shall be forward but not more than four inches forward of the rearmost part of the vehicle. Two trailer safety chain attachment devices, one adjacent to each side of the pintle, shall be provided. Each attachment device shall provide an ultimate strength at least equal to the GVW of the truck furnished. The attachment devices shall be capable of accomodating a standard grab hook for a 3/8-inch chain (2-3/16 inches wide, 47/64 inch thick and 31/64-inch throat width). The lighting receptacle, conforming to SAE J560 with its conductors connected and color coded as specified therein, shall be mounted in a readily accessible location near the pintle. The trailer brake control system shall conform to 3.4.11.3.

* 3.1.1.10 Hydraulic tailgate. When specified (see 6.2), the vehicle shall be equipped with an electric motor driven hydraulic tailgate having not less than 2000 pounds rated capacity. All hydraulic cylinders shall be provided with flow restrictors in the down port of the cylinders to prevent the tailgate from falling rapidly in the event of hydraulic system failure. The tailgate platform shall be of the ramping type and shall have a depth of not less than 32 inches exclusive of the ramp. The ramp shall taper down to the ground level to facilitate ease of loading with wheeled hand carts. Platform loading area shall be of non-skid sheet steel. The tailgate shall have devices for holding the platform in stowed position for vehicle travel. When the tailgate is in position for loading the vehicle, the toe clearance between the rear edge of the vehicle and the tailgate shall be not less than 1/2 inch and not more than 3/4 inch. The controls shall be mounted outside the body on the curbside of the vehicle. The vehicle ignition switch or a separate switch in the driver's compartment shall allow the driver to disconnect the power source to the tailgate. A plate describing operation of the hydraulic tailgate shall be provided and shall be in close proximity to the hydraulic tailgate controls. When a spare wheel or rim and spare tire is furnished with a hydraulic tailgate, the spare wheel or rim and spare tire shall be secured in the vehicle load space. A corrosion-resistant plate indicating the type of hydraulic fluid to be used shall be installed near the filler cap.

3.1.1.10.1 Rear fold tailgate. Unless a fold under type tailgate is specified (see 3.1.1.10.2), the tailgate shall fold vertically against the rear of the vehicle for travel. All tailgate operations shall be hydraulically powered or metered, providing for raising, lowering, folding and unfolding without manual assistance. The tailgate platform width shall be not less than 90 inches. Rear bumper and additional rear end protection need not be furnished.

3.1.1.10.2 Fold under tailgate. When specified (see 6.2), the tailgate shall manually fold under the vehicle for travel and manually unfold for use. Hydraulically powered raising and metered lowering

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

shall be provided. The tailgate platform width shall be not less than 72 inches. Rear bumperettes extending to the rear beyond the stowed tailgate shall be provided on each side of the rear, beyond the 72 inch platform width. Additional rear end protection need not be furnished.

* 3.1.1.11 Spark arrester. As specified herein (see 3.4.4.1) the vehicle shall be furnished with an exhaust system spark arrester.

* 3.1.1.12 Silicone brake fluid. When specified (see 6.2) and if available as the manufacturer's standard or optional brake fluid, silicone brake fluid conforming to MIL-B-46176 shall be provided in the hydraulic brake system. A tag shall be placed near the master cylinder stating "CAUTION: USE SILICONE BRAKE FLUID ONLY."

3.2 General design.

3.2.1 Federal Motor Vehicle Safety Standards. The vehicle and furnished accessories shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture.

3.2.2 Air pollution control. The vehicle shall comply with EPA Regulations governing Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines in effect on the date of manufacture. In addition, vehicles destined for California shall comply with State of California regulations governing air pollution control in effect on the date of manufacture.

3.2.3 Sound level. The interior sound level shall conform to Federal Motor Carrier Safety Regulation 393.94. The vehicle exterior sound level shall conform to EPA Noise Emission Standards for Transportation Equipment - Medium and Heavy Trucks.

3.2.4 Curb weight. The curb weight shall include the weight of the chassis and cab, with all attachments, accessories, equipment, and a full complement of fuel, lubricants, and coolant.

* 3.2.5 Gross vehicle weight. Gross vehicle weight (GVW) shall consist of curb weight, operator (weight computed at 175 pounds), 525 pounds in the rear seat, and a payload to provide not less than the specified GVW.

* 3.2.6 Gross axle weight ratings. The suspension, axle, and tire capacities shall be not less than 7,000 pounds on the front and 15,800 pounds on the rear.

3.2.7 Ratings. Vehicle ratings shall be manufacturer's published ratings. Component and vehicular ratings shall not be raised to meet

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

the requirements of this specification. When published ratings are not available, verification of ratings must be submitted to the engineering office of the procuring activity. Minimum GVW rating shall be 19,000 pounds.

* 3.2.8 Overall width. The overall width of the vehicle, exclusive of mirrors, lights, reflectors and tires, shall be not more than 96 inches. The width over the tires shall be not more than 100 inches.

* 3.2.9 Accessibility. The design of the vehicle and optional equipment shall permit access for routine servicing and shall permit access for replacement and adjustment of component parts and accessories with minimal disturbance of other components and systems.

3.3 Performance.

3.3.1 Speeds. High and low speed requirements shall be met with the vehicle loaded to specified GVW.

* 3.3.1.1 High speed gradeability. The vehicle shall ascend a continous grade of 3.8 percent at 50 miles per hour (mph). Gradeability requirements shall be met with the main transmission in direct drive, and when a multi-speed axle is furnished, with the axle in high speed range. Gradeability shall be verified with calculations in accordance with SAE J688 (see 6.3).

3.3.1.2 Low speed. Low speed shall be calculated with the engine operating at not less than 35 percent of the recommended governed speed, and shall provide not more than the vehicle speed specified in table I for the corresponding number of available forward speeds.

TABLE I. Low speed requirement.

Number of forward speeds	Speed (mph)
4 or 5	4.5
8	3.5
10	3

* 3.3.1.3 Maximum geared speed. The maximum geared speed at engine governed speed shall be not less than 58 mph. Conformance to geared speed specified shall be determined by calculating in accordance with the following formula:

$$\text{Maximum geared speed (mph)} = \frac{\text{Governed speed (rpm)}}{\text{Total gear reduction x tire factor (see 6.3)}}$$

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.3.2 Service brakes. The service brakes shall control and hold the vehicle, when loaded to its specified GVW, on a 30 percent grade. The service brakes shall stop the vehicle, loaded to specified GVW, within the stopping distance requirements of Federal Motor Carrier Safety Regulation 393.52.

3.4 Chassis components.

3.4.1 Engine. The engine furnished shall be the chassis manufacturer's standard or optional engine for the commercial model truck which meets or exceeds the requirements of this specification.

* 3.4.1.1 Diesel engine. Unless otherwise specified (see 3.4.1.2), the vehicle shall be equipped with a liquid cooled, compression ignition, two-stroke or four-stroke cycle diesel engine, with not less than four cylinders. Engine net horsepower used in performance prediction calculations shall be determined in accordance with SAE J816 or SAE J1349.

* 3.4.1.2 Gasoline engine. When specified (see 6.2), the vehicle shall be equipped with a liquid cooled, internal combustion, four-stroke cycle gasoline engine with not less than six cylinders. The engine furnished shall produce the required vehicle performance when operated on unleaded fuel with a research octane rating of 91, at an engine speed not more than the manufacturer's recommended operating speed. The engine shall be capable of warranted operation on unleaded fuel, when used in accordance with the operator's manual. Engine net horsepower used in performance prediction calculations shall be determined in accordance with SAE J245 or SAE J1349. Unless otherwise specified or required by foreign laws, vehicles for overseas use shall be capable of accepting and operating on leaded gasoline.

3.4.1.3 Oil filter. A full flow type oil filter shall be furnished.

3.4.1.4 Governor. An engine governor shall be furnished and set and sealed to limit the engine to the engine manufacturer's maximum recommended operating speed.

3.4.1.5 Coolant temperature control. Thermostatic control of engine coolant temperature shall be provided. On diesel engine driven vehicles, the control shall include partial thermostatic control of coolant flow through the radiator and thermostatically controlled radiator shutters or complete thermostatic control of all coolant flow through the radiator.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

* 3.4.1.6 Fan clutch. A fan clutch shall be provided. The fan clutch shall reduce the fan speed automatically when the fan is not required for cooling.

3.4.1.7 Silicone rubber hoses. When specified (see 6.2), silicone rubber radiator and heater hoses shall be furnished.

3.4.1.8 Power plant heaters and fuel warmer. When specified (see 6.2), a coolant heater, engine oil heater, and a fuel warmer (diesel engine driven vehicles only) shall be provided. Unless otherwise specified (see 6.2), a battery heater shall be provided when power plant heaters are specified. Heaters shall operate on 110-volt alternating current (ac), and shall be wired through the branch and main power panel circuits and the inlet connector receptacle of the van body (see 3.5.13 through 3.5.13.2.5). Electrical apparatus shall conform to Federal Motor Carrier Safety Regulation 393.77(c)(7). All heater lead wires shall be installed without interfering with vehicle component operation and without loose excess wire. Heaters shall be furnished as follows:

* (a) Coolant heater, 1500-watt minimum rating, shall be installed in the engine block or lower, coolant inlet hose. An engine thermostat with an operating range of 170°F to 195°F shall be installed.
(b) Immersion type engine oil heater, 300-watt minimum rating, with 170°F to 195°F thermostat, shall be installed in the oil pan through any convenient opening.
(c) Battery heater shall have a capacity adequate to maintain the battery electrolyte at a temperature of not less than 10°F during vehicle exposure in ambient air temperatures as low as minus 60°F, and shall embody a thermostat to limit the temperature of the electrolyte to not more than 80°F.
(d) For diesel engine driven vehicles, a fuel warmer or pre-heater shall be provided to prevent clogging of fuel filters due to wax crystallization in the fuel. The fuel warmer shall use engine coolant to transfer sufficient heat to the diesel fuel to heat it from an inlet temperature of minus 40°F to an outlet temperature of plus 9°F, with a flow rate not less than the maximum fuel demand of the engine fuel system. A coolant shutoff valve shall be provided for the coolant inlet side of the fuel warmer unit.

3.4.2 Electrical system. The electrical system shall be in accordance with Federal Motor Carrier Safety Regulations 393.27 through 393.31 and 393.33.

* 3.4.2.1 Starting system (diesel engines). For diesel engine driven vehicles, a 12- or 24-volt direct current (dc) starting system, with a 12-volt dc lighting system, and not less than a 60-ampere

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

alternator, shall be furnished. Engine starting equipment shall include an ether starting system or a glow plug. If an ether system is furnished in lieu of a glow plug, it shall be of the measured shot type. The measured shot type ether system shall be key operated or manually operated from the driver's compartment, and shall be inoperative with the engine warm. Complete provisions for a replaceable ether reservoir of not less than 12 fluid ounces shall be furnished. A reservoir need not be furnished.

3.4.2.2 Ignition system (gasoline engines). For gasoline engine driven vehicles, a 12-volt dc ignition system shall be furnished. Unless otherwise specified (see the following), an alternator of not less than 40 amperes rated capacity, and which provides not less than 16 amperes dc output at normal engine idle speed, shall be furnished. When an electric motor driven hydraulic tailgate is furnished (see 3.1.1.10), or when a converter type 24-volt system is furnished (see 3.4.2.7), an alternator of not less than 60 amperes rated capacity and which provides not less than 16 amperes dc output at normal engine idle speed shall be furnished.

3.4.2.3 Lighting. All vehicle lights, reflectors, and wiring shall conform to Federal Motor Carrier Safety Regulations 393.12, 393.19, 393.20 and 393.22 through 393.26(d). Lights and reflectors shall not be mounted on vertical surface of rub rails (unless recessed and fully protected) or mounted on vehicle bumpers.

3.4.2.4 Turn signals. Turn signal lamps shall conform to SAE J588. Operating units shall conform to SAE J589, class A, and shall be mounted on the steering column. The vehicle shall be provided with double faced front signal units and with single faced rear signal units installed in accordance with SAE J588 except that turn signals shall not be mounted on engine compartment hood. Turn signal operating units shall be self-cancelling type with visible and audible type flash indicator.

3.4.2.5 Trailer lighting cable. When specified (see 6.2), a trailer lighting cable conforming to SAE J1067 shall be furnished. The cable shall be coiled and shall be not less than 110 inches long when fully extended. Both ends of the cable shall be equipped with a round plug conforming to SAE J560. The plugs shall be equipped with a grip for withdrawing from the connector sockets. The cable shall be packaged and stowed in the vehicle tool compartment.

* 3.4.2.6 Batteries. Each battery shall be of 12-volt potential. The total reserve capacity rating at 80°F and the total cold cranking rating at 0°F, both measured in accordance with SAE J537, shall be not

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

less than as specified in table II. The batteries shall be of the maintenance-free type having the maintenance-free characteristics listed in W-B-131.

TABLE II. Batteries.

Engine type	Reserve capacity (minutes)	Cold cranking (amperes)
Diesel (less than 220 gross horsepower)	320	1200
Diesel (220 gross horsepower or over)	480	1800
Gasoline	100	450

3.4.2.7 Auxiliary 24-volt system with trailer receptacle. When specified (see 6.2), an auxiliary 24-volt system with a trailer receptacle shall be furnished. The auxiliary 24-volt system output capacity shall be not less than 12 amperes. Either a converter type (see 3.4.2.7.1) or an alternator type (see 3.4.2.7.2) system meeting specified requirements shall be furnished. A trailer receptacle, conforming to MS75021-2, with cover assembly, shall be provided in an accessible location on the rear end of the vehicle. A twelve-conductor cable not less than 110 inches long with both ends of cable equipped with connectors conforming to MS75020-1 and MS75020-2 shall be furnished. The cable assembly shall be stowed in the vehicle. The 24-volt, 12 ampere output service lighting circuit shall be connected through the appropriate lighting controls to terminals B, D, E, J and L of MS75021-2.

3.4.2.7.1 Converter type 24-volt system. The 12- to 24-volt converter(s) shall operate from the 12-volt battery (see 3.4.2.6).

3.4.2.7.2 Alternator type 24-volt system. The alternator type 24-volt system shall be separate from the 12-volt vehicle lighting and ignition system and shall include:

(a) Nominal 24-volt alternator with not less than 24-ampere rated capacity and capable of providing not less than 7 amperes dc output at normal engine idle speed
(b) Two 12-volt batteries with a combined capacity of at least 40 ampere hours at a 20 hour rate or one 24-volt battery with a 20 ampere hour capacity at a 20 hour rate
(c) Voltage regulating device
(d) An ammeter, mounted on the instrument panel.

3.4.2.8 Battery charger. When specified (see 6.2), a battery charger, trickle charge type, with approximately 10 ampere maximum charge rate and built-in protective device to preclude battery overcharge, shall be furnished. The charger shall be installed in the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

engine compartment and connected from the 120-volt circuit breaker at the main power panel (see 3.5.12.1.2 or 3.5.14.2) and to the vehicle battery(s) (see 3.4.2.6).

* 3.4.2.9 Radio interference suppression. The vehicle shall be suppressed to limit the electromagnetic radiation in accordance with SAE J551. Any body equipment emitting radiation shall be suppressed to the same level as the vehicle chassis.

3.4.3 Fuel system. The fuel system shall conform to Federal Motor Carrier Safety Regulations 393.65 and 393.67.

3.4.3.1 Air cleaner. An air cleaner shall be furnished. When equipped with an oil-bath type, oil capacity shall be not less than 1 quart.

3.4.3.2 Fuel tanks. Fuel tank(s) shall be the manufacturer's standard for the vehicle and shall have not less than 80 gallons total capacity. When more than one tank is furnished on diesel engine driven vehicles, means shall be provided to assure equalized fuel level in both tanks. When more than one tank is furnished on gasoline engine driven vehicles, a selector valve connecting either tank to the engine fuel intake shall be provided and means shall be provided to monitor the fuel level of either tank from a single gage.

* 3.4.4 Exhaust system. The exhaust system shall conform to Federal Motor Carrier Safety Regulation 393.83. If vertical exhaust mufflers are furnished and if they are capable of being reached easily by personnel entering or leaving either side of the cab, a heat shield shall be provided. Vertical exhaust systems shall be provided with a hinged rain cap.

* 3.4.4.1 Spark arrester. When specified (see 6.2), a spark arrester shall be furnished, except on vehicles with turbocharged engines. The spark arrester shall have an 80 percent arresting efficiency when rated in accordance with SAE J350.

3.4.5 Transmission. Unless otherwise specified (see 3.4.5.2), a manually shifted transmission shall be provided on the vehicle. Input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine. The transmission and axle gear ratios shall be selected to provide the performance specified in 3.3.1.

3.4.5.1 Manually shifted transmission. The manually shifted transmission shall have not less than four forward and one reverse speed with SAE J704 power takeoff opening. The transmission shall provide for synchronized shift for at least the three highest forward speeds.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:24Z
Check the source to verify that this is the currentversion before use.

* 3.4.5.1.1 Clutch. The clutch shall be the largest capacity clutch offered for the vehicle and engine furnished, with clutch torque capacity exceeding maximum delivered engine torque.

* 3.4.5.2 Automatic or semiautomatic transmission. When specified (see 6.2), the vehicle shall be provided with an automatic or semiautomatic transmission. The transmission shall provide continuous drive. The transmission shall include a hydraulic torque converter and not less than four forward gear ratios. Normal driving range selector position shall provide not less than four gear ratios without movement of the selector. The transmission shall be provided with SAE J704 power takeoff opening(s). The input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine.

3.4.5.3 Power takeoff. When a power takeoff is furnished, it shall be of a rated capacity to operate powered equipment. Controls to operate the power takeoff shall be located in the truck cab accessible to the seated driver. A caution plate or decal reading "DO NOT OPERATE VEHICLE AT HIGHWAY SPEEDS WITH POWER TAKEOFF ENGAGED" shall be provided and installed so as to be readily visible to the seated driver.

3.4.6 Drive line components. Drive line components shall be adequate to transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction.

* 3.4.7 Frame. The chassis frame shall be the manufacturer's standard for the vehicle furnished. The vehicle shall have a frame with reinforcements extending at least from the rear of the front-suspension, rear hanger bracket to the front of the rear-spring, front hanger bracket or a heavy duty frame with a resisting bending moment of not less than 600,000 inch-pounds may be furnished. Reinforcement shall provide sufficient structural strength in the chassis frame through increased resisting bending moment to at least equal the load imposed, with the vehicle body loaded to provide specified GVW. Chassis frame rails shall not project beyond the rear end of the body.

3.4.8 Suspension. The vehicle shall be equipped with a suspension system with components having a rated capacity at least equal to that specified in 3.2.6. The right rear spring shall have an adequate spring constant (force/length) to insure level suspension of the unladen vehicle with an 800 pound crane located as specified in 3.5.2. When suspension capacity is rated at the spring pads, unsprung weight shall be deducted. The vehicle shall be equipped with hydraulic, double-acting shock absorbers at the front wheels. When specified (see 6.2), auxiliary rear springs shall be provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.4.9 Axles. Axle ratings shall be at least equal to that specified in 3.2.6. Vehicles provided with automatic or semiautomatic transmission shall be equipped with a single speed axle. Unless a two speed axle is provided, a single reduction rear axle shall be furnished.

3.4.9.1 Two-speed axles. When specified (see 6.2), a two-speed axle shall be furnished, equipped with electric, vacuum, or air shift and provided with ratios which will permit proper gear splitting. The gear ratio shall provide performance specified in 3.3.1.

3.4.9.2 Traction control. When specified (see 6.2), the vehicle shall be furnished with a traction control on the rear axle. The traction control shall actuate automatically to insure that power is transmitted to the wheel having traction when the opposite wheel loses traction. Maximum traction capabilities shall be maintained at all times under each drive wheel for the life of the vehicle.

* 3.4.10 Wheels, rims, tires and tubes. The vehicle shall be equipped with single front and dual rear wheels. Rims and tire ratings shall conform to Tire and Rim Association recommendations for the type and size of tires furnished. Rim and disc wheel sizes shall be the same for all wheels on each vehicle. Tire size and ply rating shall be the same for all tires on each vehicle. When specified (see 6.2), the vehicle shall be equipped with wide base type tires and wheels for the front and rear axle in lieu of dual rear wheels. Wide base wheels shall be interchangeable without the use of an adapter. When specified (see 6.2), 10-stud disc type wheels shall be furnished.

* 3.4.10.1 Tires. Tires shall be steel belted radial or, when specified (see 6.2), bias ply. Tires shall be tube or tubeless type with highway tread. Tires shall be of rated capacity at least equal to that specified in 3.2.6. Tires shall conform to the Tire and Rim Association recommendations or to ZZ-T-381 with a size designation system the same as the Tire and Rim Association.

3.4.10.2 Inner tubes. When tube type tires are furnished, inner tubes shall be of heavy duty type, and shall be of proper size for tires furnished. Tire flaps shall be provided for tube type tires in accordance with Tire and Rim Association recommendations.

* 3.4.10.3 Carrier for spare tire assembly. When specified (see 6.2), a carrier for a spare wheel or rim and tire assembly shall be installed in a readily accessible location on the vehicle. Threaded fasteners, when used to secure the spare tire in the carrier, shall be constructed of or plated with corrosion-resistant material. The carrier

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

design shall enable removal or mounting of a spare wheel assembly using only the tools specified in 3.4.16.1. A carrier is not required when a hydraulic tailgate is furnished.

3.4.10.4 Spare wheel or rim. When specified (see 6.2), a spare wheel or rim shall be installed on the carrier. When a spare tire assembly is specified (see 3.4.10.5), a spare wheel or rim shall be furnished.

3.4.10.5 Spare tire assembly. When specified (see 6.2), a spare tire assembly shall be furnished. The spare tire assembly shall include an inflated spare tire mounted on the spare wheel or rim. The spare tire shall be of the same size, tread design and load range (ply rating) as the tires furnished on the vehicle.

3.4.10.6 Tire chain clearance. Tire chain clearance in accordance with SAE J683 shall be provided. Allowance for spring deflection shall be included.

3.4.11 Brakes. The brakes shall conform to Federal Motor Carrier Safety Regulations 393.40 through 393.43 and 393.45 through 393.52.

3.4.11.1 Power-hydraulic type. Unless otherwise specified (see 3.4.11.2), the vehicle shall be equipped with power assisted, hydraulically actuated, four-wheel, service brakes.

* 3.4.11.1.1 Split hydraulic brake system. The power-hydraulic brake system shall be so arranged as to provide separate systems for at least two wheels and so designed and constructed that rupture or leakage-type failure of any single pressure component of the service brake system, except structural failures of the brake master cylinder body, effectiveness indicator body, or other housing common to the divided system, will not result in complete loss of function of the vehicle brakes when force on the brake pedal is continued. "Pressure component" means any internal component of the brake master cylinder or master control unit, wheel brake cylinder, brake line, brake hose, or equivalent, except power assist components.

* 3.4.11.1.2 Indicator light. Split hydraulic brake system shall be equipped with an electrically operated red light mounted on the instrument panel to indicate system effectiveness. The light shall have an area of not less than 0.196 square inch. It shall illuminate before or upon application of the brakes when an actuating-pressure component of the system has sustained a loss of pressure. The indicator light system shall include a means of testing by the vehicle operator to assure that the light bulb is operable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

* 3.4.11.2 Air type. When a trailer towing package is specified or when specified by the procuring activity, (see 6.2), the vehicle shall be equipped with four wheel, full-air-application brakes. The braking system, complete with all necessary components, shall include:

(a) Air compressor, unloader-head type, engine driven and engine lubricated, air or water cooled, and having a capacity of not less than 7 1/4 cubic feet per minute (cfm)
(b) Air storage reservoir(s) with not less than 2,000 cubic inches total capacity; each tank equipped with drain, and with safety and check valves between compressor and last reservoir tank
(c) Foot control, suspended or treadle type
(d) Air control valves
(e) Air pressure gage, visible to the driver
(f) Low-air-pressure warning, visible and audible
(g) Service brake stop lamp switch
* (h) Alcohol aspirator with unbreakable container
(i) Automatic moisture ejector
* (j) Automatic slack adjusters
* (k) When specified (see 6.2), in lieu of subparagraph(h), an air dryer shall be furnished. The air dryer shall be of the desiccant or after-cooled type.

3.4.11.3 Trailer brake control system. When a trailer towing package is specified (see 3.1.1.4), a trailer brake control system shall be furnished. The trailer brake control system shall include:

(a) Identification of emergency and service lines
(b) Coincident control of trailer brakes with prime mover foot control
(c) Independent hand control for trailer brakes
(d) Prime mover protection valve with dash control and automatic break-away feature
(e) Trailer stoplight control operable with foot brake and with hand control for trailer brakes
(f) Two SAE J844 coiled air hoses, not less than 110 inches long when fully extended, with SAE J318 gladhand couplers on both ends of hoses. The hoses shall be packaged and stowed in the vehicle tool compartment for shipment
(g) Air connectors for trailers with SAE J318 gladhand couplers mounted at the rear of the vehicle, located to preclude interference with trailer
(h) Dummy gladhand couplers with chains
* (i) Prime mover only parking brake valve to permit prime mover parking brakes to be applied while charging the trailer brake system.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

* 3.4.11.4 Brake controls for use from a towing vehicle. When specified for vehicles with air brakes (see 6.2), the vehicle shall be furnished with a system for controlling the brakes from a towing vehicle (wrecker). The installation shall be complete with air brake couplers, relay emergency valve with no-bleed-back feature (except when spring applied emergency brake is furnished), additional air lines and fittings. The service and emergency couplers shall be mounted on the front in a protected position providing for ready attachment of air hoses from a towing vehicle. The service and emergency couplers shall be identified and provided with dummy gladhand couplers with chains. The system shall not compromise conformance to any Federal Motor Carrier Safety Regulation referenced herein or to any Federal Motor Vehicle Safety Standard.

3.4.12 Crew cab. A four-door full width, crew cab shall be furnished. The cab shall have an upholstered, full width, adjustable front seat and back or, when specified (see 6.2), an individual adjustable, driver's seat and an individual passenger seat. An upholstered, full width rear seat and back shall be furnished. The color of the upholstery and the interior finish shall be compatible with the exterior color (see 3.1.1.1). White upholstery shall not be furnished. Fastenings and seat belts shall be installed for each seating position (five or six). Cab doors shall be equipped with locks operable from inside the cab through mechanical linkage, with both front doors equipped with external key-operated lock. Cab doors shall have windows with crank-operated window regulators. Interior lighting shall be provided. The cab roof shall be of one piece construction; or, if welded, the roof shall give the appearance of one piece, with weld seams being continuous, waterproof, and free of visible seams, bumps or protrusions. Full length drip moldings shall be mounted above the doors. The cab-to-axle dimension shall be measured from the back face of the crew cab.

3.4.12.1 Seat spacing. With the front seat adjusted to the extreme forward position there shall be not less than 30 inches, measured in a horizontal plane, between the front of the rear seat-back and the rear of the front seat-back. A kick-space height of not less than 2-3/4 inches shall be maintained between the floor and the rear of the front seat in all positions of adjustment. Leg room and space forward of the front seat shall be equivalent to that provided ahead of the seat in a two-door standard cab.

3.4.13 Steering. Power steering shall be furnished.

3.4.14 Windshield wipers and washers. The vehicle shall be equipped with dual windshield wipers and windshield washers. The windshield wipers shall be of the multispeed type and operated by either air or electric motor(s).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

3.4.15 Bumpers. Unless the bumper is an integral part of vehicle cab, a channel type front bumper shall be provided.

3.4.15.1 Rear end protection. The rear end of vehicle shall be protected in accordance with Federal Motor Carrier Safety Regulation 393.86.

3.4.16 Tool stowage. Stowage space of sufficient size to accommodate the vehicle jack, hand tools, anti-skid chains and emergency reflective triangles shall be furnished for retaining equipment during vehicle operation. Stowage space for these tools may be furnished in cab. When stowage space for these tools is located outside of cab, it shall be weatherproof and shall provide for locking with a padlock.

3.4.16.1 Tools. When specified (see 6.2), the vehicle shall be furnished with tools required for exchanging a mounted tire assembly with the spare assembly, and shall include at least a jack, jack handle and wheelnut wrench. The jack shall be of such closed height as to permit its location under axle, or other satisfactory lift point, at any wheel with the tire flat. The jack, without blocking, shall be capable of raising any wheel of the loaded vehicle to a height adequate to permit removal and replacement of the wheel and tire assembly.

3.4.17 Heater and defroster. A hot water heater shall be provided. The heater shall have fresh air intakes. Discharge outlets shall be provided to direct heated air to the floor and to defroster louvers. The heater shall be complete with blower and mounted controls convenient to the driver.

3.4.17.1 Auxiliary hot water heater. When specified (see 6.2), the crew cab shall have an auxiliary hot water heater with blower installed underneath the front seat or, when individual driver and passenger seats are provided, between the front seats. Sufficient thermal insulation material and heater capacity shall be provided to maintain a temperature of at least 40°F at the cab floor level with an ambient temperature of minus 45°F and a wind providing a chill factor of minus 70°F. The auxiliary heater airflow shall be directed toward the rear seat. The blower controls and shut-off valve shall be convenient to the driver.

* 3.4.17.2 Auxiliary electric heating. When specified (see 6.2), auxiliary electric heating unit(s) shall be permanently installed in the truck cab for use when the vehicle is parked with the engine shut off. The heater(s) shall have a total output of not less than 14,000 British thermal units (Btu) and shall be permanently mounted under the dash instrument panel or underneath or between the front seat(s). The units

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

shall operate on 120/208 volt ac or 120 volt ac power, as required (see 3.5.13 and 3.5.14). Heating unit(s) shall not interfere with the operation of the vehicle or with the occupant's comfort. The heater(s) shall be enclosed by sheet metal, with a protective finish and shall be equipped with a manually operated thermostat.

3.4.18 Controls and operating mechanisms. All controls and operating mechanisms shall be located for left-hand drive. Controls shall be complete and conveniently operable by the driver. Lever controls shall be designed and located to permit easy entrance and exit by the operator to and from the driver's compartment. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. Instruments shall be panel mounted.

3.4.19 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

(a) Key-operated ignition switch
(b) Ammeter, charging indicator, or voltmeter
(c) Fuel gage
(d) Oil pressure gage or indicator
(e) Engine temperature gage or indicator
(f) Speedometer with recording odometer
(g) Ash receptacle
(h) Dual sunvisors
(i) Front door mounted armrest on driver's side
(j) Driver's compartment ventilator other than window
(k) Tachometer (for diesel engine driven vehicles only).

3.4.20 Rearview mirrors. Outside rearview mirrors shall be mounted on each side of the cab. The mirrors shall be of the combination type having flat and convex areas inclosed in a common housing. The flat portion shall have not less than 50 square inches of reflective area. The convex portion shall have not less than 20 square inches of reflective area. The mirrors shall have not less than three supporting arms.

* 3.4.21 Horn. The manufacturer's standard electric horn shall be furnished. When specified (see 6.2), in addition, an air operated horn shall be furnished on vehicles equipped with an air brake system.

3.4.22 Engine hour meter. When specified (see 6.2), an engine hour meter having a totalizing mechanism of not less than 9,999 hours shall be furnished for the chassis engine to register accurately the number of hours of operating time. The meter shall be of rugged

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

construction to insure continuous trouble-free performance under severe operating conditions. The engine hour meter shall be mounted on the cab instrument panel or in the engine compartment in a readable location.

3.4.23 Back up alarm. When specified (see 6.2), the vehicle shall be provided with an audible, pulsating signaling device (electrical or mechanical) to caution personnel when the vehicle is in reverse gear operation.

* 3.5 Body. The body subframe, rear corner posts, rear header and rear crossmember shall be constructed of steel. Body side posts, front posts, side and front wall panels, roof panels, and rub rails or buffer sheets shall be constructed of aluminum. Roof bows shall be aluminum or steel (see 3.5.4). Steel used shall be of the minimum gages specified for carbon steel; high tensile steel used may be two gages lighter weight in accordance with US Standard gages. Effective means shall be taken to preclude electrolytic action between dissimilar metals. The maintenance van shall have the dimensions specified in table III.

TABLE III. Dimensions.

Designation	Dimension (inches)
Rear-of-cab to rear axle (minimum)	100
Length (outside) (minimum)	167
Width (inside) (minimum)	89
Height (inside) (minimum)	89
Overall height (maximum)	150

3.5.1 Body surface shapes. The van body surface shall be smooth-skinned, without exposed exterior vertical posts or vertical corrugations, so as to minimize aerodynamic drag. Stretcher-leveled skins are not required. The front corner radius and top longitudinal edge radius shall be the largest furnished for the model offered.

* 3.5.1.1 Van body wind deflection. Unless otherwise specified herein, an aerodynamically streamlined body front shall be incorporated into the design of the body to direct airflow around the sides and over the top of the van body. The construction shall be integral with the van body front wall, sidewalls and roof, giving a curved front radius. When specified (see 6.2), a wind deflector fairing shall be attached to the upper front face of the van body. The deflector shall have an aerodynamic fairing shape to direct airflow around the sides and over the top of the van body. The deflector fairing shall have a rounded nose with a convex profile in both side and top views, forming a smooth compound curved surface blending into the rectangular body cross section. The nose of the fairing shall project forward sufficiently to

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

achieve a significant drag reduction at low yaw angles, and shall have a large enough radius to produce minimal flow separation at yaw angles of up to 20 degrees. In no case shall the forward portion of the fairing be less than 22 inches from the front face of the van body. The lower edge of the fairing shall be located as required to minimize drag due to turbulent airflow from the cab. The fairing construction material shall be molded fiberglass. Design operational limits shall include forward vehicle speeds of 60 mph during wind gusts of 60 mph from any direction.

* 3.5.2 Body subframing. Body subframing shall be of welded or bolted construction, braced at all points of stress. There shall be not less than ten full width crossmembers, including ends, of full channel or equivalent section, steel construction, attached to longitudinal sills by welds, and at the front, rear, and every second intervening crossmember by gussets. When subframing is by welded assembly, angle gussets, crossmembers, longitudinal sills, and welded reinforcements (when used) shall be joined by weld for not less than 50 percent of the length of the contact edge(s). Spacing of crossmembers shall be equal, ahead of, and to rear of wheels except for a square area for location of a floor crane. The crane will be mounted on an area of 16-3/4 inches square with the center located 19-3/8 inches forward of the rear door and 17-3/8 inches from the curb side wall. The crane mounting area shall be reinforced to withstand the loads imposed by an 800-pound crane loaded with 14,000 pounds at a 32-inch radius, without permanent deformation. Longitudinal sills shall be constructed of structural steel channel, structural I-beam or reinforced formed channels or I-beams. Formed channel sills and I-beams shall be reinforced within the sill, at each crossmember and body mounting point, with formed channel reinforcements. Crossmembers, gussets, formed longitudinal sills and reinforcements shall be of not less than 10 gage (0.1345 inch) steel. Extruded aluminum or steel side and front rails shall be furnished. When steel side and front rails (out-rails) are furnished they shall be of not less than 12 gage (0.1046 inch) steel. The design of the subframe shall permit a low floor height without wheel wells, while providing tire chain clearance, and shall permit vehicle operation at speeds up to 50 mph over improved roads, when loaded with an evenly distributed payload to the rated GVW, without evidence of permanent deformation.

3.5.3 Body framing. Side and front post construction shall be extruded aluminum and shall be not less than 1.125 inches in depth and 0.330 pound per foot when side and front wall posts are spaced on maximum 16 inch centers. Side and front post construction shall be extruded aluminum and shall be not less than 1.250 inches in depth and 0.430 pound per foot when side and front wall posts are spaced on maximum 24 inch centers. Front corner post construction shall be extruded aluminum and shall be not less than one inch in depth and 0.482

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

pound per foot. The front structure shall be capable of withstanding a horizontal static load equal to 0.4 times the payload capacity of the vehicle without permanent distortion. Rear corner posts shall be of not less than 12 gage (0.1046 inch) steel.

* 3.5.4 Body exterior. The roof assembly shall be standard for the vehicle, and shall be constructed to insure drainage. Roof support bow construction shall be extruded aluminum or not less than 18 gage (0.478 inch) galvanized steel, 1.38 inches in depth. When aluminum roof support bows are spaced on 24 inch maximum centers, the roof bow shall be not less than 1.000 inch in depth and 0.394 pound per foot, and the roof panel shall be not less than 0.040 inch aluminum alloy. When aluminum roof support bows are spaced on 18 inch maximum centers, the roof bows shall be not less than 1.000 inch in depth and 0.380 pound per foot, and the roof panel shall be not less than 0.025 inch aluminum alloy. When steel roof support bows are used, they shall be spaced on not more than 24 inch centers and the roof panel shall be not less than 0.040 inch aluminum alloy. Body side panels shall be not less than 0.032 inch aluminum alloy. Body side panels shall be removable to facilitate body repair. All roof and body seams and joints shall be weatherproof. All body and roof rails shall have a maximum radius of 4.50 inches and shall be extruded aluminum. Rub rails or buffer sheets extending outward beyond the body skin shall be provided on both sides of the body. The rub rails or buffer sheets shall be permanently attached to or shall be an integral part of the exterior of the body at the floor line.

* 3.5.5 Body interior. The complete interior of the body sides, top, and front shall be insulated. Insulation shall provide resistance to heat transfer equivalent to that offered by a 1-inch thick batt having a thermal conductivity (K) of 0.24 Btu/square foot/°F/hour/1-inch and having a moisture absorption capacity of less than 2 percent by weight. Materials shall be odorless and fire retardent. The insulation shall not breed nor promote the growth of fungus and shall not cause nor accelerate corrosion of steel, copper, or aluminum. Insulation shall be cemented to inner side of exterior walls and shall be provided with means to retain insulation in place under all operating conditions. The interior of the body walls, including front wall and ceiling, shall be lined with not less than 1/4-inch exterior grade plywood, full height. Plywood lining shall fit between the tiedown rails (see 3.5.5.1). Galvanized steel shall line the exposed surface of the plywood. Metal lining shall extend under the tiedown rails and all seams of the metal lining shall be located under the tiedown rails. The seams shall overlap to prevent water leakage.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

* 3.5.5.1 Tiedown rails. Three rows of Aeroquip Model 34030-2, or equal, cargo tie-down rails shall be installed the full length of all three interior walls of the van body. The bottom row shall be located 12 inches ± 1/2 inch above the floor; the middle row shall be located 36 inches ± 1/2 inch above the floor; and the top row shall be located 60 inches ± 1/2 inch above the floor. The tie-down rails shall be secured by screws to the wall frame members.

* 3.5.6 Floor. The floor shall be of not less than one-inch exterior grade plywood, covered by 1/8-inch minimum steel tread plate. Wood shall be treated in accordance with 3.1.1.6. Steel floor sections shall overlap and shall be sealed to prevent leakage of moisture through the floor. The sides and the front of the floor shall have an inverted skirt extending upwards for not less than 5 inches and shall be fitted between the insulation and the inner panels. The floor design shall withstand vehicle operation at speeds up to and including 58 mph, over improved roads, with a concentrated load of not less than 200 pounds on any square foot of floor area. Tread plate shall be rustproofed on underside prior to installation.

3.5.7 Floor tie-down rings. Recessed floor tie-down rings shall be installed as follows: 6 tie-down rings shall be evenly spaced, 24 inches from the street side wall, along the full length of the body; 4 tie-down rings shall be evenly spaced, 24 inches from the curb side wall, and forward of the crane mounting location (see 3.5.2); 1 tie-down ring shall be located 24 inches from the curb side wall and centered between the rear door and the crane mounting location. The 4 forward tie-down rings and the most rearward tie-down ring on the curb side shall be in line with the corresponding tie-down rings on the street side. The tie-down rings shall withstand a pull in any direction of not less than 2,000 pounds. Two safety lanyard tie-down rings, of 5,400 pounds capacity each, shall be located in the floor, 30 inches from the left side wall, and located at 6 and 48 inches forward of the rear doors.

* 3.5.8 Rear steps. Unless a hydraulic tailgate is specified (see 3.1.1.10), not less than two steps shall be provided on the rear of the van body between ground level and the van floor. The steps shall be the full width of the body. The steps shall be constructed of slip-resistant safety steel floor plate. The steps shall fold up against the lower truck frame and shall be provided with a locking device to secure the steps in place when the truck is traveling at high speed over rough roads. When the steps fold down into operating position, they shall be able to support a load of not less than 300 pounds per square foot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.5.9 Double rear doors. Double rear doors shall be provided, full width and height, with bracing to prevent sagging, and equipped with three cast steel, or equal, hinges per door. The door locking devices shall include not less than three bolts, or latches, top, bottom and intermediate on the door. A cam type locking device shall be provided with an operating handle and shall be installed to insure closing under all operating conditions. Provisions for use of a padlock shall be furnished. The body shall be equipped at the sides with catches for holding doors in fully opened position. Hardware shall be the manufacturer's standard.

3.5.10 Side door. When specified (see 6.2), a curbside swing type door not less than 30 inches wide by 70 inches high shall be furnished. The door shall be located near the center of the van body but entirely ahead of the wheel well. The door shall be of aluminum faced plywood or of all-aluminum with bracing to prevent sagging. The door shall be equipped with at least three hinges. A cam-type locking device shall be provided with an operating handle and shall be installed to insure positive closing under all operating conditions. Provisions shall be incorporated for a padlock. Handles shall be located to permit operation from ground level. The hardware shall be the manufacturer's standard. The door shall have a weathertight rubber or plastic seal all around. The side wall shall be reinforced at the door opening. The body shall be equipped with latches to hold the door in a fully open position.

3.5.11 Rear and dock bumpers. A channel type rear dock bumper of not less than 10 gage (0.1345 inch) steel, not less than three inches in height, shall be provided. The dock bumper shall be integral with the body. The dock bumper shall be not less than one inch below the hinged rear doors. A drop bumper with cross bar shall be provided in addition to the dock bumper. The bumper shall be the full width of the body.

3.5.12 Body mounting. The body shall be secured with U-bolts, twin-studs, brackets or J-bolts and shall include a wood breaker strip.

3.5.12.1 U-bolts or twin-studs. When U-bolts or twin-studs are used, there shall be not less than three U-bolts or twin-studs per side, each having 9/16-inch diameter with 5/8-inch minimum thread diameter. Tie-plates shall be at least 1/2-inch thick. The vehicle chassis frame shall be braced, using wood blocks at each mounting point unless mounting point is located at a full depth, frame crossmember. Blocks shall incorporate a keeper strap or groove for the mounting bolt, and shall be of a width and thickness to assure retention. Two tie-back straps shall be provided, one bolted to each side of the rear portion of the body subframe, to maintain body alinement on vehicle chassis. Forward body mounting bolts shall be located to the rear of the tapered portion of breaker strips (see 3.5.12.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.5.12.2 Brackets. When brackets are used, they shall be bolted to the web of the chassis frame rails. The body mounting brackets shall provide means for drawing down the body on the chassis rails and provisions shall be made to prevent lateral shifting of the breaker strips. When additional holes are required to secure mounting brackets to chassis frame rails, they shall be located within the area of the rail which is designated as being safe for drilling in accordance with the chassis manufacturer's body builders layouts. Attachments shall not interfere with nor obstruct existing chassis components.

3.5.12.3 J-bolts. When J-bolts are used, there shall be not less than seven J-bolts per side, each not less than 3/8-inch in diameter. J-bolts shall encircle the lower chassis frame flange. Two tie-back straps as specified in 3.5.12.1 shall be provided. The forward J-bolts shall be located to the rear of the tapered portion of the breaker strips (see 3.5.12.4). Provisions shall be made to prevent lateral shifting of the breaker strips.

3.5.12.4 Breaker strips. A hardwood or dense southern yellow pine breaker strip, not less than 1-1/16 inches finished thickness, shall be installed between the longitudinal sills and the vehicle chassis frame. Breaker strips shall have a taper of one inch in 18 inches at the forward end.

* 3.5.13 Interior electrical system. Unless otherwise specified (see 3.5.14), a van body interior electrical system rated for 60-ampere, 120/208 volt ac, 3-phase, 60 hertz (Hz) power shall be provided.

* 3.5.13.1 Electrical system - 120/208 volts ac. The system shall include an exterior body-wall mounted connector for receiving external power, a main circuit breaker, branch circuit breakers, overhead interior lights, switches, and wall receptacles. The electrical system shall also include branch circuit breakers for the power plant heaters, electric cab heater(s), and battery charger when these items are furnished with the vehicle. The entire assembly shall be rated weatherproof in accordance with National Electrical Manufacturer's Association (NEMA) Practice 5.

* 3.5.13.1.1 External power receptacle. A connector that meets NEMA standards or that is Underwriter Laboratories listed and that is rated for 60-amperes, 120/208-volts, 3-phase, 60 Hz power shall be furnished. The connector shall be a 5-wire, grounded neutral, outdoor male type inlet receptacle (Pyle-National Company part number ZZMWFB17120-37P or equal). The connector shall mate with a Pyle-National Company part number ZZMWF1712-37P. The connector shall be wired as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

a. Pin 1 - ground
b. Pin 2 - neutral
c. Pins 3, 4, and 5 - 60-amperes, 120/208-volts ac, 3-phase power.

The inlet receptacle shall be installed on the vehicle exterior at the right rear corner of the vehicle below the floor level, with suitable protection from wheel splash. The inlet receptacle shell shall be heavy cast or forged aluminum and shall be securely bolted to the body. The connector shall be securely bolted or screwed into the shell. A screw-on cover with chain attached to the shell shall be provided on the receptacle. The entire assembly shall be rated weatherproof in accordance with NEMA practices.

* 3.5.13.1.2 Wiring and circuit breakers. All wiring methods and materials shall conform to the National Electrical Code. All interior wiring shall be enclosed in aluminum conduit. The wiring shall be routed from the exterior receptacle to inside the van body and shall run to a 50-ampere, 2-pole, thermal-magnetic main circuit breaker for main power panel overcurrent protection. The main circuit breaker shall be installed in a main power panel. The main power panel and circuit breaker shall be NEMA rated at 60 amperes, 120/208 volts ac, 3 phase, 5 wire. The main power panel shall be located at the rear end of the curbside wall just below the ceiling, as convenient, and not less than 6 inches from the rear doors. The main power panel shall have a hinged cover which can be locked in, or an equivalent locking-in-place feature. In addition to the main circuit breaker, the main power panel shall include branch 20/30-ampere circuit breakers for the lighting, wall receptacles and, when furnished, for the power plant heaters (see 3.4.1.7), battery charger (see 3.4.2.8), and for the auxiliary electric cab heaters (see 3.4.17.2). Separate ground and neutral wiring shall be maintained throughout. The circuits shall be wired to allow approximately equal loads on each phase.

3.5.13.1.3 Wall receptacles. Below the main power panel there shall be two 120-volt, 30-ampere, 1-phase, 3-wire grounded receptacles with spring loaded caps.

3.5.13.1.4 Interior lighting. The vehicle body interior shall be equipped with the quantity and arrangement of ceiling flush-mounted light fixtures in the middle of the ceiling and extending the length of the van, as required, to provide a minimum lighting intensity of 25 foot-candles at a level of 30 inches above the floor over the entire body interior. There shall be a clear headroom of 84 inches between the floor and the light fixtures. The light fixtures shall operate from the 120 volt ac, 60 Hz electrical system and shall be suitable for use in mobile service. Lamps shall be protected by wire mesh guards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.5.13.1.5 Switches. Light control switches shall be furnished for each light fixture. Control switches shall also be provided for the power plant heaters, battery charger, and electric cab heater(s), when furnished. Switches shall be located below the main power panel.

* 3.5.14 Electrical system - 120 volts ac. When specified (see 6.2), a 120-volt ac, single-phase electrical system shall be furnished in lieu of the 120/208-volt ac, 3-phase system specified in 3.5.13. The van body interior electrical system shall be rated for 60-ampere, 120-volt ac, single-phase, 60 Hz power. The electrical system shall include an exterior body-wall mounted connector for receiving external power, a panel with a main circuit breaker, not less than six branch circuit breakers, overhead interior lights, switches, and wall receptacles. The electrical system shall also include branch circuit breakers for the power plant heaters, battery charger and electric cab heater(s), when these items are required to be furnished.

* 3.5.14.1 External power receptacle. A connector meeting NEMA standards or that is Underwriter Laboratories listed and that is rated for 60-ampere, 120-volt ac, single-phase, 60 Hz power shall be furnished. The connector shall be a 3-wire, grounded neutral, outdoor male type and shall be mounted on the outside of the body wall, not more than 6 feet from the ground, near the curbside. A matching cable connecter, with self locking device, shall be furnished.

3.5.14.2 Wiring and circuit breakers. All wiring methods and materials shall conform to the National Electrical Code. All interior wiring shall be enclosed in aluminum conduit; and cable and conduit required for electrical devices inside the body shall be installed inside the side and roof panels to permit the use of lamps and outlets of the flush mounted type. All wiring shall be fastened or clipped at points of bending and supported and protected against chafing and damage. The wiring shall be routed from the exterior receptacle to inside the van body and shall run to a 60-ampere, single pole, thermal-magnetic main circuit breaker for main power panel overcurrent protection. The main circuit breaker shall be installed in a main power panel. The main power panel shall be rated at 60 amperes, 120 volts ac, 1-phase. The main power panel shall be located at the rear end of the curbside wall just below the ceiling, as convenient, and not less than 6 inches from the rear doors. The main power panel shall have a hinged cover which can be locked in, or an equivalent locking-in-place feature. All circuits shall be connected through the main power panel circuit breaker with individual circuit breakers to protect individual circuits. In addition to the main circuit breaker, the main power panel shall include branch 20 ampere circuit breakers for the lighting, wall

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

receptacles and, when furnished, for the power plant heaters, battery charger and auxiliary electric cab heater(s). Separate ground and neutral wiring shall be maintained throughout. Circuits shall be identified and a wiring diagram furnished in each vehicle.

3.5.14.3 Wall receptacles. Four 120-volt minimum, 20-ampere rated, 3-wire, grounded duplex outlets of the flush-mounted type shall be connected to the ac system at the main power panel. Each outlet shall be on a separate circuit and shall be protected by a separate 20-ampere circuit breaker. Two outlets shall be placed on each side wall at a height approximately 48 inches from the floor. The two outlets on each side shall be equally spaced approximately 42 inches from the vertical centerline of the side wall. Each outlet and its respective circuit breaker shall be appropriately labeled for identification.

3.5.14.4 Interior lighting. Interior lighting shall be furnished and shall comply with 3.5.13.1.4.

3.5.14.5 Switches. Not less than two light control switches shall be furnished for the interior lights and located inside the body below the main power panel. Control switches shall also be provided for the battery charger, power plant heaters, and electric cab heater(s) when furnished and shall be located below the main power panel.

3.6 Servicing and adjusting. Prior to acceptance of the vehicle by the Government inspector, the contractor shall service and adjust each vehicle for operational use including at least the following: alinement of lights; adjustment of engine and brake systems; filling and charging of batteries; alinement of front wheels; inflation of all tires; complete lubrication of chassis, engine, and running gear, with grades of lubricants recommended for the ambient air temperature at the delivery point; servicing of cooling system with a solution of ethylene glycol type antifreeze and water in equal parts by volume and servicing of windshield washer reservoir with water and appropriate additives.

3.7 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished. Welded, bolted, and riveted construction utilized shall be in accordance with the highest standards of the industry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods, and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

4.3 First production vehicle inspection. The first production vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformance to the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

* 4.3.1 Vehicle weight. The first production vehicle shall be weighed to determine curb weight and distribution of curb weight on front and rear axles. The imposed loading on front and rear axles shall be computed by the contractor and verified by the Government, using the curb weight, the operator weight at 175 pounds, 525 pounds in the rear seat and an evenly distributed payload (see 3.2.5) to provide the specified GVW. Calculated imposed loads on front and rear axles shall be compared to the suspension, axle and tire ratings to assure they are of adequate capacity for the intended loading.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

* 4.3.2 Road test. The first production vehicle shall be examined and road tested by the contractor to assure that the vehicle shall operate in accordance with contractual requirements. The vehicle, loaded with payload and all equipment specified herein, shall be driven at speeds up to at least 50 mph, for a minimum distance of 50 miles. The distance traveled shall consist of a highway, rough dirt roads, partly surfaced gravel roads, puddles, and sharp turns. For each 10 miles of travel at least one sudden stop shall be accomplished. Upon completion of the road test all equipment shall be thoroughly examined. The equipment shall show no evidence of damage; all doors shall be opened and shut; there shall be no evidence of mud or dust inside, and there shall be no evidence of racking of the body.

* 4.3.2.1 Brake performance. The first production vehicle shall be tested for performance of the service brakes (see 3.3.2) in accordance with the stopping distance requirements of Federal Motor Carrier Safety Regulation 393.52. Brake holding ability on the maximum grade in the vicinity of the inspection point (contractor's plant) shall be demonstrated.

* 4.3.2.2 Hydraulic tailgate test. When a hydraulic tailgate is specified (see 3.1.1.10) it shall be tested with full rated payload for at least 5 complete continuous cycles from fully raised to fully lowered position.

* 4.3.2.3 Electrical test. All electrical circuits shall be functionally tested.

* 4.3.3 Radio frequency suppression verification. The vehicle manufacturer shall indicate on the military questionnaire (commercial vehicle engineering data), if the vehicle will be suppressed to limit electromagnetic radiation in accordance with SAE J551.

4.3.4 Wood treatment certification. Manufacturer's records, acceptable to the Government representative, shall be furnished to verify that all wood requiring treatment in accordance with MIL-STD-1223 has been treated.

4.3.5 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and shall be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

4.3.6 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under contract until corrective action has been taken.

4.4 Inspection of production vehicles. The contractor's inspection system shall, as a minimum, assure that the vehicle conforms to the physical and dimensional requirements and is capable of meeting performance requirements contained herein. For each vehicle under contract, the contractor shall make available to the Government, at the point of final acceptance, records acceptable to the Government indicating that the servicing and adjusting required by 3.6 have been accomplished.

5. PACKAGING

5.1 Vehicle processing. The vehicle shall be processed for shipment, from manufacturer's plant to initial receiving activity, in accordance with the manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use. The vehicles covered by this specification are intended for general nontactical use by the Government in transporting personnel or cargo and for use in performance of the maintenance tasks indicated.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Identification of appropriate service for painting and marking (see 3.1.1.1).
(c) Concealed marking, if required (see 3.1.1.1).
(d) Rustproofing, if required (see 3.1.1.2).
(e) Tropical rustproofing, if required (see 3.1.1.2).
(f) Heavy duty cooling system, if required (see 3.1.1.4).
* (g) Rear towing devices, if required (see 3.1.1.7).
(h) Trailer towing package, if required (see 3.1.1.9).
(i) Hydraulic tailgate, if required (see 3.1.1.10).
(j) Fold-under type hydraulic tailgate, if required (see 3.1.1.10.2).
* (k) Silicone brake fluid, if required (see 3.1.1.12).
(l) Gasoline engine, if required (see 3.4.1.2).
(m) Silicone rubber radiator and heater hoses, if required (see 3.4.1.7).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

(n) Power plant heaters and fuel warmer, if required (see 3.4.1.8).
* (o) If a battery heater is not required with power plant heaters (see 3.4.1.8).
(p) Trailer lighting cable, if required (see 3.4.2.5).
(q) An auxiliary 24-volt system with trailer receptacle, if required (see 3.4.2.7).
(r) A battery charger, if required (see 3.4.2.8).
* (s) A spark arrester, if required (see 3.4.4.1).
(t) Automatic or semiautomatic transmission, if required (see 3.4.5.2).
(u) Auxiliary rear springs, if required (see 3.4.8).
(v) Two-speed axle, if required (see 3.4.9.1).
(w) Traction control, if required (see 3.4.9.2).
(x) Wide base front and rear tires and wheels, if required (see 3.4.10).
(y) Disc type wheels, if required (see 3.4.10).
(z) Bias ply tires, if required (see 3.4.10.1).
(aa) Spare tire carrier, if required (see 3.4.10.3).
(ab) Spare wheel or rim, if required (see 3.4.10.4).
(ac) Spare tire assembly, if required (see 3.4.10.5).
(ad) Air brakes, if required (see 3.4.11.2).
* (ae) An air dryer, if required (see 3.4.11.2(k)).
(af) Brake controls for use from a towing vehicle, if required (see 3.4.11.4.1).
(ag) Individual driver and passenger seats, in lieu of bench seats, if required (see 3.4.12).
(ah) Tools, if required (see 3.4.16.1).
(ai) An auxiliary hot water heater with blower, if required (see 3.4.17.1).
(aj) Auxiliary electric heating, if required (see 3.4.17.2).
(ak) Air operated horn, if required (see 3.4.21).
(al) Engine hour meter, if required (see 3.4.22).
(am) Back up alarm, if required (see 3.4.23).
(an) Body wind deflector fairing, if required (see 3.5.1.1).
(ao) Side door, if required (see 3.5.10).
(ap) A 120-volt ac single-phase system in lieu of a 120/208-volt three-phase ac system, if required (see 3.5.13).

6.3 Performance prediction. Completed copies of SAE Truck Ability Prediction Procedure form and computation for low speed requirement for each vehicle model furnished under contract should be submitted as specified in the contract. The SAE Work Sheet Item 1 should include vehicle model number, wheelbase, engine model number, and vehicle type. Unless other conditions are cited in the contract, computations should be made for normal atmospheric pressure, normal ambient air temperature,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

and still, dry, air. The factors to be used in predicting truck ability (see 3.3.1.1) are established as follows for the corresponding SAE Truck Ability Prediction Procedure Tables:

Table 1	- Tire Factor. This factor must relate to the size of tires furnished by the contractor in accordance with this specification.
Table 2	- Altitude Factor. 1.00
Table 3	- Rolling Factor. 1.613
Table 4	- Area Factor. 0.173
Table 5	- Velocity Factor. 250.0
Table 6	- Altitude Factor. 1.00
Table 7	- Chassis Friction Horsepower. Use applicable power unit GVW (to nearest, higher, 1,000 pounds) and the engine rpm (to nearest 100 revolutions) which is required for 50 mph geared speed. For GVW and engine speed beyond the range of this table, factors shall be extrapolated.
Table 8	- Grade Factor. 0.75
Table 8A	- Correction Factor. Not required.
Table 9	- Road Factor. 0.0.

* 6.4 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these quotations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content regardless of the marginal notations and relationship to the last previous issue.

Custodians:
Army - AT
Air Force - 99
Review Activities:
Air Force - 84

Preparing Activity:
Army - AT

Project No. 2320-0276

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.