INCH - POUND

MIL-B-29605(AS)
15 December 1994

MILITARY SPECIFICATION

BODY ARMOR, SOFT, SMALL ARMS PROTECTIVE, PRU-60/P22P-15

This specification is approved for use by the Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the general requirements and inspections for soft body armor used by helicopter aircrewmen for protection against small arms projectiles.

1.2 Classification. The soft body armor assemblies furnished under this specification will be one of the following sizes (see 6.2d):

Small
Medium
Large
X-Large

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2e).

Beneficial comments (recommendations, additions, deletions, and any pertinent data which may be of use in improving this document should be addressed to: Commander, Systems Standardization, Code 4.1.11B120-3, Naval Air Warfare Center Aircraft Division, Highway 547, Lakehurst, NJ 08733-5100, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC-N/A FSC 8470

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

UU-P-268	-	Paper, Kraft, Wrapping.
PPP-B-636	-	Boxes, Shipping, Fiberboard.

MILITARY

MIL-W-4088	-	Webbing, Textile, Woven Nylon
MIL-W-5664	-	Webbing, Textile, Elastic (Validated)
MIL-F-21840	-	Fastener Tapes, Hook and Pile, Synthetic
MIL-C-43734	-	Cloth, Duck, Textured Nylon
MIL-C-43842	-	Cloth, Oxford, Aramid
MIL-C-44050	-	Cloth, Ballistic, Aramid

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MS27980	-	Fastener, Snap, Style 2 (Regular Wire Spring Clamp Type)

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from DODSSP, Standardization Document Order Desk, 700 Robbins Avenue, Bldg. 4D, Philadelphia, PA 1911-5094.)

2.1.2 Government drawings. The following Government drawings form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

3241AS201	-	Soft Body Armor System Assembly, PRU-60/P22P-15
3241AS202	-	Soft Ballistic Insert Assembly, PRU-60/P22P-15
3241AS203	-	Casing Assemblies, PRU-60/P22P-15
3241AS204	-	H-Harness Assembly, PRU-60/P22P-15
3241AS205	-	Label, Identification, PRU-60/P22P-15
3241AS280	-	Ballistic Patterns, Small, PRU-60/P22P-15
3241AS281	-	Ballistic Patterns, Medium, PRU-60/P22P-15
3241AS282	-	Ballistic Patterns, Large, PRU-60/P22P-15

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

DRAWINGS (cont'd)

3241AS283	-	Ballistic Patterns, Extra Large, PRU-60/P22P-15
3241AS284	-	Cover Patterns, Front, Back, Side, Small, PRU-60/P22P-15
3241AS285	-	Cover Patterns, Front, Back, Side, Medium, PRU-60/P22P-15
3241AS286	-	Cover Patterns, Front, Back, Side, Large, PRU-60/P22P-15
3241AS287	-	Cover Patterns, Front, Back, Side, Extra Large, PRU-60/P22P-15
3241AS288	-	Casing Pattern, Small, PRU-60/P22P-15
3241AS289	-	Casing Pattern, Medium, PRU-60/P22P-15
3241AS290	-	Casing Pattern, Large, PRU-60/P22P-15
3241AS291	-	Casing Pattern, Extra Large, PRU-60/P22P-15

(Unless otherwise specified, copies of drawings required by contractors in connection with specific acquisition functions should be obtained from the contracting activity, or as directed by the Contracting Officer.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified issues of documents not listed in the DODISS are the issues of documents cited in the solicitation (see 6.2e).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D3951 - Packaging, Commercial

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL INSTITUTE OF JUSTICE

NIJ Standard 0101.03 - Ballistic Resistance of Police Body Armor

(Application for copies should be addressed to Chief, Law Enforcement Standards Laboratory, National Bureau of Standards, Gaithersburg, MD 20899.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Qualification. The soft body armor furnished under this specification shall be products which are authorized by the qualifying activity for listing on the applicable qualified products list at the time of award of contract (see 4.3 and 6.4). Qualification of any one size assembly, under this specification, will automatically qualify a supplier for all sizes specified herein (see 1.2).

3.2 First article. When specified (see 6.2f), a sample shall be subjected to the first article inspection (see 6.5) in accordance with 4.4.

3.3 Materials and components. The materials and components shall conform to applicable specifications, standards, and drawings and shall be as specified herein. Equivalent materials and parts require approval by the Naval Air Warfare Center Aircraft Division Warminster (Code 603), Warminster, Pennsylvania 18974-5000. Requests for use of equivalent items shall be submitted to the Contracting Officer.

3.3.1 Ballistic inserts. The ballistic inserts shall be fabricated from ballistic aramid cloth conforming to MIL-C-44050, Type I and Type II (see 3.4.1.2).

3.3.2 Ballistic insert covers. The ballistic insert covers shall be fabricated from texture nylon duck cloth conforming to MIL-C-43734, Class 3, Color 106 Olive Green (See 3.4.1.2).

3.3.3 Casing Assemblies. The casing assemblies shall be fabricated from oxford aramid cloth conforming to MIL-C-43842, Class I, Color 106 Olive Green (see 3.4.1.2).

3.3.4 Webbings.

3.3.4.1 Back casing assembly.. The side straps for the back casing assembly shall be fabricated from elastic webbing conforming to MIL-W-5664, Type I, Class 1, 2 inch wide. The shoulder straps for the back casing assembly shall be fabricated from nylon webbing conforming to MIL-W-4088, Type XII, Class 2, 1 23/32 inch wide.

3.3.4.2 H-Harness assembly. The side straps for the H-Harness assembly shall be fabricated from nylon webbing conforming to MIL-W-4088, Type VIII, Class I, 1 23/32 inch wide. The shoulder straps for the H-Harness assembly shall be fabricated from nylon webbing conforming to MIL-W-4088, Type VII, Class I, 1 23/32 inch wide.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

3.3.5 Hook and pile tapes.

3.3.5.1 Hook tape. The hook tape shall be nylon in accordance with MIL-F-21840, Type II, Class I, 1 and 2 inch wide as specified in 3.4.

3.3.5.2 Pile tape. The pile tape shall be nylon in accordance with MIL-F-21840, Type II, Class I, 1, 2 and 4 inch wide as specified in 3.4.

3.3.6 Snap fasteners.

3.3.6.1 Front and back casing assemblies. The front and back casing assemblies eyelet and stud snap fasteners shall be in accordance with MS27980-8B and MS27980-7B, respectively.

3.3.6.2 Side casing assembly. The side casing assembly socket and button snap fasteners shall be in accordance with MS27980-6B and MS27980-1B, respectively.

3.4 Design and construction. Unless otherwise specified, the design and construction of the soft body armor assembly shall conform to the drawings listed in paragraph 2.1.2 of this specification.

3.4.1 Cut edges. The cut edges of the nylon webbings and tapes, except for the hook and pile fastener tapes, shall be seared, prior to the fabrication of the soft body armor, to prevent fraying. No sharp edges shall be formed. The cut edges of the nylon duck cloth, except those that are completely covered by nylon binding tape, hook and pile fastener tapes, or are completely encased by the seam construction, shall be overedged stitched (serged).

3.4.1.1 Patterns. Standard patterns will be furnished by the Government to the contractor for use in cutting working patterns (see 6.6). The working patterns shall be identical to the Government patterns. Neither the Government patterns nor the working patterns shall be altered in any way. Seams shall be in accordance with seam allowances specified in 3.4.

3.4.1.2 Component parts. The component parts shall be cut from the material specified, in accordance with the pattern parts in Table I.

3.4.2 Seams and stitching. All the seams used in the fabrication of the soft body armor shall conform to the applicable drawings. Except for the serging (overedge), the stitching shall be accomplished with Stitch Type 301. The overedge stitching shall be accomplished with Stitch Type 502, 503, 504, or 505. The width of the overedge stitching shall be approximately 1/4 inch. The thread and stitching used in fabrication shall conform to applicable drawing requirements. All the seam edges shall be properly forced out and shall not contain any folds. No seams

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

shall be twisted, puckered, or pleated and no part of the soft body armor assemblies shall be caught in an unrelated operation or seam. All the thread ends shall be trimmed to a length of 1/4 to 3/8 inch and except for the webbing, cord, and tape, excluding the binding tape, no raw or cut edge shall be visible on the exterior of the soft body armor assemblies. The cut edges of the binding tape shall be turned under.

3.4.2.1 Sewing. Each row of stitching shall be straight and parallel to the seam edge. The straightness of the stitching, in any row, shall be maintained within a tolerance of plus or minus 1/32 inch. The ends of the stitching that are not caught in other seams or stitching shall be securely backstitched, by overlapping on themselves, for at least 1/2 inch. Thread breaks, skips, and run-offs shall be over-stitched not less than one inch. The thread tension shall be maintained so that there shall not be any loose or tight stitching and the lock shall be embedded in the materials sewn together.

3.5 Identification labels. Unless otherwise specified, identification labels shall conform to the requirements of Dwg 3214AS205.

3.5.1 Serial numbers. The soft body armor shall be identified by individual serial numbers which shall be assigned by the manufacturer. Serialization shall be by a block of consecutive numbers to cover the entire acquisition document quantity.

3.6 Markings. Unless otherwise specified, the markings shall be legible and durable upper case black letters and Arabic numerals and shall be thoroughly dry prior to packaging. The markings shall be lusterless and the letters and numerals shall be sharply defined. The markings shall be accomplished by using such methods and materials as shall be resistant to erasure or fading under the condition of usage. The marking medium shall not contain any materials which are deleterious to the substance being marked.

3.7 Color. Unless otherwise specified, the color of the soft body armor and components shall conform to applicable drawing requirements.

3.8 Ballistic protection. When tested as specified in 4.7.1, the soft body armor shall conform to the ballistic protection requirements for Type III-A Armor specified in Section 4, Paragraph 4.5 of National Institute of Justice Standard, NIJ0101.03.

3.9 Visual examination. When visually examined as specified in 4.7.2, the soft body armor shall conform to the requirements of this specification and applicable drawings. Table VI, Classification of defects for visual examination, shall be used to classify the defects.

3.10 Dimensional check. When dimensionally checked as specified in 4.7.3, the dimensions of the assembled soft body

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

armor, the dimensions and locations of components, the widths of seams and hems, and the stitching shall conform to applicable drawing requirements. Table VII, List of defects for dimensions of the soft body armor assemblies, shall be used to enumerate the defects.

3.11 Preparation for delivery. When inspected as specified in 4.7.4, the fully prepared shipping containers, containing soft body armor, shall conform to the requirements of this specification. Table VIII, List of defects for packaging, shall be used to enumerate the defects found.

3.12 Workmanship. After completion of the final assembly, the soft body armor shall be thoroughly cleaned and all loose thread, lint, and foreign matter shall be removed. The snap fasteners shall be clinched without distortion, damage, splitting, or cutting of the cloth, webbing, or tape, as applicable. The metal components shall not be misaligned nor contain any sharp edge, crack, dent, nick, burr, or sliver. The soft body armor assemblies shall not contain any non-specified hole, abraded area, tear, cut, mend, needle chew, spot or stain. Drill holes shall be not greater than 1/16 inch in diameter and shall be covered by the component assemblies. The soft body armor assemblies shall conform to the quality and grade of product established by this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements; however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. The examination and testing of the soft body armor furnished under this specification shall be classified as follows:

a. Qualification inspection (see 4.3).
b. First article inspection (see 4.4).
c. Quality conformance inspection (see 4.5).
d. Quality conformance verification inspection (see 4.6).

4.3 Qualification inspection. Qualification inspection shall be as specified in Table II.

4.3.1 Qualification samples. Qualification samples shall consist of three soft body armors (size optional to the manufacturer). Samples shall be forwarded to the test facility set forth in the letter of authorization to submit samples (see 6.3). The samples shall be plainly identified by securely attached durable tags marked with the following information:

> Samples submitted by (Name) on (Date) for qualification inspection in accordance with the requirements of MIL-B-29605(AS) and qualification test number ( ) under authorization (reference authorizing letter).

4.3.2 Retention of qualification. The retention of qualification shall consist of periodic verification to determine compliance of the qualified soft body armor with the requirements of this specification. The time and method of periodic verification shall be specified by the activity responsible for the Qualified Products List and shall be included in the Notice of Qualification letter.

4.4 First article inspection. The first article inspection shall be as specified in Table III.

4.4.1 First article samples. Unless otherwise specified, as soon as practicable after award of the contract or order, the contractor shall submit three soft body armors of each of the size(s) specified in the acquisition document. The samples shall be representative of the construction,, workmanship, components and materials to be used during production. When a contractor is in continuous production of soft body armors from contract to contract, submission of further first article inspection samples, on the new contract, may be waived at the discretion of the procuring activity (see 6.2f). Approval of the first article inspection samples or the waiving of the first article inspection does not preclude the requirements for performing the quality conformance inspection. The first article inspection samples shall be furnished to the Government as directed by the contracting officer (see 6.2g).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

4.4.2 First article test report. Upon completion of the first article inspection program (4.4), the government activity responsible for conducting the program (see 6.2g) shall report the results of the tests, with appropriate recommendations, to the contracting officer.

4.4.3 First article sample disposition. Upon successful completion of the first article inspection program, sample disposition will be as follows:

a. One sample (each size) will be returned to the manufacturer for use in monitoring production, and
b. Two samples (each size) will be destroyed during the first article inspection program and shall not be considered as part of the quantity to be delivered under the contract.

4.5 Quality conformance inspection. The sampling and inspection levels shall conform to MIL-STD-105 and Table IV. The quality conformance inspection shall be as specified in Table IV.

4.5.1 Sampling.

4.5.1.1 Inspection lot.

4.5.1.1.1 Soft body armor. An inspection lot size shall be expressed in units of one soft body armor made essentially under the same conditions and from the same materials and components. The sample unit shall be one assembly.

4.5.1.1.2 Packaging. An inspection lot size shall be expressed in units of one fully prepared shipping container, containing soft body armors, fully prepared for delivery, from essentially the same materials and components. The sample unit shall be one shipping container, containing assemblies, fully prepared for delivery with the exception that it need not be sealed.

4.5.1.2 Sampling for examinations and tests of the soft body armor assemblies. The sample size, acceptance criteria, examinations, and tests required for the soft body armor shall be as specified in Table IV.

4.6 Quality conformance verification.

4.6.1 Quality conformance verification inspection. The quality conformance verification inspection shall be as specified in Table V.

4.6.2 Quality conformance verification samples. Upon completion of the tests and examinations specified in Table IV, a random sample shall be selected from each lot in accordance with MIL-STD-105, Inspection Level S-3. The tests and examinations required for the soft body armor shall be as specified in Table V. The sample size and acceptance criteria shall be in accordance with

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

MIL-STD-105 for single sampling plans for normal inspections. Each assembly, selected as a sample unit, shall be identified by its assigned serial number (see 3.5.1) and shall be forwarded to the inspection facility specified in the acquisition document (see 6.2). Additionally, the serial numbers of the units within the lot, represented by the sample units, shall be furnished to the inspection facility.

4.6.3 Quality conformance verification approval. Upon completion of the quality conformance verification inspection, the Government activity responsible for conducting the inspection program (see 6.2) shall report the results of tests, with recommendations, to the contracting officer of the procuring activity specified in the acquisition document. Final acceptance of the lot from which the samples were selected shall be based upon completion of the inspection program by the Government Quality Assurance Representative/Specialist.

4.7 Inspection methods.

4.7.1 Ballistic protection. The soft body armors shall be tested for ballistic protection in accordance with the test methods prescribed for Type III-A Armor in Section 5 of National Institute of Justice Standard 0101.03. When tested in this manner, the assemblies shall conform to the requirements of paragraph 3.8.

4.7.2 Visual examination. Each of the soft body armors, selected as a sample from the lot, shall be visually examined to determine conformance to the requirements specified in 3.9.

4.7.3 Dimensional check. Each of the soft body armors, selected as a sample from the lot, shall be dimensionally checked to determine conformance to the requirements specified in 3.10. The armors to be measured shall be laid flat, without tension, on a smooth, flat surface so that any creases or wrinkles shall not affect the measurement.

4.7.4 Packaging. Each of the fully prepared shipping containers, containing soft body armors, selected as a sample unit from the lot, shall be visually examined to determine that the packaging, packing, and marking conform to the requirements specified in section 5 and 3.11.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2h).

5.1.1 Level A. Each complete soft body armor, with back panel superimposed over the front panel so that the identification label is visible and with the side panels and H-harness underneath, shall be inserted flat in a close-fitting clear polyethylene film bag having a thickness of 0.0015 inch (+/- 20 percent tolerance). The bag shall be formed with heat sealed seams that are straight,

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

continuous, and parallel to each other and the formed edges of the bag. The final closure of the bag shall be heat sealed with the heat seal made as close as possible to the open end. The bag may be fabricated from polyethylene film tubing or sheeting. A 1/4-inch diameter hole shall be made at one corner of the polyethylene bag to allow excess air to escape. Alternatively, the final closure of the polyethylene bag may be accomplished by means of a tuck or reverse flap.

5.1.2 Commercial. Each complete soft body armor shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2h).

5.2.1 Level A. Five complete soft body armors, of one size only, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. The body armor shall be packed flat, each alternatively reversed top to bottom, within a shipping container. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636, except the inspection shall be in accordance with 4.7.4. Toward the end of the contract or when there are less than the required amount per container of the same size, mixed sizes may be packed within the same container.

5.2.2 Level B. Five complete soft body armors, of one size only, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. The body armor shall be packed flat, each alternately reversed top to bottom, within a shipping container. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636 except the inspection shall be in accordance with 4.7.4. Toward the end of the contract or when there are less than the required amount per container of the same size, mixed sizes may be packed within the same container.

5.2.3 Commercial. The soft body armor, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking. In addition to any special marking required by the contract or purchase order (see 6.2i) exterior shipping

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

containers shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

5.3.1 Polyethylene bag. Prior to heat sealing, a white paper label with legible and durable black letters and numerals shall be placed inside each polyethylene bag. The label shall be placed so that the information in the label shall be capable of being read through the bag. The paper shall contain the same information as specified in 5.3.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory).

6.1 Intended use. The soft body armor covered by this specification is intended to be worn by helicopter aircrewmen to provide protection against small arms projectiles.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification, including any amendments

b. Applicable drawings, including revisions.

c. Government part number and National Stock Number.

d. Quantity and size desired.

e. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1).

f. Whether First Article Inspection is waived (see 4.4.1).

g. Name and address of the First Article Inspection facility (see 4.4.1); and the name and address of the Government activity responsible for conducting the First Article Inspection program (see 4.4.2).

h. Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

i. Whether any special markings are required (see 5.3).

j. Items of data required (see 6.3).

6.3 Consideration of data requirements. The following data requires should be considered when this specification is applied on a contract. The applicable Data Item Descriptions (DID's) should be reviewed in conjunction with the specific acquisition to ensure

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

that only essential data are requested/provided and that the DID's are tailored to reflect the requirements of the specific acquisition. To ensure correct contractual application of the data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DOD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

Paragraph	DID Number	DID Title	Tailoring
4.4.2	DI-NDTI-80809	Test reports	Use contractor format

The above DID's were those cleared as of the date of this specification. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DID's are cited on the DD Form 1423.

6.4 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in the applicable Qualified Products List whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or purchase orders for the products covered by this specification. The activity responsible for the Qualified Products List is the Commander, Naval Air Systems Command, Department of the Navy, Washington, DC 20361; however, authorization for qualification of products may be obtained from the Commanding Officer, Naval Air Warfare Center Aircraft Division Warminster, (Code 6031), Warminster, PA 18974-5000.

6.5 First article. When first article inspection (see 3.2) is required, the contracting officer should provide specific guidance to offerors whether the item(s) should be a first article sample, a first production item, or a standard production item from the contractor's current inventory, and the number of items to be tested as specified in 4.4.1. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

6.6 Patterns and drawings. For access to patterns and drawings, address the acquiring activity issuing the invitation for bids.

6.7 Subject term (key word) listing.

Aircrewman, helicopter
AISAP
Ballistic protection
Garment, protective
Standard, NIJ-0101.03

Preparing Activity
Navy - AS
(Project No. 8470-N158)

Source: https://assist.dla.mil - Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

TABLE I. Component parts.

Material	Nomenclature of Component Parts	Cut Parts
Cloth, ballistic, aramid (MIL-C-44050, Type I)	Ballistic insert, front Ballistic insert, side Ballistic insert back	14 28 14
Cloth, ballistic aramid (MIL-C-44050, Type II)	Ballistic insert, front Ballistic insert, side Ballistic insert, back	8 16 8
Cloth, duck, textured nylon (MIL-C-43734, Class 3)	Ballistic insert cover, front, body side Ballistic insert cover, front, outer side Ballistic insert cover, back, body side Ballistic insert cover, back, outer side Ballistic insert cover, side	1 1 1 1 2
Cloth, oxford aramid (MIL-C-43642, Class 1)	Casing, front outside casing, front, body side casing, back, outside casing, back, body side casing, side casing, patch	1 1 1 1 2 4

TABLE II. Qualification inspection (see 4.3).

	Paragraph		Sample
Inspection	Requirement	Test Method	Number
Ballistic protection	3.8 & applicable drawings	4.7.1	1
Visual examination	3.9, applicable drawings and Table VI	4.7.2	Every Assembly
Dimensional check	3.10, applicable drawings & Table VII	4.7.3	Every Assembly
Packaging	3.11 & applicable drawings	4.7.4	Every Assembly

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

TABLE III. First article inspection (see 4.4).

	Paragraph	
Inspection	Requirement	Test Method
Ballistic protection	3.8 & applicable drawings	4.7.1
Visual examination	3.9, applicable drawings and Table VI	4.7.2
Dimensional check	3.10, applicable drawings & Table VII	4.7.3
Packaging	3.11 & applicable drawings	4.7.4

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

TABLE IV. Quality conformance inspection (see 4.5).

INSPECTION 1/	PARAGRAPH		SAMPLE SIZE 2/	ACCEPTANCE CRITERIA 2/
	REQUIREMENT	METHOD		
Visual examination	3.9, applicable drawings & Table VI	4.7.2	Every assembly for critical defects. Inspection Level II for minor defects.	Reject all units with any critical defects. An acceptable quality level off 15.0 defects per 100 units for minor defects.
Dimensional check	3.10, applicable drawings & Table VII	4.7.3	Inspection Level S-3	An acceptable quality level of 4.0 defects per 100 units
Preparation for delivery	3.11, Section 5 & Table VIII	4.7.4	Inspection Level S-2	An acceptable quality level of 2.5 defects per 100 units

1/ The results of the examinations and tests shall be identifiable by the assigned serial numbers (see 3.5.1).

2/ The sample size and acceptance criteria shall be in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

TABLE V. Quality conformance verification inspection (see 4.6)

	Paragraph		Sample
Inspection	Requirement	Test Method	Number
Visual examination	3.9, applicable drawings & Table VI	4.7.2	Every Assembly
Dimensional check	3.10, applicable drawings & Table VII	4.7.3	Every Assembly

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

TABLE VI. Classification of defects for the visual examination of the soft body armor assemblies

Defect	Classification	
	Critical	Minor
GENERAL		
a. Any non-specified hole, except drill holes, scissors, or knife cut, tear, mend, burn, or weakening defect such as smash, multiple float, loose slub, needle chew or abraded area	X	
b. Color of any component not as specified	1/	
c. Opposite sides of each main panel do not approximate each other in shade or any shade bar, spot, or stain		X
d. Any thread end not trimmed to a length of 1/4 to 3/8 inch or loose thread ends not removed		X
e. Any cut edge of the webbings, or tapes, except for the hook and pile fastener tapes, not seared or any sharp edge formed by the searing	1/	
f. Any cut edge of the nylon duck not overedged stitched (serged)	1/	
g. Less than 25 percent of the hooks or pile flattened or missing from any fastener tape closure area		X
h. 25 percent or more of the hooks or pile flattened or missing from any fastener tape closure area	X	
i. Any hook or pile tape misplaced, not serving the intended purpose	X	
j. Any drill hole more than 1/16 inch in diameter or not covered by any attached component		X
METALLIC COMPONENTS		
a. Any surface rough, misaligned, or contains any crack, nick, burr, sharp edge, dent, or sliver	X	
b. Any surface unclean or contains embedded foreign matter		X
c. Any loose, detached, or otherwise not securely retained.	X	
d. Any malformed, corroded, fractured, broken, chipped, bent, or distorted	X	
e. Any improperly finished or finish missing		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

TABLE VI. Classification of defects for the visual examination of the soft body armor assemblies - Continued

Defect	Classification	
	Critical	Minor
METALLIC COMPONENTS (Continued)		
f. Any snap fastener misplaced or improperly clinched resulting in cutting of the cloth, tape, or webbing, as applicable	X	
g. Any snap fastener mismated 2/		X
COMPONENTS AND ASSEMBLY		
a. Any component not specified or any defect of a component or defect of assembly not herein classified	1/	
b. Any component, component part, or required operation omitted or any operation improperly performed not herein classified	1/	
SEAMS AND STITCHING		
a. Accuracy of Seaming:		
1. Any seam, hem, or attachment of any component twisted, puckered, pleated, or caught in an unrelated operation or stitching; any seam edge not properly forced out or contains any fold		X
2. Ends of stitching that are not caught in other seams or stitching:		
(a) Not securely backstitched	X	
(b) Secure but backstitched for a distance less than 1/2 inch		X
(c) Backstitching not overlapped on itself		X
3. Thread breaks:		
(a) Not securely overstitched	X	
(b) Secure but overstitched for a distance less than one inch		X
b. Gage of stitching 3/:		
1. Any stitching irregular, unevenly gaged, or various stitchings not uniform		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

TABLE VI. Classification of defects for the visual examination of the soft body armor assemblies - Continued

Defect	Classification	
	Critical	Minor
SEAMS AND STITCHING (Continued)		
c. Open seams 4/:		
1. Other than on any hem:		
(a) Up to an including 1/4 inch		X
(b) More than 1/4 inch but not more than one inch		X
(c) More than one inch	X	
2. On any hem:		
(a) 1/2 inch or less		X
(b) More than 1/2 inch		X
d. Raw edges 5/:		
1. More than 1/4 inch but not more than one inch		X
2. More than one inch		X
e. Seam and stitch type:		
1. Not specified seam or stitch	1/	
f. Stitch tension 6/:		
1. Loose tension resulting in a loose seam or tight tension resulting in breaking of the stitches, when normal pull is applied	X	
g. Stitches per inch 7/:		
1. Stitches more or less than specified:		
(a) One or 2		X
(b) Three		X
(c) More than 3	X	
h. Bartacks:		
1. Any loose or misplaced, not serving the intended purpose		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

TABLE VI. Classification of defects for the visual examination of the soft body armor assemblies - Continued

Defect	Classification	
	Critical	Minor
SEAMS AND STITCHING (Continued)		
MARKINGS		
a. Any missing, incomplete, incorrect, or illegible		X
b. Improperly located		X

1/ The defect shall be considered critical when it seriously affects the serviceability or appearance, otherwise it is to be classified as a minor defect.

2/ The snap fasteners shall be checked for proper function and attachment by snapping closed and unsnapping each snap fastener at least three times.

3/ The gage of stitching defect shall be scored only when the condition exists on the major portion of any row of stitching.

4/ A seam shall be classified as open when one or more stitches, joining a seam, are broken, or when two or more continuous skipped stitches or run-offs occur. On double-stitched seams, a seam shall be classified as open when either one or both sides of the seam contains any of the aforementioned defects for a single stitched seam.

5/ Any edge that should be turned under and is not, but is securely caught in the stitching, shall be classified as a raw edge. Any raw edge that is not securely caught in the stitching shall be classified as an open seam.

6/ Puckering is evidence of tight tension or gathering of the material. When puckering is evident, and not caused by the gathering of the material, the seam or hem, as applicable, shall be inspected by exerting normal pull in the direction of the stitching. Gathering of the material shall be classified as an accuracy of seaming defect.

7/ The stitches per inch defects shall be scored only when the condition exists on the major portion of any row of stitching.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

Table VII. List of defects for the dimensions of the soft body armor.

Examine	Defect
Measure the components, location of the components, width of the seams and hems, and length and width of the assembled vest	Any measurement deviating from the dimensions and tolerance as specified in the applicable drawings shall be enumerated as a dimensional defect.

TABLE VIII. List of defects for packaging.

Item	Defect
Exterior and interior marking	Missing, incomplete, incorrect, illegible; of improper size, location, sequence, or method of application; information on the label in the polyethylene bag not readable through the film or no label in the polyethylene bag
Materials	Any non-conforming component; any component or component part missing, damaged, or otherwise defective
Workmanship	Inadequate application of the components such as incomplete closure of the unit package, container flaps, loose strappings, etc.; bulging or distortion of the containers; exterior containers contain metal fastenings or stitches; polyethylene bag vent hole missing, open or non-continuous heat sealed seams; any portion of the vest caught in a heat sealed seam.
Exterior and interior weight or content	Gross or net weight exceeds the requirements; number per container is more or less than specified; not individually packaged within the polyethylene bag; manner of folding damages the vest

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:45Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.
   NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-B-29605(AS)	2. DOCUMENT DATE (YYMMDD) 941215

3. DOCUMENT TITLE
BODY ARMOR, SOFT, SMALL ARMS PROTECTIVE, PRU-60/P22P-15

4. NATURE OF CHANGE (*Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.*)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (*Last, First, Middle Initial*)	b. ORGANIZATION	
c. ADDRESS (*Include Zip Code*)	d. TELEPHONE (*Include Area Code*) (1) Commercial: (2) DSN: (*If Applicable*)	7. DATE SUBMITTED (*YYMMDD*)

8. PREPARING ACTIVITY

a. NAME COMMANDER NAVAL AIR WARFARE CENTER AIRCRAFT DIVISION	b. TELEPHONE NUMBER (*Include Area Code*) (1) Commercial (908) 323-7488 (2) DSN 624-7488
c. ADDRESS (*Include Zip Code*) CODE 4.1.11.2B120-3 HIGHWAY 547 LAKEHURST, NJ 08733-5100	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office, 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 DSN 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026l0-21T00:45Z
Check the source to verify that this is the current version before use.