INCH-POUND

MS27480G

12 July 2002

SUPERSEDING

MS27480F

16 January 1975

DETAIL SPECIFICATION SHEET

CONNECTORS, PLUG, ELECTRICAL, STRAIGHT, CRIMP TYPE, BAYONET COUPLING, SERIES II

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-DTL-38999.

Inactive for new design




FIGURE 1. Plug, classes E and T.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:41Z
Check the source to verify that this is the current version before use.




FIGURE 1. Plug, classes E and T – Continued.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:41Z
Check the source to verify that this is the current version before use.

Shell size	A dia +.005 -.001	B ±.020	C +.015 -.001	D dia +.001 -.005	E min dia	F dia +.000 -.006	K max REF	N dia +.010 -.006
8	.481	.096	.090	.357	.306	.630	.155	.576
10	.602			.485	.423	.752		.697
12	.761			.597	.537	.925		.871
14	.885			.722	.662	1.050		.995
16	1.010			.847	.787	1.172		1.120
18	1.136			.947	.876	1.304		1.245
20	1.260	.123	.137	1.072	1.001	1.435	.109	1.370
22	1.385			1.197	1.126	1.560		1.495
24	1.510			1.322	1.251	1.688		1.624

Shell size	Q max dia	R +.005 -.006 dia	S +.001 -.010 dia	W ±.015	For insert arrangement, see MS drawing	I max dia
8	.750	.316	.402	.547	27343, 27516	.290
10	.859	.436	.530		27344, 27517	.418
12	1.031	.549	.679		27345, 27518	.532
14	1.156	.675	.804		27346, 27519	.657
16	1.281	.799	.929		27347, 27520	.782
18	1.406	.893	1.029		27348, 27521	.871
20	1.531	1.018	1.154	.524	27349, 27522	.996
22	1.641	1.143	1.279		27350, 27523	1.121
24	1.766	1.268	1.404	.575	27351, 27524	1.246

FIGURE 1. Plug, classes E and T – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:41Z
Check the source to verify that this is the current version before use.



NOTES:

1. Insert front surface shall be flat within .005 T.I.R.
2. Diameter D with respect to diameter S shall be concentric at MMC.
3. Diameters A and N shall be concentric within .008 T.I.R.
4. Dimensions are in inches.
5. Normal keyway position. For other keyway positions see MIL-DTL-38999.
6. The point at which a gage pin, having the same basic diameter as the mating contact and a square face, touches socket contact spring.
7. Holes shall be provided for visual inspection of lock when mated with receptacle.

FIGURE 1. Plug, classes E and T - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:41Z
Check the source to verify that this is the current version before use.

Shell size	G insert projection class T only	HH dia +.000 -.005	KK DATUM dia	NN	PP dia ± .003
8	.120 ± .030	.387	.366	12	.344
10		.515	.487	16	.472
12		.628	.609	20	.586
14		.754	.731	24	.711
16		.879	.853	28	.836
18		.985	.974	32	.942
20		1.110	1.097	36	1.067
22		1.235	1.218	40	1.192
24	.0900 ± .050	1.360	1.340	44	1.317

Shell size	LE max overall length	LT max overall length	XE max dia	VV thread UNEF-2A MOD (plated)	
				Size	Major dia MOD
8	.953	.766	.594	7/16 – 28	.421 – .417
10			.719	9/16 – 24	.542 – .538
12			.844	11/16 – 24	.667 – .663
14			.969	13/16 – 20	.791 – .787
16			1.094	15/16 – 20	.916 – .912
18			1.219	1 1/16 – 18	1.034 – 1.030
20			1.344	1 3/16 – 18	1.158 – 1.154
22			1.469	1 5/16 – 18	1.283 – 1.279
24		.844	1.594	1 7/16 – 18	1.408 – 1.404

FIGURE 1. Plug, classes E and T - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:41Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.
Interface dimensions shall conform to MIL-DTL-38999.
Mating connectors: MIL-DTL-38999/10, MS27472, MS27474, MS27475, MS27476, MS27477, MS27478, MS27479, MS27480, MS27481, MS27497, MS27499, MS27504, MS27508 and MS27513.
Insert arrangements: See MIL-STD-1560.

Part or Identifying Number (PIN) example:



no letter is required for normal.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – AS
Air Force – 11
DLA – CC

Preparing activity:
DLA – CC

(Project 5935–4374)

Review activities:
Army – AR, MI
Navy – EC, MC, OS
Air Force – 19, 99
DLA – IS

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:41Z
Check the source to verify that this is the current version before use.