MILITARY SPECIFICATION

CONVERTER, 200 AMPERE, CLASS A, NONREGULATED, AIRCRAFT, FAN COOLED

This amendment forms a part of MS28126F(AS), dated 15 November 1991, and is approved for use by the Naval Air Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

Add the following new paragraphs to MS28126F(AS):

Page 4

3.7.1.2.1.1b Delete and add "Peak to peak ripple voltage shall not exceed 0.40 Volts from zero to 100 percent load current."

3.7.1.2.1.2c Delete "peak to mean output ripple voltage for either polarity shall not exceed 2.0 Volts" and add "peak to peak ripple voltage shall not exceed 0.53 Volts."

4.7.2.4 Output ripple. Delete "peak-to-mean ripple voltage shall be measured for both the positive and negative polarities" and add "peak to peak ripple voltage shall be measured."

4.7.2.15 Performance verification. First sentence delete "both positive and negative peak to mean ripple voltages" and add "peak to peak ripple voltage."

4.7.2.21 Vibration. First sentence add "except that only the sinusoidal cycling test is to be performed, and for vibration testing purposes the converter is considered Category C (helicopter installed) equipment."

Preparing activity:
Navy - AS
Project No. 6130-N360

FSC 6130

Distribution Statement A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:58Z
Check the source to verify that this is the current version before use.