INTERIM AMENDMENT

FEDERAL SPECIFICATION

FEED, DRY, FOR DOGS

This interim amendment was developed by the U.S. Army Natick Laboratories (GL), Natick, Massachusetts, 01760, based on currently available technical information. It is recommended that Federal Agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized Federal Agencies to use this interim amendment as a valid exception to Interim Federal Specification N-F-170e dated April 22, 1968.

Page 10, Paragraph 3.3.1. Delete and substitute:

"3.3.1 Acceptability and nutritional adequacy shall be determined by feeding exclusively once a day at a rate of not less than 35 calories per pound body weight to five dogs for 19 days. Weight shall be recorded for each dog daily. The dogs shall be working German Shepheards. Failure of one or more dogs to eat more than 60 percent, on a dry weight basis, of an individual feeding during the last 5 days of the period, loss by any dog of more than 3 percent of the original body weight at the end of the 19 day period, or loss by any dog of more than 10 percent of the original body weight at any time during the 19 day period shall be considered a nonacceptance.

3.3.1.1 Texture or hardness requirement (applicable to composition 1 only). The finished product shall comply with the water absorbtion test as specified in 4.3.4."

Table II, column five. Delete "Retained on U.S. #5/8" and substitute "Retained on U.S. #1/2".

Page 14, Paragraph 4.2.6.2, line 5. Delete "omposition" and substitute "composition".

Page 15, Table V. Delete minor defect 203.

Page 16, 4.2.6.3.2, lines 6 and 7. Delete last sentence and substitute: "weight of dog shall be recorded to the nearest ounce. One of more nonacceptances shall be considered a failure to meet the acceptability and nutritional adequecy requirements and shall be cause for rejection of the lot."

Page 17, Add new paragraph:

"4.2.6.4.1 Sampling procedures and acceptance criteria for testing of finished product. The finished product shall be tested as specified in 3.3.1.1. Procedures for testing shall be expressed in terms of the number of primary containers. The sample unit for testing shall be 2-ounces of product selected from a

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:12Z
Check the source to verify that this is the current version before use.

primary container. The sample size shall be the number of sample units indicated by inspection level S-1. Failure of one or more of the sample units to pass the water absorbtion test shall be cause for rejection of the lot."

Page 20, Add new paragraph:

"4.3.4 Water absorbtion test. The product shall be rehydrated in an excess of water at a temperature of 70°F. to 80°F. for 1 hour and drained. A defective sample unit is a unit which, after draining, more than 50 percent of the pieces in the sample unit will not break up or disintegrate when subjected to pressure (by hand) from a hard object, such as the flat side of a table knife blade or a table fork. Fully moisture laden (spongy) pieces shall be acceptable."

Paragraph 5.1.1.2, line 4. Delete "0.0011" and substitute "0.00075".

Page 21, Paragraph 5.2.1.1.1, line 2. Delete "0.001-inch" and substitute "0.00075".

Page 22, Paragraph 5.4.1.1. Delete and substitute:

"5.4.1.1 Labeling, shipping containers. Labeling shall comply with the Federal Food, Drug and Cosmetic Act and Regulations Promulgated Thereunder and shall show crude protien, fat, fiber, ash, and moisture content and caloric value per ounce. Instructions for feeding are optional."

Paragraph 5.4.2.1, line 1. Delete "polyethylene bags".

Military custodian:

Army–GL

Preparing activity:

Army–GL

Project No. 8710-A006

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:12Z
Check the source to verify that this is the current version before use.