INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

DEICING-DEFROSTER FLUID (AEROSOL)

This interim amendment was developed by the General Services Administration, Federal Supply Service, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal Specification O-D-190B, dated September 10, 1976.

PAGE 3

3.4, Add new sentence: "The use of fluorocarbon propellants is prohibited."

PAGE 6

4.3.9, Delete and substitute: "4.3.9 Analysis of propellant gas for fluorocarbons and vinyl chloride."

Add in sequence new paragraphs 4.3.9.1 and 4.3.9.2.

4.3.9.1 Special apparatus and materials. The chemical analysis procedure described herein requires the following apparatus and materials:

(a) A can-piercing, pressure-measuring device recommended in the CSMA Aerosol Guide for determining the internal pressure of aerosol products. The device is available as Model CBA-6 from Builders Sheet Metal Works, Inc., 110 Wooster Street, New York, NY 10012.

(b) A temperature programmable gas chromatograph (Hewlett-Packard Model 5750, or equivalent equipped with a 0.5 ml gas sampling valve and thermal conductivity detector.

(c) Two stainless steel gas chromatography columns, 6 feet long by 1/8" outside diameter, packed with 60-200 mesh silica gel.

(d) Standard propellant gases in lecture bottles from Matheson Gas Products (or another supplier): vinyl chloride, fluorocarbons no. 11, 12, 114, 115.

(e) Matheson lecture bottle control valve Model 58, or equivalent.

4.3.9.2 Gas chromatographic analysis. Condition the chromatographic columns at 200°C with normal helium as the carrier gas at 75-100 ml/minute for one hour. Remove the actuator and cap of an unused aerosol container. Puncture the can using the pressure-measuring device and connect the device to the gas chromatograph. Triplicate chromatographic analyses shall be done on the aerosol propellant sample and on mixtures of the aerosol propellant with each of the five standard propellant gases. For mixing the standard propellants with the aerosol propellant sample, use a "T" connection (Swaglock, or equivalent). The "T" connection shall be removed entirely when the aerosol propellant sample alone is to be analyzed. Bubble each gas sample through the sampling valve at a moderate rate for two minutes before each run is made to purge the valve of any other gases. Analyze the samples using a thermal conductivity detector. The temperature program shall be 100°C to 200°C at 6°C per minute with a 2 minute post injection hold at 100°C and a 5 minute upper limit hold at 200°C. Helium is used as the carrier gas at the rate of 75-100 ml per minute. There shall be no detectable material in the aerosol propellant sample having the same retention time as any of the five standard propellant gases.

GSA DC 77-6457

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:12Z
Check the source to verify that this is the current version before use.