O-H-210C
September 26, 1969
SUPERSEDING
Int. Fed. Spec. O-H-00210B (GSA-FSS)
June 11, 1968 and
Fed. Spec. O-H-210A
September 5, 1958

FEDERAL SPECIFICATION

HERBICIDE, 2,4,5-TRICHLOROPHENOXYACETIC ACID (2,4,5-T) (SALTS AND ESTERS)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. 2,4,5-Trichlorophenoxyacetic acid (2, 4, 5-T) is an organic acid relatively insoluble in water or oil. It is normally compounded before use as a herbicide. 2,4,5-T is a selective herbicide. When applied in the same manner as 2,4-dichlorophenoxyacetic acid (2,4-D) it has similar effects on most plants. As a postemergence spray it will kill many broad-leaved weeds and woody plants, with little or no injury to many grasses and sedges. As a preemergence spray or as a foliage spray on seedlings, 2,4,5-T can also be used to control many annual grasses. However, 2,4,5-T is more effective on many woody plants and will control certain species not effectively controlled by 2,4-D. This specification covers two general types of 2,4,5-T.

1.2 Classification.

1.2.1 Types. Formulations of 2,4,5-T covered by this specification shall be two general types as specified:

Type I - Liquid, amine salt forms which are usually less effective on plants per pound of 2,4,5-T acid equivalent than the ester forms.
Type II - Liquid, ester forms which are the most toxic forms of 2,4,5-T to plants per pound of 2,4,5-T acid equivalent.

Class 1 - Volatile alkyl esters of 2,4,5-T (see 6.2.3).
Class 2 - Low volatile esters of 2,4,5-T (see 6.2.4).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-C-96 - Cans, Metal 28 Gage and Lighter.
PPP-D-729 - Drums: Metal 55-Gallon (For Shipment of Noncorrosive Materials).
PPP-P-704 - Pails, Metal: (Shipping, Steel, 1 Through 12 Gallon).

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D. C. 20402.

FSC 6840

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:12Z
Check the source to verify that this is the current version before use.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Laws and Regulations

Federal Insecticide, Fungicide, and Rodenticide Act.

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D. C. 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Nongovernmental:

Association of Official Analytical Chemists:

Official Methods of Analysis. Tenth Edition, 1965.

(Application for copies should be addressed to the Association of Official Analytical Chemists, P. O. Box 540, Benjamin Franklin Station, Washington, D.C. 20044.)

Uniform Freight Classification Rules.

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, Chicago, Illinois 60606.)

National Motor Freight Classification Rules.

(Application for copies should be addressed to the National Classification Board, 1616 P Street, N. W., Washington, D.C. 20036.)

3. REQUIREMENTS

3.1 Type I. The liquid, amine salt forms of 2,4,5-Trichlorophenoxyacetic acid shall contain a minimum of four pounds of 2,4,5-T acid equivalent per gallon of formulation at 68° F., as determined in 4.5.1. The amine in this formulation shall be either an alkyl or alkanolamine or mixtures of these types. The product shall be soluble in hard or soft water at the concentrations specified in the directions for use, nonfoaming, disperse easily, making a solution that contains no ingredients which will inhibit the application of the material at the concentrations normally used for weed and woody plant control. The product shall contain no ingredients which will coagulate with water. The material shall contain sequestering agents which facilitate its application in hard or soft water.

NOTE: Water containing up to about 5 grains (85.5 p.p.m.) of hardness is considered soft, over 30 grains (513 p.p.m.) is very hard. Degree of hardness is often expressed in terms of grains per gallon of calcium carbonate (1 grain per gallon $CaCO_3$ is equivalent to 17.1 parts per million $CaCO_3$.).

3.2 Type II. The liquid ester forms of 2,4,5-Trichlorophenoxyacetic acid.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T11:12Z
Check the source to verify that this is the current version before use.

3.2.1 Class 1, the volatile esters formulations of 2,4,5-Trichlorophenoxyacetic acid. Formulations of the alkyl liquid esters of 2,4,5-T shall contain a minimum of four pounds of 2,4,5-T acid equivalent per gallon of formulation at 68°F. as determined in 4.5.2. The esters in this class shall belong to the alkyl group such as methyl, ethyl, propyl, isopropyl, butyl, amyl, and pentyl, or mixtures of these alkyl esters. The formulation shall be a clear solution readily miscible with oil and emulsifiable when mixed with water. It shall contain the necessary solvents and emulsifying agents, such that the emulsion formed with water required a minimum of agitation to maintain intimate mixture with the diluent during the mixing and application period. The oil carrier for the formulation shall be of such gravity and viscosity, not detracting from the killing power of the active ingredients, to offer maximum penetration and spread of the spray solution. The combination of solvents and emulsifiers used in the formulation shall not contain more than 0.1 mg. of organic chlorine per gram when analyzed according to 4.5.2. The product shall remain free of solid material when held at a temperature of 25°F. for a period of 5 days.

3.2.2 Class 2, the low volatile esters. These include the glycol, polyglycol and their ether ester derivatives of 2,4,5-T as well as other heavy molecular weight esters of 2,4,5-T that are known to be low volatile. The low volatile esters of 2,4,5-T shall contain a minimum of four pounds of 2,4,5-T acid equivalent per gallon of formulation at 68°F., as determined in 4.5.2. This class shall not include esters of the lower alkyl group such as methyl, ethyl, propyl, isopropyl, butyl, amyl, and pentyl, or mixtures of these alkyl esters. The formulation shall be readily miscible with oil and emulsifiable with water. The product shall be a clear solution, nonfoaming and shall include the necessary solvents, and emulsifying agents, such that the emulsion formed with water requires a minimum of agitation to maintain intimate mixture with the diluent during the mixing and application period. The oil carrier for the formulation shall be of such gravity and viscosity, not detracting from the killing power of the active ingredients, to offer maximum penetration and spread of the spray solution. When tested for volatility as described in 4.5.3 the product shall have an average vapor activity rating of less than 4.0. The combination of solvents and emulsifiers used in the formulation shall not contain more than 0.1 mg. of organic chlorine per gram when analyzed according to 4.5.2. The product shall remain free of solid material when held at a temperature of 25° F. for a period of 5 days.

3.4 Workmanship. The finished products shall be clean and uniform, and free from any defects which might impair their utility.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling for lot acceptance.

4.2.1 Inspection lot. A lot shall consist of one batch of material produced by one manufacturer from the same materials and under essentially the same manufacturing conditions. (A batch is defined as that quality of material which has been manufactured by source unit chemical process and subjected to some physical mixing process intended to make the final product substantially uniform). In the event of the operation is a continuous operation, that material produced in one 24 hour period shall constitute a lot.

4.2.2 Sampling for inspection of filled containers. A random sample of filled containers shall be taken from each lot by the inspector in accordance with MIL-STD-105 at inspection level I, and acceptable quality level (AQL) = 2.5 percent defective to verify compliance with all stipulations of this specification regarding fill, closure, marking, and other requirements not involving tests.

4.2.3 Sampling for tests. From each inspection lot the inspector shall take three separate 1-pint samples. In case the material is produced by a batch process, and the inspection lot contains more than 2 batches, the three samples shall normally be taken from different batches, from time to time; however, at the discretion of the inspector, two or three of the samples shall be taken from the same batch, in which case the samples shall be obtained in a manner calculated to disclose any nonuniformity of the material within the batch. Where material is produced by a continuous-run process the three samples shall be taken so as to represent respectively, the first part, the middle part, and the last part of the run which produced the inspection lot. Each sample shall be thoroughly mixed and divided into three equal portions. The portions shall be placed in separate

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:12Z
Check the source to verify that this is the current version before use.

clean, dry, metal or glass containers, which shall be sealed and carefully marked. One of the portions of each sample shall be forwarded to a Government Laboratory designated by the bureau or agency concerned, one shall be delivered to the contractor, and one shall be held by the Government inspector to be used for retests in case of dispute.

4.3 Inspection.

4.3.1 Inspection of filled containers. Each sample filled container selected in accordance with 4.2.4 shall be examined by the inspector for defects of the container and the closure, for evidence of leakage, and for unsatisfactory markings. Each sample filled container shall also be weighed to determine the amount of the contents. Any container in the sample having one or more defects, or under required fill, shall be rejected, and if the number of defective containers in any sample exceeds the acceptance number for the appropriate sampling plan of MIL-STD-105 the lot represented by the sample shall be rejected. Rejected lots may be resubmitted for acceptance tests provided that the contractor has removed or repaired all nonconforming containers.

4.4 Lot acceptance tests. The sample specimens selected in accordance with 4.2.3 shall be subjected separately to the tests specified in 4.5. If either specimen fails in one or more of the tests the lot shall be rejected. Rejected lots may be resubmitted for acceptance tests provided the contractor has removed or repaired all nonconforming products.

4.5 Test methods.

4.5.1 2,4,5-Trichlorophenoxyacetic acid content in amine salts of 2,4,5-Trichlorophenoxyacetic acid. Transfer a sample equivalent (or a suitable aliquot of a sample diluted with water) to about 1 g. of 2,4,5-T acid to a 250-ml. separatory funnel. Neutralize if necessary with 10 percent H_2SO_4, and add 10 ml. in excess. Extract the aqueous phase twice with 75-ml. portions of ether. Wash the combined ether extracts free from mineral acid with 3 portions of water exactly 10 ml. each. Avoid slight emulsification by excessive shaking. Filter the ether solution through a funnel containing a small piece of cotton previously saturated with ether into a 400-ml. beaker, rinsing the separatory funnel with ether. Add 25 ml. of water, a few boiling chips, and evaporate off the ether layer on a steam bath until approximately 25 ml. of ether remains. Remove the beaker from the steam bath and evaporate off the remaining portion of ether at room temperature by means of a current of air. Dissolve the aqueous mixture in 100 ml. of neutral ethyl alcohol and titrate with 0.1 N NaOH using 1 ml. of indicators* (1 g. in 100 ml. of alcohol).

Each ml. of 0.1 N NaOH is equivalent to 0.02555 g. of 2,4,5-trichlorophenoxyacetic acid. Calculate the percent 2,4,5-T acid found to the specific amine present in the sample. Ref: Methods of analysis, A.O.A.C., Tenth Edition, par. 4.138 (c), page 55.

4.5.2 Esters of 2,4,5-trichlorophenoxyacetic acid by determination of total chlorine. Weigh and mix 1.5 g. of boric anhydride (Eastman Kodak Co., Cat. #2685 or equivalent), 1.0 g. finely powdered potassium nitrate, and 0.4 g. finely powdered sucrose. Transfer approximately one-fourth of this mixture to a 42-ml. Parr bomb, electric ignition type, and add from a small weighing buret about 0.25 to 0.30 g. of sample containing from 0.030 to 0.035 g. chlorine. (When a sample larger than 0.30 g. is required, 2.5 g. of boric anhydride should be used. In no cases should a sample larger than 0.6 g. be taken.) Mix well with a thin stirring rod. Add the remainder of the boric anhydride, potassium nitrate and sucrose mixture in small portions and thoroughly mix after each addition. Measure 15 g. of calorimetric grade sodium peroxide in a standard measuring dipper, add a small portion to the contents of the bomb, and stir. Add the balance of sodium peroxide and thoroughly mix by stirring with the rod. Withdraw the rod and brush free of adhering particles. Quickly cut or break off the lower 1-1/2 inches of the stirring rod and imbed it in the fusion mixture. Sprinkle on the top of the fusion mixture a small quantity of finely ground sucrose. Prepare the head by heating the fuse wire momentarily in a flame and immersing it into a small quantity of sucrose. One milligram of the substance is sufficient to start the combustion. Assemble the bomb and ignite in the usual manner with a satisfactory shield between the operator and apparatus.

Place about 100 ml. of distilled water in a 600-ml. beaker and heat nearly to boiling. After cooling of the bomb, dismantle it and dip the cover in the hot water to dissolve any of the fusion which may be adhering to its under side. Wash cover with a fine jet of distilled water catching the washings in the beaker. With a pair of tongs lay the fusion cup on its side in the same beaker of hot water, covering it immediately with a watch glass. After the fused material has been dissolved, remove the cup and rinse with hot water, cool the solution, add several drops of phenolphthalein indicator, neutralize with concentrated nitric acid and add 5 ml. in excess. From this point, the chlorine may be determined by electrometric titration or by the Volhard procedure as directed in the Methods of Analysis A.O.A.C., Tenth Edition, page 64, par. 4.189 (a) (c).

*Either brom thymol blue or phenolphtalein may be used in the titration provided the one selected is used in the standardization of the sodium hydroxide.

Source: https://assist.dla.mil -- Downloaded: 20260-26T11:12Z
Check the source to verify that this is the current version before use.

NOTE 1. The combination of materials used in a sodium peroxide bomb has explosive properties if wrongly handled, and the operator should remain fully aware at all times of the precautions that must be observed and the steps which must be taken to avoid damage to the apparatus and possibly personal injury. It is suggested that the instructions and precautions given in the "Parr Manual Number 121 - Peroxide Bomb Apparatus and Methods," Parr Instrument Company, Moline, Illinois, be observed.

NOTE 2. A flame fired bomb may be used in place of the electric ignition type, but in case of dispute the electric ignition type will govern.

4.5.3 Volatility test (Relative Vapor Activity). The vapor activity test is conducted with gas-tight polyethylene cases approximately 4 x 4 x 18 inches in size. Young rapidly growing red Kidney bean plants about 4 inches in height are used as test plants. A single bean plant growing in a 3-inch pot is placed in each polyethylene case just prior to testing the ester.

4.5.3.1 Two milligrams of acid equivalent as the ester is dissolved in 10 milliliters of 95 percent ethyl alcohol and a Whatman No. 1 filter paper (9 cm. diameter) is thoroughly moistened by dipping in the solution. (Do not reuse the container used in this impregnation.) The alcohol is then allowed to evaporate and the filter paper impregnated with the ester is inserted into the polyethylene case containing the bean and fastened to the inside of the case 6 inches above the leaves of the test plant. The open end of the polyethylene case is then sealed.

4.5.3.2 The case containing the test plant and treated filter paper is then placed in a dark room for a period of 24 hours. The temperature range of the room should be 80° F. Control plants are also sealed in separate cases. The experimental design is a randomized block with three replications and each test is repeated three times. The evaluation shall be made following an exposure period of 24 hours.

4.5.3.3 Observation of the effect of the vapors on test plants should take into consideration whether or not the plant is slightly, moderately or severely injured, including such symptoms as degree of stem curvature, terminal bud inhibition and degree of leaf curl. The relative vapor activity of an ester can be numerically designated as follows: 0 - no visible effect; 1,2,3 - slight injury - plants usually recovered with little or no reduction in growth, slight epinasty present, stem curvature slight; 4,5,6 - moderate injury - plant usually recovered, moderate epinasty, moderate terminal bud inhibition and moderate stem curvature present; 7,8,9 - severe injury - plant usually does not recover, pronounced epinasty, together with pronounced stem curvature; 10 - plant killed.

4.5.3.4 Chemically pure 2,4,5-T acid and the butyl ester of 2,4,5-T are used as standards. The 2,4,5-T acid under most conditions is rated 0 while the butyl ester has a high vapor activity with a rating of 9.0. Esters receiving the following ratings would be classed as follows:

0 - no vapor activity.
1,2,3 - low vapor activity.
4,5,6 - moderate vapor activity.
7 and above - high vapor activity.

Esters must receive a vapor activity rating of less than 4 to be designated low volatile.

4.6 Inspection of preparation for delivery. The packaging, packing and marking of the herbicide shall be inspected to determine conformance to the requirements of Section 5 of this specification.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.3).

5.1.1 Level A. Herbicide shall be packaged in a 1-gallon oblong can conforming to PPP-C-96, type V, class 4 having a plan B coating. Five-gallon or 55-gallon quantities shall be packed directly into containers as specified in 5.2.1.2 or 5.2.2.2.

5.1.2 Level B. The herbicide shall be packaged as specified for level A except that for cans, the exterior coating shall be plan A.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T11:12Z
Check the source to verify that this is the current version before use.

5.1.3 Level C. The herbicide shall be packaged in accordance with the supplier's standard practice. The size of containers shall be as specified (see 6.3).

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.3).

5.2.1 Level A.

5.2.1.1 One-gallon cans. The herbicide packaged as specified in 5.1.1 shall be packed in accordance with the level A requirements of the appendix of PPP-C-96.

5.2.1.2 Five gallon pails or 55-gallon drums. The herbicide shall be packed in a five-gallon pail conforming to PPP-P-704, type I, class 3, or in a 55-gallon drum conforming to PPP-D-729, type II, as specified (see 6.3).

5.2.2 Level B.

5.2.2.1 One-gallon cans. The herbicide, packaged as specified in 5.1.2 shall be packed in accordance with the level B requirements of the appendix to PPP-C-96.

5.2.2.2 Five-gallon pails or 55-gallon drums. The herbicide shall be packed in a five-gallon pail conforming to PPP-P-704, type I, class 3, except that commercial colors shall be acceptable, or in a 55-gallon drum conforming to PPP-D-729, type II, except that commercial coatings are acceptable as specified (see 6.3).

5.2.3. Level C. The herbicide shall be packed in containers which are acceptable by carriers for safe transportation to point of destination specified in the procurement document at the lowest rate for such supplies. Containers and packing shall conform to the requirements of the Uniform Freight Classification Rules, or National Motor Freight Classification Rules.

5.3 Marking.

5.3.1 Civil agencies. In addition to any special marking required by the contract or order, marking for shipment shall be in accordance with Fed. Std. No. 123.

5.3.1.1 Labeling. Unless otherwise specified, each container of 2,4,5-T formulation shall be labeled with instructions for use and marked in compliance with the Federal Insecticide, Fungicide, and Rodenticide Act and other applicable existing Federal laws. Date of pack and lot number shall appear on the label.

5.3.2 Military agencies. In addition to the marking specified in 5.3.1.1, and any special marking required in the contract or order, all containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Net content. Statements of liquid measure shall be in terms of the United States gallon at 68° F.

6.2 Intended use.

6.2.1 Type I. The liquid amine forms of 2,4,5-T are highly soluble in water, making a relatively clear solution. They are quite stable and are effective for easy-to-kill or moderately easy-to-kill weeds and woody plants. The amine salts of 2,4,5-T are much less volatile than the ester forms of 2,4,5-T and are somewhat better adapted for spraying for weed control near plants sensitive to 2,4,5-T. However, the amine salts of 2,4,5-T are usually less effective on old, semiresistant weeds and woody species than the esters of 2,4,5-T per pound of acid equivalent.

6.2.2 Type II. The liquid ester forms of 2,4,5-trichlorophenoxyacetic acid.

6.2.3 Class 1. Not authorized for Military use. The lower alkyl esters of 2,4,5-trichlorophenoxyacetic acid are comparatively volatile. When the lower alkyl esters of 2,4,5-T are used for weed and woody plant control they may be used at lower acid equivalent rates than the amine salts of 2,4,5-T. The lower alkyl esters of 2,4,5-T are better adapted for the control of harder-to-kill weeds and older semiresistant weed and woody species than the amine salts of 2,4,5-T. The lower alkyl esters of 2,4,5-T should not be used in areas near sensitive crops such as cotton, grapes, tomatoes, and tobacco.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:12Z
Check the source to verify that this is the current version before use.

6.2.4 Class 2. The low volatile esters of 2,4,5-T have the same intended use as the ester forms specified in class 1. However, in areas where sensitive crops are grown such as cotton, etc., if an ester form of 2,4,5-T is necessary, the esters specified in class 2 should be used to reduce the hazard of volatility.

6.3 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Level of packaging and packing (see 5.1 and 5.2).
(c) Quantity to shipping container (see 5.1.1 and 5.1.3).
(d) Special markings required (see 5.3.1 and 5.3.2).

6.4 Basis of award.

6.4.1 Type I and type II (classes 1 and 2). Bids should be evaluated and the award made primarily on the basis of computing the price per pound of 2,4,5-T acid equivalent contained in each gallon of preparation of concentrate (supplier should be requested to furnish 2,4,5-T acid equivalent data).

Custodians:

Army - MU
Air Force - 79

User activity:

Marine Corps - MC

MILITARY COORDINATING ACTIVITY:

Navy - YD

Preparing activity:

GSA-FSS

Order for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:12Z
Check the source to verify that this is the current version before use.

GENERAL SERVICES ADMINISTRATION - FEDERAL SUPPLY SERVICE

SPECIFICATION COMMENT SHEET

BUDGET BUREAU NO. 29-R0175

INSTRUCTIONS

This form provides a way for users of this specification to inform the originator of problems encountered in its use. It is not to be used to request changes to accommodate proprietary features. All comments will be considered and appreciated, but please do not expect a reply. To comment: detach, complete, fold, staple, and mail.

NOTE: Comments on this form do not constitute or imply authorization to waive any part of the document or serve to amend contractual requirements.

1. SPECIFICATION

O-H-210C - Herbicide, 2,4,5-Trichlorophenoxy acetic Acid (2,4,5-T)(Salts and Esters)

2. CONTRACT NO. *(If any)*	3. QUANTITY ON CONTRACT *(Optional)*	4. DOLLAR VALUE *(Optional)*

5. GENERAL NATURE OF PROBLEM *(e.g., inspection difficulties, manufacturers unable to meet tolerances, containers collapse under normal warehousing conditions, etc.)*

6. SPECIFIC REQUIREMENTS AFFECTED *(Include paragraph number and lines of wording)*

7. SPECIFIC PROBLEMS *(e.g. tests in 4.2.2 will not assure that the battery will last required time; temperature ranges in table 2 do not conform to commercially available items.)*

8. RECOMMENDATIONS

9. NAME OF MANUFACTURER, ASSOCIATION, GOVT. AGENCY, ETC.	10. ADDRESS *(Number, Street, City, State and Zip Code)*

11. NAME AND TITLE OF SUBMITTER	12. DATE

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:12Z
Check the source to verify that this is the current version before use.

FOLD

GENERAL SERVICES ADMINISTRATION

OFFICIAL BUSINESS
FMSC

POSTAGE & FEES PAID
GENERAL SERVICES ADMINISTRATION

General Services Administration
Federal Supply Service (FMSC)
Washington, D. C. 20406

FOLD

GSA FORM FEB 69 2200

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:12Z
Check the source to verify that this is the current version before use.