MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 5749W

This amendment forms a part of Military Specification Sheet MIL-E-1/8G, dated 10 February 1981, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Quality conformance inspection, part 3, Method 1501, Intermittent life, conditions column: Delete "Group E" and "TA = room", and substitute "see note 10".

PAGE 4

NOTES, add the following note:

"10. The life-test sample shall consist of 20 tubes per lot and not more than 1 tube failure shall be permitted. In the event of rejection of the first sample, due to failure of more than 1 tube, a second sample of 40 tubes shall be selected from the lot. Acceptance shall then be based on the combined first and second samples. The total tube failures from the combined first and second samples shall not exceed three."

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - MI, AR
Air Force - 99
DLA - ES

User activities:
Army - ME, AV
Navy - AS, OS, CG, MC
Air Force - 11

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5960-3268)

☆ U.S. GOVERNMENT PRINTING OFFICE: 1981—505-022/8251

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:45Z
Check the source to verify that this is the current version before use.