INCH-POUND

MIL-PRF-1/95D
22 January 2007
SUPERSEDING
MIL-E-1/95C
4 June 1970

PERFORMANCE SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 5886

Inactive for new design
after 7 March 1997.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the electron tube described herein shall consist of this specification sheet and MIL-PRF-1.

DESCRIPTION: Pentode, subminiature, filamentary electrometer.

| | | |
|---|---|---|
| Outline | - - - - | 2-1 (EIA). |
| Base | - - - - | Pinch press (5 leads). |
| Envelope | - - - - | T2X3. |
| Cathode | - - - - | Coated filament. |

Base connections:

| | | | | | | |
|---|---|---|---|---|---|---|
| Pin No. | - - - - | 1 | 2 | 3 | 4 | 7 |
| Element | - - - - | a | g2 | +f, 1g3 | -f, 2g3 | g1 |

ABSOLUTE RATINGS:

| Parameter: / Unit: | Ebb V dc | Ef V dc | Eb V dc | Ec2 V dc | Ec1 V dc | Ik μA dc | R1 Ohms | Alt ft |
|---|---|---|---|---|---|---|---|---|
| Maximum: | --- | 1.5 | 22.5 | 22.5 | --- | 300 | --- | 10,000 |
| Minimum: | --- | 1.0 | --- | --- | --- | --- | --- | --- |
| Test conditions: | 22.5 | 1.25 | --- | --- | -3.0 | --- | 60,000 (triode connected) | --- |

GENERAL:

Qualification - Not required.

AMSC N/A

FSC 5960

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:54Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection.

| MIL-STD-1311 method | Requirement or test | Conditions | Acceptance level (see note 4) | Symbol | Limits | | Unit |
|---|---|---|---|---|---|---|---|
| | | | | | Min | Max | |
| | Conformance inspection, part 1 | | | | | | |
| 1266 | Total grid current | (see notes 1 and 2) | 0.65 | Ic1 | 0 | $2.5x10^{-13}$ | A dc |
| --- | Voltage gain | Esig = 0.2 V ac | 0.65 | Ep | 0.24 | --- | V ac |
| 1201 | Short and discontinuity detection | | 0.4 | --- | --- | --- | --- |
| 1256 | Electrode current (anode) | | 0.65 | Ib | 175 | 225 | μA dc |
| | Conformance inspection, part 2 | | | | | | |
| 1301 | Filament current | | --- | If | 8.8 | 11.2 | mA dc |
| 1306 | Transconductance | Eb = 10.5 V dc; R1 = 0 | --- | Sm | 120 | 240 | μmhos |
| 1316 | Amplification factor (triode) | Eb = 10.5 V dc; R1 = 0 | --- | Mu | 1.6 | 2.1 | --- |
| 1331 | Direct-interelectrode capacitance | No shield | --- | Cg1-all | 1.0 | 3.0 | pF |
| 1116 | Lead fatigue | | --- | --- | --- | --- | --- |
| 1211 | Insulation of electrodes | | --- | --- | --- | --- | --- |
| 1105 | Permanence of marking | | --- | --- | --- | --- | --- |

See notes at end of table.



Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:54Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection.

| MIL-STD-1311 method | Requirement or test | Conditions | Acceptance level (see note 4) | Symbol | Limits | | Unit |
|---|---|---|---|---|---|---|---|
| | | | | | Min | Max | |
| | Conformance inspection, part 3 | | | | | | |
| --- | Life-test provisions | Group C; triode connected | --- | --- | --- | --- | --- |
| --- | Life-test end points<br>(500 hours): | Voltage gain<br>Total grid current | ---<br>--- | Ep<br>Ic1 | 0.22<br>--- | ---<br>$5x10^{-13}$ | V ac<br>A dc |
| --- | Life-test provisions | Group C; triode connected (see note 3) | --- | --- | --- | --- | --- |
| --- | Life-test end point (10,000 hours) | Voltage gain | --- | Ep | 0.22 | --- | V ac |

NOTES:

1. Measurement shall be made with tube in an electrostatically shielded, light-tight container. One hour pre-heating is permitted prior to testing.
2. This test to be performed at the conclusion of the holding period.
3. During months in which there is production, the manufacturer shall conduct one test per month on at least five tubes.
4. This specification sheet uses accept on zero defect sampling plan in accordance with MIL-PRF-1, table III.

Referenced documents. In addition to MIL-PRF-1, this document references the following: MIL-STD-1311.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5960-2007-006)

Review activities:
Navy - AS, CG, MC, OS
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:54Z
Check the source to verify that this is the current version before use.