INCH-POUND

MIL-C-13743A (AR)
AMENDMENT 1
16 August 2000

MILITARY SPECIFICATION

CORE, STEEL, HARDENER; FOR ARMOR PIERCING TYPES
OF SMALL ARMS AMMUNITION

MIL-C-13743A was inactivated on January 31, 1996 for new design.

This amendment forms part of MIL-C-13743A (AR), dated 20 March 1969, and is approved for use by the US Army Armament, Research, Development, and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 6

* 4.3.3.1, Delete in its entirety and substitute the following:

"4.3.3.1 Hardness. A sample of 100 cores, selected in such a manner that the cores are representative of the entire lot, shall be tested for hardness. Failure of four or more cores to comply with 3.2 shall be cause for rejection of the lot. If more than one but less than four cores fail in the first test, a single retest is permitted using only one of the two following methods:

4.3.3.1.1 Double sample hardness test. A second sample, consisting of double the number of cores in the first sample, shall be tested. The lot shall be rejected if, in the combined first and second sample, four or more cores fail to comply with 3.2.

4.3.3.1.2 Penetration test. A sample of 20 cores shall be assembled, loaded and fired for penetration against 7/8 inch thick armor plate (MIL-S-13812) placed at 100 yards from the weapon. The M8 shall completely perforate the plate. The M20 shall completely penetrate the plate. These definitions are provided in the cartridge specification (MIL-C-3066). Failure of two or more cartridges to meet the requirement of MIL-C-3066 will be cause for rejection of the lot. No penetration retest is permitted."

PAGE 9

* 6.3.1, Delete in its entirety and substitute the following:

"6.3.1 Carbonitride heat treated cores shall be verified in a similar manner as described in 4.4.1."

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:14Z
Check the source to verify that this is the current version before use.

* 6.3.2, Add the following paragraph:

"6.3.2 If the hardness reading is still below the minimum specified, the lot shall be either subjected to a second sample or rejected see 4.3.3.1)."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-0232)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:14Z
Check the source to verify that this is the current version before use.