MIL-H-13719C
AMENDMENT 2
7 September 1981
SUPERSEDING
AMENDMENT 1
17 January 1972

MILITARY SPECIFICATION
HOSE ASSEMBLY, RUBBER: HYDRAULIC BRAKE

This amendment forms a part of Military Specification MIL-H-13719C, dated 17 March 1969, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, under "SPECIFICATIONS, FEDERAL", delete:
"VV-B-680 - Brake Fluid, Automotive."

2.1, under "SPECIFICATIONS, Military", add:
"MIL-B-46176 - Brake Fluid, Silicone, Automotive, All Weather, Operational and Preservative.
MIL-C-81562 - Coatings, Cadmium, Tin-cadmium and Zinc (Mechanically Deposited)."

2.1, under "STANDARDS, Federal", add:
"FED-STD-H28/2 - Screw Thread Standards for Federal Services.
FED-STD-162 - Rubber, Visual Inspection Guide for."

2.1, under "STANDARDS, Military", delete:
"MIL-STD-166 - Visual Inspection Guide for Rubber Hose."

PAGE 2

2.2, Delete in its entirety.

3.1, delete in its entirety, and substitute:

"3.1 Qualification. Hose assemblies furnished under this specification shall be products which have been tested and have passed the qualification tests specified herein, and have been listed on, or approved for listing on, the applicable Qualified Products List (QPL) (see 4.2, 6.3 and 6.4)."

3.2, line 2, delete "(see 6.2)" and add: "(see 6.2 and 6.6)".

FSC 2530

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:12Z
Check the source to verify that this is the current version before use.

3.2.3, delete in its entirety, and substitute:

"3.2.3 Fittings. Fittings of hose assemblies shall be securely attached to the hose. Dimensions and materials of fittings shall conform to the applicable standard or drawing. Steel fittings shall be zinc coated to conform to type II, class 3, of QQ-Z-325, or type II, class 3 of MIL-C-81562, or cadmium plated to conform to type II, class 3 of QQ-P-416 (see 6.7). Threads on fittings shall conform to FED-STD-H28/2. Form, threads per inch, and class of fit shall be as specified in applicable specifications, standards or drawings."

PAGE 5

4.1, delete in its entirety, and substitute:

"4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

4.2, delete in its entirety, and substitute:

"4.2 Qualification testing. A qualification sample of sixteen (16) hose assemblies, 1/8 inch ID (see 6.3), and a free hose length of 14 inches (measured between fittings) shall be furnished for qualification testing. Hose assemblies shall be representative of units proposed to be furnished under contract. Qualification testing shall be conducted under Government surveillance by the contractor, or by an authorized testing facility at a site approved by the Government. Inspection shall consist of examination for the defects specified in 4.3.2.2 and testing as specified in table III."

4.2.1: Delete in its entirety.

PAGE 6

4.3.2.1, line 1, delete "MIL-STD-166", and substitute: "FED-STD-162".

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:12Z
Check the source to verify that this is the current version before use.

PAGE 7

4.3.3 and 4.3.3.1, delete in their entirety (except table V), and substitute:

"4.3.3 Acceptance tests. Samples selected in accordance with 4.3.1.3 shall be subjected to the tests specified in table V.

4.3.3.1 Failure. Failure of samples to pass the constriction test (see 4.4.3) in excess of an AQL of 6.5 percent shall constitute failure of the lot. Failure of any sample to pass the burst test (see 4.4.5) shall constitute failure of the lot."

Table V, title, delete "quality conformance", and substitute: "acceptance".

PAGE 10

4.4.10, line 4, delete "VV-B-680", and substitute: "MIL-B-46176".

PAGE 12

Add new paragraph:

"6.6 Recycled materials. The use of recycled materials which meet the requirements of the applicable material specifications without jeopardizing the intended use of the item shall be encouraged (see 3.2)."

Add new paragraph:

"6.7 Cadmium effluents. Electroplaters of cadmium plated fittings must meet all Federal, state and local requirements for waste treatment of cadmium effluents."

Custodians:
Army - AT
Air Force - 99

Review activities:
Army - MI, ME
DLA - CS

User activity:
Navy - MC

Preparing activity:
Army - AT

Project No. 2530-0268

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:12Z
Check the source to verify that this is the current version before use.