A-A-50691
02 Nov 1990

COMMERCIAL ITEM DESCRIPTION

TRUCK, AIRCRAFT BAGGAGE LOAD UNLOADING

This commercial item description authorized by the
US Department of Defense.

Abstract.This specification covers a self-propelled, operator driven, vehicle mounted belt conveyor used 10 load and unload aircraft baggage and cargo.

Applicable documents The following documents form a part of this commecial item description to the extent specified herein. The issues of the documents which are Department of Defense (DoD) adopted shall be those listed in the issue of the DoDISS specified in the solicitation. The issues of the documents not listed in the DoDiSS shall be those in effect on the date specified in the solicitation.

SPECIFICATIONS

FEDERAL

FED-STD-595	Colors
VV-F-800	Fuel Oil, Diesel

MILITARY

MIL-T-5624	Turbine fuel, Aviation, Grades JP-4 and JP-5
MIL-T-83133	Turbine Fuel, Aviation, Kerosene Type. Grade JP-8

Request for copies should be directed to, Standardization Documents Order Desk, Building 4D, 700 Robins Avenue, Philadelphia, PA 19111-5094

TIRE AND RIM ASSOCIATION YEARBOOK

(Applications for copies should be addressed to Tire and Rim Association, Inc., 3200 West Market Street, Akron, OH 44313.)

Salient Characteristics.

1. Dimensions. The fully operational vehicle shall have a front to rear wheelbase of not less than 110 inches, a maximum overall conveyor size of 36 inches wide and 25 feet long, and a minimum belt width of 24 inches.

2. Conveyer. The belt shall be a minimum 2-ply, non-slip rubber with only one lace joint. The conveyor shalt have a reversible motor with infinite variable speed control from 40 feel per minute (pm) to 100 pm in each direction under full load of 1000 pounds. Surface treated automatic belt aligners shall be provided, to prevent corrosion, and non-slip pulleys. A permanently mounted control station shall be mounted at the left rear and a removable remote control, with a minimum 90 foot length extension cable, shall be located at the left front. Both control stations shall be continually active at any conveyor position.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent by letter to: WR-ALC/MMDETB, Robins AFB, GA 31098

F-se 3930

DISTRIBUTION STATEMENT A:. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:46Z
Check the source to verify that this is the current version before use.

The hydraulic driven elevating mechanism shall be capable of raising and lowering the loaded (1 000 lbs) conveyor from 39 to 132 inches at front end and 20 to 62 inches at rear end. Minimum 7 inch OD rubber bumpers, located front and rear of conveyor, positive locking maintenance stands and guide rails shall be provided.

3. Neutral start switch and lockout. The vehicle electrical system shall be designed to prevent engaging the starter while the engine is running or when the transmission is in any position except neutral.

4. Engine and transmission The vehicle shall be equipped with a commercial, liquid cooled, diesel engine which shall demonstrate performance characteristics in accordance with VV-F-800 using diesel fuel and shall be certified as able to operate satisfactorily on Grades JP-4 and JP-5 turbine fuel in accordance with MIL-T-5624 and Grade JP-8 in accordance with MIL-T-83133. The engine exhaust shall not be directed toward the ground. A minimum 20 gallon capacity fuel tank with at least one water separator type filter located between the tank and engine shall be provided. Glow plugs shall be provided for cold weather starting. A commercial automatic transmission shall be provided, complete with hydraulic torque converter, with a capacity of at least 105 percent of the maximum net engine torque. The drive range selector shall provide not less than four gear ratios without selector movement.

5. Hydraulic system. A hydraulic tank sight gauge, return line filter and suction line strainer shall be provided. The pump shall be engine driven.

6. Electrical system. A 12 or 24 volt electrical system may be provided. Ail circuits shall be protected by circuit breakers and guarded from environmental conditions. Circuit breakers shall be readily accessible. Minimum capacity of the alternator shall be 60 amperes. At least one 12 V, maintenance free battery rated at a minimum of 350 cold cranking amps shall be provided.

7. Vehicle lighting. Headlights, running, braking, backing lights and a rear work light shall be provided for all weather operation. All lights and reflectors mounted on vertical surfaces shall be flush or recessed.

8. Operator's compartment. The operator's compartment shall be large enough to permit comfortable operation by a 200 pound driver without hampering movement. As a minimum the following shall be provided; low oil pressure, battery voltage, hydraulic fluid pressure and water temperature indicators; horn, hourmeter, fuel gauge, odometer, speedometer and instrument panel lighting. All controls shall be clearly marked and identified. Two side mounted mirrors shall be provided and shall not interfere with the forward or side line-of-sight of the driver.

9. Brakes,wheels and tires. The vehicle shall be equipped with four-wheel hydraulic service brakes capable of withstanding 250 lbs brake pedal force without component failure. Power assisted braking is acceptable. The brake pedal shall have a nonskid metal surface or replaceable rubber cap. The parking brake shall be capable of retaining the unloaded conveyor on a 20.4 percent smooth concrete incline in both the forward and reverse position. The vehicle shall be equipped with wheels and tires which meet all Tire and Rim Association or European Tyre and Rim Technical Organization requirements for this application.

10. Vehicle finish. The outer surface of the vehicle and interior surfaces of compartments shall be painted with the manufacturers standard commercial paint matching, Forest Green, Color Number 24052 of FED-STD-595. The vehicle shall be rustproofed with a compatible undercoating.

11. Manuals. A complete set of operator, service and parts list manuals shall be provided with each vehicle upon delivery. Manuals shall include all necessary information for manufacturer optional equipment provided.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:46Z
Check the source to verify that this is the current version before use.

12. **Materials**. Recycled and recovered raw materials may be used in lieu of virgin raw materials as long as these materials do not jeopardize the intended use of the vehicle and fully comply with all contract requirements. All materials used shall be free from defects which could affect the performance or maintainability of individual components of the end item. Wood shall not be used.

Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this commercial item description, that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices and is the same product offered for sale in the commercial marketplace. Small businesses that cannot offer products with established commercial market acceptability may compete by submission of bid samples. The government reserves the right to require proof of such conformance before first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Metrication. Products manufactured using metric units, considered equal to the specified requirements, will be considered when the measurements are in the same tolerances as specified in accordance with FED-STD-376 conversions factors.

intended use. The belt conveyor is intended for use at aircraft to transfer baggage between both military and civilian configured aircraft and material handling ground support equipment. The vehicle will be used in areas requiring a 30 foot minimum turning radius and a maximum speed of 20 MPH. During non operational hours, the vehicle will be driven back to a loading area, clearing the flight line from unnecessary vehicles and equipment. The life expectancy requirement of this vehicle is projected to be 14 years.

Preservation, packing. labehing and marking. The items shall be packaged according to normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipment, handling and storage. The shipping container shall be in compliance with both national and uniform motor freight classifications, Shipping containers shall be marked as required unless otherwise specified in the contract order.

Military interests:

Civil Agency Coordinating Activities:
GSA/FSS (7FXE)

Preparing activity: (Project 3930-F008)
Air Force -84

Custodian:
Air Force-99

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:46Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER A-A 50691	2. DOCUMENT DATE (YYMMDD) 02 Nov 1990

3. DOCUMENT TITLE

TRUCK, AIRCRAFT BAGGAGE LOADING-UNLOADING

4. NATURE OF CHANGE (*Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.*)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)
	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME Kevin Cox	b. TELEPHONE (Include Area Code) (1) Commercial (912) 926-2192 (2) AUTOVON AV 468-2192
c. ADDRESS (Include Zip Code) WR-ALC/MMVRG Robins AFB, GA 31098-5609	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:46Z
Check the source to verify that this is the current version before use.